Blue-Point, No compromise!

AP.ON TOOLS, Inc.

muy simps

LIFETIME WARRANTY

VISIMM Det ISI

BURNER

History of Blue-Point



1925 Blue Point Tool Company was formed



1930 Snap-on Wrench Company and Blue Point Tool Company merged to become Snap-on Tools, Inc.



1940 Superior tools from Snap-on, Inc. Making headlines in the industry



1945 Forged Steel Products Company finally merged into Snap-on Tools, Inc.

Founded in 1925, Blue Point Tool Company was formed in Wisconsin, United States, as a tools manufacturing company. The Blue Point name was derived then from the blue-coloured tip of punches & chisels formed after oil quenching and tempering. This distinguished Blue Point's products from competitors' and Blue Point eventually became a brand synonymous with quality hand tools.

Following the successful introduction of the Blue Point punches and chisels, the management turned to their Milwaukee supplier factory to provide open end wrenches and issued this order: "Forget competition, forget price, forget precedent; just take our order to make the best wrench in the world, and we will sell them regardless of competition and regardless of price." A short time later the factory delivered their first set of eight open end wrenches and guaranteed that it was IMPOSSIBLE - to break the head; to spread the jaws; to bend the handle; to injure them; or, to destroy their everlasting efficiency. That sounded like a pretty wild and extravagant claim, but the sales force set out to sell them on that basis...and sell them they did!



Contents

	TOOL STORA	GE Roll Carts	Tool Boxes	Roll Cab Accesso	ies
	MASTER TOO General Service Sets		omotive Tool Sets	Modular Tool Sets	8-19
	SOCKETS, RA 1/4" 3/8"	TCHETS 1/2"	5 & ACCESS _{3/4"}	ORIES	20-37
Ð	WRENCHES Wrench Sets Double Open End Wren L and T shape Wrenche	nches (Adjustable Wrenche Dffset Box Wrenche Dther Wrenches		
	SCREWDRIVE Screwdrivers		TS		48-53
	PLIERS Plier Sets Locking Pliers	Standard Retaning	Pliers Ring Pliers	VDE Pliers Special Pliers	54-69
	TORQUE TOO Adjustable Click-Type Electronic Type	F	Preset Click-Type Digital Torque Tester	S	70-75
J.	POWER TOOL Air Tools Impact Sockets	Core	dless Tools essories		76-105
	STRIKING & C Hammers		ches & Chisels	Cutting Tools	106-115
A CONTRACTOR	MEASURING & Measuring Tools Safety	Flas	R HAND TOC shlights cellaneous	DLS	116-129
	SHOP & TECH Testing and Electronics		TOOLS Decial Tools	Automotive Specialty Tools	130-157



158-161



Tool Storage









Getting organized for the job gives you more than you may have realized. You can be sure that tools you need are readily available. The work space gets less messy and you focus better. No more searching of tools all over and replacement of missing tools. Time is spent more productively and work is done more efficiently. End of the day, you feel better and you look forward to your day's work, with your tools.

Professionals have long realized that and they work with pride. And we have been providing the exact tool storage they require to make this possible. Our tool storage are designed with the latest computeraided design systems and built to last the daily knocks of the work environment they are put into. Our paint and finishing systems deliver the finest, most durable finishes available and our rigorous testing ensures a trouble free lifetime of service.





Tool Storage Roll Cabinets

6 Drawers Roll Cab

KRB2006KPQP Order NO.: 101009

Order NO.: 101010

_	
	05

156 791 75 95 965 6 660 503 5 544 445 91 544 445 193

Colors Available

KRB2006KPQR

- Full double walled construction making for a stronger box which resists the constant pounding of weight and vibration
- Stiffeners are added between the walls to reduce stress on the box and keep the drawers from sagging
- Welded lock tabs on the back of each drawer
- Casters are fastened to the roll cab using weld nuts so they won't loosen over time
- Drawer edges are hemmed to double thickness so they are extra stiff

8 Drawers Roll Cab

KRB13008KPRB

Order NO · 101007



Colors Available

- Order NO.: 101008
- 40" double bank roll cab, greater capacity
- Double-wall design for a more rigid tool box
- · Welded lock tabs on the back of each drawer

stiff

- Popular choice with side cabinet for your work center • Full double walled construction making for a stronger box which
- resists the constant pounding of weight and vibration
- Stiffeners are added between the walls to reduce stress on the box and keep the drawers from sagging

5 Drawers Roll Cab

KRB13005KPRB Order NO.: 101005

	Cubic (cm ³)	Net Weig	ght (kg)	Shipping	g Weight (kg)
	159,387	6′	1		68
		Drawers	Width (mm)	Depth (mm)	Height (mm)
	Specifications	5	677	501	822
		1	543	445	54
	Drawers	2	543	445	119
600		2	543	445	184
Colors Available	KRB1300	5KPRR		Order	NO.: 101006

- High grade steel plate with PE Powder painting for better flowing property to avoid peel
- 45 kg slider with fully-openable drawers
- Bigger sized with greater capacity at 508 kg
- Tubular lock-stronger over molded key lock
- Ribs added for enhanced strength to prevent cabinet deformation

6 Drawers Roll Cab

KRB13006KPRB

Order NO · 101003

822

54

119

250



Colors Available

• High grade steel plate with PE Powder painting for better flowing property to avoid peel

- 45 kg slider with fully-openable drawers
- Bigger sized with greater capacity at 508 kg
- Tubular lock-stronger over molded key lock
- Ribs added for enhanced strength to prevent cabinet deformation

8 Drawers Roll Cab





Tool Storage Roll Cabinets / Roll Carts

153 695



7 Drawers Roll Cab

KRB13007KPRB Order NO.: 101001 t Weight (kg)

75

54

501 822 7 677 5 543 445 543 445 119 1 543 445 250 1 KRB13007KPRR Order NO · 101002

68

Colors Available

- High grade steel plate with PE Powder painting for better flowing property to avoid peel
- 45 kg slider with fully-openable drawers
- Bigger sized with greater capacity at 508 kg
- Tubular lock-stronger over molded key lock
- Ribs added for enhanced strength to prevent cabinet deformation

1 Drawer Roll Cart

KRBC3TDPCM Order NO.: 102003

KRBC7TDPCM Order NO.: 102005

1,041

51

51

102

76

431

399

391

391

391

Order NO.: 102006

6 0				0.00.00	
Audited State	Net Weigh	t (kg)	Loa	d Capacity	' (kg)
	29.5			136	
		Drawers	Width (mm)	Depth (mm)	Height (mm)
	Specifications	1	813	452	920
	Trays	-	762	686	102
0 0	Drawer	1	368	686	102
Colors Available)	(Order NO.	: 102004

Colors Available

KRBC3TD

t Weight (kg)

4

2

1

1 1 889

350

700

700

700

56.2

- Features 4" deep locking drawer with tubular lock for added tool security
- Two sturdy, 3" deep trays are positioned for convenience
- Friction drawer slides

4 Drawers Flip-Top

Made of heavy-gauge steel

5 Drawers Top Chest



KRB2055KPQP	'
Order NO.: 101011	



Colors Available

- Can be placed on all Blue-Point rollcabs as a top chest
- Lockable top lid
- Side grooves for easy lifting

Shipping Weight (kg) 44 437 47

KRB2055KPQR

Order NO.: 101012 **Colors Available**

79

• Latch System to unlock all 4 drawers once the top lid has been opened with a key

KRBC7TD

- · Folding side work shelf provides extra work space
- Padded lid provides an additional work surface
- · Locking prybar compartment securely holds all length prybars and screwdrivers

2 Shelves



KRBC2TCPCM

Order	NO.:	10200
-------	------	-------

Order NO.: 102002

	17.2		15	59
	Drawers	Width (mm)	Depth (mm)	Heigl (mn
Specifications	-	756	428	920
Trays	-	756	428	75

Colors Available

- KRBC2TC
- This model cart offers a more rugged construction
- Cart is also slightly larger than past models
- Trays feature rolled edges for improved strength and rigidity
- Maximum load capacity 68kg per tray
- Welded post holders
- Two locking casters

4 Drawers Flip-Top

KRBC10TBPCM Order NO.: 102007

e 1	Cubic (cm	3)	Load	d Capacity	(kg)
	121,700)		245	
		Drawers	Width (mm)	Depth (mm)	Height (mm)
	Specifications	4	775	520	1,048
		2	292	445	64
	Drawers	1	622	445	64
		1	622	445	64
6 6	Bottom Shelf	2	762	483	89
0	Top Compartment	—	762	483	64
Colors Available	KRBC10T	В	C	Order NO.	: 102008

Colors Available

- Auto locking mechanism locks drawers when lid is closed
- Plated fasteners resist corrosion and self locking nuts assure a rigid, secure assembly
- Non-toxic mats in shelf, drawers and top compartment protect unit and keep tools from sliding
- 🔺 warning 💷 🙆 🚺 🚷 Do not open multiple drawers
 Read safety precautions on page 162 3





25,070

Split top opening for tool access

• Cantilever trays on either side of cover, carrying handle

457 x 254 x 337



Tool Storage Tool Boxes



- Rugged construction featuring reinforced feet formed cantilever bars and larger hasps for strength in use
- Comfortable, recessed soft grip handle permits stacking of kits or other items in transit
- Cantilever design allows immediate visibility and access to all your tools
- Huge bottom section holds large items, such as power tools and larger hand tools
- Lightweight: 12.3 kg

Tool Box 18", 2 Drawers

KRW182B Order NO.: 103004



Cubic (cm ³)	Dimensions (mm)
18,630	470 x 216x 241

- Net weight: 5.67 kg
- Shipping weight: 6.58 kg



- Drawers lock when lid is closed
- Net weight: 9.07 kg



- Four drawers lock when lid is closed
- Tote tray not included
- Net weight: 11.07 kg

Plastic Tool Box 20"

BPBOX20 Order NO.: 103018







Tool Bag 17"





Order NO.: 103001 419 267 311

dth (mm)

240

- Rugged and versatile
- Constructed from heavy duty 600 x 300D polyester
- Water resistant
- Embroidered Blue-Point[®] logo
- Wide top opening for easy access
- Multiple interior and external pockets for tool organization

Plastic Tool Box 18"

BPBOX18 Order NO.: 103014

206

BPBOX20

YA481



• Steel pins for extra durable usage, connecting the lid and the box

ngth (mm)

445

- Strong handle and lock material
- Separate top tray to hold small tools

Plastic Tool Box 20"

	(Strate
NI	
35	
	and the second

Order NO.: 103018 558 277 270

- Larger capacity 20" box
- Made from shock-resistant ABS and PP for durability and toughness
- Light weight and portable
- Removable dividers
- Steel pins connecting the lid and box for strength
- Strong handle and lock material

Plastic Tool Box 15"



		Order NO.: 103009	
Length (mm)	Width (mm)	Height (mm)	
368	184	114	

- Ideal for a wide range of storage needs
- YA481 through YA486 are made of tough, injection molded plastic to ensure a precise fitting lid and durability
- Top carrying handle, tension latches, tote tray, and padlock provision are also featured

Plastic Tool Box 16"

YA482 Order NO · 103010



Length (mm)	Width (mm)	Height (mm)	
419	210	165	

- Ideal for a wide range of storage needs
- YA481 through YA486 are made of tough, injection molded plastic to ensure a precise fitting lid and durability
- Top carrying handle, tension latches, tote tray, and padlock provision are also featured

Plastic Tool Box 20"

•	YA483



- Ideal for a wide range of storage needs
- YA481 through YA486 are made of tough, injection molded plastic to ensure a precise fitting lid and durability
- Top carrying handle, tension latches, tote tray, and padlock provision are also featured

Plastic Tool Box 23"

YA484 dor NO · 103012



Length (mm) Width (mn	n) Height (mm)
587 260	267

- Ideal for a wide range of storage needs
- YA481 through YA486 are made of tough, injection molded plastic to ensure a precise fitting lid and durability
- Top carrying handle, tension latches, tote tray, and padlock provision are also featured

Plastic Tool Box 27"





- Ideal for a wide range of storage needs
- YA481 through YA486 are made of tough, injection molded plastic to ensure a precise fitting lid and durability
- Top carrying handle, tension latches, tote tray, and padlock provision are also featured



1470K-AC2

Tool Storage Roll Cab Accessories

Roll Cab Tops



Stock No.	Size (mm)	Description	Packing	Order No.
SKRWT4008	660	wooden top	1	101013
SKRWT4800B	1016	wooden top	1	101014
SKRSST4107	1016	stainless steel top	1	101015

• For use with all Blue-Point roll-cabs of respective sizes (KRB13008KPRB/R uses 1016mm, other models use 660mm)



- 1470K-AC2 Lockable holder for up to 23 pry bars or screwdrivers
- 18 Steel Gauge thickness
- PE paint, PE texture
- Applicable for Asia Market Only

Can Holder

1470K-AC3 Order NO.: 103022



- Slots-N-DotsTM side panel 822 x 419 x 20mm
- Can be hung or screwed on the roll cab side wall
- Mix and match storage accessories

Roll Cab Slots & Dots Side Panel

- 18 Steel Gauge thickness
- PE paint, PE texture

Foldable Tray

1470K-AC1 Order NO.: 103020

1470K-ACSIDE

Order NO.: 103019

Document Holder

1470K-AC4 Order NO.: 103023

7



- 1470K-AC4 14" Document holder
- 18 Steel Gauge thickness
- PE paint, PE texture
- Applicable for Asia Market Only



- 1470K-AC3 18" storage tray; holds up to 6 cans
- 18 Steel Gauge thickness
- PE paint, PE texture
- Applicable for Asia Market Only





• Applicable for Asia Market Only



Our tool sets comprise of quality tools each carefully selected to suit applications that the set is created for.

Every set is designed to avoid duplication of tools so that you can get a series of tool sets that are complimentary without having too many of the same tools.

Likewise, the tools in each set have been streamlined to cater more accurately to the task and environment it has been created for so you do not pay for tools you will not need.

You will likely find a set that fits your needs in our growing range of tool sets catered to meet today's most commonly faced applications.



Master Tool Sets







1/4" & 3/8" Drive Socket Set, 155pcs

BLPGSSC155 Order NO.: 201001 1/4" & 1/2" Drive Socket & Tool Set, 78pcs





Set Components (1/4" Drive):

- 10 fractional (3/16" to 9/16") and 13 metric (4 to 14mm) standard sockets
- 10 fractional (3/16" to 9/16") and 11 metric (4 to 14mm) deep sockets
- 20 assorted 1/4" hex bits with bit holder
- 5 ratchet/socket accessories
- 1 quick release ratchet

Set Components (3/8" Drive):

- 13 fractional (1/4" to 1") and 19 metric (6 to 24mm) standard sockets
- 11 fractional (3/8" to 1") and 15 metric (10 to 24mm) deep sockets
- 11 external Torx[®] sockets (E4 to E20)
- 2 spark plug sockets (5/8", 13/16")
- 3 metric hex socket drivers (7, 8, 10mm)
- 4 tamper resistant Torx[®] socket drivers (T40, T45, T50, T55)
- 6 ratchet/socket accessories
- 1 quick release ratchet
- 1 spinner handle
- Storage case included

Set Components (1/4" Drive):

- 12 sockets (4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13mm)
- 4 accessories (quick release ratchet, spinner handle, 4" extension bar and 1/4"F *1/4"H coupler)
 Set Components (1/2" Drive):
- 21 sockets (8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 27, 30, 32, 34mm)
- 7 accessories (quick release ratchet, 16mm & 21mm spark plug socket, 3", 6" & 10" extension bar, 3/8" F*1/2" M 3 way adapter) Set Components:
- 20 bits: hex bit (3, 4, 5, 6mm), Phillips[®] bits (#0, #1, #2, #3), square bit (S1 & S2), flat bit (4, 5, 5.5mm), Torx[®] bits (T8, T10, T15, T20, T25, T27, T30)
- 10 combination wrenches (10, 11, 12, 13, 14, 15, 16, 17, 18, 19mm)
- 3 pliers (side cutter (7"), long nose pliers (6"), slip joint pliers (10"))
- 1 adjustable wrench (8")
- Storage case included

1/4" & 1/2" Drive Socket & Tool Set





1/4". 3/8" & 1/2" Drive Torx[®] Bit Socket Set. 1/4" & 3/8" Drive Socket & Wrench Set. BLPGSSC100 Order NO.: 201002 100pcs 43pcs 14444 Set Components (1/4" Drive): Set Components (1/4" drive): • 10 fractional (3/16" to 9/16") and 13 metric (4 to 14mm) standard • 5 external Torx[®] sockets (E4 to E8) • 10 tamper resistant Torx[®] socket drivers (T6 to T10, T15, T20, T25, sockets 5 ratchet/socket accessories T27. T30) • 10 tamper resistant long Torx[®] socket drivers (T6 to T10, T15, T20, 1 ratchet Set Components (3/8" Drive): T25, T27, T30) Set Components (3/8" drive): • 13 fractional (1/4" to 1") and 19 metric (6 to 24mm) standard sockets • 4 external Torx[®] sockets (E10, E12, E14, E16) • 11 external Torx[®] sockets (E4 to E20) 3 tamper resistant Torx[®] socket drivers (T40, T45, T50)
3 tamper resistant long Torx[®] socket drivers (T40, T45, T50) • 2 spark plug sockets (5/8", 13/16") • 5 ratchet/socket accessories Set Components (1/2" drive):

- 1 ratchet
- 1 spinner handle
- Set Components (Combination Wrenches):
- 9 fractional combination wrenches (1/4" to 3/4")
- 10 metric combination wrenches (10 to 19mm)
- Storage case included

1/4" Drive Stubby Bit Socket Set, 40pcs

BLPBSS40 Order NO.: 201005



Storage case included

• 4 external Torx[®] sockets (E18, E20, E22, E34)

• 2 tamper resistant Torx[®] socket drivers (T55, T60)

• 2 tamper resistant long Torx[®] socket drivers (T55, T60)

BLPGSS1462 Order NO.: 201006



Set Components:

- 10 metric hex drivers (2, 2.5, 3, 4, 5, 6, 7, 8, 9, 10mm)
- 10 fractional hex drivers (5/64", 3/32", 7/64", 1/8", 5/32", 3/16", 7/32", 1/4", 5/16", 3/8")
- 10 Torx[®] tamper proof drivers (TP8, TP10, TP15, TP20, TP25, TP27, TP30, TP40, TP45, TP50)
- 6 XZN triple square drivers (XZN4, XZN5, XZN6, XZN8, XZN10, XZN12)
- 2 Phillips[®] drivers (#1, #2)
- 2 flat tip drivers (1/4", 3/8")
- Storage case included



Set Components:

- 11 fractional (3/16" to 5/8") and 11 metric (4mm to 14mm) standard sockets
- 11 fractional (3/16" to 5/8") and 11 metric (4mm to 14mm) deep sockets
- 1 bit holder
- 4 hex bits (9/64", 3/16", 7/32", 1/4")
- 3 flat tip bits (5/32", 3/16", 1/4")
- 2 Phillips[®] bits (#1, #2)
- 7 ratchet/socket accessories
- 1 ratchet
- Storage case included



BLPTSSC43 Order NO.: 201004





- 11 external Torx[®] sockets (E4 to E20)
- 1 Phillips[®] socket driver (#3)
- 2 Pozidriv[®] socket drivers (#3 and #4)
- 8 tamper resistant Torx® socket drivers (T10 to T45)
- 2 spark plug sockets (5/8", 13/16")
- 4 ratchet/socket accessories
- 1 ratchet
- 1 breaker bar
- 1 spinner handle
- Storage case included

- sockets
- 2 spark plug sockets (5/8", 13/16")
- 1 quick release ratchet
- 1 spinner handle
- 3 extensions (3", 6", 10")
 1 bit holder (3/8" drive)
- 4 hex bits (1/8", 5/32", 7/32", 1/4")
- 3 flat tip bits (5/32", 3/16", 1/4")
- 4 Phillips[®] tip bits (#0, #1, #2, #3)
- 2 square tip bits (#1, #2)
- 1 diagonal cutting pliers (7")
- 1 long nose pliers (6")
- 1 groove joint pliers (10")
- 1 adjustable wrench (8")
- Storage case included



3/8" Drive Socket Set, 49pcs

Set Components:

- 8 fractional (5/16" to 3/4") and 14 metric (6 to 19mm) standard 6 pt. sockets
- 8 fractional (5/16" to 3/4") and 13 metric (7 to 19mm) deep 12 pt. sockets
- 2 extensions (3", 6")
- 1 universal joint
- 1 3/8" female to 1/4" male Adaptor
- 1 ratchet
- Storage case included

3/8" Drive Socket & Wrench Set, 37pcs

BLPGSS3837 Order NO.: 201012

BLPGSS1233 Order NO.: 201014





Set Components:

- 8 fractional (5/16" to 3/4") and 14 metric (6 to 19mm) standard 6 pt. sockets
- 4 fractional (5/16"-3/8", 7/16"-1/2", 9/16"-5/8", 11/16"-3/4") and 5 metric (10-11mm, 12-13mm, 14-15mm, 16-17mm, 18-19mm) double open end wrenches
- 2 extensions (3", 6")
- 1 ratchet
- 1 universal joint
- 2 adaptors: 1/4" female x 3/8" male, 3/8" female x 1/4" male
- Storage case included

Pass Thru Socket Set, 22pcs

Order NO.: 201013

BLPGSS3849

Order NO.: 201011



Set Components:

- BLPPTS38 thru BLPPTS34 (3/8" to 3/4") sockets
- BLPPTSM8 thru BLPPTSM19 (8 to 19mm) metric sockets
- BLPPTA3438 pass thru adaptor
- BLPPTEXT3 extension and BPRFPT10 ratchet
- Storage case included



Set Components:

- 15 fractional (3/8" to 1 1/4") and 12 metric (12 to 24mm) standard sockets
- 1 breaker bar
- 1 universal joint
- 1 quick release ratchet
- 3 extensions (3", 6", 10")
- Storage case included



1/2" Drive Socket Set, 33pcs BLPPTSS3822



Master Tool Sets General Service Sets / Automotive Tool Sets

General Service Set. 27pcs

BLPGSS1427 Order NO.: 202010

1/4", 3/8" & 1/2" Drive Socket & Wrench Set, 100 pcs

BLPATSCM100 Order NO.: 202001





Imperial Set:

- 11 Fractional (3/16" to 5/8") 6 pt. Shallow Sockets
- 11 Fractional (3/16" to 9/16") 6 pt. Deep Sockets
- 3 Socket Adaptors/Extensions
- 1 Quick Release Ratchet & 1 Spinner Handle

FEATURES:

- Square Drive: 1/4"
- Good for automotive and home use
- Range of deep and shallow sockets for common fastener applications
- Ratchet and Handle Driver both available for a variety of jobs

3/8" Drive Socket Set, 77pcs

BLPATSM3877 Order NO.: 202005



- Set Components:
- 19 6 pt. sockets (6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24mm)
- 19 12 pt. deep sockets (6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24mm)
- 11 external Torx[®] sockets (E4, E5, E6, E7, E8, E10, E12, E14, E16, E18, E20)
- 4 hex bit sockets (6, 7, 8, 10mm)
- 2 Phillips[®] bit sockets (#3, #4)
- 2 PZ bit sockets (#3, #4)
- 8 tamper Torx[®] bit sockets (TT10, TT15, TT20, TT25, TT27, TT30, TT40, TT45)
- 12 accessories (quick release ratchet, 3", 6" & 10" extension bar, 16 & 21mm spark plug sockets, universal joint, 10" flexible handle, 3/8" female x 1/2" male adapter, 3/8" female x 1/4" male adapter, spinner handle, 8" sliding T-handle)
- Storage case included



Set Components (1/4" drive):

- 10 sockets (4, 5, 6, 7, 8, 9, 10, 11, 12, 13mm)
 10 deep sockets (4, 5, 6, 7, 8, 9, 10, 11, 12, 13mm)
- 6 accessories (quick release ratchet handle, spinner handle, 1 1/2" & 3" extension bar, universal joint, 6" flexible handle)
- 6 hex bit sockets (3, 4, 5, 6, 7, 8mm)
- 7 flat & Phillips[®] bit sockets (4, 5.5, 6.5mm, #0, #1, #2, #3)
- 4 PZ bit sockets (#0, #1, #2, #3)
- 7 tamper Torx[®] bit sockets (TT10, TT15, TT20, TT25, TT27, TT30, TT40)

Set Components (3/8" drive):

- 10 6 pt. sockets (10, 11, 12, 13, 14, 15, 16, 17, 18, 19mm)
- 10 deep 12 pt. sockets (10, 11, 12, 13, 14, 15, 16, 17, 18, 19mm)
 10 accessories (quick release ratchet, 3", 6" & 10" extension bar,
- 16mm & 21mm spark plug socket, universal joint, 10" flexible handle, 3/8" female x 1/4" male adapter, 8" sliding T-handle) Set Components (1/2" drive):
- 6 12 pt. sockets (20, 21, 22, 24, 27, 32mm)
- 8 6 pt. impact sockets (14, 15, 16, 17, 18, 19, 21, 22mm)
- 2 accessories (ratchet handle, 5" extension bar)
- Set Components: • 4 ratcheting wrenches (13, 14, 15, 17mm)
- Storage case included

1/4" Dr. Socket Set, 29pcs

BLPATSM1429 Order NO.: 202002



Set Components:

- 13 6 pt. sockets (4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13, 14mm)
- 11 6 pt. deep sockets (4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14mm)
- 5 accessories (quick release ratchet, spinner handle, 3" & 6" extension bar, universal joint)
- Storage case included



BI PATSM3824 Order NO.: 202004

Master Tool Sets Automotive Tool Sets

Automotive Tool Set. 120pcs

BI PATSCM120 Order NO.: 202008

FEATURES:

- Specially Catered to Automotive Workshop
- Complete Set of Common Tools Needed for Regular Passenger
- Vehicle Servicing
- Three Square Drive Sizes range of Sockets
- Oil-Filter Wrench
- Spark Plug Sockets
- Set of L-Shaped Wrenches
- Test Pen

Set Components:

- 1/4" Socket 4, 5, 6, 7, 8, 9, 10, 11, 12, 13mm
- 1/4" Deep Socket 8, 9, 10, 12mm
- 1/4" Ratchet
- 1/4" Spinner Handle
- 1/4" Extension Bar 3"
- 1/4"F*1/4"H Coupler
- 1/4" Universal Joint
- 1/4" Hex Bit Socket 3, 4, 5, 6, 7, 8mm
- 1/4" Flat Bit Socket 4, 5.5, 6.5mm
- 1/4" Phillips Bit Socket #1, #2, #3
- 1/4" Pozidriv Bit Socket #1, #2
- 1/4" Torx Bit Socket TT10, TT15, TT20, TT25, TT27, TT30, TT40
- 3/8" Socket 10, 11, 12, 13, 14, 15, 16, 17, 18, 19mm
 3/8" 12pt Deep Socket 13, 14, 15, 17mm
- 3/8" E8, E10, E11, E12, E14, E16, E18, E20
- 3/8" Ratchet
- 3/8" 3" Extension Bar, 6" Extension Bar
- 3/8" Spark Plug Socket 16, 21mm
- 3/8" Universal Joint
- 3/8" Female to 1/4" Male Adaptor
- 3/8" 8" Sliding Handle
- 1/2" 6pt. Socket 20, 21, 22, 24, 27, 32mm
- 1/2" Impact Socket 17, 19, 21, 23mm
- 1/2" Ratchet
- 1/2" 5" Extension Bar
- 1/2" 10" Extension Bar
- 1/2" Universal Joint
- 1/2" Female to 3/8" Male Adaptor
- Adjustable 3-Claw Oil Wrench
- Test Pen
- Hex Key Set (9pcs)
- Bit Set (20pc)
- Combi Wrench 8, 9, 10, 11, 12, 13, 14, 16, 17, 18, 19mm
- Socket for air cylinder T52

3/8" Drive Socket Set. 24pcs



Set Components:

- 10 12 pt. sockets (10, 11, 12, 13, 14, 15, 16, 17, 18, 19mm)
- 10 12 pt. deep sockets (10, 11, 12, 13, 14, 15, 16, 17, 18, 19mm)
- 4 accessories (quick release ratchet, 3" extension bar, 16 & 21mm spark plug sockets)
- Storage case included

1/4", 3/8" & 1/2" Socket Set, 128pcs

BLPATSCM128 Order NO .: 202007



Set Components (1/4" Drive):

- 10 6pt. metric (4 to 13mm) deep sockets
- 10 6pt. metric (4 to 13mm) standard sockets
- 24 socket driver: Flat (4, 5.5, 6.5mm), Hex (3, 4, 5, 6, 7, 8mm), Phillips[®] (#0, 1, 2, 3), Tamper Resistant Torx[®] (T10, 15, 20, 25, 27, 30, 40), Pozidriv[®] (#0, 1, 2, 3)
- 7 accessories (38mm & 75mm extension bar, universal joint, 6" flexible handle, 6" spinner handle, quick release ratchet handle, 1/4"F*1/4"H bit adaptor)
- 17 bits: Hex (1/8, 5/32, 3/16, 7/32, 1/4"), Flat (7/32, 3/16, 1/4, 9/32"), bit adaptor, Torx[®] (T8, T10, T15, T20, T25, T27, T30, T40) Set Components (3/8" Drive):
- 10 12pt. metric (10 to 19mm) deep sockets
- 10 6pt. metric (10 to 19mm) standard sockets
- 10 accessories (3/8" female x 1/4" male adaptor, 75mm, 150mm & 250mm extension bar, 10" flexible handle, quick release ratchet handle, universal joint, 8" sliding bar, 6pt. 16mm & 21mm spark plug socket)

Set Components (1/2" Drive):

- 6 6pt. metric (20, 21, 22, 24, 27, 32mm) standard sockets
- 8 6pt. metric (14, 15, 16, 17, 18, 19, 21, 22mm) impact sockets
- 3 accessories (125mm extension bar, quick release ratchet handle, ¼" female x ¼" hex coupler) Set Components:
- 4 ratcheting wrenches (13, 14, 15, 17mm)
- 9pcs hex key set (1.5, 2, 2.5, 3, 4, 5, 6, 8, 10mm)
- Storage case included



Master Tool Sets Automotive Tool Sets



BLPATSM1232 Order NO.: 202009 Impact Socket Set, 13pcs

BLPATSIMM3813 Order NO.: 202011



Set Components:

- 1/2" 6pt Socket 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 27, 30, 32mm
- 1/2" 12pt Socket 8, 10, 12, 13, 14, 17, 19mm
- 1/2" Ratchet
- 1/2" Extension Bar 5", 10"
- 1/2" Universal Joint
- 1/2" Sliding Adapter ½" F 3/8" M

FEATURES:

- For Automotive and General Fastener Tightening Jobs
- Square Drive: 1/2"
- Improves on existing BLPATSM1225
- Includes smaller sizes 8, 9 & 23 mm sockets
- Additional range of 12 points sockets
- Universal Joint Added for more Applications



Set Components:

• 3/8" Dr. Shallow Impact Socket 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19mm

FEATURES:

- Square Drive: 3/8"
- Catered to Complement 3/8" Impact Wrenches
- Automotive and Two-Wheelers Workshops
- Compact Set with Only Commonly Used Sizes
- Complements existing BLPATSIMM1215 (1/2")

1/2" Drive Socket Set, 25pcs

BLPATSM1225 Order NO.: 202003

1/2" Drive Impact Socket Set, 15pcs

BLPATSIMM1215 Order NO.: 202006



Set Components:

- 19 6 pt. sockets (10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 24, 27, 30, 32, 34, 36mm)
- 6 accessories (quick release ratchet, 5" & 10" extension bar, 3/8" female x 1/2" male 3 way adapter, 16 & 21mm spark plug socket)
- Storage case included



Set Components:

- 14 6 pt. impact sockets (10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 23, 24mm)
- 1 impact extension bar (5")
- Storage case included



BPS4P

Order NO.: 202015

Master Tool Sets Modular Tool Sets

Double Open End Wrench Set

BPS1 Order NO.: 202012



Set Components: • Double Open End Wrench 6x7, 8x9, 10x11, 12x13, 14x15, 16x17, 18x19, 20x22, 21x23, 24x27, 30x32mm



Set Components: • Combination Wrench 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19mm

Combination Wrench Set

45° Double Ring Wrench Set

BPS2 Order NO.: 202013

Ratcheting Combination Wrench Set

BPS5 Order NO.: 202016



Set Components: • 45° Double Ring Wrench 6x7, 8x9, 10x11, 12x13, 14x15, 16x17, 18x19, 20x22, 21x23, 24x27mm



Set Components: • Ratcheting Combination Wrench 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19mm

75° Double Ring Wrench Set

BPS3 Order NO.: 202014 Adjustable Wrench Set

BPS6 / BPS6A** Order NO.: 202017 / 202027



Set Components: • 75° Double Ring Wrench 6x7, 8x9, 10x11, 12x13, 14x15, 16x17, 18x19, 20x22, 21x23, 24x27mm



Set Components:

WARNING

- Adjustable Wrench, 8, 10"
- Curved Jaw Locking Pliers, 7"
- Straight Jaw Locking Pliers, 7"
- **BPS6A for China & India only



Master Tool Sets Modular Tool Sets

1/4" Square Drive Socket Set

BPS10 Order NO.: 202021

Standard Pliers Set

BPS7 Order NO.: 202018



Set Components:

- 1/4" Long Sockets 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14mm
- 1/4" Hex Socket Driver 3, 4, 5, 6, 7, 8mm
- 1/4" Flat Socket Driver 4, 5.5, 6.5mm
- 1/4" Phillips Socket Driver #1, 2, 3
- 1/4" Pozidriv Socket Driver #1, 2, 3
- 1/4" Torx Socket Driver T8, 10, 15, 20, 25, 27, 30, 40
- 1/4" Sockets 3.5, 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11,12, 13mm
- 1/4" Quick Release Ratchets Soft Handle
- 1/4" Spinner Handle
- 1/4" Extension Knurled 2.3/3.2"
- 1/4" Extension Knurled 4"
- 1/4" Sliding T-handle 4"
- 1/4" Universal Joint
- 1/4" Flexible Extension 6"
- 1/4" Bit Holder for 1/4" Hex
- 1/4" Adaptor 1/4"-3/8"

Set Components:

- 6" Needle Nose Pliers
- 6" Diagonal Cutting Pliers
- 8" Combination Pliers
- 8" Slip Joint Pliers

Circlip Pliers Set

BPS8 Order NO.: 202019

Screwdrivers Set

BPS9 Order NO.: 202020



Set Components:

- External Circlip Pliers, Straight, 7"
- External Circlip Pliers, 90 degrees, 7"
- Internal Circlip Pliers, Straight, 7"
- Internal Circlip Pliers, 90 degrees, 7"



Set Components:

- M Series Flat Tip 3.2x75, 5x100, 6x38, 6x150mm
- M Series Phillips Tip 0x75, 1x75, 2x38, 2x100, 3x150mm



BPS13

Order NO.: 202024

Master Tool Sets Modular Tool Sets

3/8" Square Drive Socket Set

BPS11 Order NO.: 202022

VEFFFFFFFFFFFFFFFFFFFFFF

Set Components:

- 3/8" Sockets 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24mm
- 3/8" Long Sockets 10, 11, 12, 13, 14, 15, 16, 17, 18, 19mm
- 3/8" Quick Release Ratchets Soft Handle
- 3/8" Spark Plug Sockets 16mm
- 3/8" Spark Plug Sockets 21mm
 3/8" Sliding T-handle 8"
- 3/8" Adaptor 3/8"-1/4"
- 3/8" Universal Joint
- 3/8" Locking Extension 3"



Set Components:

Impact Socket Set

- 1/2" Impact Sockets 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 24, 27, 30, 32mm
- 3/8" Impact Sockets 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19mm
- Impact Extensions 3/8" dr. x 3"
- 3/8" Dr. Adaptors 3/8"M x 1/4"F
- Impact Adaptors (M X F) 3/8" x 1/2"
- Impact Extensions 1/2" dr. x 6"
- Impact Adaptors (M X F) 1/2" x 3/8"
- Impact Adaptors (M X F) 1/2" x 3/4"
- Universal Joints 1/2" dr.

1/2" Square Drive Socket Set

BPS12 Order NO.: 202023 L-Shape Wrench Set

BPS14 Order NO.: 202025



Set Components:

- 1/2" Sockets 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 24, 27, 30, 32, 34mm
- 1/2" Long Sockets 10, 13, 17, 19, 22mm
- 1/2" Quick Release Ratchets Soft Handle
- 1/2" Sliding T-handle 15"
- 1/2" Universal Joint
- 1/2" Locking Extension 6"



Set Components:

- Ball Hex Keys Set 1.5-10mm
- L-Shape Torx Wrench Set T10-T50
- L-Shape Hex Keys 12, 14, 17, 19mm



SOCKETS, RATCHETS & ACCESSORIES

DUET GUE

Blue-Point sockets & ratchets are made combining high grade materials with the best manufacturing process available to ensure good performance and fit.

High Grade Materials

Sockets are made with high alloy content steel for a stronger, more durable tool.

Best Industrial Manufacturing Process

In making each socket, we employ the best manufacturing process available, adhering to exact treatment conditions and parameters to give it a good mixture of strength and durability.

Better Socket Design

Our sockets are thin-walled with appropriate broach depth to provide greater access into tight spots and fit better for more applications.

Patented Wrenching System

Flank Drive[®] is also incorporated into our socket design to achieve a higher torque while preventing rounding of fasteners.





High Efficiency

1/4"

22

3/8"

27

1/2"

33

3/4"

3

The ratcheting gear in Blue-Point ratchets feature high teeth count for working with a shorter swing arc. This allows jobs to be done in tight spots as well as enhancing work output with lesser swings needed.

We incorporate better design and concept wherever applicable to make a better performing tool. Blue-point sockets & ratchets are tools manufactured to the highest quality.



1/4" Socket, mm



Stock No.	Size (mm)	Length (mm)	Ŵ	Order No.
BLPSM143.5	3.5	25	6	301001
BLPSM144	4	25	6	301002
BLPSM144.5	4.5	25	6	301003
BLPSM145	5	25	6	301004
BLPSM145.5	5.5	25	6	301005
BLPSM146	6	25	6	301006
BLPSM147	7	25	6	301007
BLPSM148	8	25	6	301008
BLPSM149	9	25	6	301009
BLPSM1410	10	25	6	301010
BLPSM1411	11	25	6	301011
BLPSM1412	12	25	6	301012
BLPSM1413	13	25	6	301013
BLPSM1414	14	25	6	301014

Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

1/4" Long Socket, mm



Stock No.	Size (mm)	Length (mm)	Ŵ	Order No.
BLPLSM144	4	50	6	301015
BLPLSM145	5	50	6	301016
BLPLSM146	6	50	6	301017
BLPLSM147	7	50	6	301018
BLPLSM148	8	50	6	301019
BLPLSM149	9	50	6	301020
BLPLSM1410	10	50	6	301021
BLPLSM1411	11	50	6	301022
BLPLSM1412	12	50	6	301023
BLPLSM1413	13	50	6	301024
BLPLSM1414	14	50	6	301025

• Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

1/4" Socket, inches



Stock No.	Size (inches)	Length (mm)	i	Order No.
BLPS14532	⁵ / ₃₂	25	6	301026
BLPS14316	^{3/} 16	25	6	301027
BLPS14732	7/32	25	6	301028
BLPS1414	1/4	25	6	301029
BLPS14932	⁹ / ₃₂	25	6	301030
BLPS14516	^{5/} 16	25	6	301031
BLPS141132	¹¹ / ₃₂	25	6	301032
BLPS1438	3/8	25	6	301033
BLPS14716	7/16	25	6	301034
BLPS1412	1/2	25	6	301035
BLPS14916	⁹ /16	25	6	301036
BLPS1458	5/8	25	6	301037

• Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

1/4" Long Socket, inches



BLPLS14316 ³ / ₁₆ 50 6 301038 BLPLS14732 ⁷ / ₃₂ 50 6 301039 BLPLS14732 ⁷ / ₃₂ 50 6 301040 BLPLS1414 ¹ / ₄ 50 6 301040 BLPLS1414 ¹ / ₄ 50 6 301040 BLPLS14932 ⁹ / ₃₂ 50 6 301041 BLPLS14516 ⁵ / ₁₆ 50 6 301042 BLPLS14132 ¹¹ / ₃₂ 50 6 301043 BLPLS14138 ³ / ₈ 50 6 301044 BLPLS14716 ⁷ / ₁₆ 50 6 301045 BLPLS14712 ¹ / ₂ 50 6 301046 BLPLS14916 ⁹ / ₁₆ 50 6 301047	Stock No.	Size (inches)	Length (mm)	i	Order No.
BLPLS1414 $1/4$ 50 6 301040 BLPLS1413 $9/32$ 50 6 301041 BLPLS14516 $5/16$ 50 6 301042 BLPLS14516 $5/16$ 50 6 301043 BLPLS141132 $11/32$ 50 6 301043 BLPLS14138 $3/6$ 50 6 301044 BLPLS14716 $7/16$ 50 6 301045 BLPLS1412 $1/2$ 50 6 301046 BLPLS14916 $9/18$ 50 6 301047	BLPLS14316	^{3/} 16	50	6	301038
BLPLS1414 10 60 6 301041 BLPLS14932 9/32 50 6 301041 BLPLS14932 9/32 50 6 301041 BLPLS14516 5/16 50 6 301042 BLPLS141132 11/32 50 6 301043 BLPLS1438 3/8 50 6 301044 BLPLS14716 7/16 50 6 301045 BLPLS1412 1/2 50 6 301046 BLPLS14916 9/16 50 6 301047	BLPLS14732	7/32	50	6	301039
BLPLS14516 5/16 50 6 301042 BLPLS14516 5/16 50 6 301042 BLPLS141132 11/32 50 6 301043 BLPLS14318 3/8 50 6 301044 BLPLS14716 7/16 50 6 301045 BLPLS1412 1/2 50 6 301046 BLPLS14916 9/16 50 6 301047	BLPLS1414	1/4	50	6	301040
BLPLS141132 11/b2 50 6 301043 BLPLS141132 11/b2 50 6 301043 BLPLS1438 3/a 50 6 301044 BLPLS14716 7/16 50 6 301045 BLPLS1412 1/z 50 6 301046 BLPLS14916 9/16 50 6 301047	BLPLS14932	9/32	50	6	301041
BLPLS1438 3/8 50 6 301044 BLPLS14716 7/16 50 6 301045 BLPLS1412 1/2 50 6 301046 BLPLS14916 9/16 50 6 301047	BLPLS14516	^{5/} 16	50	6	301042
BLPLS14716 7/16 50 6 301045 BLPLS1412 1/2 50 6 301046 BLPLS14916 9/16 50 6 301047	BLPLS141132	11/32	50	6	301043
BLPLS1412 1/2 50 6 301046 BLPLS14916 9/16 50 6 301047	BLPLS1438	³ /8	50	6	301044
BLPLS14916 ^{9/} 16 50 6 301047	BLPLS14716	7/16	50	6	301045
	BLPLS1412	1/2	50	6	301046
	BLPLS14916	^{9/} 16	50	6	301047
BLPLS1458 ⁵ / ₈ 50 6 301048	BLPLS1458	⁵ /8	50	6	301048

Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards



1/4" Double Square Socket





Stock No.	Size (inches)	Length (mm)	i	Order No.
BLPS81414	1/4	25	6	301049
BLPS814516	⁵ / ₁₆	25	6	301050
BLPS81438	3/8	25	6	301051

Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

1/4" External Torx[®] Socket



Stock No.	Size	Length (mm)	i	Order No.
BLPTE144	E4	25	6	301052
BLPTE145	E5	25	6	301053
BLPTE146	E6	25	6	301054
BLPTE147	E7	25	6	301055
BLPTE148	E8	25	6	301056

• Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

Finger Ratchet



Stock No.	Square Drive (inches)	i i i i i i i i i i i i i i i i i i i	Order No.
FSD14	^{3/8} male- ^{1/4} female	1	301059
FSD38	^{1/4} male- ^{3/8} female	1	301060
FSDR	^{1/4} male- ^{1/4} female	1	301061

- Reversible, finger ratchet
- Small size works great for extremely tight areas
- Aluminum knurled outer ring for sure grip



	143	RKRBPRTR936
•	Features quick release butto even with greasy or oily hand	n for rapid socket/accessory changes, ds

- Contoured handle for comfort and control
- Chrome finish for easy clean-up

- All ratchets in series meet or exceed ANSI B107-10M-1996 specifications
- Uses RKRBPRTR936 ratchet service kit

1/4" Quick Release Ratchet, Soft Grip Packing: 1

BPRTR936SG Order NO.: 301058



Square Drive (inches)	Description Gear Teeth		
1/4	Soft Grip Handle 36		
Swing Arc	A (mm)	B (mm)	
10°	12 25		
C (mm)	Repair Kit		
143	RKRBPRTR936		

- Features quick release button for rapid socket/accessory changes, even with greasy or oily hands
- · Corrosive resistant bi-mold cushion grip for improved comfort and performance
- Chrome finish for easy clean-up
- All ratchets in series meet or exceed ANSI B107-10M-1996 specifications
- Uses RKRBPRTR936 ratchet service kit





1/4" Extension, Knurled



Stock No.	Length (mm)	i	Order No.
BLPTXK1.5	40	6	301062
BLPTXK2	51	6	301063
BLPTXK3	76	6	301064
BLPTXK4	102	6	301065
BLPTXK6	152	6	301066

Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

1/4" Breaker Bar Packing: 6 Stock No. BLPBB146 Length (mm) BLPBB146 152

N

114

• Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

1/4" Extension, Extra Long Locking

1/4" Sliding T-handle, 4"

BLPSTHD144 Order NO.: 301072

BLPCGHD146

Order NO.: 301073



 \mathbb{T}

BLPEXTF146

Order NO.: 301070

Stock No.	Length (mm)	i i i i i i i i i i i i i i i i i i i	Order No.
BLPEXTL1412	305	6	301067
BLPEXTL1418	457	6	301068
BLPEXTL1424	610	6	301069

- Smooth, durable chrome finish
- Made from tough 6130 steel
- Secure socket retention
- Lifetime warranty on individual extensions
- Do not use with power or impact tools

1/4" Flexible Extension

Packing: 6



- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



Manufactured from high grade steel alloy

Manufactured from high grade steel alloy

1/4" Spinner Handle

Packing: 6

• Features a Lifetime Warranty and exceeds ANSI Standards

Features a Lifetime Warranty and exceeds ANSI Standards



1/4" Universal Joint



38

BI PU.J14

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards

1/4" Torx[®] Socket Driver

BLPUJ14

Order NO.: 301074



Stock No.	Size	Length (mm)	1	Order No.
BLPTS0148	T8	19	6	301077
BLPTS01410	T10	19	6	301078
BLPTS01415	T15	19	6	301079
BLPTS01420	T20	19	6	301080
BLPTS01425	T25	19	6	301081
BLPTS01427	T27	19	6	301082
BLPTS01430	T30	19	6	301083
BLPTS01440	T40	19	6	301084
BLPTS01445	T45	19	6	301085
BLPTS01447	T47	19	6	301086
BLPTS01450	T50	19	6	301087

- The BLPTS Series of Stubby Torx[®] socket drivers feature a reduced fastener depth penetration to increase strength and improve fastener engagement
- Manufactured from S2 Steel for longer tool life

1/4" Hex Socket Driver



Stock No.	Size (mm)	Length (mm)		Order No.
BLPHSM0142	2	19	6	301088
BLPHSM01425	2.5	19	6	301089
BLPHSM0143	3	19	6	301090
BLPHSM0144	4	19	6	301091
BLPHSM0145	5	19	6	301092
BLPHSM0146	6	19	6	301093
BLPHSM0147	7	19	6	301094
BLPHSM0148	8	19	6	301095
BLPHSM0149	9	19	6	301096
BLPHSM01410	10	19	6	301097

- The BLPHSM Series of Stubby Hex socket drivers feature a reduced fastener depth penetration to increase strength and improve fastener engagement
- Manufactured from S2 Steel for longer tool life

1/4" Hex Socket Driver, Tamper Resistant

	M T
Colort men	

Stock No.	Size (mm)	Length (mm)		Order No.
BLPTHSM0142	2	19	6	301098
BLPTHSM01425	2.5	19	6	301099
BLPTHSM0143	3	19	6	301100
BLPTHSM0144	4	19	6	301101
BLPTHSM0145	5	19	6	301102
BLPTHSM0146	6	19	6	301103
BLPTHSM0147	7	19	6	301104
BLPTHSM0148	8	19	6	301105
BLPTHSM0149	9	19	6	301106
BLPTHSM01410	10	19	6	301107

- The BLPTHSM Series of Stubby Hex Tamper Resistant socket drivers feature a reduced fastener depth penetration to increase strength and improve fastener engagement
- Manufactured from S2 Steel for longer tool life



• Features a Lifetime Warranty and exceeds ANSI Standards

1/4" Bit Holder

🂗 Packing: 6

BLPTMBS1414



- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



BLPTMBS1414 Order NO.: 301076



1/4" Phillips[®] Socket Driver



- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards

1/4" Phillips[®] Socket Driver, Stubby



- Stubby Phillips[®] socket drivers feature a reduced fastener depth penetration to increase strength and improve fastener engagement
- Manufactured from S2 Steel for longer tool life

1/4" Pozidriv[®] Socket Driver



- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards

1/4" Triple Square Socket Driver



	Stock No.	Size (mm)	Length (mm)		Order No.
	BLPXZN144	4	27	6	301132
7 T	BLPXZN145	5	27	6	301133
	BLPXZN146	6	27	6	301134
٦÷	BLPXZN148	8	27	6	301135
	BLPXZN1410	10	27	1	301136
J	BLPXZN1412	12	27	1	301137

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards

1/4" Torx, Tamper Resistant



Stock No.	Square Drive (inches)		#]	۲	Order No.
BLPT146TP	1/4	1 ⁷ / ₁₆	T6	1	301138
BLPT147TP	1/4	1 ^{7/} 16	T7	1	301139
BLPT148TP	1/4	1 ⁷ / ₁₆	Т8	1	301140
BLPT149TP	1/4	1 ^{7/} 16	Т9	1	301141
BLPT1410TP	1/4	1 ⁷ / ₁₆	T10	1	301142
BLPT1415TP	1/4	1 ^{7/} 16	T15	1	301143
BLPT1420TP	1/4	1 ⁷ /16	T20	1	301144
BLPT1425TP	1/4	1 ^{7/} 16	T25	1	301145
BLPT1427TP	1/4	1 ⁷ /16	T27	1	301146
BLPT1430TP	1/4	1 ^{7/} 16	T30	1	301147

Manufactured from high grade steel allov

• Features a Lifetime Warranty and exceeds ANSI Standards

1/4" Flat Tip Socket Driver, Standard



M T	Stock No.	Size (inches)	Size (mm)	Length (mm)	Ŵ	Order No.
	BLPFT144	⁵ / ₃₂	4	37	6	301118
jen j	BLPFT145.5	7/ ₃₂	5.5	37	6	301119
\Box	BLPFT146.5	⁹ / ₃₂	6.5	37	6	301120

Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

1/4" Flat Tip Socket Driver, Short

301115

301116

301117



Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards



3/8" Socket



3/8" Socket, mm



FD	Τ
9	
	Ĩ
Ì	1

Stock No.	Size (mm)	Length (mm)	۲	Order No.	Stock No.	Size (mm)	Length (mm)	()	Order No.
BLPSM386	6	25.5	6	302001	BLPSM3816	16	27	6	302011
BLPSM387	7	25.5	6	302002	BLPSM3817	17	27	6	302012
BLPSM388	8	25.5	6	302003	BLPSM3818	18	27	6	302013
BLPSM389	9	25.5	6	302004	BLPSM3819	19	29	6	302014
BLPSM3810	10	25.5	6	302005	BLPSM3820	20	29	6	302015
BLPSM3811	11	25.5	6	302006	BLPSM3821	21	29	6	302016
BLPSM3812	12	25.5	6	302007	BLPSM3822	22	31	6	302017
BLPSM3813	13	25.5	6	302008	BLPSM3823	23	31	6	302018
BLPSM3814	14	27	6	302009	BLPSM3824	24	31	6	302019
BLPSM3815	15	27	6	302010					

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards







Stock No.	Size (mm)	Length (mm)	۲	Order No.	Stock No.	Size (mm)	Length (mm)	()	Order No.
BLPLM386	6	64	6	302020	BLPLM3816	16	64	6	302030
BLPLM387	7	64	6	302021	BLPLM3817	17	64	6	302031
BLPLM388	8	64	6	302022	BLPLM3818	18	64	6	302032
BLPLM389	9	64	6	302023	BLPLM3819	19	64	6	302033
BLPLM3810	10	64	6	302024	BLPLM3820	20	64	6	302034
BLPLM3811	11	64	6	302025	BLPLM3821	21	64	6	302035
BLPLM3812	12	64	6	302026	BLPLM3822	22	64	6	302036
BLPLM3813	13	64	6	302027	BLPLM3823	23	64	6	302037
BLPLM3814	14	64	6	302028	BLPLM3824	24	64	6	302038
BLPLM3815	15	64	6	302029					

• Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards



3/8" Socket, inches



Stock No.	Size (inches)	Length (mm)		Order No.
BLPS3814	1/4	25	6	302039
BLPS38516	⁵ /16	25	6	302040
BLPS3838	3/8	25	6	302041
BLPS38716	7/ ₁₆	25	6	302042
BLPS3812	1/2	25	6	302043
BLPS38916	^{9/} 16	27	6	302044
BLPS3858	5/ ₈	27	6	302045
BLPS381116	¹¹ / ₁₆	27	6	302046
BLPS3834	3/4	29	6	302047
BLPS381316	¹³ / ₁₆	29	6	302048
BLPS3878	7/8	29	6	302049
BLPS381516	^{15/} 16	29	6	302050
BLPS381	1	29	6	302051

Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

3/8" Long Socket, inches

	Stock No.	Size (inches)	Length (mm)		Order No.
	BLPL3814	1/4	64	6	302052
	BLPL38516	5/ ₁₆	64	6	302053
	BLPL3838	³ /8	64	6	302054
	BLPL38716	7/ ₁₆	64	6	302055
	BLPL3812	1/2	64	6	302056
and the second sec	BLPL38916	9/ ₁₆	64	6	302057
Carlan Internet	BLPL3858	⁵ /8	64	6	302058
	BLPL381116	^{11/} 16	64	6	302059
	BLPL3834	3/4	64	6	302060
ATD I	BLPL381316	^{13/} 16	64	6	302061
	BLPL3878	7/8	64	6	302062
	BLPL381516	^{15/} 16	64	6	302063
	BLPL381	1	64	6	302064

• Manufactured from high grade steel alloy

Features a Lifetime Warranty and exceeds ANSI Standards

3/8" External Torx® Socket



Stock No.	Size	Length (mm)		Order No.
BLPTE384	E4	31	6	302065
BLPTE385	E5	31	6	302066
BLPTE386	E6	31	6	302067
BLPTE387	E7	31	6	302068
BLPTE388	E8	31	6	302069
BLPTE3810	E10	31	6	302070
BLPTE3811	E11	31	6	302071
BLPTE3812	E12	31	6	302072
BLPTE3814	E14	31	6	302073
BLPTE3816	E16	31	6	302074
BLPTE3818	E18	31	6	302075
BLPTE3820	E20	31	6	302076

Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

- Features quick release button for rapid socket/accessory changes, even with greasy or oily hands
- Contoured handle for comfort and control
- Chrome finish for easy clean-up
- All ratchets in series meet or exceed ANSI B107-10M-1996 specifications

3/8" Quick Release Ratchet, Soft Grip

じ Packing: 1

BPRFR938SG

Order NO.: 302082



- 197
 RKRBPRFR938

 • Features quick release button for rapid socket/accessory changes,
- even with greasy or oily hands
- Corrosive resistant bi-mold cushion grip for improved comfort and performance
- Chrome finish for easy clean-up
- All ratchets in series meet or exceed ANSI B107-10M-1996 specifications

Finger Ratchet



Stock No.	Square Drive (inches)	i	Order No.
FSDR1	^{3/8} male- ^{1/4} female	1	302083
FSD1	^{3/8} male- ^{3/8} female	1	302084

• Reversible, finger ratchet

• Small size works great for extremely tight areas

Aluminum knurled outer ring for sure grip

28





WARNING

Do not use chrome or industrial finish hand tools with impact drivers 29
 Read safety precautions on page 162



3/8" Universal Joint

- Manufactured from high-grade alloy steel
- Offering same quality and features as our sockets with lifetime warranty

nore working



- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards

- Smooth, durable chrome finish
- Made from tough 6130 steel
- Secure socket retention
- Lifetime warranty on individual extensions



Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

3/8" Adaptor

10						
-	A T	Stock No.	Internal Square Drive (inches)	External Square Drive (inches)	۲	Order No.
into a off	Ð.	BLPAFM3814	3/8	1/4	6	302097
ULL BLIG		BLPAFM3812	3/8	1/2	6	302098

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards

3/8" Bit Holder

📦 Packing: 6

Stock No.	Length (mm)	Description
BLPTMBS3814	19	For 1/4" Hex Bits
BLPTMBS3814	19	For ^{1/4} " Hex Bits
F		

BLPTMBS3814 Order NO.: 302099

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards

Pass Thru Socket

- Anna	
1	
	j

	Stock No.	Size (inches)	Length (mm)	Ĩ	Order No.
	BLPPTS38	3/8	37	6	302101
	BLPPTS716	7/ ₁₆	37	6	302102
٩T	BLPPTS12	1/2	37	6	302103
	BLPPTS916	^{9/} 16	37	6	302104
	BLPPTS58	⁵ /8	37	6	302105
	BLPPTS1116	^{11/} 16	37	6	302106
1	BLPPTS34	3/4	37	6	302107
-					

- Pass thru socket design avoids "bottoming out" on long fasteners and threaded rods
- Sockets can reach fasteners in tight spaces with relative ease

3/8"	Tory	Tamper	Resistant
3/0	IUIX,	Tamper	resistant



1 27/32 BLPT3810TP 3/8 T10 302166 1 3/8 1 27/32 T15 302167 1 3/8 1 27/32 T20 302168 1 3/8 1 27/32 T25 1 302169 3/8 1 27/32 T27 302170 1 3/8 1 ²⁷/₃₂ Т30 302171 1 3/8 2 T40 1 302172 BL<u>PT38</u>45TF ³/8 2 T45 1 302173 3/8 2 T50 302174 1 3/8 **BLPT**3 2 T55 1 302155

• Manufactured from high grade steel alloy

Features a Lifetime Warranty and exceeds ANSI Standards

3/8" Torx[®] Socket Driver



Stock No.	Size	Length (mm)		Order No.
BLPTS3810	T10	48	6	302123
BLPTS3815	T15	48	6	302124
BLPTS3820	T20	48	6	302125
BLPTS3825	T25	48	6	302126
BLPTS3827	T27	48	6	302127
BLPTS3830	T30	48	6	302128
BLPTS3840	T40	51	6	302129
BLPTS3845	T45	51	6	302130
BLPTS3850	T50	51	6	302131
BLPTS3855	T55	51	6	302132
BLPTS3860	T60	51	6	302133

• Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

Pass Thru Socket



Stock No.	Size (mm)	Length (mm)	۲	Order No.
BLPPTSM8	8	37	6	302108
BLPPTSM9	9	37	6	302109
BLPPTSM10	10	37	6	302110
BLPPTSM11	11	37	6	302111
BLPPTSM12	12	37	6	302112
BLPPTSM13	13	37	6	302113
BLPPTSM14	14	37	6	302114
BLPPTSM15	15	37	6	302115
BLPPTSM16	16	37	6	302116
BLPPTSM17	17	37	6	302117
BLPPTSM18	18	37	6	302118
BLPPTSM19	19	37	6	302119

- Pass thru socket design avoids "bottoming out" on long fasteners and threaded rods
- Sockets can reach fasteners in tight spaces with relative ease

3/8" Phillips[®] Socket Driver

		Stock No.	Size	Length (mm)		Order No.
	M T	BLPP381	#1	47	6	302141
22.8		BLPP382	#2	47	6	302142
14. 11 3. A.	Мi	BLPP383	#3	47	6	302143
	Ы	BLPP384	#4	47	6	302144

• Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards





3/8" Pozidriv[®] Socket Driver



	Stock No.	Size	Length (mm)	Ĩ	Order No.
ΠT	BLPPD381	#1	47	6	302145
	BLPPD382	#2	47	6	302146
Щi	BLPPD383	#3	47	6	302147
- MI	BLPPD384	#4	47	6	302148

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards

3/8" Flat Socket Driver

Pass Thru Extention

 \mathcal{T}

じ Packing: 6

ബ

3" extension

• 3/8" drive



- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



Packing: 6

BLPPTA3438 Order NO.: 302122



Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards



- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards

3/8" Hex Socket Driver

		Stock No.	Size (mm)	Length (mm)		Order No.
		BLPH383	3	47	6	302134
		BLPH384	4	47	6	302135
	PH T	BLPH385	5	47	6	302136
		BLPH386	6	47	6	302137
2		BLPH387	7	47	6	302138
Print 1		BLPH388	8	50.5	6	302139
BU BI		BLPH3810	10	50.5	6	302140

SLOCK NO.	3120 (11111)	Lengui (min)		Order No.
BLPH383	3	47	6	302134
BLPH384	4	47	6	302135
BLPH385	5	47	6	302136
BLPH386	6	47	6	302137
BLPH387	7	47	6	302138
BLPH388	8	50.5	6	302139
BLPH3810	10	50.5	6	302140

Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

3/8" Triple Square Socket Driver

	014		
		Ì.	
		L	
-	-		
		-	

BLPPTEXT3 Order NO.: 302121

76

	Stock No.	Size	Length (mm)	(Order No.
	BLPXZNM0384	M4	27	6	302157
Τ	BLPXZNM0385	M5	27	6	302158
	BLPXZNM0386	M6	27	6	302159
λÌ	BLPXZNM0388	M8	27	6	302160
	BLPXZNM03810	M10	27	6	302161
JŢ	BLPXZNM03812	M12	27	6	302162

Manufactured from high grade steel alloy

Features a Lifetime Warranty and exceeds ANSI Standards

- Pass Thru Ratchet BPRFPT10 Packing: 6 Order NO.: 302120 254
- Ratchet features a flex head design that allows for seven different locking positions


1/2" Socket, mm



Stock No.	Size (mm)	Length (mm)	۲	Order No.	Stock No.	Size (mm)	Length (mm)	1	Order No.
BLPSM128	8	38	6	303001	BLPSM1219	19	38	6	303012
BLPSM129	9	38	6	303002	BLPSM1220	20	38	6	303013
BLPSM1210	10	38	6	303003	BLPSM1221	21	38	6	303014
BLPSM1211	11	38	6	303004	BLPSM1222	22	38	6	303015
BLPSM1212	12	38	6	303005	BLPSM1223	23	38	6	303016
BLPSM1213	13	38	6	303006	BLPSM1224	24	38	6	303017
BLPSM1214	14	38	6	303007	BLPSM1227	27	38	6	303018
BLPSM1215	15	38	6	303008	BLPSM1230	30	38	6	303019
BLPSM1216	16	38	6	303009	BLPSM1232	32	38	6	303020
BLPSM1217	17	38	6	303010	BLPSM1234	34	38	6	303021
BLPSM1218	18	38	6	303011	BLPSM1236	36	38	6	303022

Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

1/2" Socket, inches





Stock No.	Size (inches)	Length (mm)		Order No.	Stock No.	Size (inches)	Length (mm)		Order No.
BLPS12516	⁵ / ₁₆	38	6	303040	BLPS121316	¹³ / ₁₆	38	6	303048
BLPS1238	3/8	38	6	303041	BLPS1278	7/8	38	6	303049
BLPS12716	⁷ / ₁₆	38	6	303042	BLPS121516	^{15/} 16	40	6	303050
BLPS1212	1/2	38	6	303043	BLPS121	1	40	6	303051
BLPS12916	⁹ / ₁₆	38	6	303044	BLPSB121116	1 ¹ /16	40	6	303052
BLPS1258	5/ ₈	38	6	303045	BLPSB12118	1 ^{1/8}	44	6	303053
BLPS121116	¹¹ /16	38	6	303046	BLPSB121316	1 ³ /16	44	6	303054
BLPS1234	3/4	38	6	303047	BLPSB12114	1 ^{1/4}	44	6	303055

Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

1/2" Long Socket, mm



Stock No.	Size (mm)	Length (mm)	()	Order No.	Stock No.	Size (mm)	Length (mm)	Ŵ	Order No.
BLPLM1210	10	76	6	303023	BLPLM1219	19	76	6	303032
BLPLM1211	11	76	6	303024	BLPLM1220	20	76	6	303033
BLPLM1212	12	76	6	303025	BLPLM1221	21	76	6	303034
BLPLM1213	13	76	6	303026	BLPLM1222	22	76	6	303035
BLPLM1214	14	76	6	303027	BLPLM1224	24	76	6	303036
BLPLM1215	15	76	6	303028	BLPLM1227	27	76	6	303037
BLPLM1216	16	76	6	303029	BLPLM1230	30	76	6	303038
BLPLM1217	17	76	6	303030	BLPLM1232	32	76	6	303039
BLPLM1218	18	76	6	303031					

Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

1/2" Long Socket, inches



	1
	l
>	1

Stock No.	Size (inches)	Length (mm)	1	Order No.	Stock No.	Size (inches)	Length (mm)		Order No.
BLPL1238	3/8	76	6	303056	BLPL121316	^{13/} 16	76	6	303063
BLPL12716	⁷ / ₁₆	76	6	303057	BLPL1278	7/8	76	6	303064
BLPL1212	1/2	76	6	303058	BLPL121516	^{15/} 16	76	6	303065
BLPL12916	^{9/} 16	76	6	303059	BLPL121	1	76	6	303066
BLPL1258	5/ ₈	76	6	303060	BLPLB121116	1 ^{1/} 16	76	6	303067
BLPL121116	¹¹ / ₁₆	76	6	303061	BLPLB12118	1 ¹ /8	76	6	303068
BLPL1234	3/4	76	6	303062	BLPLB125114	1 ^{1/} 4	76	6	303069

Manufactured from high grade steel alloy





1/2" Double Hex Socket, mm



Stock No.	Size (mm)	Length (mm)		Order No.	Stock No.	Size (mm)	Length (mm)		Order No.
BLPDM128	8	38	6	303070	BLPDM1218	18	38	6	303080
BLPDM129	9	38	6	303071	BLPDM1219	19	38	6	303081
BLPDM1210	10	38	6	303072	BLPDM1220	20	38	6	303082
BLPDM1211	11	38	6	303073	BLPDM1221	21	38	6	303083
BLPDM1212	12	38	6	303074	BLPDM1222	22	38	6	303084
BLPDM1213	13	38	6	303075	BLPDM1223	23	38	6	303085
BLPDM1214	14	38	6	303076	BLPDM1224	24	38	6	303086
BLPDM1215	15	38	6	303077	BLPDM1227	27	38	6	303087
BLPDM1216	16	38	6	303078	BLPDM1230	30	38	6	303088
BLPDM1217	17	38	6	303079	BLPDM1232	32	38	6	303089

• Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

1/2" Double Hex Socket, inches



Stock No.	Size (inches)	Length (mm)		Order No.	Stock No.	Size (inches)	Length (mm)	۲	Order No.
BLPD12516	⁵ /16	38	6	303090	BLPD121316	¹³ /16	38	6	303098
BLPD1238	3/8	38	6	303091	BLPD1278	7/8	41	6	303099
BLPD12716	7/16	38	6	303092	BLPD121516	¹⁵ /16	41	6	303100
BLPD1212	1/2	38	6	303093	BLPD121	1	41	6	303101
BLPD12916	^{9/} 16	38	6	303094	BLPDB121116	1 ¹ / ₁₆	44	6	303102
BLPD1258	⁵ /8	38	6	303095	BLPDB12118	1 ¹ /8	44	6	303103
BLPD121116	11/16	38	6	303096	BLPDB12114	1 ^{1/} 4	44	6	303104
BLPD1234	3/4	38	6	303097					

• Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

1/2" External Torx[®] Socket

	Ð
fond es	

	Stock No.	Size	Length (mm)		Order No.
	BLPTE1210	E10	38	6	303105
	BLPTE1212	E12	38	6	303106
	BLPTE1214	E14	38	6	303107
	BLPTE1216	E16	38	6	303108
Ť	BLPTE1218	E18	38	6	303109
	BLPTE1220	E20	38	6	303110
L	BLPTE1222	E22	38	6	303111
	BLPTE1224	E24	38	6	303112

Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

1/2" Quick Release Ratchet BPRSR940 Packing: 1 Order NO.: 303117



(Incnes)		
1/2	Standard Handle	40
Swing Arc	A (mm)	B (mm)
9°	18	44
C (mm)	Repair Kit	
251	RKRBPRSR	940

- Features quick release button for rapid socket/accessory changes, even with greasy or oily hands
- Contoured handle for comfort and control
- Chrome finish for easy clean-up

All ratchets in series meet or exceed ANSI B107-10M-1996 specifications

1/2" Torx, Tamper Resistant



Manufactured from high grade steel alloy



1/2" Spark Plug Socket, mm BLPSPS1216 65 6 303113 16 21 57 6 303114 BLPSPS12 Manufactured from high grade steel alloy • Features a Lifetime Warranty and exceeds ANSI Standards 1/2" Spark Plug Socket, inches 📦 Packing: 6 5/, 65 6 303115 BLPSPS121316 ¹³/₁₆ 57 303116 6 Manufactured from high grade steel alloy • Features a Lifetime Warranty and exceeds ANSI Standards 1/2" Quick Release Ratchet, Soft Grip BPRSR940SG Order NO.: 303118 Packing: 1 1/2 Soft Grip Handle 40 9° 44 18 103 RKRBPRSR940 1/2" Extension Knurled

w F T

-				
	Stock No.	Length (mm)	i i i	Order No.
	BLPEXTK123	76	6	303119
	BLPEXTK125	127	6	303120
·	BLPEXTK126	152	6	303121
	BLPEXTK1210	254	6	303122

1/2" Locking Extension

0.	Stock No.	Length (mm)		Order No.
	SXLBP3	76	6	303123
k	SXLBP6	152	6	303124
ei])	SXLBP10	254	6	303125

Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

1/2" Sliding T-handle

BLPSTHD1215 Order NO.: 303129



Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

1/2" Universal Joint

Packing: 6

BLPUJ12 Order NO.: 303130



- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards

1/2" Adaptor Packing: 6

BLPAFM1238 Order NO.: 303131



Manufactured from high grade steel alloy





1/2" Sliding Head BLPSH1238 ● Packing: 6 Order NO.: 303132 Image: Constraint of the state of the

1/2" Torx[®] Socket Driver



			100 A	
Stock No.	Size	Length (mm)		Order No.
BLPT1220	T20	37	6	303134
BLPT1225	T25	37	6	303135
BLPT1227	T27	37	6	303136
BLPT1230	T30	37	6	303137
BLPT1240	T40	37	6	303138
BLPT1245	T45	37	6	303139
BLPT1250	T50	37	6	303140
BLPT1255	T55	37	6	303141
BLPT1260	T60	37	6	303142

• Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

1/2" Breaker Bar



• Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

1/2" Triple Square Socket Driver

	Stock No.	Size (mm)	Length (mm)	()	Order No.
	BLPH123	3	36.5	6	303143
	BLPH124	4	36.5	6	303144
	BLPH125	5	36.5	6	303145
10	BLPH126	6	36.5	6	303146
	BLPH127	7	36.5	6	303147
	BLPH128	8	36.5	6	303148
	BLPH1210	10	36.5	6	303149
	BLPH1212	12	36.5	6	303150
	BLPH1214	14	36.5	6	303151
	BLPH1217	17	36.5	6	303152
1	BLPH1219	19	36.5	6	303153
	BLPH125L180	5	180	6	303154
h-a-d	BLPH126L70	6	70	6	303155
ÎÎ	BLPH126L140	6	140	6	303156
	BLPH126L250	6	250	6	303157
P	BLPH128L120	8	120	6	303158
\Box	BLPH1210L140	10	140	6	303159

• Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards



Stock No.	Size (inches)	Length (mm)	Ŵ	Order No.
BLPXZNM125	M5	37	6	303160
BLPXZNM126	M6	37	6	303161
BLPXZNM128	M8	37	6	303162
BLPXZNM1210	M10	37	6	303163
BLPXZNM1212	M12	37	6	303164
BLPXZNM1214	M14	37	6	303165
BLPXZNM1216	M16	37	6	303166

• Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

1/2" Long Torx[®] Socket Driver

	Stock No.	Size	Len
	BLPTL1220	T20	
	BLPTL1225	T25	
	BLPTL1227	T27	
	BLPTL1230	T30	
	BLPTL1240	T40	
T	BLPTL1245	T45	
L	BLPTL1250	T50	
	BLPTL1255	T55	
L.	BLPTL1260	T60	

1/2" Hex Socket Driver

P

Manufactured from high grade steel alloy



1/2" Long Hex Socket Driver

	Stock No.	Size (mm)	Length (mm)		Order No.
	BLPHL124	4	100	6	303176
	BLPHL125	5	100	6	303177
	BLPHL126	6	100	6	303178
	BLPHL127	7	100	6	303179
	BLPHL128	8	100	6	303180
ÎÎ [÷]	BLPHL1210	10	100	6	303181
L	BLPHL1212	12	100	6	303182
M	BLPHL1214	14	100	6	303183
\Box	BLPHL1217	17	100	6	303184

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards

3/4" Double Hex Socket



Stock No.	Size (mm)	Length (mm)	۲	Order No.	Stock No.	Size (mm)	Length (mm)	۲	Order No.
BLPDM3419	19	47	6	304001	BLPDM3432	32	58	6	304012
BLPDM3421	21	47	6	304002	BLPDM3433	33	60	6	304013
BLPDM3422	22	47	6	304003	BLPDM3434	34	60	6	304014
BLPDM3423	23	50	6	304004	BLPDM3435	35	60	6	304015
BLPDM3424	24	50	6	304005	BLPDM3436	36	63	6	304016
BLPDM3425	25	53	6	304006	BLPDM3438	38	63	6	304017
BLPDM3426	26	53	6	304007	BLPDM3441	41	66	6	304018
BLPDM3427	27	53	6	304008	BLPDM3446	46	68	6	304019
BLPDM3428	28	53	6	304009	BLPDM3450	50	68	6	304020
BLPDM3429	29	53	6	304010	BLPDM3455	55	69	6	304021
BLPDM3430	30	58	6	304011	BLPDM3460	60	72	6	304022

Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards



- Features quick release button for rapid socket/accessory changes, even with greasy or oily hands
- Contoured handle for comfort and control
- Chrome finish for easy clean-up
- All ratchets in series meet or exceed ANSI B107-10M-1996 specifications

3/4" Extension





- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards

3/4" Universal Joint

Packing: 6

BLPUJ34 Order NO.: 304029

Order No 304024

6



Manufactured from high grade steel alloy

Features a Lifetime Warranty and exceeds ANSI Standards



Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

3/4" Sliding T-handle

BLPSTHD3418 Order NO.: 304027 📦 Packing: 6 457

Manufactured from high grade steel alloy

Features a Lifetime Warranty and exceeds ANSI Standards

3/4" L-Shape Wrench

📦 Packing: 6

WARNING

BLPLW3415 Order NO.: 304030

۹E:		
دد	Stock No.	Length (mm)
	BLPLW3415	381

Manufactured from high grade steel alloy

1511werPlatinita



WRENCHES



OLLER. LE



The first of Blue-Point wrenches were designed to be unbreakable at its head, unable to spread its jaws or bend its handle, and cannot injure them nor destroy their everlasting efficiency. While most of our wrenches have evolved and improved with time, these core philosophies to quality are observed till today in our design.

Our ratcheting wrench uses gears with higher number of teeth so that you need less swings to tighten and loosen a fastener. In short, you work less to get each job done.

We kept the thickness of the jaws to the minimal without losing its required strength. This allows our wrench to reach better into constricted openings for any tightening or loosening task.

Flexible head is also incorporated into some designs to accommodate awkward working angles.

The ends of our wrench are set in an optimal angle so that you can flip it to get the best working angle.

Nickel chrome exterior finishes the wrench for corrosion resistance and a durable tool.



Wrenches Wrench Sets

Adjustable Wrench Set, 4pcs



 Includes GAJ6A (6"), GAJ8A (8"), GAJ10A (10") and GAJ12A (12") adjustable wrenches

Adjustable Wrench Set, 3pcs

Packing: 3

BLPADJ703 Order NO.: 401002

BLPADJ404 Order NO.: 401001



 Includes GAJ15A (15"), GAJ18A (18") and GAJ24A (24") adjustable wrenches



 Includes BADJC6 (6"), BADJC8 (8") and BADJC10 (10") composite handle adjustable wrenches

Adjustable Wrench Set, 4pcs

Packing: 4

BLPADJ404SG Order NO.: 401004



 Includes GAJ6SG (6"), GAJ8SG (8"), GAJ10SG (10") and GAJ12SG (12") adjustable wrenches

Ratcheting Wrench Set



Stock No.	(Order No.
BOER708	1	401009
BOER704	1	401010

BOER708

Includes 5/16" to 3/4" ratchet combination wrenches
 BOER10
 BOER18
 BOER18

BOER12	BOER20
BOER14	BOER22
BOER16	BOER24

BOER704

 Includes BOER26, BOER28, BOER30 and BOER32 (13/16" to 1") ratchet combination wrenches

Ratcheting Wrench Set



Stock No.	i i i	Order No.
BOERM712	1	401007
BOERM704	1	401008

BOERM712

• Includes 8 to 19mm ratchet combination wrenches

BOERM8	BOERM12	BOERM16
BOERM9	BOERM13	BOERM17
BOERM10	BOERM14	BOERM18
BOERM11	BOERM15	BOERM19

BOERM704

• Includes BOERM21, BOERM22, BOERM24 and BOERM25 (21 to 25mm) ratchet combination wrenches





BOERS708

Order NO.: 401014

Wrenches Wrench Sets

Ratcheting Wrench Set, 12pcs 📦 Packing: 1

BOERMF712A Order NO.: 401011



 Includes 8 to 19mm flexible head ratchet combination wrenches BOERMF8A BOERMF12A BOERMF16A BOERMF9A BOERMF13A BOERMF17A BOERMF10A BOERMF14A BOERMF18A BOERMF11A BOERMF15A BOERMF19A

Ratcheting Wrench Set, 12pcs

Packing: 1

BOERMS712 Order NO.: 401013

combination wrenches BOERMS8 BOERMS12 BOERMS16 BOERMS9 BOERMS13 BOERMS17 BOERMS10 BOERMS14 BOERMS18 BOERMS11 BOERMS15 BOERMS19

Ratcheting Wrench Set, 8pcs Packing: 1

BOERF708A

Order NO.: 401012

• Includes 5/16" to 3/4" flexible head ratchet combination wrenches BOERF10A BOERF18A BOERF20A BOERF12A BOERF14A BOERF22A BOERF16A BOERF24A

Ratcheting Wrench Set, 8pcs Packing: 1



Includes 5/16" to 3/4" short ratchet combination wrenches BOERS10 BOERS18 BOERS12 BOERS20 BOERS14 BOERS22 BOERS16 BOERS24

Ratcheting Wrench Set, 8pcs Packing: 1

BOERSF708 Order NO.: 401016



 Includes 5/16" to 3/4" short flexible head ratchet combination wrenches BOERSF10 BOERSF18 BOERSF12 BOERSF20 BOERSF14 BOERSF22 BOERSF16 BOERSF24

Ratcheting Wrench Set, 12pcs Packing: 1

BOERMFLCG712 Order NO.: 401017



• Includes 8 to 19mm locking flexible head ratchet combination wrenches BOERMFLCG8 BOERMFLCG12 BOERMFLCG16 BOERMFLCG9 BOERMFLCG13 BOERMFLCG17 BOERMFLCG10 BOERMFLCG14 BOERMFLCG18 BOERMFLCG11 BOERMFLCG15 BOERMFLCG19

Flexible Head Ratchet Combination Wrench



Highly polished and smooth surface for comfort

Durable and tough 3 nickel chrome finish



teeth count for better work efficiency







Wrenches Wrench Sets / Adjustable Wrenches

Ratcheting Wrench Set, 8pcs



Ľ

 Includes 5/16" to 3/4" locking flexible head ratchet combination wrenches

BOERFLCG10 BOERFLCG18 BOERFLCG12 BOERFLCG20 BOERFLCG14 BOERFLCG22 BOERFLCG16 BOERFLCG24

Ratcheting Box Wrench Set, 5pcs Packing: 1

RBZM605 Order NO.: 401019

RBZ605

Order NO.: 401020

BOERFLCG708

Order NO.: 401018



Includes 7-8 to 15-17mm ratcheting box wrenches

RBZM78 RBZM1314 RBZM1517 RBZM1112

M1314 RBZM910 M1112

Ratcheting Box Wrench Set, 5pcs

📦 Packing: 1



Includes 1/4" - 5/16" to 3/4" - 7/8" ratcheting box wrenches

RBZ810 RBZ1214 RBZ1618

L-Shape Hex Keys Wrench Set, 9pcs

Packing: 1

BLWSM9

Order NO: 407001

2	
ŀ	

ck No.	••• <u>Ì</u>	A (mm)	L (mm)	Ŵ	Order No.
VM1.5	1.5	13.5	77	6	407022
NM2	2	15.5	82	6	407023
VM2.5	2.5	17.5	88.5	6	407024
VM3	3	19	98.5	6	407025
NM4	4	24	104	6	407026
NM5	5	27	116	6	407027
NM6	6	31	138	6	407028
NM8	8	35	158	6	407029
VM10	10	39	167	6	407030

• Set includes 1.5-2-2.5-3-4-5-6-8-10mm in plastic holder

- Made from high torque steel
- Ball hex allows angle entry

L-Shape Torx Wrench Set, 9pcs

BLWTS9 Order NO.: 407006



#]	A (mm)	L (mm)	# <u>]</u>	A (mm)	L (mm)
T10	17	86	T30	24	114
T15	18	90	T40	26	124
T20	19	95	T45	29	133
T25	20	100	T50	32	152
T27	21	105			

Includes T10-T15-T20-T25-T27-T30-T40-T45-T50 in plastic holder
Made from high torque steel

Adjustable



Stock No.*	A (mm)	L (mm)	I	Order No.	Stock No.*	A (mm)	L (mm)	(Order No.
GAJ4A	13	108	6	402001	GAJ15A	43	385	4	402006
GAJ6A	25	160	6	402002	GAJ18A	52	450	2	402007
GAJ8A	29	210	6	402003	GAJ24A	62	610	1	402008
GAJ10A	33	260	6	402004	GAJS30A	85	778	1	402009
GAJ12A	38	310	6	402005					

*For China & India

Stock No.**	A (mm)	L (mm)	(Order No.	Stock No.**	A (mm)	L (mm)	۲	Order No.
GAJ4AP	13	108	6	402017	GAJ15AP	43	385	4	402022
GAJ6AP	25	160	6	402018	GAJ18AP	52	450	2	402023
GAJ8AP	29	210	6	402019	GAJ24AP	62	610	1	402024
GAJ10AP	33	260	6	402020	GAJS30AP	85	778	1	402025
GAJ12AP	38	310	6	402021					

**For Rest of Asia

- Wrench features a durable black phosphate finish
- Wide-open jaw design with polished head
- Heat treated steel alloy construction
- Inch scale laser etched on head face

Wrenches Adjustable / Combination / Double Open End Wrenches

Adjustable, Composite Grip



*For China & India

**For Rest of Asia

- Ergonomic, lightweight handle design reduces fatigue while providing easier gripping and greater balance
- Inch scale is laser etched on face
- Fully polished head
- Durable heat treated alloy construction

Adjustable, Soft Grip



Stock No.*	A(mm)	L (mm)	i	Order No.
GAJ6SG	25	160	6	402013
GAJ8SG	29	210	6	402014
GAJ10SG	33	260	6	402015
GAJ12SG	38	310	6	402016

*For China & India

Stock No.**	A(mm)	L (mm)	Ĩ	Order No.
GAJ6SGAP	25	160	6	402029
GAJ8SGAP	29	210	6	402030
GAJ10SGAP	33	260	6	402031
GAJ12SGAP	38	310	6	402032

**For Rest of Asia

- Now the most popular Blue-Point[®] Adjustable Wrenches are available with soft grips
- Durable black phosphate finish
- Wide open jaw design with oversized capacity
- Laser-etched SAE/metric scale for easy determination of bolt size
- Soft Grip design for added comfort



- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards

								/	
Stock No.	•••• <u>1</u>	L (mm)	(Order No.	Stock No.	••• <u>1</u>	L (mm)	()	Order No.
BLPCWM6AP	6	104	6	403040	BLPCWM20AP	20	239	6	403054
BLPCWM7AP	7	110	6	403041	BLPCWM21AP	21	249.8	6	403055
BLPCWM8AP	8	120	6	403042	BLPCWM22AP	22	249.8	6	403056
BLPCWM9AP	9	125	6	403043	BLPCWM23AP	23	269	6	403057
BLPCWM10AP	10	135	6	403044	BLPCWM24AP	24	269	6	403058
BLPCWM11AP	11	144	6	403045	BLPCWM25AP	25	290	6	403059
BLPCWM12AP	12	155	6	403046	BLPCWM26AP	26	290	6	403060
BLPCWM13AP	13	165	6	403047	BLPCWM27AP	27	310	6	403061
BLPCWM14AP	14	175	6	403048	BLPCWM28AP	28	330	6	403062
BLPCWM15AP	15	184	6	403049	BLPCWM29AP	29	330	6	403063
BLPCWM16AP	16	195	6	403050	BLPCWM30AP	30	330	6	403064
BLPCWM17AP	17	204	6	403051	BLPCWM32AP	32	350	6	403065
BLPCWM18AP	18	215	6	403052	BLPCWM34AP	34	350	6	403066
BLPCWM19AP	19	229	6	403053					

Manufactured from high grade steel alloy

• Features a Lifetime Warranty and exceeds ANSI Standards

New high polish

Combination, Regular

Double Open End



Stock No.	•••• <u>Ī</u>	L (mm)	Ŵ	Order No.	Stock No.	••• <u>Ī</u>	L (mm)	۲	Order No.
BDOEM67	6-7	125	6	404001	BDOEM1719	17 - 19	225	6	404014
BDOEM68	6-8	125	6	404002	BDOEM1819	18 - 19	225	6	404015
BDOEM89	8 - 9	135	6	404003	BDOEM1921	19 - 21	237	6	404016
BDOEM810	8 - 10	135	6	404004	BDOEM1922	19 - 22	237	6	404017
BDOEM1011	10 - 11	145	6	404005	BDOEM2022	20 - 22	255	6	404018
BDOEM1012	10 - 12	145	6	404006	BDOEM2123	21 - 23	255	6	404019
BDOEM1113	11 - 13	165	6	404007	BDOEM2224	22 - 24	255	6	404020
BDOEM1213	12 - 13	165	6	404008	BDOEM2326	23 - 26	295	6	404021
BDOEM1214	12 - 14	165	6	404009	BDOEM2426	24 - 26	295	6	404022
BDOEM1314	13 - 14	165	6	404010	BDOEM2427	24 - 27	295	6	404023
BDOEM1415	14 - 15	185	6	404011	BDOEM2528	25 - 28	334	6	404024
BDOEM1417	14 - 17	185	6	404012	BDOEM3032	30 - 32	368	6	404025
BDOEM1617	16 - 17	185	6	404013					

Stock No.		L (Inches)	i	Order No.
BDOE1012	⁵ /16 - ³ /8	5 ⁵ /16	6	404026
BDOE1416	⁷ /16 - ¹ /2	6 ¹ /2	6	404027
BDOE1820	⁹ /16 - ⁵ /8	7 ⁹ /32	6	404028
BDOE2224	¹¹ /16 - ³ /4	8 ¹⁵ /16	6	404029

Manufactured from high grade steel alloy





Wrenches Offset Box / Ratcheting Wrenches

75° Offset Box



Stock No.	••• <u>Ī</u>	L (mm)	۲	Order No.	Stock No.	•••• <u>]</u>	L (mm)	()	Order No.
BBWDM67	6-7	168	6	405001	BBWDM1921	19 - 21	318	6	405014
BBWDM89	8-9	183	6	405002	BBWDM1922	19 - 22	318	6	405015
BBWDM810	8 - 10	183	6	405003	BBWDM2022	20 - 22	318	6	405016
BBWDM1011	10 - 11	198	6	405004	BBWDM2123	21 - 23	330	6	405017
BBWDM1012	10 - 12	198	6	405005	BBWDM2224	22 - 24	330	6	405018
BBWDM1113	11 - 13	218	6	405006	BBWDM2326	23 - 26	346	6	405019
BBWDM1213	12 - 13	218	6	405007	BBWDM2426	24 - 26	346	6	405020
BBWDM1214	12 - 14	218	6	405008	BBWDM2427	24 - 27	346	6	405021
BBWDM1415	14 - 15	235	6	405009	BBWDM2528	25 - 28	355	6	405022
BBWDM1417	14 - 17	260	6	405010	BBWDM2430	24 - 30	355	6	405023
BBWDM1617	16 - 17	260	6	405011	BBWDM2730	27 - 30	355	6	405055
BBWDM1719	17 - 19	292	6	405012	BBWDM3032	30 - 32	372	6	405024
BBWDM1819	18 - 19	292	6	405013	BBWDM3436A	34 - 36	440	6	405056

Ratchet Combination



Stock No.	••• <u>T</u>	A (mm)	B (mm)	L (mm)	Ŵ	Order No.
BOERM6	6	6.6	3.6	114	6	406001
BOERM7	7	6.6	3.9	125	6	406002
BOERM8	8	6.5	4.0	135	6	406003
BOERM9	9	7.4	4.0	150	6	406004
BOERM10	10	8.0	5.0	160	6	406005
BOERM11	11	8.5	5.5	170	6	406006
BOERM12	12	9.0	5.5	175	6	406007
BOERM13	13	10.0	6.3	180	6	406008
BOERM14	14	10.0	6.5	190	6	406009
BOERM15	15	11.0	7.0	200	6	406010
BOERM16	16	11.0	7.0	210	6	406011
BOERM17	17	12.0	7.0	230	6	406012
BOERM18	18	12.0	8.0	2 40	6	406013
BOERM19	19	12.9	8.7	250	6	406014
BOERM21	21	13.7	9.4	266	6	406015
BOERM22	22	14.5	9.4	286	6	406016
BOERM24	24	15.5	11.2	305	6	406017
BOERM25	25	15.5	11.2	327	6	406018

- Dual pawl ratcheting box end yields smooth operation and maximum strength
- 15° offset box head provides extra knuckle clearance
- 4.5° (5° on smaller wrenches) gear engagement means less movement to engage the next gear
- Inch scale laser etched on head face
- Ratcheting box is reversible
- Box end features the FLANK DRIVE[®] wrenching configuration for greater torque with less applied force
- Tough, durable nickel-chrome finish
- Meets or exceeds strength specifications in ASME B107.6

45° Offset Box



Stock No.	•	L (mm)	()	Order No.	Stock No.	• <u>Ī</u>	L (mm)	()	Order No.
BBWSM67	6-7	165	6	405025	BBWSM1819	18 - 19	250	6	405040
BBWSM89	8 - 9	175	6	405026	BBWSM1921	19 - 21	270	6	405041
BBWSM810	8 - 10	185	6	405027	BBWSM1922	19 - 22	270	6	405042
BBWSM911	9 - 11	195	6	405028	BBWSM2022	20 - 22	270	6	405043
BBWSM1011	10 - 11	195	6	405029	BBWSM2122	21 - 22	290	6	405044
BBWSM1012	10 - 12	195	6	405030	BBWSM2123	21 - 23	290	6	405045
BBWSM1113	11 - 13	205	6	405031	BBWSM2224	22 - 24	320	6	405046
BBWSM1213	12 - 13	205	6	405032	BBWSM2326	23 - 26	360	6	405047
BBWSM1214	12 - 14	220	6	405033	BBWSM2426	24 - 26	360	6	405048
BBWSM1314	13 - 14	220	6	405034	BBWSM2427	24 - 27	360	6	405049
BBWSM1415	14 - 15	235	6	405035	BBWSM2528	25 - 28	370	6	405050
BBWSM1417	14 - 17	235	6	405036	BBWSM2730	27 - 30	380	6	405053
BBWSM1516	15 - 16	240	6	405037	BBWSM2732	27 - 32	380	6	405051
BBWSM1617	16 - 17	240	6	405038	BBWSM3032	30 - 32	380	6	405052
BBWSM1719	17 - 19	250	6	405039	BBWSM3436	34 - 36	405	6	405054

Ratchet Combination



Stock No.		A (inches)	B (inches)	L (inches)	Î	Order No.
BOER8	1/4	1/4	⁵ /32	4 ¹ /2	6	406019
BOER10	⁵ /16	1/4	⁵ /32	5 ⁵ /16	6	406020
BOER12	³ /8	⁵ /16	³ /16	6 ⁵ /16	6	406021
BOER14	⁷ /16	11/32	7/32	6 ¹¹ /16	6	406022
BOER16	1/2	¹³ /32	1/4	7 ¹ /16	6	406023
BOER18	⁹ /16	¹³ /32	1/4	7 ¹ /2	6	406024
BOER20	⁵ /8	⁷ /16	⁹ /32	8 ¹ /4	6	406025
BOER22	¹¹ /16	¹⁵ /32	⁹ /32	9 ¹ /16	6	406026
BOER24	³ /4	1/2	11/32	9 ¹³ /16	6	406027
BOER26	¹³ /16	17/32	³ /8	10 ¹ /2	6	406028
BOER28	7/8	⁹ /16	³ /8	11 ¹ /4	6	406029
BOER30	¹⁵ /16	5/8	7/16	12	6	406030
BOER32	1	⁵ /8	⁷ /16	12 ⁷ /8	6	406031

- Dual pawl ratcheting box end yields smooth operation and maximum strength
- 15° offset box head provides extra knuckle clearance
- 4.5° (5° on smaller wrenches) gear engagement means less movement to engage the next gear
- Inch scale laser etched on head face
- Ratcheting box is reversible
- Box end features the FLANK DRIVE[®] wrenching configuration for greater torque with less applied force
- Tough, durable nickel-chrome finish
- Meets or exceeds strength specifications in ASME B107.6



Wrenches Ratcheting Wrenches

Short Ratchet Combination



Stock No.	•••• <u>1</u>	A (mm)	B (mm)	L (mm)	i	Order No.
BOERMS8	8	6.5	4.0	90	6	406052
BOERMS9	9	7.4	4.0	95	6	406053
BOERMS10	10	8.0	5.0	100	6	406054
BOERMS11	11	8.5	5.5	105	6	406055
BOERMS12	12	9.0	5.5	110	6	406056
BOERMS13	13	10.0	6.3	115	6	406057
BOERMS14	14	10.0	6.5	120	6	406058
BOERMS15	15	11.0	7.0	125	6	406059
BOERMS16	16	11.0	7.0	128	6	406060
BOERMS17	17	12.0	7.0	132	6	406061
BOERMS18	18	12.0	8.0	138	6	406062
BOERMS19	19	12.9	8.7	142	6	406063

- Dual pawl reversible ratcheting box end
- · Low profile easy action reverse lever won't get in your way
- Tough, durable nickel chrome finish
- Up to 80 gear teeth for ratcheting in tight areas

Short Ratchet Combination





Stock No.	• I	A (inches)	B (inches)	L (inches)	i	Order No.
BOERS10	⁵ /16	1/4	5/32	3 ⁹ /16	6	406064
BOERS12	³ /8	⁵ /16	³ /16	3 ¹⁵ /16	6	406065
BOERS14	⁷ /16	11/32	7/32	4 ¹ /8	6	406066
BOERS16	1/2	¹³ /32	1/4	4 ¹ /2	6	406067
BOERS18	⁹ /16	¹³ /32	¹ /4	4 ³ /4	6	406068
BOERS20	⁵ /8	7/16	⁹ /32	5 ¹ /16	6	406069
BOERS22	¹¹ /16	¹⁵ /32	⁹ /32	5 ³ /16	6	406070
BOERS24	3/4	1/2	11/32	5 ⁶ /16	6	406071

- Dual pawl reversible ratcheting box end
- Low profile easy action reverse lever won't get in your way
- Tough, durable nickel chrome finish
- Up to 80 gear teeth for ratcheting in tight areas

Flex Head Ratchet Combination



Stock No.	•••• <u>1</u>	A (mm)	B (mm)	L (mm)	Ŵ	Order No.
BOERMF8A	8	6.5	4.0	142	6	406032
BOERMF9A	9	7.4	4.0	152	6	406033
BOERMF10A	10	8.0	5.0	162	6	406034
BOERMF11A	11	8.5	5.5	172	6	406035
BOERMF12A	12	9.0	5.5	180	6	406036
BOERMF13A	13	10.0	6.3	188	6	406037
BOERMF14A	14	10.0	6.5	196	6	406038
BOERMF15A	15	11.0	7.0	204	6	406039
BOERMF16A	16	11.0	7.0	214	6	406040
BOERMF17A	17	12.0	7.0	228	6	406041
BOERMF18A	18	12.0	8.0	242	6	406042
BOERMF19A	19	12.9	8.7	256	6	406043

- Flex head pivots 90 degrees in either direction
- Dual pawl reversible ratcheting box end
- Low profile easy action reverse lever won't get in your way
- Tough, durable nickel chrome finish
- Up to 80 gear teeth for ratcheting in tight areas

Flex Head Ratchet Combination





Stock No.	🕛 Ī	A (inches)	B (inches)	L (inches)	Ì	Order No.
BOERF10A	⁵ /16	1/4	5/32	5 ¹⁹ /32	6	406044
BOERF12A	³ /8	⁵ /16	³ /16	6 ³ /8	6	406045
BOERF14A	7/16	11/32	7/32	6 ³ /4	6	406046
BOERF16A	1/2	¹³ /32	1/4	7 ¹³ /32	6	406047
BOERF18A	⁹ /16	¹³ /32	1/4	7 ²³ /32	6	406048
BOERF20A	⁵ /8	⁷ /16	⁹ /32	8 ⁷ /16	6	406049
BOERF22A	¹¹ /16	¹⁵ /32	⁹ /32	8 ³¹ /32	6	406050
BOERF24A	³ /4	1/2	11/32	10 ¹ /16	6	406051

• Flex head pivots 90 degrees in either direction

- Dual pawl reversible ratcheting box end
- Low profile easy action reverse lever won't get in your way
- Tough, durable nickel chrome finish
- Up to 80 gear teeth for ratcheting in tight areas





Wrenches Ratcheting Wrenches

Short Flex Head Ratchet Combination



Stock No.	••• <u>1</u>	A (mm)	B (mm)	L (mm)	Ŵ	Order No.
BOERMSF8	8	6.5	4.0	94	6	406072
BOERMSF9	9	7.4	4.0	98	6	406073
BOERMSF10	10	8.0	5.0	103	6	406074
BOERMSF11	11	8.5	5.5	108	6	406075
BOERMSF12	12	9.0	5.5	111	6	406076
BOERMSF13	13	10.0	6.3	115	6	406077
BOERMSF14	14	10.0	6.5	120	6	406078
BOERMSF15	15	11.0	7.0	124	6	406079
BOERMSF16	16	11.0	7.0	128	6	406080
BOERMSF17	17	12.0	7.0	133	6	406081
BOERMSF18	18	12.0	8.0	140	6	406082
BOERMSF19	19	12.9	8.7	147	6	406083

• Flex head pivots 90 degrees in either direction

Dual pawl reversible ratcheting box end

• Up to 80 gear teeth for ratcheting in tight areas

Short Flex Head Ratchet Combination



Stock No.	•1	A (inches)	B (inches)	L (inches)	Ŵ	Order No.
BOERSF10	⁵ /16	¹ /4	5/32	3 ¹¹ /16	6	406084
BOERSF12	³ /8	⁵ /16	³ /16	4 ¹ /16	6	406085
BOERSF14	⁷ /16	¹¹ /32	7/32	4 ¹ /4	6	406086
BOERSF16	1/2	¹³ /32	1/4	4 ¹⁷ /32	6	406087
BOERSF18	⁹ /16	¹³ /32	1/4	4 ²³ /32	6	406088
BOERSF20	⁵ /8	7/16	⁹ /32	5 ¹ /32	6	406089
BOERSF22	¹¹ /16	15/32	⁹ /32	5 ¹ /4	6	406090
BOERSF24	³ /4	1/2	11/32	5 ²⁵ /32	6	406091

- Flex head pivots 90 degrees in either direction
- Dual pawl reversible ratcheting box end
- Up to 80 gear teeth for ratcheting in tight areas

Locking Flex Head Ratchet



Stock No.	•••• <u>T</u>	A (mm)	B (mm)	L (mm)	i	Order No.
BOERMFLCG8	8	6.55	32	228	6	406092
BOERMFLCG9	9	7.45	34	229	6	406093
BOERMFLCG10	10	8.05	38	233	6	406094
BOERMFLCG11	11	8.55	40	235	6	406095
BOERMFLCG12	12	9.05	42	285	6	406096
BOERMFLCG13	13	10.05	45	287	6	406097
BOERMFLCG14	14	10.05	48	289	6	406098
BOERMFLCG15	15	11.05	52	293	6	406099
BOERMFLCG16	16	11.05	54	347	6	406100
BOERMFLCG17	17	12.05	56	348	6	406101
BOERMFLCG18	18	12.05	60	352	6	406102
BOERMFLCG19	19	12.95	64	354	6	406103

Locking Flex Head Ratchet



Stock No.		A (inches)	B (inches)	L (inches)	Ŵ	Order No.
BOERFLCG10	⁵ /16	1/4	1 ¹ /4	9	6	406104
BOERFLCG12	³ /8	⁵ /16	1 ¹ /2	8 ¹ /4	6	406105
BOERFLCG14	7/16	¹¹ /32	1 ⁹ /16	9 ¹⁹ /32	6	406106
BOERFLCG16	1/2	¹³ /32	1 ²⁵ /32	11 ⁹ /32	6	406107
BOERFLCG18	⁹ /16	¹³ /32	1 ²⁹ /32	11 ³ /8	6	406108
BOERFLCG20	⁵ /8	7/16	2 ¹ /8	13 ²¹ /32	6	406109
BOERFLCG22	¹¹ /16	¹⁵ /32	2 7/32	13 ²³ /32	6	406110
BOERFLCG24	³ /4	1/2	2 ¹⁷ /32	13 ¹⁵ /16	6	406111

- Corrosive resistant bi-mold cushion grips for improved comfort and performance
- Wrenches have multiple locking head positions for easier access to tough to reach fasteners
- Long reach solid shank steel handle for improved reach and leverage
- Dual pawl reversible ratchet head
- Flex head pivots 90 degrees in either direction



Wrenches Ratcheting Wrenches / L and T shape Wrenches / Other Wrenches

Ratcheting Box



Ratcheting Box



Stock No.	ΦI	A (inches)	L (inches)	Ŵ	Order No.
RBZ810	¹ /4 - ⁵ /16	3/8	4 ¹ /2	1	406119
RBZ1214	³ /8 - ⁷ /16	3/8	5 ⁷ /2	1	406120
RBZ1618	¹ /2 - ⁹ /16	1/2	6 ¹ /8	1	406121
RBZ2022	⁵ /8 - ¹¹ /16	1/2	9 ¹ /4	1	406122
RBZ2428	³ /4 - ⁷ /8	1/2	9 ¹ /4	1	406123

L-Shape Hex Keys



Stock No.	•	A (mm)	L (mm)	()	Order No.
BLWM11	11	42	190	6	407031
BLWM12	12	44	209	6	407002
BLWM13	13	50	220	6	407032
BLWM14	14	54.5	233	6	407003
BLWM15	15	56.5	237	6	407033
BLWM16	16	58.5	240	6	407034
BLWM17	17	61.5	246	6	407004
BLWM18	18	64.5	261	6	407035
BLWM19	19	68.5	276	6	407005

- Made from high torque steel
- Heavy duty usage
- Satin finish

T-Shape Hex Keys



Stock No.	•••• <u>T</u>	A (mm)	L (mm)	Ŵ	Order No.
BTWM1.5	1.5	83	122	6	407007
BTWM2.5	2.5	83	122	6	407008
BTWM3	3	83	122	6	407009
BTWM4	4	83	122	6	407010
BTWM5	5	83	122	6	407011
BTWM6	6	134	186	6	407012
BTWM7	7	134	186	6	407013
BTWM8	8	134	186	6	407014

- Ergonomical handle for a better grip
- Made from high torque steel

T-Shape Speeder Wrench



Stock No.	A (mm)	B (mm)	L (mm)	Ŵ	Order No.
BPTHM08	8	200	250	1	407015
BPTHM09	9	200	250	1	407016
BPTHM10	10	200	250	1	407017
BPTHM11	11	200	250	1	407018
BPTHM12	12	250	250	1	407019
BPTHM13	13	250	300	1	407020
BPTHM14	14	250	300	1	407021

• Speedy socket wrench, convenience for use

• Magnetic inset for convenience

Chain Wrench



Stock No.	Chain Length (inches)	Capacity (inches)	Handle Length (inches)	۲	Order No.
CW12A	16	4	12	6	408001
CW15A	19	5	15	6	408002
CW24A	23	6	24	6	408003

Strap Wrench



Stock No.	Diameter	(Order No.
BLPSTWR4	4" max	1	408005
BLPSTWR6	6" max	1	408006

• Adjusts to fit any circumference or irregular shape

- Grip, loosen or tighten almost anything
- Won't scratch or damage surfaces
- Cushioned grip for maximum comfort

• Heavy duty construction for longer life

BLPSTWRKT(Order No.408004)Set includes BLPSTWR4 & BLPSTWR6





SCREWDRIVERS & BITS

aligned that the set

Blue-Point's screwdrivers give you better grip and higher turning force with tool tip durability to match.

Handles using dual compound are ergonomically shaped to fit your palm for comfort and better grip.

The high strength Molybdenum-Vanadium steel shanks are nickel and chrome plated for toughness and corrosion resistance.

Vapor-blasted tips offer greater screw-tip adherence to prevent the rounding of screws and screwdrivers alike.

Finer details like laser-etching of the size and part numbers are not missed. This ensure permanence with continual usage over time.

We even offer three colours in the same range to facilitate tool identification and differentiation for different work-teams.







Blue.Print



Screwdriver & Bits Screwdrivers





P Series, Phillips[®]



Stock No. (Blue)	Ũ	Order No.	Stock No. (Yellow)	۲	Order No.	Stock No. (Red)	۲	Order No.	Tip Size	A (mm)	L (mm)
BSGD75PH0B	10	501001	BSGD75PH0Y	10	501030	BSGD75PH0R	10	501059	PH0	75	148
BSGD100PH0B	10	501002	BSGD100PH0Y	10	501031	BSGD100PH0R	10	501060	PH0	100	187
BSGD150PH0B	10	501003	BSGD150PH0Y	10	501032	BSGD150PH0R	10	501061	PH0	150	237
BSGD100PH1B	10	501004	BSGD100PH1Y	10	501033	BSGD100PH1R	10	501062	PH1	100	208
BSGD150PH1B	10	501005	BSGD150PH1Y	10	501034	BSGD150PH1R	10	501063	PH1	150	258
BSGD200PH1B	10	501006	BSGD200PH1Y	10	501035	BSGD200PH1R	10	501064	PH1	200	308
BSGD250PH1B	10	501007	BSGD250PH1Y	10	501036	BSGD250PH1R	10	501065	PH1	250	358
BSGD300PH1B	10	501008	BSGD300PH1Y	10	501037	BSGD300PH1R	10	501066	PH1	300	408
BSGD100PH2B	10	501009	BSGD100PH2Y	10	501038	BSGD100PH2R	10	501067	PH2	100	208
BSGD150PH2B	10	501010	BSGD150PH2Y	10	501039	BSGD150PH2R	10	501068	PH2	150	258
BSGD200PH2B	10	501011	BSGD200PH2Y	10	501040	BSGD200PH2R	10	501069	PH2	200	308
BSGD250PH2B	10	501012	BSGD250PH2Y	10	501041	BSGD250PH2R	10	501070	PH2	250	358
BSGD300PH2B	10	501013	BSGD300PH2Y	10	501042	BSGD300PH2R	10	501071	PH2	300	408
BSGD150PH3B	10	501014	BSGD150PH3Y	10	501043	BSGD150PH3R	10	501072	PH3	150	270
BSGD200PH3B	10	501015	BSGD200PH3Y	10	501044	BSGD200PH3R	10	501073	PH3	200	320

• 2-Component handle gives the screwdriver an ideal ergonomic shape

• Perfectly adapted to the forces exerted by the hand and permits work efficiently

• The chrome molybdenum vanadium blade is hardened to HRC 59±1

- Nickel and chrome plated blade and the tip is especially vapor-blasted for greater screw-tip adherence and a full anti-rust guarantee
- With hanging hole moulded to the blade

• The size and part number are laser-etched on the blade to ensure their permanence



Screwdriver & Bits Screwdrivers

P Series, Slotted

					Man Paris				$\overline{}$		
				Concession of the second		H					
Stock No. (Blue)	Ŵ	Order No.	Stock No. (Yellow)	Ĩ	Order No.	Stock No. (Red)	Ŵ	Order No.	Tip Size	A (mm)	L (mm)
BSGD75S3B	10	501016	BSGD75S3Y	10	501045	BSGD75S3R	10	501074	3mm	75	147
BSGD75F4B	10	501017	BSGD75F4Y	10	501046	BSGD75F4R	10	501075	4mm	100	168
BSGD100S4B	10	501018	BSGD100S4Y	10	501047	BSGD100S4R	10	501076	4mm	125	188
BSGD125S4B	10	501019	BSGD125S4Y	10	501048	BSGD125S4R	10	501077	4mm	150	233
BSGD150S4B	10	501020	BSGD150S4Y	10	501049	BSGD150S4R	10	501078	4mm	250	308
BSGD250S4B	10	501021	BSGD250S4Y	10	501050	BSGD250S4R	10	501079	5.5mm	125	358
BSGD125S5B	10	501022	BSGD125S5Y	10	501051	BSGD125S5R	10	501080	5.5mm	150	208
BSGD150S5B	10	501023	BSGD150S5Y	10	501052	BSGD150S5R	10	501081	6.5mm	250	258
BSGD125F5B	10	501024	BSGD125F5Y	10	501053	BSGD125F5R	10	501082	4mm	75	233
BSGD125F6B	10	501025	BSGD125F6Y	10	501054	BSGD125F6R	10	501083	5.5mm	125	208
BSGD150F6B	10	501026	BSGD150F6Y	10	501055	BSGD150F6R	10	501084	6.5mm	125	258
BSGD250F6B	10	501027	BSGD250F6Y	10	501056	BSGD250F6R	10	501085	6.5mm	150	358
BSGD150F8B	10	501028	BSGD150F8Y	10	501057	BSGD150F8R	10	501086	8mm	150	270
BSGD175F8B	10	501029	BSGD175F8Y	10	501058	BSGD175F8R	10	501087	8mm	175	320

• 2-Component handle gives the screwdriver an ideal ergonomic shape

Perfectly adapted to the forces exerted by the hand and permits work efficiently

• The chrome molybdenum vanadium blade is hardened to HRC 59±1

• Nickel and chrome plated blade and the tip is especially vapor-blasted for greater screw-tip adherence and a full anti-rust guarantee

• With hanging hole moulded to the blade

• The size and part number are laser-etched on the blade to ensure their permanence

Ratcheting Screwdriver



1/4" Ratchet Screwdriver, Pistol Handle

Packing: 1



- 5" magnetic bit holder blade for 1/4" hex bits
- 45 tooth ratcheting mechanism ensures precise positioning and movement
- Bits are stored in a bit magazine inside the handle
- Includes six 1/4" hex bits: Flat Tip (4.5 and 5.5), Phillips® (#1 and #2) plus Torx® (T15 and T20)
- Ergonomically designed two component handle is textured for excellent grip and user comfort
- Provides three functional options, left and right turning and locked position
- Blade features a knurled-grip for fast spinning of the fastener
- Screwdriver carries a lifetime warranty (Bits are consumable and carry no warranty)

BSGDMR6 Order NO.: 502001



Screwdriver & Bits Screwdrivers

P Series VDE, Phillips[®]



Stock No.	Tip Size	A (mm)	L (mm)		Order No.
BSGDV100PH0	PH0	100	148	10	501088
BSGDV150PH1	PH1	150	188	10	501089
BSGDV175PH2	PH2	175	208	10	501090
BSGDV200PH3	PH3	200	270	10	501091

P Series VDE, Slotted



233

258

10

10

501095

501096

125

150

Insulated screwdriver for Phillips PH-head screws, for work on live equipment up to 1000V

- Examination of screwdrivers according to latest national and international standards
- Examination piece-wise in water bath with 10 KV
- Ergonomically developed 2-component handle
- Blade black oxidized, entirely hardened

M Series, Slotted



Stock No.	Tip Size	A (mm)	L (mm)		Order No.	Stock No.	Tip Size	A (mm)	L (mm)	1	Order No.
BSGDM65F2	2.4	65	136	6	501097	BSGDM38F6	6	38	100	6	501105
BSGDM75F3	3.2	75	149	6	501098	BSGDM100F6	6	100	220	6	501106
BSGDM100F3	3.2	100	175	6	501099	BSGDM150F6	6	150	270	6	501107
BSGDM150F3	3.2	150	225	6	501100	BSGDM200F6	6	200	321	6	501108
BSGDM75F5	5	75	182	6	501101	BSGDM250F6	6	250	372	6	501109
BSGDM100F5	5	100	208	6	501102	BSGDM150F8	8	150	280	6	501110
BSGDM150F5	5	150	258	6	501103	BSGDM200F8	8	200	331	6	501111
BSGDM200F5	5	200	309	6	501104	BSGDM200F9	9.5	200	331	6	501112

M Series, Pozidriv[®]

5.5mm

6.5mm



Stock No.	Tip Size	A (mm)	L (mm)	Ŷ	Order No.	Stock No.	Tip Size	A (mm)		Ŷ	Order No.
BSGDM65PZ00	0	65	136	6	501128	BSGDM100PZ2	2	100	218	6	501136
BSGDM75PZ0	0	75	148	6	501129	BSGDM150PZ2	2	150	268	6	501137
BSGDM100PZ0	0	100	173	6	501130	BSGDM200PZ2	2	200	318	6	501138
BSGDM150PZ0	0	150	223	6	501131	BSGDM250PZ2	2	250	368	6	501139
BSGDM75PZ1	1	75	181	6	501132	BSGDM150PZ3	3	150	278	6	501140
BSGDM100PZ1	1	100	206	6	501133	BSGDM200PZ3	3	200	328	6	501141
BSGDM150PZ1	1	150	256	6	501134	BSGDM200PZ4	4	200	328	6	501142
BSGDM38PZ2	2	38	100	6	501135						

• Tri-lobe handle shape for reducing user strain while operating and offering optimum torque

• Soft cushion grip for the best performance without fatigue

• Concave hollow of the handle neck for firm pinch pressure and precision control



Screwdriver & Bits Screwdrivers / Bits

M Series, Phillips[®]

Stock No.	Size	A (mm)	L (mm)	Ì	Order No.	Stock No.	Tip Size	A (mm)	L (mm)		No.
BSGDM65PH00	00	65	136	6	501113	BSGDM100PH2	2	100	218	6	501121
BSGDM75PH0	0	75	148	6	501114	BSGDM150PH2	2	150	268	6	501122
BSGDM100PH0	0	100	173	6	501115	BSGDM200PH2	2	200	318	6	501123
BSGDM150PH0	0	150	223	6	501116	BSGDM250PH2	2	250	368	6	501124
BSGDM75PH1	1	75	181	6	501117	BSGDM150PH3	3	150	278	6	501125
BSGDM100PH1	1	100	206	6	501118	BSGDM200PH3	3	200	328	6	501126
BSGDM150PH1	1	150	256	6	501119	BSGDM200PH4	4	200	328	6	501127
BSGDM38PH2	2	38	100	6	501120						





Stock No.	Tip Size	A (mm)	L (mm)	1	Order No.	Stock No.			L (mm)	7	Order No.
BSGDM75TX6	T6	75	148	6	501143	BSGDM100TX20	T20	100	206	6	501149
BSGDM75TX7	T7	75	148	6	501144	BSGDM100TX25	T25	100	218	6	501150
BSGDM75TX8	T8	75	148	6	501145	BSGDM100TX27	T27	100	218	6	501151
BSGDM75TX9	Т9	75	148	6	501146	BSGDM100TX30	T30	100	218	6	501152
BSGDM100TX10	T10	100	206	6	501147	BSGDM100TX40	T40	100	218	6	501153
BSGDM100TX15	T15	100	206	6	501148						

• Tri-lobe handle shape for reducing user strain while operating and offering optimum torque

• Soft cushion grip for the best performance without fatigue

• Concave hollow of the handle neck for firm pinch pressure and precision control

Bits



🔿 Hex Bit 🏚 Tamper Resistant Torx Bit 🗕 Flat Tip Bit 🛉 Phillips Tip Bit 📕 Square Tip Bit

Stock No.	Description	Size	i	Order No.
BLPFB532	Flat Tip Bit	5/ ₃₂ "	6	502002
BLPFB732	Flat Tip Bit	7/32"	6	502003
BLPFB932	Flat Tip Bit	⁹ / ₃₂ "	6	502004
BLPFB316	Flat Tip Bit	^{3/} 16"	6	502005
BLPFB14	Flat Tip Bit	1/4"	6	502006
BLPPB0	Phillips Tip Bit	#0	6	502007
BLPPB1	🔶 Phillips Tip Bit	#1	6	502008
BLPPB2	🔶 Phillips Tip Bit	#2	6	502009
BLPPB3	Phillips Tip Bit	#3	6	502010
BLPHBM3	Hex Bit	3mm	6	502011
BLPHBM4	Hex Bit	4mm	6	502012
BLPHBM5	Hex Bit	5mm	6	502013
BLPHBM6	Hex Bit	6mm	6	502014
BLPHB18	Hex Bit	1/8"	6	502015
BLPHB964	Hex Bit	⁹ / ₆₄ "	6	502016
BLPHB532	Hex Bit	5/ ₃₂ "	6	502017
BLPHB316	Hex Bit	^{3/} 16"	6	502018
BLPHB732	Hex Bit	7/32"	6	502019
BLPHB14	Hex Bit	1/4"	6	502020
BLPTB10TP	Tamper Resistant Torx Bit	T10	6	502021
BLPTB15TP	Tamper Resistant Torx Bit	T15	6	502022
BLPTB20TP	Tamper Resistant Torx Bit	T20	6	502023
BLPTB25TP	Tamper Resistant Torx Bit	T25	6	502024
BLPTB30TP	Tamper Resistant Torx Bit	T30	6	502025
BLPSQB1	Square Tip Bit	#1	6	502026
BLPSQB2	Square Tip Bit	#2	6	502027





At Blue-Point, we created a broad range of high performance pliers for most applications today while keeping at a very affordable price.

Like our screwdrivers, we also adopt a dual compound design for the handle to improve gripping comfort and reduce hand fatigue.

The joints are precision machined and located for high leverage thus requiring less effort for every crimping and cutting task.

We even use laser hardening on the cutting edges of our pliers!

Blue-Point pliers are where good quality comes at a good price. And our broad range completes your search for the right tool to the job. Colue Paint

CB







Pliers Pliers Sets

Pliers Set, Dipped Grips, 8pcs Packing: 8 BDGPL800 Order NO.: 601007

A A A A A

Stock No.	Description	Jaw Capacity (inches)	Length (inches)	i	Order No.
BDGAWP100Z	Adjustable Joint Pliers	1 ³ /4	10	6	602001
BDG48CPZ	Slip Joint Pliers	1 ²⁷ / ₃₂	8	6	602037
BDG98CPZ	Needle Nose Pliers	3	8	6	602004
BDG9845CPZ	45° Bent Needle Nose Pliers	2 ¹³ / ₁₆	7 ³ / ₄	6	602010
BDG57CPZ	Lineman's Pliers	1 ¹ /4	7 ¹ /2	6	602006
BDGEC7Z	End Cutter	7/16	7	6	602009
BDG86CPZ	Diagonal Cutter	21/ ₃₂	6 1/2	6	602005
BDG88CPZ	Diagonal Cutter	^{15/} 16	8 ¹ / ₈	6	602008

 Includes BDGAWP100Z adjustable joint pliers, BDG48CPZ slip joint pliers, BDG98CPZ and BDG9845CPZ needle nose pliers, BDG57CPZ Lineman's pliers, BDG86CPZ and BDG88CPZ diagonal cutters plus BDGEC7Z end cutters (8 pcs) in storage tray Mini Pliers Set, 10pcs Packing: 10

BMPL1000 Order NO.: 601009



Stock No.	Description	Jaw Capacity (inches)	Length (inches)	۲	Order No.
B45CMPAP	Combination Pliers	1	4 ¹¹ / ₁₆	6	602011
B65CMPAP	Duck Bill Pliers	1 ⁵ / ₃₂	4 7/8	6	602014
B75CMPAP	Round Nose Pliers	1 ⁵ /32	5	6	602017
B85CMPAP	Diagonal Cutter	²¹ / ₃₂	4 ¹¹ / ₃₂	6	602015
B85CTMPAP	Thin Diagonal Cutter	²³ / ₃₂	4 ⁵ /8	6	602020
B945CMPAP	45° Bent Nose Pliers	1	4 ¹¹ / ₁₆	6	602013
B95CMPAP	Long Nose Pliers	1 ¹ /8	4 ⁷ /8	6	602012
B95CLMPAP	Needle Nose Pliers	2 ¹ / ₁₆	5 ²⁵ / ₃₂	6	602019
B960CMPAP	60° Bent Nose Pliers	^{15/} 16	4 ¹¹ / ₁₆	6	602018
BMPEC5AP	End Cutter	⁵ / ₁₆	4 ¹ / ₃₂	6	602016

 B45CMPAP, B65CMPAP, B75CMPAP, B85CMPAP, B85CTMPAP, B945CMPAP, B95CLMPAP, B95CMPAP, B960CMPAP and BMPEC5AP (10 pcs.) in storage tray

Pliers Set, Standard, 5pcs

Packing: 5

BPL501 Order NO.: 601008



Stock No.	Description	Jaw Capacity (inches)	Length (inches)	۲	Order No.
B48CPAP	Slip Joint Pliers	2 ³ / ₃₂	8 ¹³ / ₃₂	6	602036
B58HLPAP	Lineman's Pliers	1 ¹ /2	8 ³¹ / ₃₂	6	602007
B96CPAP	Long Nose Pliers	2 ¹ / ₃₂	6 ⁵ / ₁₆	6	602003
BAWP100AP	Adjustable Joint Pliers	1 ³ /8	10 5/32	6	602038
B87CPAP	Diagonal Cutters	31/ ₃₂	6 ¹⁹ / ₃₂	6	602002

• B48CPAP, B58HLPAP, B87CPAP, B96CPAP and BAWP100AP (5 pcs.) in storage tray

Mini Pliers Set, 8pcs

Packing: 8

BDGMPL845 Order NO.: 601015



Stock No.	Description	Jaw Capacity (inches)	Length (inches)	١	Order No.
BDG45CMP	Mini Combination Pliers	1"	4.5"	6	602074
BDG85CMP	Mini Diagonal Nose Pliers	²¹ / ₃₂ "	4.5"	6	602075
BDG85CTMP	Mini Thin Diagonal Nose Pliers	²³ / ₃₂ "	4.5"	6	602076
BDG945CMP	Mini 45 Deg Bent Nose Pliers	1"	4.5"	6	602077
BDG65CMP	Mini Flat Nose Pliers	1 ⁵ / ₃₂ "	4.5"	6	602078
BDG95CMP	Mini Long Nose Pliers	4 7/8"	4.5"	6	602079
BDG95CLMP	Mini Needle Nose Pliers	2 ¹ / ₁₆ "	6"	6	602080
BDGMPEC5	Mini End Cutters	4 ¹ / ₃₂ "	4.5"	6	602081

• Comes in a compact pouch that is easy to store and carry around

- Pouch design allows for flexibility in storage of different pliers
- Commonly used pliers are included
- Dipped grips deliver optimal comfort during high strength gripping
- Drop forged chrome vanadium steel and fine polished



Pliers Pliers Sets

Plier Sets, Standard, 7pcs Packing: 7

Stock No.	Description	Jaw Capacity (inches)	Length (inches)	Ĩ	Order No.
BDG98CPZ	Needle Nose Pliers	3"	8"	6	602072
BDG88CPZ	Diagonal Cutters	¹⁵ / ₁₆ "	8"	6	602073
BDG45CMP	Mini Combination Pliers	1"	4.5"	6	602074
BDG95CLMP	Mini Long Needle Nose Pliers	2 ¹ / ₁₆ "	6"	6	602080
BDG85CTMP	Mini Thin Diagonal Nose Pliers	23/ ₃₂ "	4.5"	6	602076
BDG945CMP	Mini 45 Deg Bent Nose Pliers	1"	4.5"	6	602077
BDG48CPZ	Slip Joint Pliers	1 ²⁷ / ₃₂ "	8"	6	602071

- Comes in a compact pouch that is easy to store and carry around
- Pouch design allows for flexibility in storage of different pliers
- Commonly used pliers are included
- Dipped grips deliver optimal comfort during high strength gripping
- Drop forged chrome vanadium steel and fine polished

Long Reach Miniature Pliers Set, 4pcs Packing: 4

BDGPL400LMP Order NO.: 601010

BDGCPL700

Order NO.: 601016



Stock No.	Description	Jaw Capacity (inches)	Length (inches)	۲	Order No.
BDG96LMPZ	Long Nose Pliers	1 ⁵ /16	6	6	602021
BDG97LMPZ	Needle Nose Pliers	2 ¹³ / ₃₂	7	6	602022
BDG9645LMPZ	45° Bent Nose Pliers	1 ⁷ / ₃₂	6	6	602023
BDG86LMPZ	Diagonal Cutting Pliers	3/4	5 ¹ / ₂	6	602024

- Set includes BDG86LMPZ cutters plus BDG96LMPZ, BDG9645LMPZ and BDG97LMPZ pliers (4 pcs)
- Chrome nickel finish prevents against rust and corrosion
- Cushioned grips offer comfort during extended use
- Vinyl grips provide easy cleanup and durability
- Pliers exceed ANSI standards

Extended Reach Hose Grip Pliers Set, 3pcs BDGPL300HG Packing: 3 Order NO.: 601012



Stock No.	Description	Jaw Capacity (inches)	Length (inches)	Ĩ	Order No.
BDGPL410HGZ	Small Hose Grip Pliers	2 1/4	11	6	602030
BDGPL411HGZ	Medium Hose Grip Pliers	2 ¹ / ₄	11	6	602031
BDGPL412HGZ	Large Hose Grip Pliers	2	11	6	602032

- Grips are double dipped offering increased comfort and control during use
- Pliers extra length provides additional access to otherwise difficult to reach areas
- Corrosion resistant finish
- · Leaf springs improve maneuverability

Long Reach Pliers Set, 3pcs

Packing: 3

BDGPL300LR Order NO.: 601013



Stock No.	Description	Jaw Capacity (inches)	Length (inches)	۲	Order No.
BDG311CPZ	Diagonal Cutter	1 %16	11	6	602025
BDG91145CPZ	45° Bent Needle Nose Pliers	3 ³ / ₁₆	11	6	602026
BDG911CPZ	Needle Nose Pliers	3 %16	11	6	602027

 BDG911CPZ and BDG91145CPZ pliers plus BDG311CPZ cutter (3 pcs) in storage tray

Extra Long Reach Pliers Set, 2pcs Packing: 2

BDGPL200XLR Order NO.: 601014



Stock No.	Description	Jaw Capacity (inches)	Length (inches)	۲	Order No.
BDG91645CPZ	45° Bent Needle Nose Pliers	3 ³ / ₁₆	16	6	602028
BDG916CPZ	Needle Nose Pliers	3 ⁹ /16	16	6	602029

• BDG916CPZ and BDG91645CPZ (2 pcs) in storage tray

7



Pliers Pliers Sets / Standard Pliers

Retaining Ring Pliers Set, 2pcs

PR36 Order NO.: 601001



Stock No.	Length (inches)	Ring Size Range (inches)	Tip Kit Included	Ũ
PR37	6 ¹ /4	Internal ³ / ₈ - 2	PR5 (For PR36 only)	1
PR38	6 ¹ /4	External ¹ / ₄ - 2	_	1
	Tip Sizes Included Inches/Degree	Optional Kits	Optional Tip Sizes	Order No.
PR37	2 pair each in PR36 set: .047" 0°, .070" 0°, .047" 45°, .039" 90°	PR5	.047" 0°, .070" 0°, .047" 45°, .039" 90°	605001
PR38	-	PR5	.047" 0°, .070" 0°, .047" 45°, .039" 90°	605002

Includes PR37 and PR38 pliers plus tips

Retaining Ring Pliers Set, 3pcs

Packing: 1







Stock No.	Length (inches)	Ring Size Range(inches)	Tip Kit Included	Ŵ	Order No.
PR51	9 ¹ / ₂	2 ⁷ / ₁₆ - 4	PR502	1	605006
PR52	9 ¹ / ₂	$1 \frac{1}{2} - 3 \frac{11}{32}$	PR507	1	605007
	Tip Sizes Included Inches/Degree	Optional Kits		Optional Tip Sizes	
PR51	.108", 15°	PR501		.108", 0°	
PR52	.120", 45°	PR505		.120", 0°	

• Includes PR51 and PR52 pliers plus tips in a plastic case



Stock No.	Length (inches)	Ring Size Range (inches)	۲	Order No.	Tip Kit Included	Tip Sizes Included/ Degree
PRH56A (Convertible)	6 ³ /8	Internal ¹ / ₄ - 1 External ¹ / ₈ - 1	6	605003	PRH56A-1	1 pair each: .023" 0°, .036" 0°, .047 0°, .036" 90 °, .047" 90°
PRH57A (Convertible)	8	Internal ³ / ₈ - 2 External ¹ / ₄ - 2	6	605004	PRH57A-1	1 pair each: .036" 0°, .047" 0°, .070 0°, .036" 90 °, .047 90°
PRC65A (Convertible)	10	Internal 1 ¹³ / ₆₄ - 4 External 1 ¹ / ₃ - 4	6	605005	PRC65A-1	1 pair each: .090", .108", .120" (15° and 90°)

Includes PRH56A, PRH57A and PRC65A retaining ring pliers
 PRH502A(Order No.601002) set includes PRH56A and PRH57A

retaining ring pliers

Pliers in storage case

Diagonal Cutter

PRH503 Order NO.: 601003



Stock No.	Description	Jaw Capacity (inches)	Length (inches)	۲	Order No.
BDG86CPZ	Diagonal Cutter	²¹ / ₃₂	6 ¹ / ₂	6	602005
BDG88CPZ	Diagonal Cutter	^{15/} 16	8 1/8	6	602008
BDGCT6K	Diagonal Cutting Pliers, Dipped Grip	7/ ₁₆	6	6	602048

• Dipped grip handles for easy cleaning

- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish
- Laser hardened cutting edge



BDGEC7Z

Order NO.: 602009

Pliers Standard Pliers

Combination Pliers



Stock No.	Description	Jaw Capacity (inches)	Length (inches)	۲	Order No.
BDG57CPZ	Combination Pliers	1 ¹ / ₄	7 ¹ / ₂	6	602006
BDGCB8K	Combination Pliers, Dipped Grip	7/8	8	6	602050
BDGCB9HK	Combination Pliers, Dipped Grip, High Leverage	7/ ₈	9	6	602051

- Dipped grip handles for easy cleaning
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish
- Laser hardened cutting edge

Slip Joint Pliers, Dipped Grip 📦 Packing: 6

BDG48CPZ Order NO.: 602037

🎁 Packing: 6



Stock No.	Description	Jaw Capacity (inches)	Length (inches)
BDG48CPZ	Slip Joint Pliers	1 ²⁷ / ₃₂	8

- Dipped grip handles for easy cleaning
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish

	~		
Stock No.	Description	Jaw Length	Length

Stock No.	Description	Jaw Length (inches)	Length (inches)
BDGEC7Z	End Cutter	7/16	7

• Dipped grip handles for easy cleaning

End Cutter

Packing: 6

• Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



Adjustable Joint Pliers, Dipped Grip BDGAWP100Z Order NO.: 602001

Stock No.	Description	Jaw Capacity (inches)	Length (inches)
BDGAWP100Z	Adjustable Joint Pliers	1 3/4	10

• Dipped grip handles for easy cleaning

0

• Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish









• Laser hardened cutting edge

45° Bent Needle Nose Pliers

🎁 Packing: 6

BDG9845CPZ Order NO.: 602010



Stock No.	Description	Jaw Capacity (inches)	Length (inches)
BDG9845CPZ	45° Bent Needle Nose Pliers	2 ¹³ / ₁₆	7 ³ / ₄

- Dipped grip handles for easy cleaning
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish
- Laser hardened cutting edge

Packing: 6

Long Nose Pliers, Dipped Grip

BDGLN6K Order NO.: 602049



- Dipped grip handles for easy cleaning
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish
- Laser hardened cutting edge



Stock No.	Description	SizeRange (mm)	Length (inches)	۲	Order No.
BCES7	External Circlip Pliers, Straight	19-60	7	6	605012
BCES9	External Circlip Pliers, Straight	40-100	9	6	605013
BCIS7	Internal Circlip Pliers, Straight	19-60	7	6	605016
BCIS9	Internal Circlip Pliers, Straight	40-100	9	6	605017

Circlip Pliers, Bent



Stock No.	Description	Size Range (mm)	Length (inches)	Ŵ	Order No.
BCER7	External Circlip Pliers, 90 degrees	19-60	7	6	605014
BCER9	External Circlip Pliers, 90 degrees	40-100	9	6	605015
BCIR7	Internal Circlip Pliers, 90 degrees	19-60	7	6	605018
BCIR9	Internal Circlip Pliers, 90 degrees	40-100	9	6	605019

Screw Removal Pliers





- Jaws shaped specially for removing screws
- Optimal 6" Length



Cable Cutter ۴ Cable Cutter, 6" 6 6 602062 8 Cable Cutter 8" 602063 6 Cable Cutter, 10" 10 6 602064 Special flip over handle design allows tool to be used for slicing cable sleeve • Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish Precise machined joint for ease of use and longer life For cutting cables only **Cable Diagonal Cutter BDGCT6W** Order NO.: 602067 Packing: 6 • Diagonal cutter with holes for stripping cable Laser hardened cutting edge **Plastic Cutter** BPC6 Order NO.: 602066 🍘 Packing: 6 • Flushed cutting edge for perfect cuts Thin cutting edge for precise trimming Laser hardened cutting edge **High Leverage Combination Pliers** Orde ength ٦ High Leverage Combination Pliers 160 6 602053 High Leverage Combination Pliers 180 6 602054 High Leverage Combination Pliers 240 6 602055 • New high leverage design delivers superior crimping and cutting force

- Laser hardened cutting edge
- Dual compound soft grip handles provide good grip and comfort
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish
- Precise machined joint for ease of use and longer life

High Leverage Long Nose Pliers



Stock No.	Description	Length (inches)	Ŵ	Order No.
BLN6HD	High Leverage Long Nose Pliers	160	6	602059
BLN7HD	High Leverage Long Nose Pliers	180	6	602060
BLN8HD	High Leverage Long Nose Pliers	200	6	602061

- New high leverage design delivers superior crimping and cutting force
- Laser hardened cutting edge
- Dual compound soft grip handles provide good grip and comfort
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish
- Precise machined joint for ease of use and longer life

High Leverage Diagonal Pliers



Stock No.	Description	Length (inches)	Ŵ	Order No.
BCT6HD	High Leverage Diagonal Cutting Pliers	160	6	602056
BCT7HD	High Leverage Diagonal Cutting Pliers	180	6	602057
BCT8HD	High Leverage Diagonal Cutting Pliers	200	6	602058

New high leverage design delivers superior crimping and cutting force

Laser hardened cutting edge

- Dual compound soft grip handles provide good grip and comfort
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish
- Precise machined joint for ease of use and longer life





Diagonal Cutter





B48CPAP Order NO.: 602036



Stock No.	Description	Jaw Capacity (inches)	Length (inches)	()	Order No.
B87CPAP	Side Cutter	31/ ₃₂	6 ¹⁹ / ₃₂	6	602002
BDMCT5	Diagonal Cutting Pliers	⁵ /16	5	6	602045
BDMCT6	Diagonal Cutting Pliers	⁷ / ₁₆	6	6	602046
BDMCT7	Diagonal Cutting Pliers	1/2	7	6	602047

- good grip and comfort
- polished for corrison resistant finish
- Laser hardened cutting edge

		1	
	4		-
-	-		
-			

Stock No.	Description	Jaw Capacity (inches)	Length (inches)	٢	Order No.
B58HLPAP	Combination Pliers	1 1/2	8 ³¹ / ₃₂	6	602007
BDMCB6	Combination Pliers	⁵ /8	6	6	602039
BDMCB7	Combination Pliers	⁵ /8	7	6	602040
BDMCB8	Combination Pliers	7/8	8	6	602041

- Dual compound soft grip handles provide Dual compound soft grip handles provide good grip and comfort
- Drop forged chrome/nickel alloy is fine
 Drop forged chrome/nickel alloy is fine polished for corrison resistant finish
 - Laser hardened cutting edge



B48CPAP	Slip Joint Plier	2 ³ / ₃₂	8 ¹³ / ₃₂
Stock No.	Description	Capacity (inches)	Length (inches)

- Dual compound soft grip handles provide good grip and comfort
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish







Long Nose Pliers



Stock No.	Description	Jaw Capacity (inches)	Length (inches)	۲	Order No.
B96CPAP	Long Nose Pliers	2 ¹ / ₃₂	6 ⁵ / ₁₆	6	602003
BDMLN6	Long Nose Pliers	1	6	6	602042
BDMLN8	Long Nose Pliers	1 ¹ /8	8	6	602043

Dual compound soft grip handles provide good grip and comfort
 Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish

BDMAJ10

• Laser hardened cutting edge

Adjustable Joint Pliers



Dual compound soft grip handles provide good grip and comfort
Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



BAWP100AP	Adjustable Joint Pliers	Jaw Capacity (inches) 1 ³ /8	Length (inches) 10 ⁵ / ₃₂

Dual compound soft grip handles provide good grip and comfort
Drop forged chrome/nickel alloy is fine polished for corrison resistant finish

Mini Rour	nd Nose Pliers		B75CMPAP
Packing: 6			Order NO.: 602017
Stock No.	Description	Jaw Capacity (inches)	Length (inches)
B75CMPAP	Mini Round Nose Pliers	1 ⁵ / ₃₂	5

Dual compound soft grip handles provide good grip and comfort
Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



- Dual compound soft grip handles provide good grip and comfort
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish
- Laser hardened cutting edge

Mini Thin Diagonal Cutter Packing: 6

Stock No.	Description	Jaw Capacity (inches)	Length (inches)
B85CTMPAP	Mini Thin Diagonal Cutter	²³ / ₃₂	4 ⁵ / ₈

Dual compound soft grip handles provide good grip and comfort
Drop forged chrome/nickel alloy is fine polished for corrison resistant finish



B85CTMPAP Order NO.: 602020







- Drop forged chrome/nickel alloy is fine polished for corrison resistant finish
- Laser hardened cutting edge



- Dual compound soft grip handles provide good grip and comfort
- Drop forged chrome/nickel alloy is fine polished for corrison resistant finish







	Stock No.	Description	Jaw Capacity (inches)	Length (inches)
BWPEC5AP MINI PINCER 7/16 4 7/32	BMPEC5AP	Mini Pincer	5/16	4 ¹ / ₃₂

Dual compound soft grip handles provide good grip and comfort
Drop forged chrome/nickel alloy is fine polished for corrison resistant finish



Dual compound soft grip handles provide good grip and comfort
Drop forged chrome/nickel alloy is fine polished for corrison resistant finish





- Dual compound soft grip handles provide good grip and comfort
 Drop forged chrome/nickel alloy is fine polished for corrison
- Drop forged chrome/nickel alloy is fine polished for corrison resistant finish

Mini Circlip Pliers, Straight



Stock No.	Description	Length (inches)	I	Order No.
BCES5	External	5	6	605020
BCES6	External	6	6	605021

- Dual compound soft grip handles provide good grip and comfort
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish
- Precise machined joint for ease of use and longer life

Mini Circlip Pliers, Straight



Stock No.	Description	Length (inches)	(Order No.
BCIS5	Internal	5	6	605022
BCIS6	Internal	6	6	605023

- Dual compound soft grip handles provide good grip and comfort
 Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish
- Precise machined joint for ease of use and longer life

Mini Circlip Pliers, 45 Degree



Stock No.	Description	Length (inches)	i	Order No.
BCEH5	External	5	6	605024
BCEH6	External	6	6	605025

- Dual compound soft grip handles provide good grip and comfort
- Drop forged chrome/nickel alloy is fine polished for corrison resistant finish
- Precise machined joint for ease of use and longer life



Mini Circlip Pliers, 45 Degree



Stock No.	Description	Length (inches)	i i i	Order No.
BCIH5	Internal	5	6	605026
BCIH6	Internal	6	6	605027

- Dual compound soft grip handles provide good grip and comfort
 Drop forged chrome/nickel alloy is fine polished for corrosion
- resistant finish
- Precise machined joint for ease of use and longer life



0



Mini Circlip Pliers, 90 Degree



Stock No.	Description	Length (inches)	i	Order No.
BCER5	External	5	6	605028
BCER6	External	6	6	605029

- Dual compound soft grip provides comfort and control
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish
- Precise machined joint for ease of use and longer life

Mini Circlip Pliers, 90 Degree



Stock No.	Description	Length (inches)	(Order No.
BCIR5	Internal	5	6	605030
BCIR6	Internal	6	б	605031

Dual compound soft grip provides comfort and control

 Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish

• Precise machined joint for ease of use and longer life

Diagonal Cutting Pliers





Pliers VDE Pliers

Long Nose Pliers



Stock No.	Description	Length (mm)	i	Order No.
WT1001-6	Long Nose Pliers	160	6	603005
WT1001-8	Long Nose Pliers	200	6	603006

- Chrome vanadium steel
- All tools are tested under 10,000 Voltage testing machine
- Special designed soft grips
- Laser hardened cutting edge

Side Cutter



Stock No.	Description	Length (mm)	i i i	Order No.
WT1003-6	Side Cutter	160	6	603007
WT5403-8	Side Cutter	203	6	603008

• Chrome vanadium steel

- All tools are tested under 10,000 Voltage testing machine
- Special designed soft grips
- Laser hardened cutting edge

Wire Stripping Pliers



Stock No.	Description	Length (mm)	i	Order No.
WT1017C-6	Wire Stripping Pliers	160	6	603009

- Chrome vanadium steel
- All tools are tested under 10,000 Voltage testing machine
- Special designed soft grips
- Laser hardened cutting edge

Slip Joint Pliers



Stock No.	Slip Joint Pliers	Length (mm)	(Order No.
WT8627-10	Slip Joint Pliers	250	6	603010

- Chrome vanadium steel
- All tools are tested under 10,000 Voltage testing machine
- Special designed soft grips
- Laser hardened cutting edge

7

Combination Pliers



Stock No.	Description	Length (mm)	(Order No.
WT1014-6	Combination Pliers	160	6	603001
WT1014-7	Combination Pliers	180	6	603002
WT1014-8	Combination Pliers	200	6	603003
WT5414-9	Combination Pliers, Heavy Duty	225	6	603004

- Chrome vanadium steel
- All tools are tested under 10,000 Voltage testing machine
- Special designed soft grips
- Laser hardened cutting edge





Pliers Locking Pliers

Straight Jaws



Stock No.	Description	Jaw Capacity (inches)	Length (inches)	۲	Order No.
BDGLP7SAP	Straight Jaws	1 ⁵ /16	7	6	604013
BDGLP10SAP	Straight Jaws	1 ³ /4	10	6	604014

- Exceed ASME specification
- Straight jaws with maximum contact area
- Nickel plated to resist corrosion
- · Convenient, one hand release lever

Straight Jaws, Soft Grip



Stock No.	Description	Jaw Capacity (inches)	Length (inches)	Ŵ	Order No.
BDMLP7SAP	Straight Jaws, Soft Grip	1 ⁵ /16	7	6	604015
BDMLP10SAP	Straight Jaws, Soft Grip	1 ³ /4	10	6	604016

- Exceed ASME specification
- · Straight jaws with maximum contact area
- Nickel plated to resist corrosion
- Convenient, one hand release lever
- Non-slip cushion grip

Packing: 1

Chain Style Locking Pliers

VGP18110 Order NO.: 604012



Stock No.	Chain Capacity (inches)	Handle Length (inches)
VGP18110	up to 6 ⁹ /32	9 ²⁷ /32

 Wraps around and holds irregular shaped objects like oil filters and mufflers quickly and easily

C-Clamp Locking Pliers



	Stock No.	Jaw Capacity (inches)	Length (inches)	Ì	Order No.
	VGP12406	2 ⁵ /16	6	1	807020
Standard Tip	VGP12412	3 ⁵ / ₁₆	12	1	604011
Stanuaru rip	VGP12418	10 ¹ / ₄	18	1	807021
	VGP12424	15 ^{11/} 16	24	1	807022
	Stock No.	Jaw Capacity (inches)	Length (inches)	Ŵ	Order No.
	Stock No. VGP22406) 1	
Suival Tin		(inches)	(inches)) 1 1	No.
Swivel Tip	VGP22406	(inches) 1 ^{5/} 16	(inches) 6	-	No. 807023

- Quick and easy handling clamps for autobody and metal fabrication applications
- Spring-loaded release lever permits quick "NO PINCH" release even when tool is firmly locked
- Locking nut allows setting for repetitive jobs

Locking U-Clamp Pliers

Packing: 1

VGP12509 Order NO.: 604009



Stock No.	Jaw Capacity (inches)	Length (inches)	
VGP12509	2 ^{5/} 16	9	

- U-shaped jaws allow access and perfect visibility when welding
- E-coat provides extra resistance against corrosion and welding splatter
- Quality cold-rolled steel ensures years of service
- Drop forged jaws ensure a tough, durable tool
- Smooth rounded edges allow comfortable handling and reduce risk of injury
- Spring-loaded release lever permits quick "NO PINCH" release even when tool is firmly locked
- · Piano wire spring provides smooth jaw opening
- Adjustment bolt features deep knurl to accommodate greasy hands
- Locking nut allows setting for repetitive jobs
- Drilled (not punched) holes in mobile jaw ensure maximum bearing with rivets for smooth action
- Large diameter rivets add strength and durability


Pliers Locking Pliers / Retaining Ring Pliers / Special Pliers

Sheet Metal Locking Pliers



Stock No.	Jaw Capacity (inches)	Length (inches)
VGP12808	1 ³ /4	8

- · Wide jaws allow clamping, bending, forming and crimping of sheet metal without gripping effort
- · E-coat provides extra resistance against corrosion and welding splatter
- Quality cold-rolled steel ensures years of service
- Drop forged jaws ensure a tough, durable tool
- Smooth rounded edges allow comfortable handling and reduce risk of injury
- Spring-loaded release lever permits quick "NO PINCH" release even when tool is firmly locked
- · Piano wire spring provides smooth jaw opening
- Adjustment bolt features deep knurl to accommodate greasy hands
- Locking nut allows setting for repetitive jobs
- Drilled (not punched) holes in mobile jaw ensure maximum bearing with rivets for smooth action
- Large diameter rivets add strength and durability

Retaining Ring Pliers, Internal

PR7 Order NO.: 605008



Tip Kit Included	Tip Sizes Included	Optional Kits	Optional Tip Sizes
PR7-1	.120", 0°	PR7-2	.120", 45°
Optional Kits	Optional Tip Sizes	Length (inches)	Ring Size Range (inches)
PR7-3	.120", 90°	15 ^{11/} 16	3 ¹ /16 - 6 ¹ /4

• Retaining ring pliers, interchangeable tip

Retaining Ring Pliers, External

📦 Packing: 1

Packing: 1

PR8 Order NO.: 605009



Tip Kit Included	Tip Sizes Included	Optional Kits	Optional Tip Sizes
PR7-1	.120", 0°	PR7-2	.120", 45°
Optional Kits	Optional Tip Sizes	Length (inches)	Ring Size Range (inches)
PR7-3	.120", 90°	15 ^{11/} 16	3 ¹ / ₁₆ - 6 ¹ / ₄

Retaining ring pliers, interchangeable tip

Retaining Ri	PR54 Order NO.: 605010		
			-
Tip Kit Included	Tip Sizes Included	Optional Kits	Optional Tip Sizes
Tip Kit Included PR54-1	Tip Sizes Included .150", 0°	Optional Kits PR54-2	Optional Tip Sizes .150", 45°

• Retaining ring pliers, interchangeable tip, internal, 29"

Retaining Ring Pliers, External

Packing: 1

PR53 Order NO.: 605011



Tip Kit Included	Tip Sizes Included	Optional Kits	Optional Tip Sizes
PR53-1	.170", 0°	PR53-2	.170", 45°
Optional Kits	Optional Tip Sizes	Length (inches)	Ring Size Range (inches)
PR53-3	.170", 90°	19	6 ¹ /2 - 10

Retaining ring pliers, interchangeable tip, external, 19"

Bolt Cutter, Heavy Duty



Stock No.	Capacity- (Soft Material) (inches)	Capacity- (Hard Material) (inches)	Length (inches)	Weight (kg)	Ŵ	Order No.
BLPBC18	3/8	1/4	18	1.55	2	606001
BLPBC24	⁷ / ₁₆	⁵ / ₁₆	24	2.55	2	606002
BLPBC30	1/2	3/8	30	3.90	1	606003
BLPBC36	^{9/} 16	⁷ / ₁₆	36	6.45	1	606004

Ideal for cutting rod, bolts, concrete form ties and fencing wire

Hardened alloy steel jaws

Center cut jaw configuration provides balance while cutting

Cuts soft or hard materials

Rubber gripped steel handles ensure firm grip during use

Bolt Cutter Replacement Jaws



Stock No.	Description	i i i	Order No.
BLPBC18-1	Bolt Cutter Replacement Jaws, 18"	1	606005
BLPBC24-1	Bolt Cutter Replacement Jaws, 24"	1	606006
BLPBC30-1	Bolt Cutter Replacement Jaws, 30"	1	606007
BLPBC36-1	Bolt Cutter Replacement Jaws, 36"	1	606008

Ideal for cutting rod, bolts, concrete form ties and fencing wire

Hardened alloy steel jaws

Center cut jaw configuration provides balance while cutting

Cuts soft or hard materials







Torque Tools

Our torque wrenches are made in the USA where the best torque products come from.

Each unit is factory calibrated and certified to meet ASME specified accuracy on a torque standard traceable to the National Institute of Standards and Technology.

Designs like the sealed high strength ratchet head keeps out dirt and moisture in the harshest environment giving you a reliable tool that constantly deliver accurate results.

Its internal mechanism is also permanently lubricated during assembly for a trouble free service life.

You can thus be assured of accuracy, reliability and a maintenance-free equipment when getting our torque products.





7) E

-Point®



Torque Tools Adjustable Click-Type / Preset Click-Type

Adjustable Click-Type Torque Wrench





Stock No.	Square Drive (inches)	Range (Nm)	Range (Ft.Lb.)	Increment (Nm)	A (mm)	B (mm)	Weight (g)		Order No.
BP501NMRMH	1/4	1.0 - 5.0	1 - 4	0.06	258	27	386	1	203001
BP2502NMRMH	3/8	4.0 - 27.7	3 - 20	0.12	286	27	431	1	203002
BP602NMRMH	3/8	10 - 60	8 - 45	0.5	406	36	1,134	1	203003
BP1002NMRMH	3/8	20 - 100	15 - 75	0.5	406	36	1,134	1	203004
BP2003NMRMH	1/2	40 - 200	30 - 150	2	483	43	1,474	1	203005
BP3403NMRMH	1/2	60 - 340	45 - 250	2	620	43	1,542	1	203006
BP8004NMRMH	3/4	150 - 800	110 - 600	5	1,067	64	5,375	1	203007
BP15005NMRMH	1	300 - 1500	220 -1100	10	1,778	76	11,385	1	203008

- Dual scale, calibrated dual direction
- Positive lock with spring loaded pull down lock ring
- Fast, accurate and easy to set
- Easy-to-read laser marked scales
- Most feature quick release buttons which provide good socket retention as well as easy socket removal
- Accuracy: ± 3% CW ± 4% CCW of indicated value, CW, from 20% to 100% of full scale
- Meets or exceeds ASME B107.14-2004, ISO 6789 standards
- Individually serialized with matching certificate of calibration traceable to N.I.S.T.

Preset Click-Type Torque Wrench





Stock No.	Square Drive (inches)	Range (Nm)	Range (Ft.Lb.)	Range (In.Lb.)	Range (M Kg)	Length (mm)	Weight (g)	۲	Order No.
BP5T-1R	1/4	1.4- 5.4	1-5	12 - 60	0.10 - 0.70	165	227	1	204001
BP10T-2R	3/8	3.9-27.7	3-9	36 - 108	0.42 - 1.24	184	397	1	204002
BP50T-2R	3/8	10.2 - 98.3	10 - 50	120 - 600	1.25 -7.00	292	680	1	204003
BP100T-3R	1/2	34-197	45 - 150	540 - 1800	6.00 - 20.00	502	1,247	1	204004
BP200T-3R	1/2	47 - 272	45 - 200	540 - 2400	6.00 - 27.00	603	1,361	1	204005
BP300T- 4R	3/4	85 - 400	100 - 300	1200 - 3600	14.00 - 42.00	711	2,155	1	204006
BP600T- 4R	3/4	280 - 830	200 - 600	2400 - 7200	28.00 - 83.00	1,321	5,443	1	204007

- Torques in both left and right hand directions
- Accuracy: ± 3% CW ± 4% CCW of indicated value
- Automatic re-set when force on handle is released
- Torque limiting positive sensory "click" when pre-set
- Smooth knurled steel hand hold for comfortable, safe grip
- Handle length proportioned to torque range of wrench for minimum user fatigue
- Tamper proof torque setting for production line use
- Torque values can be calibrated in English and Metric settings
- All parts are made of alloy steel for maximum life and calibration retention
- Square drives meet industrial requirements and government specifications

Preset Click-Type Torque Wrench, "L" Series



Stock No.	Square Drive (inches)	Range (Nm)	Range (Ft.Lb.)	Length (mm)	Weight (g)	۲	Order No.
BP10T-2RL	3/8	4 - 30	21 - 20.4	184	450	1	204016
BP50T-2RL	3/8	10 - 100	7.3 - 72.2	350	700	1	204017
BP100T-3RL	1/2	35 - 200	25 - 145	530	1220	1	204018
BP200T-3RL	1/2	45 - 280	34.6 - 200	630	1380	1	204019
BP250T-3RL	1/2	60 - 340	44.2 - 250.8	630	1380	1	204020

- A higher performance wrench than similar ones offered by the competitor
- Blue-point ratchet heads are smaller than competitor
- Blue-point 40 tooth ratchet head vs. the competitor; much less "swing arc"
- Blue-point wrench tubes are smaller diameter at the throat; greater access
- Ratchets are bi-directional
- High durability survived 50,000 cycle testing in both directions; competitor failed at 12,000 cycles
- Improved calibration performance; Blue-point remained calibrated after 25,000 cycles. Competitors wrench fell out of calibration prior to required 5,000 cycles



Torque Tools Preset Click-Type

Preset Click-Type Torque Wrench, Interchangeable Head





Stock No.	Shank Size	English Range	Range (Nm)	A (mm)	B (mm)	C (mm)	D (mm)	Weight (g)	Ŵ	Order No.
BP5T-I	J	10 - 50 in.lb.	1.1 - 5.6	165	16	15	25	159	1	204008
BP10T-I	J	50 - 250 in.lb.	5.6 - 28	254	16	15	25	249	1	204009
BP10ST-I	J	60 - 300 in.lb.	6.8 - 34	157	17	22	36	340	1	204010
BP50T-I	J	15 - 75 ft.lb.	20 - 102	279	17	22	36	635	1	204011
BP100T-I	Y	30 - 150 ft.lb.	41 - 203	495	24	22	36	1,043	1	204012
BP200T-I	Y	40 - 200 ft.lb.	54 - 271	597	24	22	36	1,179	1	204013
BP300T-I	Х	100 - 300 ft.lb.	135 - 406	704	28	25	36	1,769	1	204014
BP600T-I	Z	120 - 600 ft.lb.	162 - 814	1,397	38	32	32	4,740	1	204015

- Eight models available with torque ranges from 10 in. lb. to 600 ft. lb.
- Featuring a durable, non-slip cushion grip
- Uses universal round shank heads
- Audible click and feel impulse torque control mechanism
- Tamper proof torque setting for production line use

Ratcheting Interchangeable Head



Allow use of torque wrench bodies with sockets,

crowfoot wrenches, or other similar attachment.

• Torque values can be calibrated in english or metric setting

Meets or exceeds ASME B107.14-2004, ISO 6789

• Calibration certificate available at additional cost

• Accuracy: ± 4% of indicated value, from 20% to 100% of full scale

Square Drive (inches)	Shank Size J	Shank Size Y	Shank Size X	Shank Size Z	Head O.D. (mm)	Depth (mm)	Ratchet Service Kit
1/4	QJD8A-72* (350)	_	_	_	3	3.5	RKRT936
3/8	QJD12A* (900)	QYD12A* (1,200)	_	_	17	4.4	RKRF936
1/2	QJD16A* (900)	QYD16A* (2,400)	QXD16A* (3,000)	_	17	4.4	RKRS936
3/4	—	_	QXD24A (3,600)	QZD24B (7,200)	20	4.4	RKRQC4
1	_	_	QXD32A (3,600)	QZD32B (7,200)	20	4.4	RKRQC5

* U.S. Patent 6,125,722 applies to these ratchet heads

Value in parentheses in chart is the Maximum Recommended Working Torque, in. Ib.

Open End Head, mm



••• <u>I</u>	Shank Size J	Shank Size Y	Shank Size X	Shank Size Z	Head O.D. (mm)	Head Depth (mm)	• 1	Shank Size J	Shank Size Y	Shank Size X	Shank Size Z	Head O.D. (mm)	Head Depth (mm)
6	QJOM6A (60)	_	_	—	13.5	3.6	20	-	QYOM20A (1,925)	QXOM20A (1,925)	_	43.7	9.2
7	QJOM7A (75)	—	—	—	13.5	3.6	21	QJOM21A (900)	QYOM21A (2,160)	QXOM21A (2,160)	_	43.7	9.2
8	QJOM8A (120)	—	_	—	16.5	3.3	22	QJOM22A (900)	QYOM22A (2,400)	QXOM22A (2,470)	_	43.7	9.2
9	QJOM9A (170)	—	—	—	19.8	4.8	23	QJOM23A (900)	QYOM23A (2,400)	QXOM23A (2,745)	_	47	10
10	QJOM10A (265)	—	—	_	19.8	4.8	24	QJOM24A (900)	QYOM24A (2,400)	QXOM24A (2,970)	QZOM24A (2,970)	49	11
11	QJOM11A (400)	_	_	—	22.9	5.6	25	QJOM25A (900)	QYOM25A (2,400)	_	QZOM25A (3,295)	52	11
12	QJOM12A (430)	—	—	—	26.9	6.1	26	QJOM26A (900)	—	QXOM26A (3,570)	QZOM26A (3,570)	53	11
13	QJOM13A (495)	—	_	_	26.9	6.1	27	QJOM27A (900)	QYOM27A (2,400)	_	QZOM27A (3,825)	55	12
14	QJOM14A (665)	QYOM14A (665)	—	—	29.5	6.6	29	-	QYOM29A (2,400)	QXOM29A (3,600)	QZOM29A (4,550)	58	12
15	QJOM15A (885)	QYOM15A (885)	_	_	33.3	6.9	30	-	QYOM30A (2,400)	QXOM30A (3,600)	QZOM30A (4,950)	61	13
16	QJOM16A (900)	QYOM16A (1,060)	_		33.3	6.9	32	-	QYOM32A (2,400)	QXOM32A (3,600)	QZOM32A (5,755)	65	14
17	QJOM17A (900)	QYOM17A (1,235)	_		37.1	7.3	34	-	QYOM34A (2,400)	QXOM34A (3,600)	QZOM34A (6,595)	68	14
18	QJOM18A (900)	QYOM18A (1,375)	QXOM18A (1,375)	_	37.1	7.3	36	-	QYOM36A (2,400)	QXOM36A (3,600)	QZOM36A (7,200)	74	15
19	QJOM19A (900)	QYOM19A (1,650)	QXOM19A (1,650)	_	40.4	7.6							

Value in parentheses is the Maximum Recommended Working Torque, in. lb.



Torque Tools Electronic Type

Computorq 3 Digital Torque Wrench



Stock No.	Square Drive (inches)	Range (Ft. Lb.)	Range (In. Lb.)	Range (Nm)	Range (Kg. Cm.)	Length (mm)	Weight (g)	Ĩ	Order No.
BP2401Cl3	1/4	2.0 - 20.0	24 - 240	2.71 - 27.10	27.6 - 276	381	910	1	205001
BP1002CF3	3/8	10.0 - 100.0	120 - 1200	13.6 - 135.6	138 - 1382	432	1,000	1	205002
BP2503CF3	1/2	25 - 250	300 - 3000	33.8 - 338	345 - 3456	686	1,590	1	205003



Torque Tools Digital Torque Testers

Digital Torque Tester



- Integral Transducer and sturdy housing allow mounting in virtually any position
- Integral Transducer: Full bridge strain gage, 350 ohm, 1500uE, 3mV/V F.S, 3.75 excitation
- Units of Torque: Nm, kgcm, ft.lb., in.lb., in-oz.
- Audible (tone)
- Torque Accuracy: ±0.5% ±1 count CW and CCW from 10 to 100% of full scale at 25° C
- LCD Touch Screen: 4.7 in. color graphics display
- Screen resolution: 480 X 272 pixels
- Display Accuracy: 4 digits, 500 cycle counts
- Six "AA" Alkaline cells for battery power included
- Track, Peak and First Peak modes of operation
- Operating Temperature: 40 to 110° F (5 to 42° C)
- Storage Temperature: 0 to 122° F (-20 to 50° C)
- Humidity up to 85% non-condensing
- ISO-6789-2003 and ASME B107-28-2005 standards compliant
- Certificate of N.I.S.T. traceability from 10% to 100% of full scale
- Includes storage case, AC adapter and USB cable110 220v
 Dates & times, serial numbers, required accuracy vs actual
- readings, percentage error & users of torque wrenches tested are stored

Stock No.	Square Drive (inches)	English Range	Range (Nm)	i	Order No.
BP1001-O-DTT	1/4	10 - 100 in.oz.	0.07 - 0.706	1	206001
BP501-I-DTT	1/4	5 - 50 in.lb.	0.56 - 5.65	1	206002
BP2502-I-DTT	3/8	25 - 250 in.lb.	2.82 - 28.25	1	206003
BP2503-F-DTT	1/2	25 - 250 ft.lb.	33.90 - 338.9	1	206004
BP6004-F-DTT	3/4	60 - 600 ft.lb.	81.35 - 813.5	1	206005
BP10002-I-DTT	3/8	100 - 1000 in.lb.	11.3 - 113	1	206006

Digital Torque Tester







Power Tools





In making our power tools, we observed the fact that not only has it got to be durable and perform well, it is not much good if you are fighting excess weight, vibration and noise. Basing on this, we come up with a whole range of power tools that embrace these qualities and more.

Air

Our impact wrench feature unique twin hammer impact mechanism to deliver more power per blow. Having more vanes in the rotor also helps in delivering more power as well as a smoother power transfer to the impact hammers. The aluminium alloy housing maintains tool toughness and durability. All these are achieved while keeping weight and vibration to a minimum.

Cordless

Heavy duty components combined with strong and lightweight bodies give our cordless tools more power while being light. Ergonomic grips coupled with vibration absorbing features offer a smoother, more comfortable operation. And long lasting high capacity batteries allow you to work longer with less disruption. The result is a compact power tool that is lightweight, balanced and delivers performance you need.





1" Impact Wrench, Heavy Duty Packing: 1 AT1300A Order NO.: 701001



AT1300AL (6"long Anvil)

Order NO.: 701002

Drive Size (inches)	Max. Torque (N•m)	Free Speed RPM	Blows per Minute
1	4,068	4,000	505
Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)
150	¹ /2"-14 NPT	1/2	4.4
Sound Level dBa Pressure	Length (mm)	Weight (kg)	Vinyl Boot (optional)
103	533	11.6	_

- Fast, 4,000 RPM free speed-strong 3,000 ft. lb. maximum torque output
- Workhorse performance for use on trucks, buses and heavy equipment
- Steel nose for rugged, demanding applications
- Pin clutch style impact mechanism for fast startup and high torque requirements

3/4" Drive Impact Wrench

🎁 Packing: 1

AT670 Order NO.: 701066



³ /8"-18 NPT	³ /4 in.	1,050 ft. lbs.	6,700
Air Inlet Thread Size	Drive Size	Max Torque	Free Speed RPM

• Aluminium nose with composite body for lightweight & durability

- Twin-hammer mechanism easily removes stubborn nuts
- Three-position lever controls amount of torque
- Two-way push buttons controls Forward/Reverse rotation

1/2" Impact Wrench, Soft Handle

💗 Packing: 1

AT555B Order NO.: 701007



Drive Size (inches)	Max. Torque (N•m)	Free Speed RPM	Blows per Minute
1/2	644(F), 745(R)	6,800 (F), 7,500 (R)	1,000
Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)
62	^{1/} 4" -18 NPT	3/8	3.75
Sound Level dBa Pressure	Length (mm)	Weight (kg)	Vinyl Boot (optional)
100	198	2.6	AT555BOOT

• Powerful twin hammer clutch

• Reverse bias air motor provides greater power in reverse when extra breakaway torque is needed

- Built-in power regulator
- Molded ergonomic handle grip
- Quiet Muffler
- Through-handle exhaust

1/2" Impact Wrench, Composite Rear Housing ATC500 Packing: 1 Order NO.: 701009



Drive Size (inches)	Max. Torque (N•m)	Free Speed RPM	Blows per Minute
1/2	712	10,500	1,250
Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)
99	^{1/4} " -18 NPT	3/8	<2.5
Sound Level dBa Pressure	Length (mm)	Weight (kg)	Vinyl Boot (optional)
95.5	198	2.3	IMC500BOOT

 Aluminum front housing and composite rear housing contribute to an extremely durable, lightweight, balanced unit

- Ribbed, textured handle for maximum comfort and control
- Four position power regulator for greater job versatility
- Twin hammer impact mechanism for longer life and greater power



1/2" Impact Wrench

Packing: 1



AT123BL (2" Long Anvil)

Order NO.: 701006

AT123B

Order NO.: 701005

Drive Size (inches)	Max. Torque (N•m)	Free Speed RPM	Blows per Minute
1/2	576	9,000	1,000
Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)
79	^{1/} 4" -18 NPT	3/8	13
Sound Level dBa Pressure	Length (mm)	Weight (kg)	Vinyl Boot (optional)
108	185	2.6	AT123-45

• Twin hammer impact mechanism provides harder hitting blows

• Steel nose case with lightweight aluminum housing

• Pressure feed grease lubrication

• Convenient slide bar forward/reverse

1/2" Composite Impact Wrench

🂗 Packing: 1

AT570 Order NO.: 701064



Drive Size (inches)	Max. Torque (N•m)	Free Speed RPM	Blows per Minute
1/2	773	6,900(F), 7,000(R)	1,050
Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)
5.0 cfm(F), 5.3 cfm (rev.)	^{1/} 4" -18 NPT	³ /8	6.08
Sound Level dBa Pressure	Length (mm)	Weight (kg)	Vinyl Boot (optional)
95	184	1.87	AT570BOOT

• Shot Peen Anvils for improved durability

- Reverse Bias motor provides additional breakaway torque
- 3 position regulator to control power
- One handed forward/reverse lever for user convenience
- Composite housing with aluminum nose combine to deliver a durable, lightweight and balanced unit.
- Twin hammer impact mechanism delivers hard hitting blows to quickly remove stubbom fasteners

Impact Wrench



Twin hammer impact mechanism provides harder hitting blows



Steel nose case with lightweight aluminum housing



Five-position air speed regulator;

convenient slide bar forward/reverse

8

Jon p



Pressure feed grease lubrication

WARNING 😡 💷 🔘 🍐 Use only impact sockets and accessories with impact wrenches 79



3/8" Impact Wrench

💗 Packing: 1



Drive Size (inches)	Max. Torque (N•m)	Free Speed RPM	Blows per Minute
3/8	230	8,700	1,680
Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)
111	^{1/} 4" -18 NPT	3/8	3.5
Sound Level dBa Pressure	Length (mm)	Weight (kg)	Vinyl Boot (optional)
94	165	1.36	AT380ABOOT

- 10% more power than the AT380
- Built-in five position adjustable air regulator plus a variable speed trigger for maximum user control
- Aluminum housing provides a lightweight yet durable tool
- Tapered nose increases accessibility to confined areas
- Ball-bearing mounted motor creates a smooth running operation for less user fatigue
- Brass inlet filter screens out dirt and grit; easy-to-remove filter for cleaning
- Twin-hammer impact mechanism designed to hit hard yet offer tool longevity. One-year limited warranty

3/8" Impact Wrench, Composite

AT370 Order NO.:701065

AT380A

Order NO.: 701010



Drive Size (inches)	Max. Torque (N•m)	Free Speed RPM	Blows per Minute
3/8	434	10,000(F), 11,000(R)	1,050
Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)
4.4 cfm(F), 4.7 cfm (R)	^{1/} 4" -18 NPT	3/8	3.25
Sound Level dBa Pressure	Length (mm)	Weight (kg)	Vinyl Boot (optional)
92	160	1.19	AT370BOOT

- Shot Peen Anvils for improved durability
- Reverse Bias motor provides additional breakaway torque
- 3 position regulator to control power
- One handed forward/reverse lever for user convenience
- Composite housing with aluminum nose combine to deliver a durable, lightweight and balanced unit.
- Twin hammer impact mechanism delivers hard hitting blows to quickly remove stubbom fasteners

3/8" Impact Wrench, Single Hammer

💗 Packing: 1



	A	T321
Order NO.	:	701011

Drive Size (inches)	Max. Torque (N•m)	Free Speed RPM	Blows per Minute
3/8	237	11,000	1,500
Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)
108	^{1/} 4" -18 NPT	3/8	9.8
Sound Level dBa Pressure	Length (mm)	Weight (kg)	Vinyl Boot (optional)
109	155	1.3	AT321-44

- Single hammer impact mechanism
- Steel nose case with lightweight aluminum housing
- Convenient slide bar forward/reverse

3/8" Impact Wrench, Compact

AT351 Order NO.:701013



Drive Size (inches)	Max. Torque (N•m)	Free Speed RPM	Blows per Minute
3/8	237	9,700	1,200
Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)
71	^{1/} 4" -18 NPT	3/8	3.09
Sound Level dBa Pressure	Length (mm)	Weight (kg)	Vinyl Boot (optional)
109.2	194	1.2	—

- Built-in air inlet swivel
- 8 position power regulator
- Rotary action air motor is ball bearing mounted for balance, speed and power
- Ideal tool for small engine repair and bench work



1/4" Impact Wre Packing: 1	nch, Mini		AT235MCA Order NO.: 701014
Drive Size (inches) M	ax. Torque (N•m)	Free Speed RPM	Blows per Minute

Drive Size (inches)	INIAN. TOTQUE (INITI)	Flee Speed KFM	Diows per minute
1/4	34	13,000	2,900
Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)
47	^{1/} 4" -18 NPT	3/8	<2.5
Sound Level dBa Pressure	Length (mm)	Weight (kg)	Vinyl Boot (optional)
95.1	158	64	

- Composite housing contributes to an extremely durable, lightweight unit with new molded comfort grip
- Composite housing is not cold to the touch
- Forward/Reverse mechanism easily operated with one-finger
- Large, variable speed trigger for control

• Exhaust is from the handle bottom, keeping exhaust away from work area and user



Drive Size (inches)	Torque Range (N•m)	Free Speed RPM	Air Consumption, Free Speed (L/MIN)
3/8	6 - 75	200	111
Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)	Sound Level dBa Pressure
^{1/} 4" -18 NPT	3/8	<3.9	104
Length (mm)	Weight (kg)		Vinyl Boot (included)
266	1.5		_

- Lightweight aluminum housing
- Rugged ball bearing mounted air motor and precision planetary gear system
- Easy to use variable speed throttle plus adjustable air regulator



Drive Size (inches)	Torque Range (N•m)	Free Speed RPM	Air Consumption, Free Speed (L/MIN)
1/2	6 - 68	150	85
Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)	Sound Level dBa Pressure
^{1/4} "-18 NPT	3/8	8.7	89
Length (mm)	Weight (kg)	Vinyl Boot (included)	
273	1.14	Α	T700E49A

- 1/2" drive ratchet in a 3/8" drive body
- Delivers 50 ft. lb. of maximum torque
- Ball bearing mounted motor for longer tool life

3/8" Ratchet, High Torque Packing: 1

AT702 Order NO.: 701018



Drive Size (inches)	Torque Range (N•m)	Free Speed RPM	Air Consumption, Free Speed (L/MIN)
3/8	6 - 81	200	85
Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)	Sound Level dBa Pressure
^{1/} 4"-18 NPT	³ /8	12.6	95
Length (mm)	Weight (kg)	Vinyl	Boot (included)
265	1.1		AT700E49A

• Flywheel mechanism

- Rugged ball bearing mounted air motor coupled with precision planetary gear system
- Easy to use variable speed throttle and adjustable air regulator



3/8" Ratchet AT738 Packing: 1 Order NO.: 701019 3/8 0 - 81 300 113 3/8 1/4"-18 NPT 5.9 102 285 1.3 AT738BOOT

- Reactionless mechanism absorbs kickback when running fasteners tight
- High RPM removes fasteners quickly
- Adjustable air regulator
- Ideal tool for spark plugs, water pumps, shocks and muffler clamps



1/4	6 - 34	285	88
Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)	Sound Level dBa Pressure
^{1/} 4" -18 NPT	3/8	<4.4	100
Length (mm)	Weight (kg)	Vinyl Boo	t (included)
188	57		_

Lightweight aluminum housing

1/4" Ratchet

- Rugged ball bearing mounted air motor and precision planetary gear system
- Easy to use variable speed throttle plus adjustable air regulator



Drive Size (inches)	Torque Range (N•m)	Free Speed RPM	Air Consumption, Free Speed (L/MIN)
3/8	6 - 61	150	85
Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)	Sound Level dBa Pressure
^{1/} 4" -18 NPT	³ /8	8.7	89
Length (mm)	Weight (kg)	Vinyl Boo	ot (included)
257	1.6	AT70	00E49A

- Lightweight aluminum housing
- Rugged ball bearing mounted air motor and precision planetary gear system
- Easy to use variable speed throttle plus adjustable air regulator

📦 Packing: 1

AT200D Order NO.: 701021



Drive Size (inches)	Torque Range (N•m)	Free Speed RPM	Air Consumption, Free Speed (L/MIN)
1/4	6 - 27	150	40
Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)	Sound Level dBa Pressure
^{1/} 4" -18 NPT	3/8	3.3	85
Length (mm)	Weight (kg)	Vinyl Boot (included)	
222	50	AT200D22A	

- Lightweight aluminum housing
- Rugged ball bearing mounted air motor and precision planetary gear system



1/4" Ratchet, Mini



Drive Size (inches)	Torque Range (N•m)	Free Speed RPM	Air Consumption, Free Speed (L/MIN)
1/4	6 - 30	275	68
Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)	Sound Level dBa Pressure
¹ /4"-18 NPT	3/8	<1.7	91
Length (mm)	Weight (kg)	Vinyl Bo	ot (included)
127	66		_

- Ideal for working in tight guarters
- Head clearance is less than 3/4"
- Includes variable speed trigger, adjustable air regulator and 5' nylon braided whip hose for maneuverability and control
- Polished aluminum housing provides strength and durability



- One hand forward/reverse operation
- Three planet gear design for durability and balance
- Bottom handle diffused exhaust
- Comfort grip handle
- Keyed chuck easily handles 120 in. lbs. of torque
- · Chuck key stores in handle



Chuck Size (inches)	Rated Power (kW)	Torque Range (N•m)	Free Speed RPM
⁵ /16	_	_	1,800
Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)
238	^{1/} 4"-18 NPT	³ /8	<1.0
Sound Level dBa Pressure	Length (mm)	Weight (kg)	Spotweld Drill Bit (8mm) (included)
84	201	1.4	AT183-50
Spotweld Drill Bit (6.5mm) (optional)	Support Arm ((optional)	5.5 Spot	weld Drill Bit (10mm) (optional)
AT183-43	AT184-26A		AT183-51

- Twist depth control collar allows precise setting of drilling depth up to 1/4"
- Two speed trigger for low or high speeds
- Pistol grip design
- Includes one 5/16" (8 mm) drill bit and removeable clamp arm



AT3000
Order NO · 701025



	$- \cap$
	/
	17.
	11 100
	234/

Chuck Size (inches)	Rated Power (kW)	Torque Range (N•m)	Free Speed RPM
3/8	0.15	0 - 4	2,000
Spindle Thread (inches)	Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)
^{3/8} -24 UNF	99	^{1/} 4" -18 NPT	3/8
Vibration Level (m/s²)	Sound Level dBa Pressure	Length (mm)	Weight (kg)
<2.5	105	194	1.4
Auxiliar	y Handle	Vinyl Boo	t (optional)
		AT300	OBOOT

• One hand forward/reverse operation

- Three planet gear design for durability and balance
- Bottom handle diffused exhaust
- Comfort grip handle
- Keyless chuck saves time when changing bits



3/8" Drill, Angle

Power Tools Air Tools

Packing: 1	A A	A LAND A	Order NO.: 701026
Chuck Size (inches)	Rated Power (kW)	Torque Range (N•m)	Free Speed RPM
3/8	0.19	0 - 6	1,320
Spindle Thread (inches)	Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)
^{3/8} -24 UNF	95	^{1/} 4" -18 NPT	3/8
Vibration Level (m/s²)	Sound Level dBa Pressure	Length (mm)	Weight (kg)
<0.8	110	208	1.1

- Rugged, reversible right angle drill gets in tight spots comfortably
- Convenient one hand push button forward/reverse
- Rear exhaust keeps air away from the work area
- Built in chuck key holder keeps the key at hand for quick bit changes
- Paddle style trigger for greater comfort
- Ball bearing construction for longer tool life
- · Lightweight helps avoid fatigue during prolonged use
- Bottom handle diffuse exhaust



AT2050

Order NO.: 701028

Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size		nded Hose nches)	Vibration Level (m/s²)
71	^{1/} 4" -18 NPT	5/	16	3.0
Vibration Level (m/s²)	Sound Level dBa Pressure	Length (mm)	Weight (kg)	Vinyl Boot (optional)
3	99	187	2.1	AT2050BOOT

- Intended for heavy duty applications such as cutting large bolts and rivets, separating ball joints, cutting heavy gauge sheet metal and driving bushings
- Comfort grip handle

Hammer

💼 Packing: 1

AT811

• Includes quick change retainer



³ /8-24 UNF	266	^{1/4} "-18 NPT	3/8
Vibration Level (m/s²)	Sound Level dBa Pressure	Length (mm)	Weight (kg)
<2.5	96.4	183	0.68

- Composite housing with new molded comfort grip is more comfortable for the user while providing less user fatigue
- Small size, light weight and a powerful motor make this tool ideal for working in confined areas
- Durable single piece polymer composite housing stands up to rugged use, resists most shop chemicals and helps insulate against the cold generated by an air tool
- Variable speed trigger

Collet Size (inches)	Rated Power (kW)	Free Speed RPM	Air Consumption, Free Speed (L/MIN)
^{1/4} (6.35mm)	0.15	22,000	113
Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)	Sound Level dBa Pressure
^{1/} 4" -18 NPT	3/8	<2.5	102
Length		Weiç	ght (kg)
165		().61

- Intended for most standard deburring operations
- Ergonomic handle grip increases comfort and control
- Safety lever throttle
- Built-in speed regulator
- Brass bearing cap and hose adaptor
- Rear diffused exhaust



AT105

Order NO.: 701031

0.61

Power Tools Air Tools

1/4" Die Grind	der, Right Angle	e Mini	AT118 Order NO.: 701030
		and the second s	
Collet Size (inches)	Rated Power (kW)	Free Speed RPM	Air Consumption, Free Speed (L/MIN)
^{1/4} (6.35mm)	0.15	20,000	59
Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)	Sound Level dBa Pressure
^{1/4} "-18 NPT	3/8	2.5	104
Lengt	h (mm)	Weig	ght (kg)
1	40	().50

- · Clean dies, rotors, backing plates and brake pad mounts
- Remove gasket material
- Grind dies and valve seats
- Dress welds and enlarge holes
- Compact mini-design with 90° angled head for easy access
- Ergonomic handle grip increases comfort and control
- Safety lever throttle
- Built-in speed regulator
- · Brass bearing cap and hose adaptor

1/4" Die Grinder, Right Angle Mini Packing: 1

AT109 Order NO.: 701032



Collet Size (inches)	Rated Power (kW)	Free Speed RPM	Air Consumption, Free Speed (L/MIN)
^{1/4} (6.35mm)	0.15	20,000	59
Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)	Sound Level dBa Pressure
¹ / ₄ "-18 NPT	3/8	2.5	104
Lengt	h (mm)	Weig	ıht (kg)
1	40	C	0.50

- Aluminum housing for long lasting durability
- Compact mini design with 90° head for easy access
- High quality bearings improve productivity with less repair
- Rear exhaust directs air away from work area

		Elina (1450)	
Collet Size (inches)	Rated Power (kW)	Free Speed RPM	Air Consumption, Free Speed (L/MIN)
^{1/4} (6.35mm)	0.15	22,000	113
Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)	Sound Level dBa Pressure
^{1/} 4" -18 NPT	3/8	<2.5	102
Lengtl	h (mm)	Weig	ght (kg)

• Aluminum housing for long lasting durability

165

1/4" Die Grinder, Standard

Packing: 1

- Intended for most standard deburring operations
- High quality bearings improve productivity with less repair
- · Rear exhaust directs air away from work area

$\int \mathcal{P}$
- Star

AT109DGK

Order NO.: 701033

Rated Power (kW)	Free Speed RPM	Air Consumption, Free Speed (L/MIN)	Air Inlet Th	nread Size
0.15	20,000	59	^{1/} 4" -18	3 NPT
Recommended Hose Size (inches)	Vibration Level (m/s²)	Sound Level dBa Pressure	Length (mm)	Weight (kg)
3/8	2.5	104	140	0.50

Aluminum housing

Die Grinder Kit

📦 Packing: 1

- Compact mini design
- Rear exhaust
 - Includes: AT109 mini angle die grinder plus 2" (50.8mm) ROLOC® pad (1 ea.), 2" (50.8mm) coarse discs (2 ea.), 2"(50.8mm) medium discs (2 ea.), 2" (50.8mm) 24 grit discs (2 ea.), 2" (50.8mm) 36 grit discs (2 ea.), 2" (50.8mm) crud discs (2 ea.), 3" (76.2mm) ROLOC[®] pad (1 ea.),

 - 3" (76.2mm) 50 grit discs (2 ea.), 3" (76.2mm) 120 grit discs (2 ea.),
 - 3" (76.2mm) crud discs (2 ea.), 1/4" shank adaptor (1 ea.)
 - and spanner wrenches (2 ea.) in storage case





- 115 degree offset head provides a more ergonomic grinding position • Thread-on style disc provides a more compact head
- One 2" quick-change disc included so tool is ready for your abrasive pad



Packing: 1

AT119DGK Order NO.: 701035



Rated Power (kW)	Free Speed RPM	Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size
33	2,000	59	¹ / ₄ " -18 NPT
Recommended Hose Size(inches)	Vibration Level (m/s²)	Sound Level dBa Pressure	Length (mm)
3/8	<6.92	100	173

- Thread-on style disc provides a more compact head than collet style units
- 115° offset head provides a more ergonomic grinding position
- Ideal for cleaning dies, rotors, backing plates and gasket material Includes: 115° Mini Offset Angle Die Grinder plus: 2" (50.8mm) ROLOC[®] pad (1 ea.), 2" (50.8mm) coarse discs (2 ea.), 2" (50.8mm) medium discs (2 ea.), 2" (50.8mm) 24 grit discs (2 ea.), 2" (50.8mm) 36 grit discs (2 ea.), 2" (50.8mm) crud discs (2 ea.), 3" (76.2mm) ROLOC[®] pad (1 ea.), 3" (76.2mm) coarse discs (2 ea.), 3" (76.2mm) medium discs (2 ea.), 3" (76.2mm) 50 grit discs (2 ea.), 3" (76.2mm) 120 grit discs (2 ea.), 3" (76.2mm) crud discs (2 ea.), and spanner wrench (1 ea.) in storage case



Collet Size (inches)	Rated Power (kW)	Free Speed RPM	Air Consumption, Free Speed (L/MIN)
^{1/8} (3.18mm)	—	75,000	28
Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)	Sound Level dBa Pressure
^{1/4} " -18 NPT	3/8	2.0	72
Length	n (mm)	Weig	ght (kg)
1;	35	().25

- Twist-action variable speed control
- 5' (1.5 M) long protected air hose
- Used with 1/8" shank grinding accessories higher than 5,4000 RPM • Ideal for tight spaces and easy cleaning of dies, rotors and brake pads

Die Grinder, Pencil, Right Angle 🍘 Packing: 1

AT1070RA Order NO.: 701037



Collet Size (inches)	Rated Power (kW)	Free Speed RPM	Air Consumption, Free Speed (L/MIN)
^{1/8} (3.18mm)	—	75,000	28
Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)	Sound Level dBa Pressure
^{1/} 4" -18 NPT	3/8	2.0	72
Length (mm)		Weight (kg)	
150			0.21

- Right angle lightweight pencil die grinder is ideal for getting in tight spaces
- Use for easy cleaning of dies, rotors, backing plates, brake pads, mounts plus many other applications
- Must be used with 1/8" shank grinding accessories rated higher than 70,000 RPM



4" Extended Packing: 1	Cut-off Tool		AT154 Order NO.: 701068
		Ç	
Wheel Size (inches)	Rated Power (kW)	Free Speed RPM	Air Consumption, Free Speed (L/MIN)
4	0.5	15,000	113.3
Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)	Sound Level dBa Pressure
^{1/} 4" -18 NPT	3/8	< 2.86	85
Length (mm)	Weight (kg)		utter Wheels prit) (optional)
348	1.95	AT1	54RWHLMP

- Overall tool length of 14.8 in. provides extended reach for easier access
- Powerful 0.7 hp motor for maximum performance when cutting under a load
- Built-in regulator permits easy speed adjustment to a maximum free speed of 15,000 RPM
- Side handle offers additional tool control



3	0.33	20,000	99
Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)	Sound Level dBa Pressure
^{1/} 4" -18 NPT	3/8	<3.8	100
Length	Weight	3" Cutter Wheels	3" Cutter Wheels
(mm)	(kg)	(36 grit) (optional)	(54 grit) (optional)
185	0.86	AT150-20A	AT150-29A

- Reversible 3" cut-off tool is ideal for use in body shops and other general automotive applications
- Recommended for cutting mufflers, hose clamps, bolts and sheet metal
- Spark direction control
- Safety throttle lever
- Rear diffused exhaust
- Comfort grip handle
- Uses wheels only rated above 18,000 RPM



(inches)	(kW)	RPM	Free Speed (L/MIN)	Air Inlet Thread Size
3	0.37	17,000	99.1	^{1/} 4" -18 NPT
Recommended Hose Size (inches)	Vibration Level (m/s²)	Sound Level dBa Pressure	Length (mm)	Weight (kg)
3/8	< 2.86	85	218.4	1.5
3"Cutter Whe thick (36 grit			/heels 1/32 " rit)(optional)	3"Cutter Wheels 3/32 "thick (54 grit)(optional)
AT150	-20A	AT15	0C28A	AT150C29A

- Its compact size is excellent for accessing areas with limited working space
- Heavy-duty bevel gears for tool longevity
- Indexing adjustable guard controls the direction of sparks
 Spindle lock eliminates the need for special wrenches for fast
- Adjustable built-in regulator easily adjusts up to17,000 RPM free speed

4 1/2" Grinder, Compact

AT415B Order NO.: 701041



Wheel Size (inches)	Rated Power (kW)	Free Speed RPM	Air Consumption, Free Speed (L/MIN)
4 ¹ / ₂	0.64	12,000	91
Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)	Sound Level dBa Pressure
^{1/} 4" -18 NPT	³ / ₈	5.1	87
Length (mm)	Weight (kg)	Grind	ling Disc
254	1.9	AT4	15A51

• 4 1/2" Compact grinder

• Includes (1) 4 1/2" diameter x 3/16" thick grinding disc







 Length (min)
 Weight (kg)
 Grinding Disc (optional)

 188
 0.82
 AT215GWSET

- Ideal for body shops, automobile, truck repair and confined areas
 Grease fitting in head-enables gears to be greased for longer tool life
- Includes 6-2" wheels-tool is ready for use providing convenience
 Moveable guard, up to 50° in either direction-fitting various
- Built in speed regulator-allows user to set desired speed
- Built in speed regulator-allows user to set desired
 Rear exhaust with rotating deflector
- Comfort grip housing-insulate from cold and vibration for less user
- fatigue
- Safety lever throttle-prevents accidental start ups for increased safety



- Comfort grip housing for greater control
- Performs straight or scroll cuts in metal and plastic
- Safety lever throttle
- Includes three 3 3/4" bi-metal blades: (1) 18TPI coarse, (1) 24TPI medium and (1) 32 TPI fine blade
- Optional blades in 4" lengths are also available



	Vibration Level	Sound Level dBa	Length	Weight
	(m/s²)	Pressure	(mm)	(kg)
1	<6.6	87	175	0.45
	Bi-Metal Blade, 18TPI,	Bi-Metal Blade, 32TPI,	Bi-Metal Blade, 24TPI,	
	3 3/4" long (qty. 5)	3 3/4" long (qty. 5)	3 3/4" long (qty. 5)	
	AT190-39A	AT190-41A		AT190-40A

- Compact size for easy access in tight quarters
- Low vibration level and lightweight yields reduced hand fatigue
- Performs straight or scroll cuts on metal or plastic
- · Adjustable blade guard to control cutting depth
- Flexible, guarded hose extension helps prevent damage to finished surface and aids in maneuverability
- Includes three 3 3/4" bi-metal blades: (1) 18TPI coarse, (1) 24TPI medium and (1) 32 TPI fine blade, blade change wrenches and guard adjustment
- Safety trigger prevent accidental start



—	320	^{1/} 4" -18 NPT	3/8
Vibration Level (m/s²)	Sound Level dBa Pressure	Length (mm)	Weight (kg)
<2.5	48.6	235	1.2

- Paddle style trigger for maximum control
- Handle exhaust directed away from operator
- Ball bearing mounted rotary air motor for long service
- Built-in speed regulator provides torque control
- Removable brass filter screens out dirt and debris
- Use to make 3/16" and 5/16" punches in light sheet metal
- Head swivels 360° for maximum versatility



Powered She	ars		AT195 Order NO.:701046
~.		and and	9
Free Speed RPM	Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)
	113	1/4" -18 NDT	3/8

—	113	^{1/} 4" -18 NPT	3/8
Vibration Level (m/s²)	Sound Level dBa Pressure	Length (mm)	Weight (kg)
<2.5	99.6	254	1.3

- Trims, outlines and shears
- Replaceable brass filter screen
- Built in speed regulator provide

8" Sander, Dual Action AT4 Packing: 1 Order NO.:701				
Pad Size (inches)	Rated Power (kW)	Free Speed RPM	Spindle Thread (inches)	
8	37	850	^{5/} 16 -24	
Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)	
142	^{1/} 4" -18 NPT	3/8	3.7	
Sound Level dBa Pressure	Length (mm)	Weight (kg)	Standard Pad	
87	281	2.18	AT408-2	

- Comfort handle helps reduce fatigue
- Rear diffused exhaust
- Built in adjustable speed regulator
- Variable speed control
- Removable brass filter screens out debris



Free Speed RPM	Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)
3,500	113	^{1/} 4"-18 NPT	3/8
Vibration Level (m/s²)			Weight (kg)
4.3	97	194	0.88

- Cuts mild steel sheet up to 16 gauge (0.62") (1.55mm) thick
- Anvil is adjustable for forward, backward and left or right cutting, enabling the nibbler to make sheet metal cuts of any configuration
- Readily cuts most non-ferrous materials including aluminum, brass, formica, laminates, fiberglass and masonite
- Includes AT180B-10 Standard Punch







Pad Size (inches)	Rated Power (kW)	Free Speed RPM	Spindle Thread (inches)
6	0.37	10,000	^{5/} 16 -18
Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)
142	^{1/} 4" -18 NPT	³ /8	3.7
Sound Level dBa Pressure	Length (mm)	Weight (kg)	Standard Pad
79	203	2.14	AT411A-1

• For fine sanding operations and swirl free finishing



5" Sander

AT425R Order NO.: 701053



Pad Size (inches)	Rated Power (kW)	Free Speed RPM	Spindle Thread (inches)
5	0.33	13,000	⁷ /16 -20
Air Consumption, Free Speed [L/MIN]	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)
122	^{1/} 4" -18 NPT	3/ ₈	<0.8
Sound Level dBa Pressure	Length (mm)	Weight (kg)	Standard Pad
93	135	1.28	AT425R-24
3" Replacement Pad (Optional)		4" Replacement P	ad (Optional)
AT425R-22		AT425R	-23

- Use in body shops and other general automotive applications
- Includes 3", 4" and 5" backing discs
- One hand reverse
- Comfort grip handle
- Built-in speed regulator
- 1 year limited warranty on tool
- No warranty on consumables
- CE-DE, ES, FR, IT, GB



In Line Sander, Heavy Duty Packing: 1 AT475A Order NO.: 701054



Rated Power (kW)	Free Speed RPM	Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size
_	1,800	65	^{1/} 4 "-18 NPT
Recommended Hose Size (inches)	Vibration Level (m/s²)	Sound Level dBa Pressure	Length (mm)
3/8	14.9	87	406
Weight (kg)		Standard Pa	ıd
3.09		AT475A-29	•

• 5/8" stroke

Minimal vibration



Jitterbug Sander

📦 Packing: 1



Rated Power (kW)	Free Speed RPM	Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size
0.37	8,000	85	^{1/} 4" -18 NPT
Recommended Hose Size (inches)	Vibration Level (m/s²)	Sound Level dBa Pressure	Length (mm)
3/8	4.5	84	171
Weight (kg)		Standard Pad	
2.09		AT435	A-48

• Features top mounted throttle

3" Surface Prep Tool, Micro

AT401MCA Order NO.: 701056

WARNING

AT435A

Order NO.: 701055



Pad Size (inches)	Rated Power (kW)	Free Speed RPM	Spindle Thread (inches)
3	0.19	15,000	^{1/4} -20
Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)
59	^{1/} 4" -18 NPT	3/8	<2.5
Sound Level dBa Pressure	Length (mm) W	eight (kg)
84	119		0.44

Small size, light weight and a powerful motor make the AT401MCA
Surface prep tool ideal for removing paint, rust, gasket material,

- or contract propriod read for removing paint, roct, gaster mate grinding welds or brake rotors in confined areas
 Accepts 2" and 3" ROLOC[®] pads
- Pads attach/release with just a 1/4 turn
- Durable single piece polymer composite housing on prep tool stands up to rugged use, resists most shop chemicals and helps insulate against the cold generated by an air tool
- Oversize trigger for easy operation
- Variable speed trigger
- Bottom handle diffused exhaust
- Built in speed regulator offers easy one hand operation

I	3" Sander, Dual Action, Micro
	🃦 Packing: 1

AT402MCA Order NO.: 701057



Pad Size (inches)	Rated Power (kW)	Free Speed RPM	Spindle Thread (inches)
3	0.19	15,000	^{5/} 16 -24
Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)
59	^{1/} 4 "-18 NPT	3/8	<2.5
Sound Level dBa Pressure	Length (mm)		Veight (kg)
84	133		0.50

- Use the AT402MCA micro sander to deliver fine swirl free results when sanding, feather edging, scuff sanding, sanding primer surfaces, top coating surface preps, scuffing door and rocker panel jams plus other finesse sanding applications
- Durable single piece polymer composite housing on sander stands up to rugged use, resists most shop chemicals and helps insulate against the cold generated by an air tool
- Oversize trigger for easy operation
- Variable speed trigger
- Bottom handle diffused exhaust
- Built-in speed regulator is easily operated with one hand

3" Polisher, Micro

AT403MCA Order NO.: 701058



Pad Size (inches)	Rated Power (kW)	Free Speed RPM	Spindle Thread (inches)	
3	0.19	6,000	^{5/} 16 -24	
Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)	
62	^{1/} 4" -18 NPT	3/8	<2.5	
Sound Level dBa Pressure	Length (m		Weight (kg)	
86	143		0.60	

- Small size, light weight and a powerful motor make the AT403MCA micro polisher ideal for polishing motorcycles, bumpers, wheels and more
- Durable single piece polymer composite housing on polisher stands up to rugged use, resists most shop chemicals and helps insulate against the cold generated by an air tool
- Oversize, variable speed trigger for easy operation with a gloved hand
 Bottom handle diffused exhaust
- Built in speed regulator offers easy one hand operation



Includes:

(5) 2" 40 grit pads

Power Tools Air Tools

Surface Prep Kit, Micro, 13 pcs

AT401MCA micro surface prep tool (1) 2" ROLOC[®] pad (1) 3" ROLOC[®] pad

(5) 3" 80 grit pads in storage case

AT401MCKA Order NO.: 701059 3" Polisher Kit, Micro, 5 pcs Packing: 1

AT403MCKA Order NO.: 701061



Includes:

AT403MCA micro polisher

- (1) 3" Hook-It® pad
- (1) 3" wool pad
- (1) 3" foam pad in storage case

3" Sander Kit, Micro, Dual Action, 72 pcs Packing: 1 AT402MCKA Order NO.: 701060 Polisher, Heavy Duty, Vertical Packing: 1

AT460BP Order NO.: 701062





Pad Size (inches)	Rated Power (kW)	Free Speed RPM	Spindle Thread (inches)
7	0.49	4,500	⁵ /8 -11
Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)
136	^{1/} 4" -18 NPT	3/8	<2.5
Sound Level dBa Pressure	Length (mm)	Weight (kg)	Standard Pad Spanner Wrench (opt.)
83	185	2.27	AT450-46H AT450-50

Removable side handle

Includes: AT402MCA micro sander
(1) 3" Hook-It[®] pad
(25) 3" 180 grit pads
(25) 3" 200 grit pads
(10) 3" 320 grit pads
(10) 3" 800 grit pads in storage case

<mark>92</mark>



Power Tools Cordless Tools

3/8" Impact Wrench Packing: 1

Square Drive (inches)	Blows per Minute (BPM)	Maximum Torque (N•m)	Free Speed (RPM)	Duration of eac	h full charge
3/8	2400	189	0-2, 200	More than 300 tig	htening cycles
Motor / Battery Voltage (V)	Length (mm)	Weight (kg)	Battery Pack	Battery Charger	Charge Time (min)
14.4	178	1.9	ETB14419A	ETB14401A	45

- Delivers 140 ft. lbs. max torque in a compact design to provide the user maximum versatility
- Includes two batteries and one charger packed in a blow molded case
- Batteries have a 1.9 Ah that provides a long run time
- Easily replaceable carbon brushes to keep your investment running like new
- Slide-on battery provides better contact and safer operation since battery won't drop
- Perfectly balanced compact shape with surrounding soft-grip handle reduces fatigue
- Space included in the molded case to add the ETB14410A LED light

LED Light

🎁 Packing: 1



Length (mm)	Weight (kg)	Battery Pack	Battery Charger	Duration of each full charge
228	0.2	ETB14419A (not included)	ETB14401A (not included)	14 hours continuous

• LED bulb provides long life and low power draw for less job interruptions

- 90 degree pivoting head puts the light ray where you need it
- Faceted reflector provides bright uniform beam
- Perfectly balanced compact shape with surrounding soft-grip handle reduces fatigue
- Slide-on battery provides better contact and safer operation since battery won't drop

3/8" Drill, Two Speed Packing: 1

FTB14438A

ETB14410A

Order NO .: 702003

Order NO.: 702001

ETB14420A Order NO.: 702002



Chuck Cap (inches)	No Load Speed (RPM)	Maximun (N•		Motor/Battery Voltage (V)	Charge Time (min)
3/8	0-400/0-1400	3	0	14.4	45
Battery Pack	Battery Charger	Length (mm)	Weight (kg)	Duration of each ful	ll charge
ETB14419A (1.9Ah)	ETB14401A	216	1.9	More than 30 drillin	g cycles

- Includes cordless drill, 2 batteries and battery charger
- Keyless chuck provides quick replacement of bits to save time
- Two speed switch and variable speed trigger offers maximum control in both forward and reverse
- Clutch cap provides 20 different settings up to 260 inch pounds torque for precision jobs
- White LED illuminates when trigger is depressed for those dim working conditions
- Slide-on battery provides better contact and safer operation since battery won't drop
- Perfectly balanced compact shape with surrounding soft-grip handle reduces fatigue
- Space included in the molded case to add the ETB14410A light

3/8" Drive Cordless Ratchet

ETB14460A Order NO.: 702007



Square Drive (inches)	Maximum Torque (N•m)	Motor / Battery Voltage (V)	Free Speed RPM	Length (mm)
3/8	47	14.4	225	378
Weight with Battery Pack (kg)	Battery Pack	Battery Charger	Vinyl Boot (optional)	
6.6	ETB14419A	ETB14401A	YA889A (Blac	k)

- Cord free eliminates dragging dirty air hoses in and across the service vehicle
- High Speed (190 RPM) increases productivity
- Delivers 35 ft.lbs. (47 N·m) of torque
- 1.9 Ah Ni-cad battery provides user with ample run time between charges
- Aluminium housing provides durability under manual stress loads





Power Tools Cordless Tools / Impact Sockets

3/8" Drill Packing: 1



Drilling Capability (mm)	No Load Speed (RPM)		Maximum Torque (N•m)	Voltage (V)	
13		0-1000	23	9.6	
Charge Time (min)	Weight (kg)	Length (mm)	Duration of each full charge	Package	
45	1.4	27	More than 30 drilling cycles	2Battery 1Charger 1Key	

• This is a professional cordless drill suitable for general purpose drilling for all type of woods and metal, which can be used in automotive repairs, construction and home improvements works

Battery, 14.4V

籣 Packing: 1

ETB14419A Order NO.: 702005

ETB14401A Order NO.: 702006

ETB14430A Order NO.: 701064

Po

- 14.4V battery pack for Blue-Point ETB series cordless tools
 Slide-on battery provides better contact and safer operation since battery won't drop
- 45 minutes charging time using ETB14401A charger

Charger, 14.4V/220V

Packing: 1

	0	
(Sel		
4		

- 14.4V battery charger for batteries used on Blue-Point ETB series cordless tools
- 45 minutes charging time on ETB14419A battery

3/8" Drive, Shallow, 6pt., mm



Stock No.	Size (mm)	Ŵ	Order No.
BLPSMIM387	7	6	703001
BLPSMIM388	8	6	703002
BLPSMIM389	9	6	703003
BLPSMIM3810	10	6	703004
BLPSMIM3811	11	6	703005
BLPSMIM3812	12	6	703006
BLPSMIM3813	13	6	703007
BLPSMIM3814	14	6	703008
BLPSMIM3815	15	6	703009
BLPSMIM3816	16	6	703010
BLPSMIM3817	17	6	703011
BLPSMIM3818	18	6	703012
BLPSMIM3819	19	6	703013

3/8" Drive, Deep, 6pt., mm



Stock No.	Size (mm)	Ŵ	Order No.
BLPLSMIM387	7	6	703014
BLPLSMIM388	8	6	703015
BLPLSMIM389	9	6	703016
BLPLSMIM3810	10	6	703017
BLPLSMIM3811	11	6	703018
BLPLSMIM3812	12	6	703019
BLPLSMIM3813	13	6	703020
BLPLSMIM3814	14	6	703021
BLPLSMIM3815	15	6	703022
BLPLSMIM3816	16	6	703023
BLPLSMIM3817	17	6	703024
BLPLSMIM3818	18	6	703025
BLPLSMIM3819	19	6	703026

- Designed for maximum engagement on 6 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove



BLPJIM38

Power Tools Impact Sockets

3/8" Drive, Shallow, 6pt., inches



Stock No.	Size (inches)	(Order No.
BLPSIM3814	1/4	6	703027
BLPSIM38516	⁵ / ₁₆	6	703028
BLPSIM3838	3/8	6	703029
BLPSIM38716	7/ ₁₆	6	703030
BLPSIM3812	1/2	6	703031
BLPSIM38916	9/ ₁₆	6	703032
BLPSIM3858	⁵ /8	6	703033
BLPSIM381116	¹¹ / ₁₆	6	703034
BLPSIM3834	3/4	6	703035

3/8" Drive, Deep, 6pt., inches



Stock No.	Size (inches)	Ŵ	Order No.
BLPLSIM3814	1/4	6	703036
BLPLSIM38516	^{5/} 16	6	703037
BLPLSIM3838	3/8	6	703038
BLPLSIM38716	7/ ₁₆	6	703039
BLPLSIM3812	1/2	6	703040
BLPLSIM38916	^{9/} 16	6	703041
BLPLSIM3858	5/8	6	703042
BLPLSIM381116	¹¹ / ₁₆	6	703043
BLPLSIM3834	3/4	6	703044

- Designed for maximum engagement on 6 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove

3/8" Drive, Extra Long, 6pt., inches



Stock No.	Size (inches)	i	Order No.
BLPSMS8	8	6	704056
BLPSMS10	10	6	704057
BLPSMS12	12	6	704058

- Extra length at 100 mm to reach two-wheelers transmission box screws
- Single piece construction
- For use on impact wrench without the need for extra extension



- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove

3/8" Drive Universal Joints Packing: 6

	Order NO.: 7
Stock No.	Size (inches)
BLPJIM38	³ /8 male X ³ /8 female

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove

3/8" Drive Extension

		6	2
	4		ŀ
			P
	4		P.
			Ľ
	4		Ľ
	4		

Stock No.	Size (inches)	Ŵ	Order No.
BLPEXIM383	3	6	703047
BLPEXIM386	6	6	703048



BLPAIM3814 Order NO.: 703045

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove

1/4" Drive, Impact Adaptor Packing: 6



- · Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove





1/2" Drive, Shallow, 6pt., mm



Stock No.	Size (mm)	Ŵ	Order No.
BLPSMIM1210	10	6	703050
BLPSMIM1211	11	6	703051
BLPSMIM1212	12	6	703052
BLPSMIM1213	13	6	703053
BLPSMIM1214	14	6	703054
BLPSMIM1215	15	6	703055
BLPSMIM1216	16	6	703056
BLPSMIM1217	17	6	703057
BLPSMIM1218	18	6	703058
BLPSMIM1219	19	6	703059
BLPSMIM1221	21	6	703060
BLPSMIM1222	22	6	703061
BLPSMIM1223	23	6	703062
BLPSMIM1224	24	6	703063
BLPSMIM1227	27	6	703064
BLPSMIM1229	29	6	703065
BLPSMIM1230	30	6	703066
BLPSMIM1232	32	6	703067

1/2" Drive, Shallow, 6pt., inches



Stock No.	Size (inches)	i	Order No.
BLPSIM1238	3/8	6	703086
BLPSIM12716	7/16	6	703087
BLPSIM1212	1/2	6	703088
BLPSIM12916	9/16	6	703089
BLPSIM1258	5/ ₈	6	703090
BLPSIM121116	11/16	6	703091
BLPSIM1234	3/4	6	703092
BLPSIM121316	¹³ / ₁₆	6	703093
BLPSIM1278	7/8	6	703094
BLPSIM121516	¹⁵ / ₁₆	6	703095
BLPSIM121	1	6	703096
BLPSIMB121116	1 ¹ /16	6	703097
BLPSIMB12118	1 ^{1/8}	6	703098
BLPSIMB12114	1 ¹ /4	6	703099
BLPSIMB121516	1 ^{5/} 16	6	703100
BLPSIMB121716	1 ^{7/} 16	6	703101

1/2" Drive, Deep, 6pt., inches

1/2"Drive, Deep, 6pt., mm





Stock No.	Size (mm)	i	Order No.
BLPLSMIM1210	10	6	703068
BLPLSMIM1211	11	6	703069
BLPLSMIM1212	12	6	703070
BLPLSMIM1213	13	6	703071
BLPLSMIM1214	14	6	703072
BLPLSMIM1215	15	6	703073
BLPLSMIM1216	16	6	703074
BLPLSMIM1217	17	6	703075
BLPLSMIM1218	18	6	703076
BLPLSMIM1219	19	6	703077
BLPLSMIM1221	21	6	703078
BLPLSMIM1222	22	6	703079
BLPLSMIM1224	24	6	703080
BLPLSMIM1226	26	6	703081
BLPLSMIM1227	27	6	703082
BLPLSMIM1229	29	6	703083
BLPLSMIM1230	30	6	703084
BLPLSMIM1232	32	6	703085

- Designed for maximum engagement on 6 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove



Stock No.	Size (inches)	Ũ	Order No.
BLPLSIM1238	3/8	6	703102
BLPLSIM12716	7/ ₁₆	6	703103
BLPLSIM1212	1/2	6	703104
BLPLSIM12916	^{9/} 16	6	703105
BLPLSIM1258	5/8	6	703106
BLPLSIM121116	¹¹ / ₁₆	6	703107
BLPLSIM1234	3/4	6	703108
BLPLSIM121316	¹³ / ₁₆	6	703109
BLPLSIM1278	7/8	6	703110
BLPLSIM121516	¹⁵ / ₁₆	6	703111
BLPLSIM121	1	6	703112
BLPLSIMB12116	1 ¹ /16	6	703113
BLPLSIMB12118	1 ^{1/8}	6	703114
BLPLSIMB121316	1 ³ / ₁₆	6	703115
BLPLSIMB12114	1 ^{1/4}	6	703116

- Designed for maximum engagement on 6 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove



BLPJIM12

Order NO.: 703123

Power Tools Impact Sockets

1/2" Impact Adaptor Packing: 6



BLPAIM3812

Order NO.: 703121

BLPAIM3412 Order NO.: 703122

Stock No.	Size (inches)
BLPAIM3812	³ /8 male X ¹ /2 female

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove





Stock No.	Size (inches)
BLPJIM12	¹ /2 male X ¹ /2 female

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove

1/2" Impact Adaptor	
Packing: 6	



Stock No.	Size (inches)
BLPAIM3412	$^{3/_{4}}$ male X $^{1/_{2}}$ female

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove

1/2" Drive Extension



- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove



🕤 💷 🔿



3/4" Drive, Shallow, 6pt., mm



Stock No.	Size (mm)	Ŵ	Order No.
BLPSMIM3417	17	6	703124
BLPSMIM3418	18	6	703125
BLPSMIM3419	19	6	703126
BLPSMIM3420	20	6	703127
BLPSMIM3421	21	6	703128
BLPSMIM3422	22	6	703129
BLPSMIM3423	23	6	703130
BLPSMIM3424	24	6	703131
BLPSMIM3425	25	6	703132
BLPSMIM3426	26	6	703133
BLPSMIM3427	27	6	703134
BLPSMIM3428	28	6	703135
BLPSMIM3429	29	6	703136
BLPSMIM3430	30	6	703137
BLPSMIM3431	31	6	703138
BLPSMIM3432	32	6	703139
BLPSMIM3433	33	6	703140
BLPSMIM3434	34	6	703141
BLPSMIM3435	35	6	703142
BLPSMIM3436	36	6	703143
BLPSMIM3437	37	6	703144
BLPSMIM3438	38	6	703145
BLPSMIM3439	39	6	703146
BLPSMIM3440	40	6	703147
BLPSMIM3441	41	6	703148
BLPSMIM3442	42	6	703149
BLPSMIM3443	43	6	703150
BLPSMIM3444	44	6	703151
BLPSMIM3445	45	6	703152
BLPSMIM3446	46	6	703153
BLPSMIM3447	47	6	703154
BLPSMIM3448	48	6	703155
BLPSMIM3449	49	6	703156
BLPSMIM3450	50	6	703157
BLPSMIM3452	52	6	703158
BLPSMIM3454	54	6	703159
BLPSMIM3455	55	6	703160
BLPSMIM3456	56	6	703161
BLPSMIM3457	57	6	703162
BLPSMIM3458	58	6	703163
BLPSMIM3459	59	6	703164
BLPSMIM3460	60	6	703165
BLPSMIM3463	63	6	703166
BLPSMIM3465	65	6	703167

• Designed for maximum engagement on 6 point fasteners

- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove

3/4" Drive, Deep, 6pt., mm



Stock No.	Size (mm)	۲	Order No.
BLPLSMIM3417	17	6	703169
BLPLSMIM3418	18	6	703170
BLPLSMIM3419	19	6	703171
BLPLSMIM3420	20	6	703172
BLPLSMIM3421	21	6	703173
BLPLSMIM3422	22	6	703174
BLPLSMIM3423	23	6	703175
BLPLSMIM3424	24	6	703176
BLPLSMIM3425	25	6	703177
BLPLSMIM3426	26	6	703178
BLPLSMIM3427	27	6	703179
BLPLSMIM3428	28	6	703180
BLPLSMIM3429	29	6	703181
BLPLSMIM3430	30	6	703182
BLPLSMIM3431	31	6	703183
BLPLSMIM3432	32	6	703184
BLPLSMIM3433	33	6	703185
BLPLSMIM3434	34	6	703186
BLPLSMIM3435	35	6	703187
BLPLSMIM3436	36	6	703188
BLPLSMIM3437	37	6	703189
BLPLSMIM3438	38	6	703190
BLPLSMIM3440	40	6	703191
BLPLSMIM3441	41	6	703192
BLPLSMIM3442	42	6	703193
BLPLSMIM3443	43	6	703194
BLPLSMIM3444	44	6	703195
BLPLSMIM3445	45	6	703196
BLPLSMIM3446	46	6	703197
BLPLSMIM3447	47	6	703198
BLPLSMIM3448	48	6	703199
BLPLSMIM3449	49	6	703200
BLPLSMIM3450	50	6	703201
BLPLSMIM3455	55	6	703202

- Designed for maximum engagement on 6 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove



3/4" Drive, Shallow, 6pt., inches



Stock No.	Size (inches)	(Order No.
BLPSIM341116	¹¹ / ₁₆	6	703203
BLPSIM3434	3/4	6	703204
BLPSIM341316	¹³ / ₁₆	6	703205
BLPSIM3478	7/8	6	703206
BLPSIM341516	¹⁵ / ₁₆	6	703207
BLPSIM341	1	6	703208
BLPSIMB341116	1 ¹ /16	6	703209
BLPSIMB34118	1 ¹ /8	6	703210
BLPSIMB341316	1 ³ /16	6	703211
BLPSIMB34114	1 ^{1/4}	6	703212
BLPSIMB341516	1 ^{5/} 16	6	703213
BLPSIMB34138	1 ^{3/8}	6	703214
BLPSIMB341716	1 ^{7/} 16	6	703215
BLPSIMB34112	1 1/2	6	703216
BLPSIMB341916	1 ^{9/} 16	6	703217
BLPSIMB34158	1 ⁵ /8	6	703218
BLPSIMB3411116	1 ^{11/} 16	6	703219
BLPSIMB34134	1 ³ / ₄	6	703220
BLPSIMB3411316	1 ^{13/} 16	6	703221
BLPSIMB34178	1 7/8	6	703222
BLPSIMB3411516	1 ^{15/} 16	6	703223
BLPSIMB342	2	6	703224

- Designed for maximum engagement on 6 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove

3/4" Drive Adaptor

Packing: 6

BLPAIM1234 Order NO.: 703232



Stock No. Size (inches)

1/2 male X 3/4 female

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove

3/4" Drive Adaptor Packing: 6		BLPAIM134 Order NO.: 703316
	Stock No.	Size (inches)
	BLPAIM134	1 male X ³ / ₄ female

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove

3/4" Drive Universal Joint

BLPJIM34 Order NO.: 703233



Stock No.	Size (inches)
BLPJIM34	3/4 male X 3/4 female

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove

3/4" Drive Extension



Stock No.	Size (inches)	Ŵ	Order No.
BLPEXIM343	3 1/2	6	703225
BLPEXIM344	4	6	703226
BLPEXIM346	6	6	703227
BLPEXIM347	7	6	703228
BLPEXIM348	8	6	703229
BLPEXIM3410	10	6	703230
BLPEXIM3413	13	6	703231

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove



1" Drive, Shallow, 6pt., mm

Stock No.	Size (mm)	Ũ	Order No.	Stock No.	Size (mm)	Ŵ	Order No.
BLPSMIM117	17	6	703234	BLPSMIM142	42	6	703259
BLPSMIM118	18	6	703235	BLPSMIM143	43	6	703260
BLPSMIM119	19	6	703236	BLPSMIM144	44	6	703261
BLPSMIM120	20	6	703237	BLPSMIM145	45	6	703262
BLPSMIM121	21	6	703238	BLPSMIM146	46	6	703263
BLPSMIM122	22	6	703239	BLPSMIM147	47	6	703264
BLPSMIM123	23	6	703240	BLPSMIM148	48	6	703265
BLPSMIM124	24	6	703241	BLPSMIM149	49	6	703266
BLPSMIM125	25	6	703242	BLPSMIM150	50	6	703267
BLPSMIM126	26	6	703243	BLPSMIM151	51	6	703268
BLPSMIM127	27	6	703244	BLPSMIM152	52	6	703269
BLPSMIM128	28	6	703245	BLPSMIM153	53	6	703270
BLPSMIM129	29	6	703246	BLPSMIM154	54	6	703271
BLPSMIM130	30	6	703247	BLPSMIM155	55	6	703272
BLPSMIM131	31	6	703248	BLPSMIM156	56	6	703273
BLPSMIM132	32	6	703249	BLPSMIM157	57	6	703274
BLPSMIM133	33	6	703250	BLPSMIM158	58	6	703275
BLPSMIM134	34	6	703251	BLPSMIM159	59	6	703276
BLPSMIM135	35	6	703252	BLPSMIM160	60	6	703277
BLPSMIM136	36	6	703253	BLPSMIM163	63	6	703278
BLPSMIM137	37	6	703254	BLPSMIM165	65	6	703279
BLPSMIM138	38	6	703255	BLPSMIM167	67	6	703280
BLPSMIM139	39	6	703256	BLPSMIM168	68	6	703281
BLPSMIM140	40	6	703257	BLPSMIM169	69	6	703282
BLPSMIM141	41	6	703258				



• Designed for maximum engagement on 6 point fasteners

- Suitable for use with pneumatic and electric impact wrenches
 Specially heat treated for impact use to provide long life, safety, and
- durabilityDrive end features pin retention hole and groove

1" Drive, Deep, 6pt., mm



Stock No.	Size (mm)	Ŵ	Order No.
BLPLSMIM117	17	6	703283
BLPLSMIM118	18	6	703284
BLPLSMIM119	19	6	703285
BLPLSMIM120	20	6	703286
BLPLSMIM121	21	6	703287
BLPLSMIM122	22	6	703288
BLPLSMIM123	23	6	703289
BLPLSMIM124	24	6	703290
BLPLSMIM125	25	6	703291
BLPLSMIM126	26	6	703292
BLPLSMIM127	27	6	703293
BLPLSMIM128	28	6	703294
BLPLSMIM129	29	6	703295
BLPLSMIM130	30	6	703296
BLPLSMIM131	31	6	703297
BLPLSMIM132	32	6	703298
BLPLSMIM133	33	6	703299
BLPLSMIM134	34	6	703300
BLPLSMIM135	35	6	703301
BLPLSMIM136	36	6	703302
BLPLSMIM137	37	6	703303
BLPLSMIM138	38	6	703304
BLPLSMIM140	40	6	703305
BLPLSMIM141	41	6	703306
BLPLSMIM142	42	6	703307
BLPLSMIM143	43	6	703308
BLPLSMIM146	46	6	703309
BLPLSMIM149	49	6	703310
BLPLSMIM150	50	6	703311
BLPLSMIM155	55	6	703312

- Designed for maximum engagement on 6 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove



1"	Drive Adaptor
	Packing: 6



BLPAIM341

Order NO.: 703317

BLPAIM1121 Order NO.: 703318

Stock No.	Size (inches)
BLPAIM341	^{3/} 4 male X 1 female

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove



Stock No.	Size (inches)
BLPJIM1	7

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove

1" Drive Adaptor Packing: 6



Stock No.	Size (inches)
BLPAIM1121	1 ¹ / ₂ male X 1 female

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove







Stock No.	Size (inches)	(Order No.
BLPEXIM17	7	6	703313
BLPEXIM113	13	6	703314

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove



Power Tools Accessories





Power Tools Accessories

Flap Wheels



Stock No.	Diameter (inches)	Туре	Grit	Quantity to Pack	i	Order No.
AC3160FWMP	3	—	60	10	1	704017
AC3180FWMP	3	—	80	10	1	704018
AC31120FWMP	3	_	120	10	1	704016

- Applications include cleaning, edge blending and smoothing metal, plastic or wood
- 3" aluminum oxide flap wheel is designed to provide fast cutting action
- 1/4" stem on solid hub permits a higher RPM rating and increased productivity
- Use on electric and pneumatic drills

Wire Wheel

📦 Packing: 1



- 3" crimped wire wheel is a great general purpose cleaner
- Features individual crimped filaments that support each other while being flexible
- General applications include deburring, weld cleaning and rust and paint removal
- Use on electric and pneumatic drills
- .0118 CWS-1/4

Wire Brush



Stock No.	Brush Dia. (inches)	Maximum Safe Free Speed (RPM)	Shank Size Arbor Size	Wire Diameter (inches)	Ĩ	Order No.
AC420A	4	20,000	⁵ /8" X 11	0.020	1	704007
AC421A	4	20,000	M10 x1.25	0.020	1	704008

Knotted wire wheel

• Use for heavy duty cleaning

• Ideal for pre-welding prep and weld cleaning



AC616 Order NO.: 704020



Stock No.	Brush Dia. (inches)	Shank Size Arbor Size (inches)	Wire Diameter (inches)	Maximum Rated RPM	Ŵ	Order No.
AC10302	1/2	1/4	.014	25,000	1	704009
AC10306	3/4	1/4	.014	22,000	1	704010

- Features individual crimped filaments that support each other while being flexible
- Ideal for cleaning right angles



POLISHW8A

Order NO.: 704023

Wire Brush



Stock No.	Brush Dia. (inches)	Shank Size Arbor Size (inches)	Wire Diameter (inches)	Maximum Rated RPM	Ŵ	Order No.
AC17D	1	1/4	.006	20,000	1	704011
AC243	3	⁵ /8 - 11	.014	14,000	1	704012

- Features individual crimped filaments that support each other while being flexible
- Use for medium duty general purpose cleaning

Wool Buffing Pad





- Ideal for cutting, buffing, and removal of scratches and paint imperfections
- 1 1/2" wool pile last longer that standard wool pads
- Washable for easy clean up

- Use for base and clear coats, acrylic, enamel, lacquer, urethane, fiberglass, plastics and other applications
- Can be used with AT450CP, AT460BP and ETB1580B Polishers



Power Tools Accessories

Blow Gun Packing: 1



- Tapered, rubber tip for a leak proof connection between gun and fluid line
- Won't mar surfaces

Blow Gun

Packing: 1

JT13B Cobalt Drill Bit Set, 21 pcs Order NO.: 704024 蘭 Packing: 1



YA1050B Order NO.: 704025

index

Packing: 1

- Vinyl coated control lever
- Hanging hook for storage
- 4 1/2" long



• DBBPC1/16 thru DBBPC3/8 (21 pcs) (1/16" to 3/8") in metal drill bit

DBBP21 Order NO.: 704054

DBBPC21

Order NO.: 704053



• DBBP1/16 thru DBBP3/8 (21 pcs) (1/16" to 3/8") in metal drill bit index

Titanium Coated Drill Bit Set, 13 pcs Packing: 1

DBBPT13 Order NO.: 704055



• DBBPT1/16 thru DBBPT1/4 (13 pcs) (1/16" to 1/4") in metal drill bit index

Air Line Couplers and Adaptors Packing: 1

AHC21PD Order NO.: 704033



Stock No.	Body Size (inches)	Style	Thread Size
AHC21PD	1/4	Rigid Mounting	^{1/} 4" -18 NPT



- Pistol grip style with front full size trigger
- Infinitely variable flow
- 10 1/4" long



Air Hoses 💗 Packing: 1

Order NO.: 704026

AIRHOSE35



- Reinforced construction eliminates layer separation resulting from expansion and contraction during pulsating operations
- More abrasion resistant than PVC and rubber hoses
- Easy to wrap and store even in subzero weather
- UV stabilized for longer outdoor life
- Strain relief features an tight bending radius to virtually eliminate hose kinking
- Reusable fittings and strain reliefs for longer life


Power Tools Accessories

Air Line Couplers and Adaptors



Stock No.	Body Size (inches)	Style	Thread Size	Quick Coupler Male	Ì	Order No.
AHC21PMD	1/4	Industrial Interchange	¹ /4" -18 NPT	AHC21PMC	1	704036
AHC21D	1/4	Industrial Interchange	^{1/} 4" -18 NPT	AHC21PMC	1	704052
AHC21MD	1/4	Industrial Interchange	^{1/} 4" -18 NPT	AHC21PMC	1	704041
AHC21FD	1/4	Industrial Interchange	¹ /4" -18 NPT	AHC21PMC	1	704032



Stock No.	Body Size (inches)	Style	Thread Size	Ŵ	Order No.
AHC22E	3/8	Industrial Interchange	¹ /4" -18 NPT	1	704028
AHC22MD	3/8	Industrial Interchange	¹ /4" -18 NPT	1	704030
AHC22FD	3/8	Industrial Interchange	¹ /4" -18 NPT	1	704046



Stock No.	Body Size (inches)	Style	Thread Size	Quick Coupler Male	۲	Order No.
AHC23PMD	1/4	ARO	¹ /4" -18 NPT	AHC23PMC	1	704039
AHC23D	1/4	ARO	¹ /4" -18 NPT	AHC23PMC	1	704037
AHC23MD	1/4	ARO	¹ /4" -18 NPT	AHC23PMC	1	704051
AHC23FD	1/4	ARO	¹ /4" -18 NPT	AHC23PMC	1	704047



Stock No.	Body Size (inches)	Style	Thread Size	Ŵ	Order No.
AHC24D	1/4	True-Flate	¹ /4" -18 NPT	1	704048
AHC24MD	1/4	True-Flate	¹ /4"-18 NPT	1	704049
AHC24FD	1/4	True-Flate	¹ /4" -18 NPT	1	704050

Air Line Couplers and Adaptors



Stock No.	Body Size (inches)	Style	Thread Size	۲	Order No.
AHC25D	³ /8	True-Flate	¹ /4" -18 NPT	1	704031
AHC25MD	3/8	True-Flate	¹ /4" -18 NPT	1	704043
AHC25FC	³ /8	True-Flate	¹ /4" -18 NPT	1	704040



Stock No.	Body Size (inches)	Style	Thread Size	Ŵ	Order No.
AHC26D	1/4	Lincoln	¹ /4" -18 NPT	1	704027
AHC26MD	1/4	Lincoln	¹ /4" -18 NPT	1	704029
AHC26FD	1/4	Lincoln	¹ /4" -18 NPT	1	704038



Stock No.	Body Size (inches)	Style	Thread Size	Ŵ	Order No.
AHC27D	1/2	Industrial Interchange	¹ /2 " -14 NPT	1	704045
AHC27FD	1/2	Industrial Interchange	¹ / ₂ " -14 NPT	1	704042



Stock No.	Body Size (inches)	Style	Thread Size	Ŵ	Order No.
AHC28D	3/8	Industrial Interchange	^{3/} 8" -18 NPT	1	704035
AHC28MD	3/8	Industrial Interchange	³ /8 "-18 NPT	1	704044
AHC28FD	3/8	Industrial Interchange	^{3/} 8" -18 NPT	1	704034





Striking & Cutting

When it comes to striking tools, Blue-Point's lineage stretches back to 1940 when the company first produced punches and chisels that managed to penetrate and cut through quarter-inch steel. That was a remarkable achievement then.

The range today includes other selection of tools for various striking and cutting applications, bearing the same trademark hardness and toughness. Our wide range of superior hammers and cutting tools set us apart from the competition.





Striking & Cutting Hammers

Ball Peen - Wood Handle



Ball Peen, Wood Handle

Ball Peen, Fiberglass Handle

Cross Peen, Hickory Handle







BPN8B BPN12B BPN16B

BPN32B

8

12

16

24

32

13

14

16

BPNH12B

BPNH24B

BPNH24B

1 801003

1 801004

1 801005





Stock No.	Weight (oz.)	Head Length (inches)	Overall Length (inches)	Replacement Handle	Ì	Order No.
BH141A	32	4 ¹ /2	15	BPH20C	1	801006
BH142A	40	5	15	BPH40C	1	801007

Stock No.	(oz.)	Ì	No.
BPB4	4	1	801013
BPB8	8	1	801014
BPB12	12	1	801015
BPB16	16	1	801016
BPB24	24	1	801017
BPB32	32	1	801018
BPB40	40	1	801019
BPB48	48	1	801020



Striking & Cutting Hammers

Soft Face



Soft Face Packing: 1



Rubber Head Mallet 🍘 Packing: 1

BF620C Order NO.: 801010 Soft Blow 📦 Packing: 1

BF623 Order NO.: 801009



Stock No.	Weight (oz.)	Length (inches)
BH232A	32	13

- Combination steel and soft face dead blow
- One-piece urethane construction
- The 13" long fiberglass handle has a plastic, shock-absorbing grip
- Tip diameter is 1 5/8"
- Includes two replaceable tips: soft (BH232-2) and hard (BH232-3)
- Optional nylon tip (BH232-4)



Stock No.	Length (inches)	Face Dimensions (inches)
BF620C	13 ^{1/4}	3 ^{3/4} x 2 ^{1/4}
Solid rub	ber head	

- 11" Hardwood handle
- · Ideal for replacing hubcaps, bodywork, etc



Stock No.	Length (inches)	Face Dimensions (inches)	Head Color
BF623	12 ¹ /2	1 ⁷ / ₈ x 2 ¹ / ₈	Blue

- Use on all types of surfaces and assemblies including metal, glass, plastic and wood
- Conforms to irregular surfaces
- Designed for maximum surface contact
- Low rebound
- Dissipates hand jarring shock
- Resists most chemicals
- Wood handle
- Reduces denting and marring



Striking & Cutting Hammers / Punches and Chisels

Brass Hammer

Fiberglass Hammer



Stock No.	Weight (lbs.)	Length (inches)	Ŵ	Order No.
HBR15	1 ^{1/2}	12	1	801011
HBR25	2 ¹ /2	12	1	801012

- Non-sparking/non-marring surface for many applications
- Flat surface for even distribution of blow
- Fiberglass handle for strength
- Comfortable, non-slip handle grip

	F			
Striking Eggs Dig	Handle Longth	Overall Length	Doplocomont	0

Stock No.	Description	Weight, Ibs	Striking Face Dia. (inches)	Handle Length (inches)	Overall Length (inches)	Replacement Handle	۲	Order No.
BC4SG	Cross Peen	4	1 ¹ / ₂	12	14	BD4SG-1	1	801021
BD4SG	Engineer	4	1 ¹ /2	12	14	BD4SG-1	1	801022
HD4SG	Hand Drilling	4	1 ¹ /2	8 ³ / ₄	10 ^{3/} 4	HD4SG-1	1	801023

• Fiberglass handle dampens vibration and provides extra strength and safety

- Brass head absorbs blow and reduces rebound Handle is epoxy-welded to hammer head and will withstand 8,000 lbs. of separation force
 - Handle is resistant to dry rot, warp and splintering
 - Comfortable, non-slip handle grip
 - Materials will resist most shop chemicals

Punch Set Packing: 1

DPFT528B Order NO.: 802001 Automatic Center Punch Packing: 1

YA879A Order NO.: 802002

Automatic Center Punch YA900 Packing: 1 Order NO.: 802003



- For transferring hole patterns • Set includes punches from 3/32" to 1/2" in 1/64" increments plus 17/32"
- Each punch is marked with its size and manufactured from tempered steel to promote long tool life
- A metal index provides convenient storage
- Punches are 4 7/8" in length



- Single handed operation
- Design eliminates need for striking with hammer
- Adjustable spring tension cap
- Hardened steel point is replaceable
- 1/2" diameter
- 5" long



- Strikes blow when pressure is applied-no hammer needed
- Cap adjusts force of blow
- 7/16" diameter
- 4 3/4" long



Scraper Set Packing: 1

PKB500A Order NO.: 802004



Stock No.	Handle Length (inches)	Blade Length (inches)	Blade Width (inches)	Blade Style	Edge	Ĩ	Order No.
PKB50A	4 ⁷ /8	3 ¹ /2	2	Stiff	Straight	1	802005
PKB52A	4 ⁷ /8	3 ¹⁹ /32	1 ¹ /4	Stiff	Straight	1	802006
PKB53A	4 ⁷ /8	3 ¹⁹ /32	1 ¹ /4	Stiff	Single Bevel	1	802007

 Set includes PKB50A, PKB52A and PKB53A Putty Knives Scrapers • Spring tempered, solid brass blades are non-marring, non-sparking, non-magnetic and non-corrosive

- Soft molded rubber handles maximize hand grip, are easy to clean and are resistant to most solvents
- Broad hilt design helps protect against hand slippling when scraping Stiff blade style

Scraper Set	PK500A Order NO.: 802008
Tacking. I	Order NO.: 802008
	00
FED FED	S. Alle

Stock No.	Blade Length (inches)	Blade Width (inches)	Blade Style	Edge	Ŵ	Order No.
PK50A	3 ¹ /2	2	Flexible	Straight	1	802009
PK52A	5 ¹⁹ /32	1 ¹ /4	Flexible	Straight	1	802010
PK53A	2 ¹⁹ /32	1 ¹ /4	Stiff Chisel	Single Bevel	1	802011

• Set includes PK50A, PK52A and PK53A Putty Knives Scrapers

- Features full length steel blades for strength and durability
- Soft molded rubber handles maximize hand grip, are easy to clean and are resistant to most solvents
- Broad hilt design helps protect against hand slipping when scraping

Walnut Handle Scraper



Stock No.	Blade Style	Blade Length (inches)	Length (inches)	Ì	Order No.
US710	Spoon	3 ¹ /2	8	1	802013
US711	Chisel Tip	2 ¹ /2	7 ¹ /8	1	802014
US712	Oyster	2 ¹ /8	6 ³ /4	1	802015

Set includes US710, US711 and US712 Knife Blade Scrapers

- Remove gaskets, sealers and other caked on materials • Blade edge designed to work effectively in both push and pull
- directions
- Stainless steel blades for durability
- Polished blades clean up easily
- Comfortable composite handles feature a contour thumb stop for maximum control and a wide hilt for control



Stock No.	Length, (inches)	Width (inches)	Blade Style	Edge	Length (inches)	i	Order No.
PKWLR53A	5 ¹ /2	1 ¹ /4	Straight	Chisel	9 ¹ /2	1	802018
PKWSS53A	2 ³ /4	1 ¹ /4	Straight	Chisel	6 ³ /4	1	802019

- Quality crafted for hard scraping applications
- Walnut wood handle for comfort
- · Full length heavy duty blades for strength
- Large steel cap for striking capability
- Remove gaskets, sealants and body weld breakaway

Wood Handle Scraper



• Mirror finished hardened steel blade extends through hardwood handle, solidly riveted for durability

• Redwood handle has metal bolster where handle meets blade



Aviation Snips (Discontinued)



Stock No.	Description	Length (inches)	Ŵ	Order No.
DAR9A	Green handled; Right hand cut	9 ¹ / ₂	1	803010
DAL9A	Red handled; Left hand cut	9 ¹ / ₂	1	803011

Offset blades allow cut material to flow beneath your hand without curling

- Maneuverable for angle cutting or pattern configurations
- Cuts up to 18 ga. mild steel
- 1 1/8" cutting edge

Tin Snips



Description	Blades Length (inches)	Length (inches)	Ũ	Order No.
Duckbill Snips	1 ^{1/2}	7	1	803005
Duckbill Snips	2 ^{1/4}	10	1	803006
Combination Snips	3	12	1	803007
Bulldog Snips	2 ¹ / ₂	16	1	803008
	Duckbill Snips Duckbill Snips Combination Snips	Description (inches) Duckbill Snips 1 ½ Duckbill Snips 2 ¼ Combination Snips 3	Description (inches) (inches) Duckbill Snips 1 ^{1/2} 7 Duckbill Snips 2 ^{1/4} 10 Combination Snips 3 12	Description (inches) (inches) Duckbill Snips 1 ^{1/2} 7 1 Duckbill Snips 2 ^{1/4} 10 1 Combination Snips 3 12 1

• Cut straight, circular, or irregular patterns; right or left cuts





Stock No.	Description	Length (inches)	Ŵ	Order No.
DAL10B	Red handled; Left hand cut	10 ^{1/} 4	1	803001
DAR10B	Green handled; Right hand cut	10 ¹ / ₄	1	803002
DAS10B	Yellow handled; Straight cut	10 ^{1/4}	1	803003

Serrated cutting blades

- Narrow bodies allow metal to pass over shears
- Oil and grease resistant grips
- DAS30 Set includes DAL10B, DAR10B and DAS10B

Shears, Angled, Heavy Duty

Packing: 1

SNP2A Order NO.: 803009



- For leather, cloth, plastic, rubber sheet, rubber hose, cardboard, gasket material, rope and many other materials
- Stainless steel blades and fasteners ensure durability
- Precision ground and heat treated for a long lasting edge
- Ergonomic handles can be used right or left handed
- Top of blade is notched for hard wire and twine
- Locking switch ensures safety during storage
- Control switch allows blades to be held in a tighter position for easier handling
- Angled shears allow easier cutting through flat materials
- Soft mold grip for comfort and control

Vinyl Cutter



Stock No.	Description	i	Order No.
YA444B	Cutter, Vinyl	1	803013
YA444B1	Replacement Blades	1	803014

Cleanly cuts plastic, rubber, vinyl, upholstery, leather, hoses, and rope

- ERGO Grip handle with safety lock
- Blade storage in handle
- Includes three (YA444B1) stainless steel replacement blades YA444B1 Replacement Blades
- Includes 3 replacement blades and anvil for YA444B



Scissors, Shop, Heavy Duty Packing: 1



HDSCISSORS

Order NO.: 803012

- For leather, cloth, plastic, rubber sheet, rubber hose, cardboard, gasket material, rope and many other materials
- Stainless steel blade and fasteners
- Precision ground and heat treated for a long lasting edge
- Ergonomic handles can be used right or left handed





Stock No.	Description	i	Order No.
YA580A	Cutter, Multi-purpose	1	803015
YA580A-1	Replacement Blades	1	803020

- · Features auto locking, fully retractable blade
- All metal body is black with pocket clip
- Includes (1) premium steel 13 pt. snap blade
- Overall length of 5 3/8" (136.5mm)
- YA580A-1 Replacement Blades
- Pack of 5

Cutter, Multi-Purpose



Stock No.	Description	(Order No.
YA581A	Cutter, Multi-purpose	1	803016
YA581A-1	Replacement Blades	1	803023

- Has three blades with eight snap off points.
- Minimum blade wobble
- Fully retractable
- YA581A-1 Replacement Blades
- Pack of 10



- Convenience and good looks of a folding lock back knife with easily replaceable two notch razor blades
- Folding lock back blade, hardwood handle with belt clip and thumb stud for one-hand opening
- Includes utility knife and leather pouch (both with Blue-Point[®] logo) plus 10 replacement blades
- Uses UKBU10 (10 pack) or UKBU50PK (50 pack) replacement blades

Utility Knife (Discontinued)

Packing: 1

LBUK2 Order NO.: 803018



- Thumb pad allows controlled application of pressure Blades are easily replaced with a flip of a switch Blade storage under spring loaded door Includes leather pouch with belt loop plus 5 replacement blades



Solidly constructed lock back utility knife sports polished, stainless steel handle with TPR grips for durability and control Two notch blades are easily changed with quick change switch Includes belt pouch and 10 titanium replacement blades Uses UKBU10 (10 pack) or UKBU50PK (50 pack) replacement blades





Utility Knife Blades

UKBU10 Order NO.: 803021

- High performance blades are perfect for thick, dense materials
 Bi-metal construction allows blade to bend/flex without breaking
- under normal work conditions
- Bi-metal lasts up to 3 times longer than normal utility knife blades
 Two metals blades dealers file provide than dealers with the last of the second state of th
- Two-notch blade design fits most standard utility knives
 Use with LBUK1, LBUK2 and LBUK3 Utility Knives
- Pack of 10 blades



Stock No.	i i i i i i i i i i i i i i i i i i i	Order No.
TF5A	1	803038
TFM5A	1	803039

TF5A

- Makes double or single flares on soft steel, brass, or aluminum tubing from 3/16" to 1/2" OD
- Makes a smooth fitting, crack free 45° flare
- Set includes five adaptors, yoke assembly, bar assembly, and handle
- Storage case included

Double Flaring Tool Set

- TFM5A Metric Double Flaring Tool Set
- Same design as TF5A except it is for tubing with an OD from 4.75 to 10mm
- Set includes yoke, bar assembly, handle, and five adaptors: 4.75, 5, 6, 8, and 10mm
- Storage case included

Utility Knife Blades Packing: 1

UKBU50PK

Order NO.: 803022

Flaring and Swaging Set

Packing: 1

TF275A Order NO.: 803040



- High performance blades are perfect for thick, dense materials
- Bi-metal construction allows blade to bend/flex without breaking under normal work conditions
- Bi-metal lasts up to 3 times longer than normal utility knife blades
- Two-notch blade design fits most standard utility knives
- Convenient dispenser provides storage for used blades
- Use with LBUK1, LBUK2 and LBUK3 Utility Knives
- Dispenser of 50 blades



- 45° flare or swage soft copper, brass, or aluminum tubing
- Die blocks handle 1/8", 3/16", 1/4", 5/16", 3/8", 7/16", 1/2", 5/8", and 3/4" OD tubing
- Swages 3/16", 1/4", 5/16", 3/8", 1/2", 5/8", and 3/4" OD tubing
- TF275PB storage case included



• Designed for crack free bubble flares on soft wall tubing up to a wall

• Adaptors included for 4.75, 6, 8, and 10mm flares

Metric Bubble Flaring Set

For automotive brake systems

• TFM428PB storage case included

thickness of .028"

TFM428 Order NO.: 803041

Tubing Cutter



Stock No.	Ŵ	Order No.
TC28C	1	803030
TC28B1	1	803032

- Cuts soft metal tubing ranging from 1/8" to 1" in diameter
- OD capacity is 1/8" to 1 1/8"
- Micrometer type adjustment
- Retractable locking reamer blade
- Cutter wheel is easily replaceable TC28B1 Cutting Wheel
- Extra cutter wheel for TC28C

Tubing Cutter



Stock No.	i i i i i i i i i i i i i i i i i i i	Order No.
TC123C	1	803031
TC123CRH	1	803035
TC123C1	1	803033

- Handles tubing from 1/8" to 5/8" OD
- Can be used where clearance around tubing is less than 1 3/8"
- 1 1/2" long when closed and 2" long when open; feed knob is 7/8" in diameter
- TC123CRH Ratcheting Tube Cutter Handle Handle for TC123C tube cutter
- TC123C1 Cutting Wheel Extra cutter wheel for TC123C

Ratcheting Tube Cutter

📦 Packing: 1

TC123CR Order NO.: 803034



• TC123C cutter and TC123CRH handle combined into one unit

Tube Cutting and Double Flaring Set

TF528D Order NO.: 803037



- Contains TC28C tubing cutter and a double flaring set with a flaring bar, rod handle, yoke, and 5 adaptors: 3/16", 1/4", 5/16", 3/8", and 1/2"
- Storage case included

MARNING 💮 🔄 Read safety precautions on page 162

115





You will find a good selection of measuring equipment with high accuracy and other hand tools that is of good quality in this section. We strive to offer a good balance of quality to the price in these products. And there are also a number of innovative items, like the magnetic-based flashlight, created with user friendliness in mind.







Measuring & Other Hand Tools Measuring Tools

Feeler Gauges, 13pcs Feeler Gauges, 25pcs Feeler Gauges, 35pcs FB310B FB325A FB335 Packing: 1 Order NO.: 804001 Packing: 1 Order NO.: 804002 Packing: 1 Order NO.: 804003

Stock No.	Increments	Blade Size	Style	Blade Dimensions (inches)	No. of Blades	Description
FB310B	-	.001", .0015", .002" thru .008", .010", .012", .013", .015"	General Use	¹ /2 x 3	13	Double stamped with U.S. and metric sizes
FB325A	.001"	.0015", .002" thru .025"	General Use	¹ /2 x 3	25	Double stamped with U.S. and metric sizes
FB335	.001"	.0015", .002" thru .035"	General Use	^{1/2} x 3	35	Swedish feeler blade steel









Stock No.	Increments	Blade Size	Style	Blade Dimensions (inches)	No. of Blades	Description
FBL325A	.001"	.0015", .002" thru .021", .025", .027", .030", .040"	Long Blade General Use	^{1/} ₂ x 12	25	Long blade, double stamped with U.S. and metric sizes
FBM320	.05mm	.05 thru 1mm	Metric General Use	^{1/2} x 3	20	Metric Feeler Gauge Set
FB316B	.001"	.010", .012", .013", .015" thru .022", .024" thru .026", .028", .030", .032", .035"	Short Blade Ignition/Spark Plug Gauge	^{1/4} x 1 ^{3/4}	18	Short Blade, Ignition/Spark Plug Gauge Set







FB300A

Feeler Gauges, 12pcs FB308D Packing: 1 Order NO.: 804009



Stock No.	Increments	Blade Size	Style	Blade Dimensions (inches)	No. of Blades	Description
FB326B	.001"	.008", .010", .012", .013", .015", .017", .018", .020", .022", .024" thru .026", .028", .030", .032", .035"	Combination Feeler/Ignition Gauge	^{1/2} x 3	26	Double stamped with U.S. and metric sizes
FB300A	.001"	.006" thru .030"	Bent Blade	^{1/2} x 3	25	Feeler Gauge Set
FB308D	.001"	.008"010", .011"013", .013"- .015", .014"016", .015"017", .017"- .019", .018"020", .020"022", .023"- .025", .025"027", .026"028", .028"030"	Step Blade	1/2 x 3	12	Step Feeler Gauge Set , Bent handle to clear manifolds, double stamped with U.S./Metric sizes. Blades are mounted on FBFT7 holder



Measuring & Other Hand Tools Measuring Tools

Feeler Gauges, 22pcs



Feeler Gauges, 2pcs

FB328A Order NO.: 804011

Feeler Gauges, 2pcs

FBM322 Order NO.: 804012







Stock No.	Increments	Blade Dimensions (inches)	Blade Size	No. of Blades	Description
FB322	.001"	¹ / ₂ x 3 ³ / ₈	.004"006" thru .025"027"	22	"Go-No Go" blades with 2 sizes each
FB328A	—	¹ /2 x 3	.011"013", .013"015"	2	For valve adjustment on GM 8.2L engines, double stamped with U.S. and metric sizes
FBM322	_	^{1/2} x 3	.2030mm, .4050mm	2	10 ^{3/4} long bent handle

FB307D





Order NO.: 804013 ade nsions Blade Size No. of Blades

.008", .011" thru .014", 1/2 x 4 1/2 .016" thru .018", .020", .023" thru .025", .027", .029"

• Bent blade cummins diesel, blade ends are bent at 90° angle: blades are secured on FB307C1 ring

Measuring Tapes





- Rubberized coating for better grip
- Tape auto-lock when extended
- Nylon coated tape

Measuring Tapes



- Tough and durable construction
- Dual scale-- metric and imperial

Long Tape, Steel, 100ft



- Includes inch/metric scale
- Quick rewind design for ease of use
- Rewinding lever conveniently stored in housing
- Non-slip grip provides confidence and comfort

Spirit Levels, 9"

TL100A Order NO.: 804021

YA328A

Order NO.: 804022

TPM100

Order NO.: 804014



- 9" precision measuring tool designed for close quarter work
- Magnetic strips and v-grooving make it ideal for pipe and conduit work

Angle Locator

📦 Packing: 1



- Precise, accurate tool to determine angle measurements
- Ideal for checking drive shaft angle
- Red degree indicator located behind numbers for exact reading of graduations
- English and metric scales molded into base of tool in 1/8" and DM
- Large 1 7/8" x 7/8" magnet inserted in base for secure retention



Measuring & Other Hand Tools Measuring Tools

C			
Combination Measuring Set SC Packing: 1	QUARECOMB12 Order NO.:804023	Digital Caliper MC Packing: 1 Order NO.:	AL6A 804029
Stock No. Descri	iption 🍟 Order No.	and the second second	
SQUAREB180 SQUAREB180	are 1 804026		
RULER12BSQ Steel Rul	or Head		
SOUAPERon Square	Sliding 1 804025	- I and the second second	
SQUAREB45 Square			
Head	145° 1 004020	• Course is 0" to 6" (0 to 150mm) in 0.0005" (0.01mm) resolution	
 Set includes SQUAREB180 Protractor, RULER12E plus SQUAREB90 and SQUAREB45 sliding heads case 		 Gauge is 0" to 6" (0 to 150mm) in 0.0005" (0.01mm) resolution Use for inside, outside, depth and step measurements Inch/metric conversion with one button Large LCD display Hardened stainless steel frame Conform to standard : GB1214 	15
Machinist's Measuring Set	SQUAREB12 Order NO.:804024	Digital Caliper MCA Packing: 1 Order NO.:	AL12A 804030
Stock No. Description 🔰 SQUAREB90 Square Sliding Head 1	Order No. 804025	 Essential tool for working on larger vehicles, trucks, tractors a earth moving equipment 	nd
RULER12BSQ Steel Rulers, 12" 1	804027	• Range is 0" to 12" (0 to 305mm) in 0.0005" (0.01mm) resolution	ons
 Set includes SQUAREB90 sliding head and RULE ruler in fitted storage case 	R12BSQ steel	 Use for inside, outside, depth and step measurements Inch/metric conversion with one button Large LCD display with floating zero set Locking nut and thumb roll for smooth action Conform to standard : GB1214 	
Dividers, 6"	CNT6521 Order NO.: 804057	Dial Type Caliper PMF Packing: 1 Order NO.:	-147A 804031
 Spring type divider has virtually no torsion or side p Previous part number was PMF129 	blay	 Gauge is 0" to 6" in high (0.001" increments) and metric (0.1m increments) Includes storage case Conform to standard : GB1214 	ım

120



Digital Micrometers



Stock No.	Range (mm)	Increments (mm)	i i i i i i i i i i i i i i i i i i i	Order No.
MIC1MB	0-25	0.01	1	804032
MIC2MB	25-50	0.01	1	804033
MIC3MB	50-75	0.01	1	804034
MIC4MB	75-100	0.01	1	804035
MIC5MB	100-125	0.01	1	804036

 MIC103MB Digital Metric Micrometer Set includes: MIC1MB. MIC2MB and MIC3MB

Digital Micrometers



Stock No.	Range (inches)	Increments (inches)	i i i i i i i i i i i i i i i i i i i	Order No.
MIC1B	0-1	0.0001	1	804037
MIC2B	1-2	0.0001	1	804038
МІСЗВ	2-3	0.0001	1	804039
MIC4B	3-4	0.0001	1	804040
MIC5B	4-5	0.0001	1	804041

MIC103B Set includes: MIC1B, MIC2B and MIC3B

Outside Micrometers



Stock No.	Range (inches)	Increments (inches)	(Order No.
MICB1B	0-1	0.0001	1	804042
MICB2B	1-2	0.0001	1	804043
MICB3B	2-3	0.0001	1	804044
MICB4B	3-4	0.0001	1	804045
MICB5B	4-5	0.0001	1	804046

• MICB103B Set includes: MICB1B, MICB2B, MICB3B

Measuring Tools

Facking: 1

Electronic Digital Micrometers

MICED1B Order NO.: 804048



- Display reads to 0.00005" (0.001mm)
- · Zero set for absolute and incremental measuring modes
- Auto shut-off after 10 minutes
- Insulated frame, hardened body, carbide tipped anvil, positive locking clamp and ratchet stop thimble

Inside Micrometer Set, 7 pcs 💗 Packing: 1

MICINSIDE12 Order NO.: 804047



- Tubular design
- Range is 2" to 12" in .001" increments
- Includes inside micrometer head and a series of coil spring pressure contact rods

Depth Micrometer Set 📦 Packing: 1

DM6 Order NO.: 804049







• Measure depths of slots, counterbores, holes and keyways up to 6" in depth

- 4" satin chrome base for greater stability
- Graduated in .001" increments
- Includes fitted storage case









Flashlights

Rechargeable LED Shop Light



Rechargeable LED Shop Light



ECFLED215AP Order NO.: 805013 Multi LED Shoplight

ECFPKT20AP Order NO.: 805015



- Contraction

- Rechargeable and cordless compact shop light that can be taken anywhere
- 21 front-facing LEDs provide high light output to work surfaces
- 5 LED spot light provides up to 15 hours of continuous illumination
- Multi-function switch toggles between front and top LED illumination
- 180° folding design offers the ultimate in flexible positioning
- Dual magnetic design for parallel use or multi angle

- 20 high output LEDs provide 1,600 lux of light
- Strong rechargeable Lithium-ion battery lasts up to 4 hours
- 360 degree folding design enables flexible light positioning
- Magnetic base allows placement on metal surface
- Handy pocket size with belt clip for great portability
- CE/UL certificated charger 110-240V



Rechargeable Shop Light Packing: 1



- IP65 rating, heavy duty and robust
- Vapor, water and dust proof
- Rechargeable, Li-ion battery with 4 hours constant output
- 3 pcs magnets, totally hand free works, easier for technicians to operate
- 1 hook new design, rotate 360 degree
- 1 Stand to support this light work on 3 angles
- 180 degree bendable. Offering all lighting angle possibilities.
- CE/UL certificated charger

Rotating Light Mag Base 📦 Packing: 1

ECFLED24 Order NO.: 805005

ECFLOODAP

ECFBP20AP

Order NO.: 805014



- 24 high output LEDs project light in wide area
- Provides 40 lumens light output

Flood Light

👔 Packing: 1

- (3) AAA alkaline cells provide 4~5 hours of light
- Strong magnet mounts securely on any magnetic surface
- Mounts under-hood, under-dash, under-car wherever it is needed
- Direct light to any angle using rotating magnetic base
- Keeps hands free to do the work, while lighting the work area



Order NO.: 805017

ECFLOODAPS1 (Stands, sold separately)

- Powerful and uniform illumination ideal for lighting working environment
- Utilizing LED reduces energy consumption
- 70 SMD LED provides up to 2500 lumen, 35W
- IP65 Resistant to water and dust infiltration
- Compact and robust construction with strong rubber protection frame
- With flexible stand to allow placing the lamp in the desired angle
- Total aluminum design for better heat distribution

Flashlights / Safety



- Bright watt LED never needs replacing
- Pivoting head and adjustable headband
- Water resistant
- 30 hours continuous run time on (3) AAA alkaline batteries

Washable Work Gloves



Stock No.	Size	Color	Î	Order No.
GLOVE103MA	Medium	Black	1	806003
GLOVE103LA	Large	Black	1	806001
GLOVE103XLA	X-Large	Black	1	806005
GLOVE103MAB	Medium	Blue	1	806004
GLOVE103LAB	Large	Blue	1	806002
GLOVE103XLAB	X-Large	Blue	1	806006

- Gloves feature stretch knit with padded back to provide extra feel and flexibility to grasp small objects
- Extra knuckle protection on back of fingers
- Heat resistant synthetic double layered leather palm for longer life
- Elastic cuff with hook and loop closure

Abrasion Resistant Nitrile Gloves



Stock No.	Size		Order No.
GLOVE400S	Small	3	806009
GLOVE400M	Medium	3	806008
GLOVE400L	Large	3	806007
GLOVE400XL	X-Large	3	806010
GLOVE400XXL	XX-Large	3	806011

- Nitrile dipped coating for protection on dirty jobs
- · Ergonomically pre-curved design gives you comfort at all times • High abrasion resistance protects hand on sharp edges and rough
- castings • Incredible grip and dexterity on wet and dry surfaces
- Lightweight nylon shell provides a nice snug fit
- CE rated for abrasion, blade cut, tear and puncture resistance





- Helps protect hands from sparks when welding
- Leather construction with added insulation for heat protection
- Reinforced palm for durability

Tig Welding Gloves

🎁 Packing: 1



- Ideal for TIG welding processes
- Pigskin material for precise control
- Helps protect hands from heat and sparks
- Thick leather cuff for wrist protection

Welding Sleeves 1 Pair Packing: 1



- Helps protect arms from sparks when welding or cutting
- Elastic bands at each end of sleeve
- Constructed of flame retardant fabric
- 18" long
- 1 pair

Face Shield Packing: 1

GA225 Order NO.: 806012

	Shield Style	Shield Size (inches)
ai	Flat	7 ³ / ₄ x 15 ¹ / ₄
	Shield Included	Replacement Shields
	Clear	GA225-1 (with PETG) GA225-2 (with PC)

- Adjustable, cushioned head band is removable
- Face shield provides impact resistance
- Includes visor (GA225-1) with PETG (impact resistance perferred)
- Optional visor (GA225-2) with PC (high temperature resistance) is available

Safety

YA4282

YA4280

Order NO.: 807031

Order NO · 807032

Safety Glasses



- Complies with ANST Z87.1-2003
- Lens provide 99.9% UV protection
- Angle and length adjustable temples provide various suitable fitting
- Soft nose pad and soft temple tips provide comfort for long-time wearing
- Anti-fog lens coating with anti-scratch protection
- GLASS30BK and GLASS30R have a ventilation channel between frame and lens

Ear Protector Packing: 1

Order NO.: 806013

 Noise Reduction Rating, dB
 Headband

 28
 Cushioned

 Ear Piece
 Weight (lbs.)

 Cushioned
 0.77

- Noise reduction rating of 28 dB for protection
- Lightweight and comfortable with cushioned headband
- Cushioned ear piece for a comfortable and snug fit that keeps out noise
- Each ear piece pivots to provide a comfortable and secure fit
- Blue hard protective ear cups with Blue-Point® logo in white
- Each ear piece easily adjusts to fit a variety of sizes

Ear Protector, Ear Plug Style

YA160A Order NO.: 806014

GA3200

Noise Reduction Rating, dB Headband 25 Plastic Ear Piece Ear Piece Replacements Weight (lbs.) Foam YA160A1 0.06

• 25 dB noise reduction rating

WARNING

- Cushioned ear piece for comfort and snug fit to keep out noise
- Non-conductive

Packing: 1

Includes extra set of foam ear piece and reusable storage bag







807001

807002

807003

1

1 1

Measuring & Other Hand Tools







NOZZLE360A

Order NO.: 807014

- Turns any standard 5/8" hose into a multi-function cleaning tool

Miscellaneous

- · Wash/rinse vehicles or water plants using a softer, cascading
- Clean pools, deck and driveways with heavy duty stream Clean service bays, shop floors and blast mud/dirt from vehicles
- 360° jetted nozzle is engineered from rugged extruded aluminum.
- forged stainless steel, high grade fiberglass and comfort grip

HP2 Order NO.: 807012





- Push button locking collet enables quick, easy blade changes
- Includes three round head deburring blades
- Blades conveniently store in handle of tool
- Weighs 1 lb
- 6" long

Magnetic Holder

📦 Packing: 1

CM6416 Order NO.: 807016



- Magnet has "on/off" switch
- Base is 2 3/8" x 1 7/8" x 2 1/2"
- Post is 7" x 15/16"
- Rod is 6" x 25/64"
- Will grip flat or curved metal surfaces

Deluxe Air Vacuum System

AV1000A



- Ideal for vehicle media installation and body shops plus other applications in need of picking up dust, metal shavings or broken glass
- Large collection bag includes a debris baffle and sliding bag clamp for emptying debris
- Lightweight ergonomic handle design
- Includes 8.7" aluminum extension tube, 8 1/2" plastic extension tube (AV1000A10), flexible extension tube (AV1000A9), pointed nozzle (AV1000A11) and crevice tool with brush (AV1000A8)

Miscellaneous

Bench Vise



Stock No.	Jaw Width		Order No.
BLPMV4	4" jaws	1	807017
BLPMV5	5" jaws	1	807018
BLPMV6	6" jaws	1	807019

- Single piece steel blocks for higher load capacity
- Extended anvil
- Lubrication points for maintenance
- Optional swivel base
- Capacity range from 3.5 ton to 9 ton at maximum opening
- Reinforced cantilever support
- Interchangeable jaws
- Diamond ground for better grip
- Heavy duty cast iron construction
- Precise jaw alignment
- Rolled thread spindle for easy locating and tightening parts
- Protected spindle

C-Clamps



- Similar to CL series c-clamps
- High visibility models conform to OSHA safety color standard for physical hazards regulation #19110.144
- 3/4" spindle diameter

Welding Helment, Auto Darkening

🎁 Packing: 1

YA4603 Order NO.: 807033



- Two arc sensors for enhanced lens triggering
- Fixed shade #10
- Clear shade of 3.5
- Fixed delay
 - Viewing area 1.38"x 3.81"
 - Solar powered
 - Fixed shade auto darkening welding helmet has a lens that is designed for carbon arc welding processes. Two arc sensors provide a range of sensitivity to trigger the lens under most welding conditions.
 - Meets ANSI Z87.1-2003, CE, DIN 4647 PZ, EN379, EN175, CSA Z 94.3 and AS/NZS 1338.1 standards



Standard Duty Welding Kit

籣 Packing: 1



Stock No.	Description
HRC1401340	85 Weld Handle with Check Valves
HRC1300380	72-3 Cut Attach
HRC9100614	D-85 Weld Mixer
HRC4300557	³ /16 x 20 Twin Hose
HRC4304482	Cover Goggle
HRC9004486	Striker
WE200A1	Oxygen Regulator
WE200A2	Acetylene Regulator
HRC1502172	6290-1 #1 AC Cut Tip
HRC1600890	23-A-90-5 #5 Weld Tip
HRC1600870	23-A-90-3 #3 Weld Tip
HRC1600850	23-A-90-1 #1 Weld Tip

Optional Accessories

Stock No.	Description
HRC1800710	J-63-1 Heating Assembly
HRC1600840	23-A-90-0 #0 Weld Tip
HRC1600860	23-A-90-2 #2 Weld Tip
HRC1600880	23-A-90-4 #4 Weld Tip
HRC1502170	6290-00AC #00AC Cut Tip
HRC1502171	6290-0AC #0AC Cut Tip
HRC1502173	6290-2AC #2AC Cut Tip
HRC1502174	6290-3AC #3AC Cut Tip
HRC4301650	88-5FBT PR. Torch Flash Arrestor
HRC9000160	E-9 Tip Cleaner (2 pc tip)
HRC9004484	Replacement Flints

- Use for auto repair, construction, fabrication, manufacturing and maintenance
- Cuts up to 1" and welds up to 1/8"
- Cuts up to 4" and welds up to 1/2" with optional tips
- Durable and strong forged brass regulator
- Regulator diameter 2 1/4" allows precise control of gas
- Internal Iter keeps particles from entering regulator
- PTFE Teon seat ensures positive sealing
- Handle shut-o valve color coding provide ease in identifying the corresponding gas control
- Two piece cutting tip allow easy cleaning
- High quality hose oers reduced tear resistance and increased exibility

Miscellaneous

WE200A

Industrial	Paper			BPAP1 Order NO.: 807035
	•	2		
Stock No.	Size(mm)	Color	Pieces / Roll	i
BPAP1	31*34cm	White	1100	1

- Excellent for cleaning off oil and residue from tools, hardware, equipment and mechanical components
- Tough for industrial use
- Lint free to prevent electrostatic charge as well as a clean surface
- Made from cellulous and polypropylene for better absorbability



BPAP2 Order NO.: 807036



Stock No.	Size(mm)	Color	Pieces / Roll	I
BPAP2	25*35cm	Green	300	6

- Excellent for cleaning off oil and residue from tools, hardware, equipment and mechanical components
- Tough for industrial use
- Lint free to prevent electrostatic charge as well as a clean surface
- Made from cellulous and polyethylene for softness and finer surface

Roller Stand

BPAPS1 Order NO.: 807039



🗟 🔲

• Foldable Metal Stand for BPAP1





Shop & Technician Tools

Blue-Point

Blue Point

Our shop and technician tools focus mainly on the automotive industry with commonly used items like multimeters and protective gloves, to equipment and devices specially made for vehicle engine code reading and valve servicing. We have almost a tool to cater for all job tasks commonly done in the automotive industry.

A REAL PROPERTY OF THE REAL PR

TM

BEMOVE

R

Testing and
ElectronicsSpecial
ToolsAutomotive
Specialty Tools132134136



Shop & Technician Tools Testing and Electronics

Borescope Packing: 1



SPECIFICATIONS:

Optimal Viewing	1" to 12" (2.5 cm — 30 cm)
Power Supply	Li-Ion Battery 3.7V, 4200 mAh
Estimated battery run time	3-5 hours
Weight	1lbs 14oz. (0.5 kg)
Internal Memory	512 MB storage
Built in micro SD card bay	high capacity compatible
Dimensions	7" (17.8 cm) L x 3.63" (9.2 cm) W x 6.25" (15.9 cm) H
Temperature	2°F to 113°F (0°C to 45°C)
Humidity	5% to 95% non-condensing (display unit)
Storage Temp	-4°F to 158°F (-20°C to 70°C)
Water Resistance	Imager to 10' (3.05 m) depth

BKB6500

Order NO.: 901017

- 4.3" TFT LCD Display with a native resolution of 480 RGB X 240
- Digital camera technology provides superior imagery under all light conditions compared to analog cameras
- Dual view Imager allows the user to see forward or 90° to the side with one touch
- Easy to use touch screen interface
- File naming for convenient file management
- Text annotation aids in documentation
- Coil cord imager handle allows for greater maneuverability while the base stays at a comfortable viewing position
- Low optical distortion provides superior image quality
- Capture still images at 640 X 480 resolution
- Capture video at a rate of 20 fps (frames per second)
- 2X digital zoom
- Excellent near-field focus (0.5" to 12")
- Imaging head made of robust aluminium

- Resistant to common automotive and industrial chemicals
- Super Bright LED
- 8.5mm outside diameter fits in most spark plug holes
- Built in microphone and speaker for recording comments and sounds
- 36" long imager is coated with a non conductive covering for protection of surfaces and safety
- Mini-USB connector for uploading images and video to a computer
- Analog video out to a larger format screen or recording device
- Rubber over-mold on all contact/gripping areas for added ergonomics and durability
- Integrated rubberized magnets secure unit to metal surfaces
- External microSD Card access
- External mini-USB access
- Integrated three position stand for added convenience
- Rechargeable internal Lithium-ion battery
- D/C plug allows the unit to be used while battery is being charged





Shop & Technician Tools Testing and Electronics

Pick Sets



- PSLR4 (Order No.901010) extra long pick set includes PSLR4-1 thru PSLR4-4 (4 pcs) in vinyl storage pouch
- PSLR6 (Order No.901001) extra long pick set includes PSLR4-1 thru PSLR4-6 (6 pcs) in vinyl storage pouch

Tweezer Kit, 5 pcs Packing: 1

TZK5 Order NO.: 901006



- Includes five tweezers neatly arranged in a vinyl zipper pouch
- All stainless steel construction
- Pointed tweezers w/plain ends, 4 3/8" long
- Self closing tweezers w/plain ends, 4 1/2" long
- Sharp point utility tweezers w/bent plain ends, 7" long
- Sharp point uitility tweezers w/plain ends, 7" long

Tweezer Kit, 7 pcs

Packing: 1

TZK7 Order NO.: 901007

PWC27

Order NO.: 901005

10, 12, 14, 16,



- Includes seven tweezers neatly arranged in a black vinyl zipper pouch
- All stainless steel construction
- Pointed tweezers, 4 3/8" long
- Curved head utility tweezers, 6 3/4" long
- Sharp pointed utility tweezers, 7" long
- Side locking tweezers, 6" long
- Spade point tweezers, 4 3/8" long
- Weighted solder tweezers, 6" long

Wire Cutter Packing: 1	
1	Description
	Automatic Wire Stripper
	Strips Metric Size (mm)

	Automatic Wire Stripper	6 ¹ / ₄	10, 12, 14, 16, 18, 20, 22
1	Strips Metric Sizes, (mm)	Application	Replacement Blades
	_	Strips PVC, THHN, and THWN	PWC27-7
oton otrinning onhou			

- One-step stripping enhances productivity
- Spring-action motion increases leverage and reduces operator fatigue
- Precision ground, knife-type blades provide clean, accurate stripping
- Cleanly strips wire up to full 7/8" (22mm)



- One-step stripping enhances productivity
- Spring-action motion increases leverage and reduces operator fatigue
- Precision ground, knife-type blades provide clean, accurate stripping
- Cleanly strips wire up to full 7/8" (22mm)





Wire Stripper 💗 Packing: 1

PWC14







Shop & Technician Tools Special Tools



- operation
- Use with insulated connectors on 10 to 22 gauge wire
- For easy, efficient, single squeeze crimping of modular connectors
- · Both primary and secondary crimps are made simultaneously to factory specifications
- Has a comfortable ergonomic design and full cycle ratchet action

Pinch Bars



Stock No.	Sq. Stock (inches)	Edge (inches)	Length (inches)	Ŵ	Order No.
1412A	1/2	5/8	14	1	902006
1658C	1/2	5/8	16	1	902010
2420A	3/4	15/16	20	1	902011
2430C	3/4	5/8	30	1	902012
2438C	3/4	7/8	38	1	902007
2842C	7/8	1	42	1	902008

41.5 in. Curved Fiberglass Prybar

PBFG415



- Drop forged, hardened steel wedge end with rust-resistant black finish, is chemically bonded to fiberglass handle
- 50,000 strands of fiberglass are sleeved by a polypropylene jacket for comfort and variable hand placement during use
- About one-half the weight of a steel prybar of the same length and less flexible than a steel prybar for greater leverage
- Polypropylene sleeve is resistant to heat and cold for greater comfort in all temperatures

Magnetic Trays



YA52PBSQC Order NO.: 902005

- Ideal for use with cordless drills and screwdrivers Includes:
- 49 1/4" hex shank bits in short and long lengths
- 2 hex adaptors
- Flat tip bits (long): 6-8, 8-10, 10-12
- Hex bits (short): 1/8", 9/64", 5/32", 3/16", 7/32", 1/4", 9/32"
 Hex bits (long): 5/32", 3/16", 7/32"
- PHILLIPS® tip bits (short): #1, #2 (2 each), #3
- PHILLIPS[®] tip bits (long): #1, #2, #3
- TORX[®] tamper resistant bits (short and long): T10, T15, T20, T25, T27, T30, T40
- Square bits (short and long): #1, #2, #3
- Clutch bits (short and long): 5/32", 3/16"
- Double end bits: 6-8 x #2 PHILLIPS®, 8-10 x #3 PHILLIPS®
- Adaptors: 1/4" hex female to 1/4" hex female, 1/4" hex male to 1/4" square male, 1/4" hex quick change chuck

Stock No.	Description	Sizes	Ŵ	Order No.
MRB5A	Magnetic tray, Round	Round 152mm diameter	1	902018
MRB10A	Magnetic tray	250mm x 140mm	1	902019
MRB12A	Magnetic tray	355mm x 140mm	1	902020
MRB15A	Magnetic tray	290mm x 265mm	1	902021

• Securely holds small parts and tools

- Magnetically attaches to any flat iron or steel surface
- Material: 430 Stainless Iron

Ø



Shop & Technician Tools Special Tools



WARNING Read safety precautions on page 162



Shop & Technician Tools Special Tools / Automotive Specialty Tools





4 Ton Portaset

🎁 Packing: 1



- 4-ton capacity kit includes hydraulic unit, five "Snap-Set" extensions, spreader plus a full selection of attachments for most push applications
- Automatic pump overload system protects against damage to rams and equipment
- 1/2-ton capacity hydraulic spreader has 2" jaw and spreads from 5/8" to 3 3/4"
- Flex head includes permanently molded rubber pad
- · Heavy walled extensions tubes stand up to the toughest loads
- Long handle reduces required pumping effort
- 18 piece set is stored in durable storage case

Tap & Die Set

GA541 Order NO.: 903037

YA1544A

Order NO.: 903132

- Taps and dies from 1/4" to 1/2" in both NF and NC threads, taps and dies from 4-40 thru 12-24 and corresponding dies in Machine Screw Threads, a pipe thread tap and die, plus two die stocks and three tap wrenches, a screw pitch gauge, and a die adjusting screwdriver (41 pcs) in a storage case
- Die size 1/4" to 1/2" and 7 mm to 12 mm are a one-piece, 12-point design that can be turned with a 1" socket wrench (5/8" socket wrench for 3 to 6 mm dies) when working in places where a normal die stock cannot be used

Metric Tap & Die Set

GAM541 Order NO.: 903038



- 40-pc set features 1" single hex non-adjustable dies from 3 to 12mm, a 1/8"-28 BSP die plus taps in the same sizes
- Also includes a die stock, 2 T-handle tap wrenches, a thread pitch gauge, a drill/tap chart and a midget screwdriver, all in a storage case



Comes in a storage case

Extractor Set

📦 Packing: 1

E1025 Order NO.: 903039

MTPV1000

Order NO.: 903041



- Extract broken screws from 1/4" to 1" diameter and standard pipe sizes 1/8" to 1"
- Packaged in a storage case

Meter ATV And Motorcycle

🏮 Packing: 1



- Peak voltage measurement of secondary ignition systems on all types of vehicles and pleasure craft
- CDI ignition diagnosis on motorcycles, ATVs, and snowmobiles
- Digital Multimeter functions to measure battery, sensor and circuit voltage
- Check continuity of wiring and resistance of ignition wires

Circuit Tester

じ Packing: 1

BPECT1 Order NO.: 903151



- Circuit tester for 6 and 12 volt systems.
- Quickly and safely tests high and low voltages on all vehicles including computerized engine.
- Can be used to detect power, ground and find shorts and breaks.
 High impedance to protect sensitive electronic sensors,
- microprocessors, electronic ignition components and air bags.
- LED indicates red for power (high) and green for ground (low).
- Insulated alligator clip.







- Unit also features Data Hold and Auto Power-Off
- Measuring Range:0-30 Amps/48 VDC-10 seconds
- Accuracy: ±2% of reading
- Resolution: 100 mA



- Straight jaw version of YA824C
- 9 3/4" long

Fuse Saver Kit

Packing: 1



- Dual type fuse box connector with 10' cord allows you to move around the vehicle shaking testing wires while looking for the short
- No wasted fuses
- Includes 3 resetting breaker handles: 10, 15 and 20 Amp
- Use when installing radios, CD players, radar detectors and other accessory equipment
- Includes YA8005-7, YA8005-10, YA8005-15 and YA8005-20 in YA8005-PB storage case
- YA8005-5 Fuse Handle and YA8005-EXT are optional accessories for the YA8005 Kit and are not included

Max Fuse Buddy[®]

EEFB315 Order NO.: 903046

YA8005

Order NO.: 903045

- MAXI circuit testing capability up to 80 Amps
- Also works with ATC and mini circuits-includes adapters
- Large LCD display with analog bar graph
- Unit features peak hold functions
- One touch zero function
- Amps: 0-80 Amps DC
- Resolution: 0.1A
- Accuracy: +2.0% of reading + 4 digits
- Power by: 9 volt Battery



Automatic Meter Packing: 1 MT454C Order NO.: 903043 Meter Manual Ranging Packing: 1

MT501C Order NO.: 903042 Meter Autoranging Packing: 1 MT574C Order NO.: 903002



- The MT454C is a durable, easy to use compact size digital multimeter
- Include:
- Compact size fits comfortably in the palm of your hand
- Easy-to-read 4000 count digital display
- Automatically selects the correct function of DC Volts, AC Volts or Ohms (Resistance)
- Use DC Voltage ranges to verify that the proper voltage level is arriving at a sensor or circuit
- Measure ohms to determine resistance of a coil
- Also test resistance of fuses, fusible links, components and circuits
- Measure AC voltage signals on digital MAF sensors, wheel speed sensors and vehicle speed sensors
- Protective boot with tilt stand, test leads, battery and instruction manual included
- Five year limited warranty



- Ergonomic, compact size fits comfortably in the palm of the hand
- Measure Ohms to determine resistance of a coil or spark plug wire
- Also test continuity of fuses, fusible links, components and circuits
- Use DC voltage ranges to verify proper voltage level is arriving at a sensor or circuit
- Large, easy-to-read, 2000 count LCD display
- Lock readings on display with data hold
- Measure AC voltage signals on digital MAF sensors plus wheel and vehicle speed sensors
- Added protection against drops and the elements with included rubber boot
- Safety cULus 3111 Listed. Meets CE and IEC 1010 safety standards
- 5 year limited warranty



- The MT574C offers both automatic and manual ranging
- Measure Ohms to determine resistance of a coil or spark plug wire
- Use the diode function to test the diode pack on a typical alternator
- Use DC voltage ranges to verify proper voltage level is arriving at a sensor or circuit
- Large, easy-to-read, 4000 count LCD display with low battery indication
- Lock readings on display with data hold
- Measure AC voltage signals on digital MAF sensors plus wheel and vehicle speed sensors
- Measure DC current to determine presence of a parasitic load
- Added protection against drops and the elements with included rubber boot
- Safety cULus 3111 Listed. Meets CE and IEC 1010 safety standards
- 5 year limited warranty

Specifications.	MT454C	MT501C	MT574C
Display Count	4,000	2,000	4,000
AC Volts	600	600	600
DC Volts	600	600	600
Basic DC Accuracy	0.50%	0.75%	0.30%
AC Amps	-	_	400mA
DC Amps	-	_	400mA
Resistance	40M Ohm	2K Ohm	40M Ohm
Auto Range	Yes	_	Yes
Data Hold	-	Yes	Yes
Min/Max	-	_	Yes
Auto Power Off	Yes	_	Yes
CE or UL Listed	CE, cULus 3111	CE, cULus 3111	CE, cULus 3111
CAT Rating	CATIII 600 Volt	CATIII 600 Volt	CATIII 600 Volt





TI T7

TLT8000

Order NO.: 903050

EELDGASCAP1

Order NO.: 903053

Order NO.: 903049

- Both shop and recreational uses
- Includes dust cover to help prevent corrosion
- 140

Ø


Mini Engine Electronic Stethoscope Packing: 1



- · Sensor clamp helps to detect noises during test drives that can not be duplicated in the work bay
- Sensor tip mounted on 6" flexible shaft allows access to hard-to-reach areas
- 5" inductive metal probe allows user to pinpoint source of noise or vibration
- Ultra sensitive microphone provides a full range of sound
- Rotary volume control allows easy adjustment
- Ear-bud style earphones provide excellent sound quality



RTEMPB3A Order NO.: 903055

YA6910

Order NO.: 903054



- Temperature range of -58° to 932°F (-20°C to 500°C)
- Use for most automotive and industrial applications requiring an infrared thermometer
- Compact size of 5.88" x 3.62" x 1.38" (149.2 x 92.1 x 34.9mm)
- Laser targeting accuracy
- Enhanced backlit 4 digit LCD for easy viewing
- Automatic power-off after 10 seconds
- Nylon holster for transport and safe storage
- · Safely monitor hot, hazardous, or hard to reach materials without contamination or damage to the surface
- Simply point at target, pull the trigger, and read the temperature on the large, backlit LCD display



- Battery operated
- Sensitivity thumb-wheel



- · Quickly detects electronic fuel injector functions on any gas or diesel engine
- Specifically designed to detect the vibrations emitted when the electronic injector fires
- No hunting for injector wires to test at the connector
- No need to remove the injector for testing
- Super bright LED strobe
- 7" removable probe tip
- Battery operation
- Sensitivity thumb wheel

Terminal Tool Kit Packing: 1

TT12KT Order NO · 903057



- Applications include most GM and other domestic computer connectors and terminals. Individual handles for easy assess in tight places. Designed for weather pack and pack-con terminals with flat blade to open connectors and fork for ALDL connectors to access trouble codes. Color coded: Red handle for GM and Green for wire terminal tools. Includes storage case
- Kit includes these GM C3 System Terminal Tools (red handle): Tube, Spring Loaded, 3.3mm x 28mm Square Blade, 1.4 x 19.00mm Flat Blade, 1.5 x 24.75mm Flat Blade, 2.0 x 23.00mm Fork Blade, 8.0 x 24.00mm Flat Blade Screwdriver, 3/16" x 1.00" • Kit includes these Wire Terminal Tools (green handle): Tube. 3.30 x 28.0mm
- Tube, 4.30 x 13.0mm Tube, 3.75 x 13.0mm Tube, 3.00 x 13.0mm
- Flat Twin Blade, 3.0mm
- Flat Twin Blade, 1.6mm





HCP3KT

Order NO.: 903005

Line Clamp Set Packing: 1



- HCP6A, HCP7A and HCP10A (6", 7", 10") in storage pouch **HCP6A Hose Pinching Pliers**
- For sealing hose sizes 1/8" to 5/16"
- Also use on brake lines, fuel lines and vacuum hoses
- 6" long
- **HCP7A Hose Pinching Pliers**
- For sealing hose sizes 1/2" to 3/4"
- Also use on heater hoses and vacuum lines • 7" long
- HCP10A Hose Pinching Pliers
- For sealing hose sizes 3/4" to 2 1/4"
- Also use on radiator hoses
- 10" lona

Portable Booster Pack

Packing: 1



- Starting current: 660AMP
- Peak current: 1200AMP
- 12V/22AH Sealed Lead-acid batteries
- With 12VDC 15A cigarette lighter socket
- Automatic circuit overload protection
- 100% Copper 4GA Heavy Duty Jump Cable

Master Plus Disconnect Set

Set; in addition the kit has:

The new blue 5/16"fuel line adapter

trucks and industrial applications

• The two most popular Jiffy-tite Disconnect tools

Packing: 1





• LDT14 contains all tools from the popular LDT8, Master Disconnect

• A set of 4 air line push-pull disconnect tools that work on heavy duty

Label inside cover of carrying case shows images and applications

Terminal Brush

Packing: 1

BTC3A Order NO.: 903063





- Stiff wire bristles thoroughly clean posts and clamps
- 3 3/8" long



Master Line Disconnect Set

Packing: 1

- A complete set of disconnect tools for spring lock and quick disconnect couplings used on air conditioning and fuel lines on Ford, GM and Chrysler vehicles
- Includes a set of six standard disconnect tools (5/16", 3/8", 1/2". 5/8", 3/4" and 7/8") and six color coded, angled disconnect tools for use in tight spots
- SPECIALIZED GM APPLICATIONS: Includes tools for use on GM 3/8" flex fuel capable fuel filter removal plus 5/16" and 3/8" GM fuel modules
- SPECIALIZED FORD APPLICATIONS: Includes tools for use on 3/8" and 1/2" Ford transmission and cooler lines with stepped line plus 5/16" x 3/8" scissor disconnect and Ford coupler disconnect tools

Battery System Tester

Packing: 1

YA2612B Order NO.: 903061

I DT8

Order NO.: 903059



- No conversion tables needed for CCA, SAE, IEC, EN, or Ah
- Battery condition is shown in % of capacity
- Uses conductance technology
- Tests 12V starting/charging systems
- Tests both flooded lead acid and AGM batteries
- Multi-colored bar graph displays battery condition
- Low voltage indicator LED lights when charging is necessary
- Bad cell is detected and displayed
- · Comfortable grip with easy to use clamps
- Tests discharged batteries Patented circuitry
 - Reverse polarity protection
 - Made in USA

Ø

EECS1AP

Order NO.: 903151



903069

903078

Shop & Technician Tools Automotive Specialty Tools

Battery Carrier

Packing: 1

Packing: 1



- For top post and side terminal batteries
- Rubber pads securely grip battery widths from 5" to 7"
- Plastic hand grip provides a firm hold



ACT1234PKT Order NO.: 903065

ACTR4131A

Order NO.: 903066

BL1B

Order NO.: 903064



 Includes various replacement lens, knobs, O-rings, gaskets and more

Kit components are used to service ACTR41511

Manifold Set

Packing: 1



- Anti-flutter gauges smooth out needle movement
- Easy grip all metal side mounted knobs
- Piston type free floating valves reduce O-ring wear
- Manual R134a couplers
- Gauges can be recalibrated to maintain accuracy
- 60" inner nylon layer hoses meet EPA, SAE, and UL standards
- Yellow hose includes shut off valve



- High intensity LED bulb with 100,000 hour service life
- Over four hours of peak performance per charge
- Power comparable to high intensity 75 watt lamps
- Compatible with all standard leak detection dyes
- Inspection range of up to 6'
- Three "AAA" batteries and fluorescence enhancing glasses are included

Replacement Hose (R12)



ACTB72

- 1/4 turn manual shutoff valves • Blue, 6' length
- ACTY72
- 1/4 turn manual shutoff valves
- Yellow, 6' length

Replacement Hose (R12)



903070
903079

ACTB72A

 Automatic shutoff valves • Blue, 6' length

ACTY72A

- Automatic shutoff valves
- Yellow, 6' length



Replacement Hose (R134a)



- Low permeation hoses for internal equipment connections ACTRB72
- Blue, 6' length
- ACTRR72
- Red, 6' length

ACTRY72

Yellow, 6' length

Replacement Hose (R134a)



- · Low permeation hoses for internal equipment connections
- ACTRB96
- Blue, 8' length

ACTRR96

• Red, 8' length

ACTRY96

Yellow, 8' length

Manual A/C Hose Crimper

📦 Packing: 1



- Unit is easily mounted to bench with holding fixture or held securely in a vise
- Includes a complete set of dies covering standard #6, #8, #10 and #12 hose sizes
- Includes storage case

ACTMAN2100 Order NO.: 903071



- Measures liquid, air and surface temperatures via sturdy stainless steel probe
- Digital display for easy viewing
- Angle viewing head can be lifted and rotated 180° for a different viewing angle
- Convertible from Fahrenheit (F) to Centigrade (C) temperature ranges
- The -58° F to 300° F (-50° C to 150° C) temperature range enables use on a wide range of applications
- Tactile on/off button for easy operator use (auto off function extends battery life)
- Tactile data hold button holds the reading when the display cannot be seen
- Temperature range noted on bevel
- · Plastic carrying sheath protects the user when carried in shirt pocket

Fin Straightener & Cleaner Packing: 1

ACT407 Order NO.: 903083



Multi-head tool handles 8, 9, 10, 12, 14, and 15 fins per inch 4 1/4" long

T











- Has an aluminum body and holds up to 2 oz. of oil
- Uses pressure differential of the high and low side of A/C system

Quick Connect Set

ACT119 Order NO.: 903092

ACT111B

Order NO.: 903090



- Simplifies connecting to core valve service fittings
- Includes both a straight coupler and a 90° coupler that accept either of two adaptors (one for low side, one for high side)
- Manual shut-off valves

Gas/Diesel Combustion Leak Tester

📦 Packing: 1

GDCT16 Order NO.: 903095



- Provides an easy and quick way to diagnose engine overheating problems
- Checks for leaks between the combustion chamber and the cooling system
- Test head and gasket for combustion leaks before removing the radiator
- Double chamber in testing unit provides a high level of accuracy
- For use on water cooled gas and diesel engines
- Kit includes complete test chamber, 16 oz. bottle of testing fluid and instructions



Universal Valve Core Service Tool

- Also useful on A/C spring couplings as well as push lock connectors on radiator and transmission lines
- Includes six tools for disconnecting spring couplings on Ford, GM, and Chrysler A/C lines
- Works on fuel lines and can be used as push lock connectors on radiator and transmission lines
- Included sizes are 5/16", 3/8", 1/2", 5/8", 3/4" and 7/8"

Cooling System Adaptor Set

📦 Packing: 1

SVTAB1400 Order NO.: 903096

ACT1290A



- TAB Series Adaptors feature a composite metal/plastic construction for a lower cost option
- Set includes 14 radiator composite metal/plastic radiator adaptors
- Includes all TAB Series Adaptors plus TA4503 Adaptor
- PBSVTA1417 Storage Case has a removable cover for display purposes

Ø





- Fluid drain tube allows coolant to be returned to reservoir or safely collected for recycling
- Bladders are cycle tested to over 1,500 inflations

Read safety precautions on page 162

Stainless Steel Braided Hose

WARNING

• 6-160 PSI, 60-1100kPa





Ø



1/2" Torque Stick Set, 6 pcs Packing: 1





YA3000C Order NO.: 903110



- Set contains sticks to compliment the BTQS1000 set to cover any applications you may still have
- Size ranges from 17 to 22mm
- Torque range from 55 to 113 ft. lbs
- 1/2" drive
- Includes BTQS12AA, BTQS12F, BTQS12G, BTQS12H, BTQS12K and BTQS12MM (6 pcs) in BTQSCASE storage case

1/2" Torque Stick Set, 10 pcs Packing: 1 BTQS1000 Order NO.: 903107



- Master set covers the majority of domestic and foreign cars and light trucks
- Size ranges from 19 to 24mm
- Torque range from 80 to 160 ft. lbs
- 1/2" drive
- Includes BTQS12A, BTQS12B, BTQS12BB, BTQS12C, BTQS12E, BTQS12EE, BTQS12I, BTQS12T, BTQS12XX and BTQS12Y (10 pcs) in BTQSCASE storage case

Wheel Lock Kit Packing: 1 LSR1000A Order NO.: 903108



- Wheel Lock Removal Socket Set
- Easily removes most lug nuts and wheel locks on most domestic and import passenger vehicles and light trucks
- Use with hand driver or impact wrench
- Some sockets cover specific GM, Ford and Chrysler applications
- Set includes 11 sockets, extension and extractor punch in storage case



- Designed to remove tie rods lacking a full hex on the socket end
- Removable crowfoot adaptors are placed on hex of tie rod
- Tool then engages crowfoot for removal or installation of tie rod
- Includes crowfoot adaptors in 1 3/16", 1 1/4",
- 1 5/16", 1 7/16", 1 1/2" and 33.6mm sizes

Inner Tie Rod Tool

YA3100 Order NO.: 903111



- Use on inner tie rods with inaccessible wrench flats found on many trucks and SUV's
- Large inner tie rod tool includes 4 crowsfoot wrenches: 1 7/16", 33.6mm, 38.4mm and 42mm
- The long socket slips over the tie rod end and the crowsfoot engages on socket for easy removal and installation
- Applications include many Toyota, Nissan, Ford, Lincoln Mercury and Chevrolet truck and SUV's
- Also fits some Cadillac Escalade, Hummer H2, Honda Passport and Jeep Liberty

Inner Tire Rod Tool

YA3500 Order NO.: 903109



- e e e
- Removes inner tie rods equipped with completely round end sockets or flats
- Designed to remove and install all inner tie rod sockets up to 1 31/64"
- Wrench head has 3 set screws that tighten against the socket
- Includes 1/4" short head hex wrench



Master MacPherson Strut Tool Packing: 1

MSC1 Order NO.: 903007



- Designed to quickly and easily compress most MacPherson strut springs
- Compresses up to 5/8" (.625mm) coil diameter
- Broad spring contact for stable compression
- Acme threaded rod and built in detent latches to help lock coil in place
- Forged construction for strength and durability

Coil Spring Compressor Packing: 1

MSC2 Order NO.: 903112



- Removes and installs coil springs guickly and safely
- · Compresses coil springs on all passenger cars and pick up trucks
- Features Acme threaded rod

Cam Lock Tool Set

Packing: 1

ML6000COMBO Order NO.: 903118



- Includes (4) CC100 Single Cam Clamps and (1) ML6000 Dual Cam Clamp in storage tray
- Single cam clamp can be used on engines where the dual clamp will not fit
- Compact design permits easy operation in confined engine areas
- Simple and easy to use
- Manufactured from high strength industrial polymers which will not corrode or damage engine pulleys
- Dual cam clamp prevent engine damage resulting from incorrect timina
- Maintain valve timing during belt replacement on twin and guad cam engines
- Compact design allows access in transverse engines
- Fits timing gear diameters from approximately 4" (101mm) to 6" (152mm)
- Fits gear spacing from approximately 0.06" (1.6mm) to 3" (76mm)



- · Easily remove engine oil, gear and transmission oil, coolant and brake fluids
- Unit creates vacuum or pressure providing a clean, fast and simple way to evacuate or dispense a wide range of fluids
- Automatic shut off prevents the overflow of the reservoir tank with shut off at 8 liters
- 2.3 gallon (8.8 liter) total capacity

Manual Fluid Dispenser

Packing: 1

- Durable polyethylene construction is impervious to automotive and house hold chemicals
- No electrical or compressed air required
- Sturdy base with exterior pump helps prevent evacuator from tipping
- Complete system includes manual fluid evacuator, main hose assembly (5/16" ID x 54" long) plus two rigid dipstick tubes for engine oil removal (3/16" ID x 34" and 1/8" ID x 34")



A91F Order NO.: 903114

VAC201

Order NO.: 903113

- Use on large diameter oil filters 1 to 6"
- Includes both 3/8" and 1/2" square drives

Oil Filter Pliers, Adjustable

YA4274 Order NO · 903008



- Use on filters from 2 1/2" to 5 1/4" diameters
- Use on automotive and truck applications
- · Spring action size adjustment assures a solid grip on filter
- Offset handle offers increased accessibility
- Heavy duty forged levers
- Cushioned grips for comfort
- Industrial black finish with blue grips
- Overall length of 13 1/2"

Ø



FWK7A

Shop & Technician Tools Automotive Specialty Tools



Funnel 🎁 Packing: 1

FUNN15 Order NO.: 903116



- High visibility red funnel for large neck fillers
- Both ends of the funnel have screw on caps to contain fluids if needed
- 1.5 qt. capacity



- Wrenches in set cover 95% of domestic and import automobile and light truck oil filters
- Storage/carrying case keeps wrenches together for quick access and contains any oil residue keeping it out of your tool storage unit
- Includes laminated application chart
- FWK7A set includes FW656714A. FW757715A. FW7614A. FW7630A, FW8015, FW9315A and FWA62121A oil filter wrenches



- Standard series grease guns
- All are steel with zinc plating
- Inner-spring chamber can be either cartridge or bulk loaded

Grease Gun, Lever

YA728A Order NO.: 903022



- Lever operated, large capacity gun accepts 16 oz. bulk or 14 1/4 oz. cartridge grease
- Develops 6,000 PSI
- Includes tough, 18" flexible whip hose with coupler and 6" rigid extension









- Operates on 90 PSI to 150 PSI, but develops up to 3 times output pressure
- Tool measures 1" x 8"



CF811B Order NO · 903122



- For "L" head, valve-in-head, high compression engines and vehicles with overhead valves
- Activating mechanism prevents cocking of valve spring as it is

C-Clamp Compressor

CF19B Order NO.: 903123

BB500

Order NO.: 903028



• This compact model includes CF19-3A Jaws for 1/4" to 1 1/16" diameter springs on small, air cooled engines and CF19A5 Jaws for both 17mm and 20.8mm diameter springs on Honda engines

• Kit includes BB5001 Vacuum Brake Bleeder and BB5002 Auto Refiller

BB5001 Vacuum Brake Bleeder:

- Large 3-pint (1.5 liter) container
- Generates 25 in Hg vacuum with air pressure of 100 psi
- On/OFF valve and flow regulator
- Quick release locking trigger, safety shut off valve and overfill check
- Compact design fits under wheel well
- 19.5" (500mm) suction hose
- Universal brake screw fitting

BB5002 Auto Refiller Bottle:

- 20 fluid oz (592 ml) container
- Automatically keeps the reservoir filled to the correct level
- Retaining clip for positive attachment
- Compact design fits under hood
- Positive venting system supplies continuous flow
- Unit can be sealed when not in use to prevent spillage





Air Adjusting Valve, with Gauge Packing: 1



- Designed for use with HVLP spray guns
- Includes 160 PSI pressure gauge
- Air Inlet: 1/4" M.P.T
- Air Outlet: 1/4" F.P.T. (swivel nut)

Seal Pliers



- Removes valve stem seals from overhead camshaft engines including 4 valve per cylinder engines that have restricted access to the valve stem seal due to the head design
- Gripping serrations in the pliers tip easily grab both OEM and aftermarket seals with ease
- Easy grip handles

Ring Compressor Set

RC980 Order NO.: 903124



- Works both horizontally and vertically with pliers grip handle
- Has a fine tooth ratcheting mechanism
- Includes 6 hardened steel bands:
 2 7/8" to 3 1/8", 3 1/8" to 3 3/8", 3 3/8" to 3 5/8", 3 5/8" to 3 7/8", 3 7/8" to 4 1/8", and 4 1/8" to 4 3/8"
- Bearing Race and Seal Driver Set

A1310A Order NO.: 903125



📦 Packing: 1

- Collars fit most standard wheel bearing sizes
- The three largest sizes fit most late model 4 wheel drive vehicles

Ring Compressors

BF555

YA8230

Order NO.: 903145



Stock No.	Band	Capacity (inches)	Deep (inches)		Order N
RC40C	2	2 ^{1/8} to 5	3 1/2	1	90302
RC50C	2	3 ¹ / ₂ to 7	3 1/2	1	90302

- Clutch control holds tension band in position as piston is inserted into cylinder
- 1/2" wide spring bands equalize tension over belt width so ring assembly may be compressed into groove until flush with piston
- "V" beads on lower edge of belt keep tool from entering cylinder
- RC40C can be used upside down for Chevrolet, Mercury, and Ford trucks with angled blocks

Rotor Micrometer

🎁 Packing: 1

RM130 Order NO.: 903030



- Range of .30" to 1.3" in .0001" graduations
- 3.5" deep frame
- Pointed anvil for checking grooves
- Includes 1" checking standard and storage case

Oval Tube Creeper Packing: 1

JCW8A Order NO.: 903126



- 40" long creeper is constructed of 16 ga. steel and has a unique drop in the shoulder area to provide for generous shoulder clearance; low ¾" ground clearance
- Fully padded with heavy duty foam for durability; pad measures 1 3/4" thick, headrest pad measures 2 3/4" thick covered with heavy duty vinyl
- Four 2 1/2" oil resistant, full ball bearing casters
- Weight is 18 lbs



BTCP1

Shop & Technician Tools Automotive Specialty Tools



- Sets structural rivets, KLIK-FAST® rivets from 5/32" to 1/4" diameter in all alloys plus KLIK-SPLIT® / Monobolt rivets from 3/16" to 1/4"
- Includes 5/32", 3/16" and 1/4" nosepieces plus mandrel collection bottle

Brake Caliper Kit, 7pcs 📦 Packing: 1

YA8610B Order NO.: 903033



- Assists in replacement of brake pads on most 4-wheel disc brake cars
- Tool and adaptors position brake piston back into caliper to allow clearance for newer, thicker brake pads
- Designed for most Audi, Chrysler Corporation, Ford, GM, Honda, Jaguar, Mazda, Mini Cooper, Mitsubishi, Nissan, Saturn, Subaru, Toyota, Volkswagen and Volvo
- Set includes one tool and seven adaptors in a storage case



- Works on both fixed and floating calipers
- · Generates more than 1600 ft. lbs. of force to retract the toughest caliper pistons
- Single lever mechanism used to apply and release force for ease of operation and faster service
- Prevents damage to pistons, hubs or calipers
- Ensures parallel piston retraction on dual and quad piston calipers
- Easy left and right side use

Throttle Depressor

📔 Packing: 1

B240B Order NO.: 903131



- Holds throttle at a constant RPM
- · Easily adjusts to desired length
- Adjustment screw fine tunes desired RPM
- Rubber tip keeps the tool firmly positioned on the accelerator pedal
- Overall length of 40" (102cm)
- Can also be used as a pedal depressor

Brake Gauge Set

💗 Packing: 1

BTG8 Order NO.: 903130



- · Color coded gauges provide instant feedback on brake pad/shoe condition
- Constructed from 20 gauge sheet metal with durable powder coat finish
- Pad/shoe condition is indicated with color by the respective testing gauge
- Red indicates service required, yellow indicates caution and green indicates an OK situation
- Set includes 8 different testing blades of various colors and thickness Red 2mm (0.0787")

Red 3mm (0.1181") Yellow 4mm (0.1575") Yellow 5mm (0.1969") Yellow 6mm (0.2362") Green 8mm (0.3150") Green 10mm (0.3937") Green 12mm (0.4724")







- Designed for the automotive refinishing painter, Blue-Point[®] spray guns are lightweight and feature great balance while delivering a quality, first class automotive finish
- A new generation of Blue-Point® spray guns for primer, base and clear coat
- Lowest trigger pull among guns in their class
- Unmatched spray pattern size and quality repair kits
- Optional interchangeable 125cc, 250cc and 600cc aluminum cups are available
- Optional 3M PPS adaptor is also available



- Lightweight and comfortable for all kinds of painting jobs
- Provides superior spray performance
- Stainless steel needle and tip

Windshield Removal Tool

YA109C Order NO.: 903137



- Steel cable pull handle
- Replaceable steel cutting blades can be resharpened
- For GM, Chrysler, and other cars with windshields set in place with sealant

Brake Service Tools

YA4000B Order NO.: 903146



- Produces vacuum or pressure at the turn of a switch
- Comfortable ergonomic design
- One finger trigger vacuum/pressure release
- Durable, accurate diaphragm type pressure/vacuum gauge
- Handheld vacuum/pressure pump with 2" compound gauge and rubber boot
- 12 oz. fluid reservoir bottle with fluid transfer and storage lids plus fluid pick up tube
- 6 tapered adaptors for connecting to tubing from .09" to .50" ID
- 2 tapered manifold plugs
- 2 universal bleed screw adaptors
- 12 vacuum cap plugs, vacuum line T-adaptor
- (2) 1/4" ID x 24" long connection tubes with quick-change connector
- 5/32" ID x 1/4" ID tubing adaptor
- 5/32" ID x 3" long vacuum test tube
- Rubber cupped adaptor
- Master cylinder refill kit
 - Applications:
- Vacuum and pressure related engine performance diagnostics and tune-ups
- Brake bleeding
- Fluid transfer, evacuation and sampling



Door Lockout Set

🂗 Packing: 1



- No danger of airbag activation or disconnected door linkages
- Actuate the door handle, manual lock button or electric lock button on most cars and trucks
- Includes:
- 4 pc door-unlocking tool that screws together without couplers for easy assembly and storage, plastic slim jim, 2 glow-in-the-dark tips, 2 plastic wedges to create gap between door and frame without damaging door or weather stripping and BF272 inflatable wedge
- Use the BF272 to easily separate door from body without damage to the vehicle
- Unlocking tool features a middle extension piece to reach across the car in extended use applications
- For sale to registered locksmiths, police and bona fide repair professionals only

Thread Setter Kits

LOS145A

Order NO.: 903136



Stock No.	Ĩ	Order No.
HP650	1	903134
HP650M	1	903135

HP650

- Includes: rugged thread setter tool and an assortment of fractional Klik Poly-Nuts: 12 each 8-32, 10-24, 10-32; (8) 1/4"-20 and (6) 5/16"-18 threads
- Includes required nosepieces and mandrels for setting the above sizes
- Packaged in a storage case

HP650M

- Metric version of the HP650 with metric poly-nuts, including 25 each 4 and 5mm, (15) 6mm and (10) 8mm threads
- Includes thread setter tool, required nosepieces and mandrels packaged in a storage case

High Volume Hose Connectors



Stock No.	Description	Size	i	Order No.
AHCC90C	Quick Coupler High volume ¹ /4" female quick coupler	1 /4"	1	903147
AHCC91C	Quick Coupler High volume ¹ /4" male quick coupler	1 /4"	1	903148
AHCCP90C	Nipple (¹ / ₄ " Female) Quick connect ¹ / ₄ " female nipple	1 /4"	1	903149
AHCCP97C	Impact Wrench Adaptor	1 /2"	1	903150

AHCC90C AHCC91B AHCCP90C

• Designed to deliver high volumes or air to spray guns and air tools

AHCCP97C

• Use with AHCC98C high flow coupler to improve low pressure performance of 1 /2" drive impact wrenches and other high air comsumption tools



Shop Equipment

Bringing on bigger sized gear, we have some heavier equipment further catering to automotive specialized needs. All equipment conform to Blue-Point's quality commitment, and complement the rest of our quality tools to be the number one choice in automotive tools.







Shop Equipment Shop Equipment



Low Profile

- Dual hydraulic cylinders
- Soft rollers for smoother & silent operation



- Fast acting pump reaches lifting height in less than a pump to allow user to reach a variety of service height situations quickly
- One piece handle for professional users features a foam pad to limit damage to vehicles
- Universal joint release mechanism for smooth action
- Rolled side frames with generous flanges to resist flexing
- Low profile design allows for easy access under vehicles
- Floor Jack used to lift cars and light trucks
- Meets ANSI-PALD standards

Motorcycle Floor Jack

Packing: 1

YA1715 Order NO.: 904009



- 1,500 pound capacity
- Low height of 4 1/2", maximum height of 14 3/4"
- Wide base for extra stability
- Double rubber lined pad provides extra protection to motorcycle while on the jack
- Pull handle assists user to maneuver jack into position
- One foot operation for ease of use
- Safety straps to secure motorcycle to jack
- Self locking safety feature and overload safety valve

12 Ton Jack Star	nds		Or	YA512 der NO.: 904006
	Stock No.	Capacity (tons)	Low Height (inches)	Maximum Height (inches)
	YA512	12 (per pair)	17 ^{1/2}	27 ¹ / ₂

- Counter-weighted pawl serves as a secure locking device to prevent the load from accidentally disengaging
- Sturdy, welded steel construction for superior strength
- One piece, multi-position ductile ratchet bar provides super strength and durability and quick adjustment mechanism that securely locks into desired location



Stock No.	Capacity (tons)	Max. Height	Min. Height	C00
YA874BP	3 (each piece)	430mm	290mm	China



YA714D Order NO.: 904007



	3		
Capacity (tons)	Maximum Height (inches)	Saddle Base (inches)	Lifting Head Size (inches)
1/2	69 ^{7/8}	8 ^{7/8} x 7 ^{1/8}	15 ^{1/2} x 15 ^{1/2}
Handle Length (inches)	Chassis Length (inches)	Chassis Width (inches)	
11	—	33 ¹ / ₂	12°
Minimum Height (inches)	Exp.Saddle Area (inches)	Jack Size (inches)	Net Weight, lbs. (kg)
33	21 x 21	34 ^{1/} 8 (L) x 36 ^{1/} 8 (W)	181 (82.1)

- Crank for precise and easy alignment
- Four adjustment load support arms fit most transmission pan flanges
- Adjustable to 0.030 inches or less
- Foot pedal pump permits hands free operation
- · Wide base and four casters for stability



BPWORKBENCH Order NO.: 904001

Shop Equipment Shop Equipment

Engine Crar	ne -	-FT -			YA12AP O.: 904011	Heavy Duty Workbench	BPWORKE Order NO
Capacity 2 Ton Certificate 2005 ASME/ PALD Bottle Jacks	Min. Heigl 340 mm Net Weigh 109 kg	1,7 it Gross	4 kg #	Dimen 1,830 x 760 x Packagi 1 – 810 x 570 x 2 – 1,695 x 195 3 – 1,295 x 315	: 1,550 mm ng 90 mm x 85 mm	 Features a full bottom shelf and superior Dimensions-60.08" x 30.73" x 34.08" Net Weight-138.9 lbs. (63.06 kg) Weight Capacity-1,200 lbs. Top panel: 2.0mm thickness Bottom shelf: 2.0mm thickness Steel support: 2.5mm thickness 	powder coat finish
Packing: 1		n Height Max Height nches) (inches)	t Adjust Heigl (inches)	nt Base (inches)	Handle (inches)		
YB2AP		6 ^{3/4} 14 ^{5/8}	4 ² /5	4 x 4 ¹ /10	16 ¹ / ₂		
YB3AP		6 ³ / ₄ 14 ⁵ / ₈	4 ² / ₅	$4 \times 4^{1/10}$	16 ¹ / ₂	Welder & Plasma Cutter Cart	MIGO
YB5AP		8 ^{1/3} 18 ^{2/5}	5 ^{3/} 4	4 ¹ / ₃ x 4 ² / ₅	16 ^{1/2}	Packing: 1	Order NO
Stock No.	Cap Dia (inches)	Operating Force (lbs)	° 🥡	Orde No.			
YB2AP	1 ¹ / ₁₀	45	1	9040 [.]	15		
YB3AP	1 ¹ /10	78.75	1	9040	16		
YB5AP Improved De 	1 ^{1/4} esign with V	90 Velded Joints t	1 o Prevent S	^{9040 Seal Leaka}			L.
8 Ton Bottle	Jack	Å			YA1228 O.: 904005		
			-			Overall Dimensions	Shipping Weight (lbs.)
						41" L x 19 ¹ / ₂ " W x 25" H	43
			-1			• Wolder and plasma cuttor cart features to	we trave along with S
						 Welder and plasma cutter cart features tw 12.75" (W) top tray to hold MIG welders a 	and plasma cutters
0				0		 Includes cylinder bracket with adjustable 	chain to hold multipl
Capacity (tons)	Low Hei (inches		num Height nches)	Screw Exte (inche		diameter gas bottles	
8	8 ¹ / ₈		17 ⁵ /8	2 ³ /4		Handle has storage tray for smaller items	i
Base Size	Handle Le	ngth <u>Cap</u>	Diameter	Operating	Force _		

- 1 ³/8 4 ³/₄ x 4 ³/₄ 18^{1/8} (assembled) 101
- Hydraulic system is protected from internal damage by a patented by-pass mechanism
- Machined and polished cylinders with die-cut threading provide non-abrasive leak-free, durable performance
- Fabricated from hard-cast steel

ler & Plasma Cutter Cart cking: 1

MIGCARTA Order NO.: 904002



- der and plasma cutter cart features two trays along with 20" (L) x 75" (W) top tray to hold MIG welders and plasma cutters
- udes cylinder bracket with adjustable chain to hold multiple neter gas bottles
- dle has storage tray for smaller items







Important Words About Safety for Users and Bystanders Following these basic safety rules is a good start toward protecting yourself and others in the vicinity from injury while using tools

- Wear safety goggles
- Use the right tool
- · Use the tool properly
- · Maintain the tool regularly
- · Keep tools away from children
- Do not use tools on live electrical circuits unless specifically designed for such use
- Read and follow instructions



Safety messages in this catalog use the guidelines of the American National Standard ANSI Z535. 4 for Product Safety Signs and Labels and ANSI Z535.3 Criteria for Safety Symbols. Messages associated with specific products use a triangular hazard alert symbol, signal word (CAUTION, WARNING, DANGER) and how to avoid the hazard.

PLEASE READ AND FOLLOW these messages to avoid injury to yourself and bystanders.



During the applicable duration of the warranty, at its option, Snap-on will repair or replace its products which fail to give satisfactory service due to defective workmanship or materials, or provide a refund by repaying or crediting customer with an amount equal to the purchase price of such products. Repair, replacement or refund shall be at the election and expense of Snap-on, and is customer's exclusive remedy in place of all other rights and remedies. Any products or parts replaced or for which Snap-on has provided a refund are the property of Snap-on and will not be returned.

THE FOREGOING WARRANTY IS IN LIEU OF AND EXCLUDES ALL OTHER WARRANTIES NOT EXPRESSLY SET FORTH HEREIN, WHETHER EXPRESS, IMPLIED OR COLLATERAL, BY OPERATION OF LAW OR OTHERWISE, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Descriptions of product contained in this catalog are for the sole purpose of identifying product and shall not be construed as an express warranty.

LIMITATION OF LIABILITY. SNAP-ON AND ITS AFFILIATED COMPANIES AND THIRD PARTY SUPPLIERS SHALL NOT BE LIABLE FOR ANY INCIDENTAL, SPECIAL OR CONSEQUENTIAL LOSSES, COSTS OR DAMAGES INCURRED BY CUSTOMER OR OTHERS, INCLUDING PERSONAL INJURY OR DEATH, DIRECTLY OR INDIRECTLY ARISING FROM THE SALE, HANDLING OR USE OF THE PRODUCTS, OR FROM ANY OTHER CAUSE WITH RESPECT TO THE PRODUCTS OR THE FOREGOING WARRANTY, WHETHER SUCH CLAIM IS BASED UPON BREACH OF CONTRACT, BREACH OF WARRANTY, STRICT LIABILITY IN TORT, NEGLIGENCE OR ANY OTHER LEGAL THEORY (INCLUDING WITHOUT LIMITATION, LOST PROFITS, REVENUES, ANTICIPATED SALES, BUSINESS OPPORTUNITIES, GOODWILL, OR INTERRUPTION OF BUSINESS OR OTHER INJURY OR DAMAGE).

Snap-on® and Blue-Point® are registered trademarks of Snap-on Incorporated

SNAP-ON ASIA PACIFIC OFFICES

Asia / Pacific Division

25 Tagore Lane, #01-02 Singapore 787602 Tel: +(65) 6459-2712 Fax: +(65) 6459-1520

Snap-on Trading (Shanghai) Co., Ltd. Fax: +(852) 2370-3400

Unit 2001-2005, Cross Tower 318 Fuzhou Road, Shanghai 200001 P.R.China Tel: +(86-21) 6391-2388 Fax: +(86-21) 6391-2382

Snap-on Trading (Shanghai) Co., Ltd. Beijing Branch

517B, Grand Pacific Building 8A Guanghua Road Beijing 100026 P.R.China Tel: +(86-10) 6581-8838 Fax: +(86-10) 6581-6681

Snap-on Tools India Private Ltd.

6/2, Begumpur Khatola, 39 Milestone, NH-8, Gurgaon, Haryana-122004, India Tel: +(91-124) 459-9700 Fax: +(91-124) 405-6866

Snap-on Tools Japan, K.K.

2-1-6 Shinkiba, Koto-ku, Tokyo, 136-0082 Japan Tel: +(81-3) 5534-1285 Fax: +(81-3) 5534-1284

Snap-on Tools Hong Kong Ltd.

Unit 2010, 20/F, Laford Centre, 838 Lai Chi Kok Road, Cheung Sha Wan, Kowloon Hong Kong Tel: +(852) 2370-3700 Fax: +(852) 2370-3400

Snap-on Tools Korea Ltd.

#505, Building 301, Bucheon Techno Park Block 3 365 SamJung-Dong, OhJung-Gu, Bucheon City GyeongGi-Do 421-809, Korea Tel: +(82-32) 326-7310 Fax: +(82-32) 326-7312

Snap-on Tools Singapore Pte. Ltd.

25 Tagore Lane, #01-01 Singapore 787602 Tel: +(65) 6451-5570 Fax: +(65) 6451-5574

Snap-on Tools Singapore Pte. Ltd. Indonesia Representative Office

Graha Pratama Building, 20th Floor Jl. M. T. Haryono Kav.15, Jakarta 12810, Indonesia Tel: +(62-21) 8370-9611 Fax: +(62-21) 8370-9612

Snap-on Tools Singapore Pte. Ltd. Malaysia Branch

Blue-Print

B-6-10, Street Mall, One South Jalan OS, Taman Serdang Perdana 43300 Seri Kembangan, Selangor Malaysia Tel: +(603) 8957-1938 Fax: +(603) 8957-2938

Snap-on Tools Singapore Pte. Ltd. Philippines Branch

4/F, 2053 Building, Edison Street San Isidro, Makati City Philippines 1234 Tel: +(63-2) 843-7935 Fax: +(63-2) 843-7730

Snap-on Tools Singapore Pte. Ltd. Taiwan Branch

3F-4, #9 Wuquan 1st Road, New Taipei Industrial Park, Xinzhuang District 24892, New Taipei City, Taiwan ROC Tel: +(886-2) 2298-9789 Fax: +(886-2) 2298-2288

Snap-on (Thailand) Company Ltd.

5th Floor, Talomsin Building, 924 Rama 3 Road Bangpongpang Yannawa, Bangkok 10120, Thailand Tel: +(66) 2294-9660 Fax: +(66) 2294-9665



Sub-Category

1/2" Sockets, Ratchets & Accessories	
1/4" Sockets, Ratchets & Accessories	22-26
3/4" Sockets, Ratchets & Accessories	
3/8" Sockets, Ratchets & Accessories	27-32
Adjustable Click-Type Torque Wrenches	
Adjustable Wrenches	42-43
Air Tools	
Automotive Specialty Tools	136-157
Automotive Tool Sets	14-16
Bits	53
Combination Wrenches	43
Cordless Tools	
Cutting Tools	111-115
Digital Torque Testers	
Double Open End Wrenches	43
Electronic Type Torque Wrenches	
Flashlights	122-124
General Service Sets	10-14
Hammers	108-110
Impact Sockets	
L and T shape Wrenches	47
Locking Pliers	68-69
Measuring Tools	118-121
Miscellaneous	126-129
Modular Tool Sets	17-19
Offset Box Wrenches	
Other Wrenches	
Plier Sets	56-58
Power Tools Accessories	
Preset Click-Type Torque Wrenches	
Punches & Chisels	110
Ratcheting Wrenches	
Retaining Ring Pliers	
Roll Cab Accessories	
Roll Cabinets	
Roll Carts	
Safety Tools	
Screwdrivers	
Shop Equipment	
Special Pliers	
Special Tools	
Standard Pliers	
Testing and Electronics	
Tool Boxes	
VDE Pliers	
Wrench Sets	
	40-42

INDEX

<u></u>	
1412A	134
1470K-AC1	7
1470K-AC2	7
1470K-AC4	7
1470K-ACSIDE	7
1658C	134
2420A	134
2430C	134
2438C	134
2842C	134

Α

1 0

	150
	154
	102
	102
AC2Z80T27MP	102
	102
AC17D	103
	103
	103
	103
	103
	103
	103
	103
	103
AC31120FWMP	103
ACT73A	144
ACT83A	144
	145
	146
	145
	146
	144
	145
	145
	145
ACT1046C	145
ACT1234PKT	143
ACT1290A	146
ACT1370	146
ACT81290	145
	143
	143
	144
	143
	144
	144
	144
ACTRR96	144
ACTRY72	144
ACTRY96	144
	143
ACTY72A	143
	147
	105
	105
	105
	104
	105
	105
	105
AHC22MD	105
AHC23D	105
	105



AHC23MD 105
AHC23PMD
AHC24D
AHC24PD
AHC25D
AHC25FD 105
AHC25MD 105
AHC26D 105
AHC26FD
AHC26MD
AHC27D
AHC28D
AHC28FD 105
AHC28MD 105
AHCC90C 157
AHCC91C 157
AHCCP90C
AHCCP97C
AIRHOSE35
AT105
AT109 85
AT109DGK 85
AT115 84
AT118
AT119
AT123B
AT153
AT154
AT157R
AT180C 89
AT184
AT185
AT192A
AT194A
AT200D
AT203A 82
AT204 83
AT215
AT235MCA
AT321
AT370
AT380A
AT401MCA 91
AT401MCKA 92
AT402MCA
AT402MCKA
AT403MCKA
AT408
AT411A
AT415B 86
AT415CWMP 102
AT415T27MP 102
AT425R
AT435A
AT475A
AT555B
AT570 79
AT670
AT700F
AT702
AT705B
AT738
AT801MCA 84
AT811 84

AT1070A	86
AT1070RA	86
AT1300A	78
AT2050	84
AT3000	83
AT5000	83
ATC500	78
AV1000A 12	28

B45CMPAP 56
B48CPAP
B58HLPAP
B65CMPAP
B75CMPAP
B85CMPAP
B87CPAP
B95CLMPAP 56
B95CMPAP 56
B96CPAP 56
B240B 155
B945CMPAP 56
B960CMPAP 56
BADJC6 43
BADJC6AP 43
BADJC8 43
BADJC8AP 43
BADJC10
BADJC10AP
BADJC703 40
BAWP100AP
BB500 153
BBWDM67
BBWDM89 44
BBWDM810 44
BBWDM1011 44
BBWDM1012 44
BBWDM1113 44
BBWDM1213 44
BBWDM1214 44
BBWDM1415 44
BBWDM1417 44
BBWDM1617 44
BBWDM1719
BBWDM1819
BBWDM1917
BBWDM1921
BBWDM2022
BBWDM2123
BBWDM2224 44
BBWDM2326 44
BBWDM2426 44
BBWDM2427 44
BBWDM2430 44
BBWDM2528 44
BBWDM2730 44
BBWDM3032 44
BBWDM3436A 44
BBWSM67 44
BBWSM89 44
BBWSM810
BBWSM911
BBWSM1011
BBWSM1011
BBWSM1012
BBWSM1213
BBWSM1214
BBWSM1314
BBWSM1415 44
BBWSM1417 44
BBWSM1516 44

BBWSM1617 44	Ļ
BBWSM1719	Ļ
BBWSM1819	
BBWSM1921	-
BBWSM1922	-
BBWSM2022	-
BBWSM2022	-
BBWSM2122	
	-
	-
BBWSM2326	-
BBWSM2426 44	-
BBWSM2427 44	
BBWSM2528 44	-
BBWSM2730 44	ł
BBWSM2732 44	ł
BBWSM3032 44	ł
BBWSM3436 44	ł
BC4SG 110)
BCB6HD 61	
BCB7HD 61	
BCB9HD 61	
BCC6HD 61	
BCC8HD 61	
BCC10HD 61	
BCEH5 65	
BCEH6 65	
BCER5	
BCER6	
BCER7 60	
BCER9 60	
BCES5 65	5
BCES6 65	5
BCES7 60)
BCES9 60)
BCIH5 65	5
BCIH6 65	5
BCIR5	5
BCIR6	;
BCIR7 60)
BCIR9)
BCIS5	
BCIS6	
BCIS7	
BCIS9 60	
BCT6HD 61	
BCT8HD	
BD4SG 110	
BDG45CMP 56	
BDG48CPZ 56	
BDG57CPZ 56	
BDG65CMP 56	;
BDG85CMP 56	j
BDG85CTMP 57	1
BDG86CPZ 56	5
BDG86LMPZ 57	/
BDG88CPZ 56	5
BDG945CMP 56	5
BDG95CLMP 56	5
BDG95CMP	
BDG96LMPZ	
BDG97LMPZ	
BDG98CPZ	
BDG311CPZ	
BDG911CPZ	
BDG916CPZ 57 BDG9645LMPZ 57	
BDG9845CPZ	
BDG91145CPZ	
BDG91645CPZ 57	
BDGAWP100Z 56	5
BDGCB8K	





BDGCT6K	58
BDGCT6W	61
BDGEC7Z	56
BDGLN6K	60
BDGLP7SAP	68
BDGLP10SAP	68
BDGMPEC5	56
BDGPL200XLR	57
BDGPL300HG	57
BDGPL300LR	57
BDGPL400LMP	57
BDGPL410HGZ	57
BDGPL411HGZ	57
BDGPL411HGZBDGPL412HGZ	57
BDGPL412HG2 BDGPL800	52
BDMAJ10	
BDMCB6	
BDMCB0	62
BDMCB7	
BDMCB8	
BDMCT6	
BDMCT0	
BDMLN6	
BDMLN8	
BDMLN8	
BDMLP73	68
BDOE1012	
BDOE1012	
BDOE1410	
BDOE1820	
BD0E2224 BD0EM67	
BDOEM67	
BDOEM08	
BDOEM89	
BDOEM1011	
BDOEM1012	
BDOEM1113	
BDOEM1219	
BDOEM1314	
BDOEM1415	
BDOEM1417	
BDOEM1617	43
BDOEM1719	
BDOEM1819	43
BDOEM1921	43
BDOEM1922	43
BDOEM2022	43
BDOEM2123	
BDOEM2224	
BDOEM2326	
BDOEM2426	
BDOEM2427	
BDOEM2528	
BDOEM3032	
	54
	09
	09
	08
	08
	09
	32 42
	43 22
	22 56
	56 56
	56 56
	56 56
	56 56
BLP15HVLP 1 BLP18HVLP	
BLP18HVLP1 BLP404	
BLP404 BLPADJ404	
BLPADJ404SG	

	40
	35
BLPAFM1438	25
	30 30
BLPAIM134	
BLPAIM341 10	01
BLPAIM1121 10	01
	99
	95
	97 95
	95
	14
BLPATSCM120	15
	15
	16 16
	10
	16
BLPATSM1429	14
	15
	14
	24 36
BLPBB1215	
	36
BLPBB3419	37
	30
BLPBC18	
BLPBC18-1	69 69
	69
	69
BLPBC30-1 6	
BLPBC36	
	69 11
	24
	32
BLPCWM6AP	
BLPCWM7AP	
BLPCWM8AP 4 BLPCWM9AP 4	
BLPCWM10AP	
BLPCWM11AP	
BLPCWM12AP	
BLPCWM13AP	
BLPCWM14AP	
BLPCWM15AP 4 BLPCWM16AP	
BLPCWM17AP	
BLPCWM18AP	43
BLPCWM19AP	
BLPCWM20AP	
BLPCWM21AP 4 BLPCWM22AP	
BLPCWM22AP	
BLPCWM24AP	
BLPCWM25AP	
BLPCWM26AP	
BLPCWM27AP	
BLPCWM28AP 2 BLPCWM29AP	
BLPCWM30AP	
BLPCWM31AP	
BLPCWM32AP	
BLPCWM33AP	
BLPCWM34AP 4 BLPCWM36	
BLPCWM38	
BLPCWM41	43
BLPCWM46 4	43

BLPD121 34	
BLPD1212 34	
BLPD1234 34	
BLPD1238 34	
BLPD1258 34	
BLPD1278 34	
BLPD12516 34	
BLPD12716 34	
BLPD12916 34	
BLPD121116 34	
BLPD121316 34	
BLPD121516 34	
BLPDB12114 34	
BLPDB12118 34	
BLPDB121116 34	
BLPDM128 34	
BLPDM129 34	
BLPDM1210 34	
BLPDM1211 34	
BLPDM1212 34	
BLPDM1213 34	
BLPDM1214 34	
BLPDM1215 34	
BLPDM1216 34	
BLPDM1217	
BLPDM1218	
BLPDM1219	
BLPDM1220	
BLPDM1221	
BLPDM1222	
BLPDM1223	
BLPDM1224	
BLPDM1230	
BLPDM1232	
BLPDM3419	
BLPDM3422	
BLPDM3422	
BLPDM3424	
BLPDM3425	
BLPDM3426	
BLPDM3427	
BLPDM3428	
BLPDM3429	
BLPDM3430 37	
BLPDM3432	
BLPDM3433 37	
BLPDM3434 37	
BLPDM3435 37	
BLPDM3436 37	
BLPDM3438 37	
BLPDM3440	
BLPDM3446	
BLPDM3450	
BLPDM3455	
BLPDM3460	
BLPEXIM17	
BLPEXIM113	
BLPEXIM123	
BLPEXIM125	
BLPEXIM126	
BLPEXIM343	
BLPEXIM344	
BLPEXIM340	
BLPEXIM348	
BLPEXIM383	
BLPEXIM386	
BLPEXIM1210	
BLPEXIM3410	
BLPEXIM3413	
BLPEXT344	



	~-
BLPEXT348 BLPEXT3416	37 37
	24
BLPEXTK123	35
BLPEXTK125	35
BLPEXTK126	35
BLPEXTK383	29
BLPEXTK386	
BLPEXTK1210	
BLPEXTK3810 BLPEXTL1412	
BLPEXTL1418	24
BLPEXTL1424	
BLPEXTL3812	29
BLPEXTL3818	29
BLPEXTL3824	
BLPFB14 BLPFB316	53 53
BLPFB310 BLPFB532	53 53
BLPFB732	53
BLPFB932	53
BLPFS01414	26
BLPFS01438	
BLPFT144	
	26 26
BLPFT146.5 BLPFT388	26 32
BLPFT3855	32 32
BLPFT3865	32
BLPGSS1233	13
BLPGSS1422	12
BLPGSS1427	14
BLPGSS1451A	12
BLPGSS1462 BLPGSS3837	11 13
	13
BLPGSS3885	12
BLPGSSC100	11
BLPGSSC155	10
BLPGSSCM78	10
BLPGSSCT71 BLPH123	12 36
BLPH123	36
BLPH125	36
BLPH125L180	36
BLPH126	36
BLPH126L70	36
BLPH126L140 BLPH126L250	
BLPH126L250	
BLPH127	
BLPH128L120	
BLPH383	
	32
BLPH385	32 32
BLPH386 BLPH387	32 32
BLPH387 BLPH388	
BLPH1210	
BLPH1210L140	36
BLPH1212	
BLPH1214	
BLPH1217 BLPH1219	
BLPH1219 BLPH3810	
BLPHB14	
BLPHB18	53
BLPHB316	53
BLPHB532	53
BLPHB732	
BLPHB964 BLPHBM3	53 53
BLPHBM3BLPHBM4	
	55

BLPHBM5	_
BLPHBM5	
BLPHL124	-
BLPHL125	-
BLPHL126	
BLPHL127 3	7
BLPHL128 3	
BLPHL1210	
BLPHL1212	
BLPHL1214 3 BLPHL1217	
BLPHSM0142	
BLPHSM0143	
BLPHSM0144 2	5
BLPHSM0145 2	5
BLPHSM0146 2	
BLPHSM0147	
BLPHSM0148	
BLPHSM01410	
BLPHSM01425	
BLPJIM1 10	
BLPJIM12	7
BLPJIM34	
BLPJIM38	
BLPK14HVLP 15 BLPL121	
BLPL121	
BLPL1212	
BLPL1234	
BLPL1238 3	3
BLPL1258 3	
BLPL1278	
BLPL3812	
BLPL3814	
BLPL3838	
BLPL3858	
BLPL3878 2	8
BLPL12716 3	_
BLPL12916	
BLPL38516	-
BLPL38716	
BLPL121116	
BLPL121316	
BLPL121516 3	
BLPL381116 2	
BLPL381316	
BLPL381516	
BLPLB121116	
BLPLB125114	
BLPLM386	
BLPLM387 2	
BLPLM388	
BLPLM389	
BLPLM1210	
BLPLM1211	
BLPLM1213	
BLPLM1214	
BLPLM1215 3	
BLPLM1216	
BLPLM1217	
BLPLM1218	
BLPLM1219	
BLPLM1220	
BLPLM1222	
BLPLM1224 3	
BLPLM1227	
BLPLM1230 3	3

BLPLM1232	33
BLPLM3810	27
BLPLM3811	27
BLPLM3812	
BLPLM3813	27
BLPLM3814	27
BLPLM3815	27
BLPLM3816	27
BLPLM3817	
BLPLM3818	27
BLPLM3819	27
BLPLM3820	27
BLPLM3821	27
BLPLM3822	
BLPLM3823	27
BLPLM3824	27
BLPLS1412	22
BLPLS1414	22
BLPLS1438	22
BLPLS1458	22
BLPLS14316	22
BLPLS14516	22
BLPLS14716	22
BLPLS14732	22
BLPLS14916	22
BLPLS14932	22
BLPLS141132	22
BLPLSIM121	96
BLPLSIM1212	96
BLPLSIM1234	96
BLPLSIM1238	96
BLPLSIM1258	96
BLPLSIM1278	96
BLPLSIM3812	95
BLPLSIM3814	95
BLPLSIM3834	95
BLPLSIM3838	95
BLPLSIM3858	95
BLPLSIM12716	96
	50
BLPLSIM12916	96
BLPLSIM12916	96
BLPLSIM12916 BLPLSIM38516	96 95
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716	96 95 95
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38916	96 95 95 95
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38916 BLPLSIM121116	96 95 95
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38916	96 95 95 95
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316	96 95 95 95 95 96
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121516	96 95 95 95 96 96 96
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121516 BLPLSIM381116	96 95 95 95 96 96 96 96 95
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121316 BLPLSIM121516 BLPLSIM381116 BLPLSIM12114	96 95 95 95 96 96 96 95 96
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121516 BLPLSIM381116 BLPLSIM812114 BLPLSIMB12116	96 95 95 95 96 96 96 95 96 96
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121316 BLPLSIM121516 BLPLSIM381116 BLPLSIM812114 BLPLSIMB12116 BLPLSIMB12118	96 95 95 96 96 96 95 96 96 96 96
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121516 BLPLSIM381116 BLPLSIM812114 BLPLSIMB12116	96 95 95 96 96 96 95 96 96 96 96
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121316 BLPLSIM121516 BLPLSIM381116 BLPLSIM812114 BLPLSIMB12116 BLPLSIMB12118	96 95 95 96 96 96 95 96 96 96 96
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121516 BLPLSIM381116 BLPLSIMB12114 BLPLSIMB12116 BLPLSIMB12116 BLPLSIMB12116 BLPLSIMB12118 BLPLSIMB121316 BLPLSIMB121316	96 95 95 95 96 96 96 96 96 96 96 96 96 22
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121516 BLPLSIM381116 BLPLSIMB12114 BLPLSIMB12116 BLPLSIMB12116 BLPLSIMB12116 BLPLSIMB121316 BLPLSIMB121316 BLPLSIMB12118 BLPLSIMB121316 BLPLSIMB121316 BLPLSIMB121316	96 95 95 95 96 96 96 96 96 96 96 96 92 22
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38716 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121316 BLPLSIM121316 BLPLSIM121316 BLPLSIM121316 BLPLSIM811116 BLPLSIM812116 BLPLSIMB12118 BLPLSIMB121316 BLPLSIM124316 BLPLSIM144 BLPLSM145 BLPLSM146	96 95 95 95 96 96 96 96 96 96 96 96 92 22 22
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38716 BLPLSIM38916 BLPLSIM38916 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121316 BLPLSIM121316 BLPLSIM812114 BLPLSIMB12116 BLPLSIMB12118 BLPLSIMB121316 BLPLSM144 BLPLSM145 BLPLSM146	96 95 95 95 96 96 96 96 96 96 96 96 92 22 22 22
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38716 BLPLSIM38916 BLPLSIM38916 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121316 BLPLSIM121316 BLPLSIM812114 BLPLSIMB12116 BLPLSIMB12118 BLPLSIMB121316 BLPLSM144 BLPLSM145 BLPLSM146	96 95 95 95 96 96 96 96 96 96 96 96 92 22 22
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121516 BLPLSIM81116 BLPLSIM812116 BLPLSIM812116 BLPLSIM812116 BLPLSIM812136 BLPLSIM812136 BLPLSIM812136 BLPLSM144 BLPLSM145 BLPLSM146 BLPLSM147 BLPLSM148	96 95 95 95 96 96 96 96 96 96 96 96 96 92 22 22 22 22 22
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38716 BLPLSIM38916 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121316 BLPLSIM121516 BLPLSIM381116 BLPLSIM812114 BLPLSIM812116 BLPLSIM812118 BLPLSIM121316 BLPLSM121316 BLPLSM144 BLPLSM145 BLPLSM144 BLPLSM145 BLPLSM144 BLPLSM145 BLPLSM144 BLPLSM145 BLPLSM146 BLPLSM147 BLPLSM148 BLPLSM149	96 95 95 95 96 96 96 96 96 96 96 96 96 92 22 22 22 22 22
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38716 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121516 BLPLSIM121516 BLPLSIM121116 BLPLSIM12116 BLPLSIM12118 BLPLSIM121316 BLPLSIM121316 BLPLSIM121316 BLPLSIM141 BLPLSM144 BLPLSM145 BLPLSM146 BLPLSM147 BLPLSM148 BLPLSM149	96 95 95 95 96 96 96 96 96 96 96 96 96 92 22 22 22 22 22 22 22 22 22
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38716 BLPLSIM38916 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121316 BLPLSIM121516 BLPLSIM81116 BLPLSIM812114 BLPLSIM812116 BLPLSIM812116 BLPLSIM8121316 BLPLSM144 BLPLSM145 BLPLSM145 BLPLSM145 BLPLSM146 BLPLSM147 BLPLSM148 BLPLSM1410	96 95 95 95 96 96 96 96 96 96 96 96 92 22 22 22 22 22 22 22 22 22 22
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38716 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121316 BLPLSIM121316 BLPLSIM121316 BLPLSIM121316 BLPLSIM121516 BLPLSIM12114 BLPLSIM12116 BLPLSIM12118 BLPLSM121316 BLPLSM141 BLPLSM144 BLPLSM145 BLPLSM144 BLPLSM145 BLPLSM145 BLPLSM144 BLPLSM145 BLPLSM141 BLPLSM1410 BLPLSM1411 BLPLSM1411	96 95 95 96 96 96 96 96 96 96 96 96 92 22 22 22 22 22 22 22 22 22 22 22 22
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38716 BLPLSIM38916 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121316 BLPLSIM121516 BLPLSIM81116 BLPLSIM812114 BLPLSIM812116 BLPLSIM812116 BLPLSIM8121316 BLPLSM144 BLPLSM145 BLPLSM145 BLPLSM145 BLPLSM146 BLPLSM147 BLPLSM148 BLPLSM1410	96 95 95 96 96 96 96 96 96 96 96 96 92 22 22 22 22 22 22 22 22 22 22 22 22
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38716 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121316 BLPLSIM121316 BLPLSIM121316 BLPLSIM121316 BLPLSIM121516 BLPLSIM12114 BLPLSIM12116 BLPLSIM12118 BLPLSM121316 BLPLSM141 BLPLSM144 BLPLSM145 BLPLSM144 BLPLSM145 BLPLSM145 BLPLSM144 BLPLSM145 BLPLSM141 BLPLSM1410 BLPLSM1411 BLPLSM1411	96 95 95 95 96 96 96 96 96 96 96 96 92 22 22 22 22 22 22 22 22 22 22 22 22
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38716 BLPLSIM38916 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121316 BLPLSIM121516 BLPLSIM812114 BLPLSIM812116 BLPLSIM121316 BLPLSIM812116 BLPLSIM121316 BLPLSIM812118 BLPLSM141 BLPLSM144 BLPLSM144 BLPLSM145 BLPLSM144 BLPLSM145 BLPLSM146 BLPLSM147 BLPLSM148 BLPLSM1414 BLPLSM141 BLPLSM1411 BLPLSM1411 BLPLSM1412 BLPLSM1413 BLPLSM1414	96 95 95 95 96 96 96 96 96 96 96 96 92 22 22 22 22 22 22 22 22 22 22 22 22
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38716 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121316 BLPLSIM121516 BLPLSIM812114 BLPLSIMB12116 BLPLSIMB12116 BLPLSIMB121316 BLPLSIMB12118 BLPLSM144 BLPLSM145 BLPLSM145 BLPLSM145 BLPLSM145 BLPLSM146 BLPLSM1418 BLPLSM1414 BLPLSM1418 BLPLSM141 BLPLSM1411 BLPLSM1411 BLPLSM1412 BLPLSM1413 BLPLSM1414	96 95 95 96 96 96 96 96 96 96 96 96 96 96 92 22 22 22 22 22 22 22 22 22 22 22 22
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38716 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121316 BLPLSIM121516 BLPLSIM12114 BLPLSIMB12116 BLPLSIMB12116 BLPLSIMB121316 BLPLSIMB12118 BLPLSM144 BLPLSM145 BLPLSM145 BLPLSM145 BLPLSM146 BLPLSM1414 BLPLSM1411 BLPLSM1411 BLPLSM1411 BLPLSM1411 BLPLSM1413 BLPLSM1414 BLPLSM1413 BLPLSM1414 BLPLSM1413	96 95 95 96 96 96 96 96 96 96 96 96 96 96 92 22 22 22 22 22 22 22 22 22 22 22 22
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38716 BLPLSIM38716 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121316 BLPLSIM121316 BLPLSIM121316 BLPLSIM121316 BLPLSIMB12114 BLPLSIMB12116 BLPLSIMB121316 BLPLSIMB121316 BLPLSM144 BLPLSM145 BLPLSM144 BLPLSM145 BLPLSM146 BLPLSM1414 BLPLSM1418 BLPLSM1410 BLPLSM1411 BLPLSM1412 BLPLSM1413 BLPLSM1414 BLPLSM1413 BLPLSM1414 BLPLSM1413 BLPLSM1414 BLPLSM1411 BLPLSM1411	96 95 95 96 96 96 96 96 96 96 96 92 22 22 22 22 22 22 22 22 22 22 22 22
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38716 BLPLSIM38716 BLPLSIM38916 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121316 BLPLSIM812114 BLPLSIMB12116 BLPLSIMB12118 BLPLSIMB12136 BLPLSIMB12136 BLPLSIM141 BLPLSM145 BLPLSM145 BLPLSM146 BLPLSM147 BLPLSM148 BLPLSM141 BLPLSM143 BLPLSM1411 BLPLSM1411 BLPLSM1412 BLPLSM1413 BLPLSM1414 BLPLSM1411 BLPLSM1411 BLPLSM1413 BLPLSM1414 BLPLSM1411 BLPLSM1411 BLPLSM1411 BLPLSM1413 BLPLSM1414 BLPLSM1411 BLPLSM1411 BLPLSM1411 BLPLSM1411 BLPLSM1411 BLPLSM1411 BLPLSM1411 <	96 95 95 96 96 96 96 96 96 96 96 92 22 22 22 22 22 22 22 22 22 22 22 22
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38716 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM1413 BLPLSM144 BLPLSM145 BLPLSM146 BLPLSM147 BLPLSM148 BLPLSM1410 BLPLSM1411 BLPLSM1412 BLPLSM1413 BLPLSM1414 BLPLSM1413 BLPLSM1414 BLPLSM1411 BLPLSM1414 BLPLSM1413 BLPLSM1414 BLPLSM1411 BLPLSM1411 BLPLSM1411 BLPLSM1414 BLPLSM1414 BLPLSM1411 BLPLSM1411 BLPLSM1411 BLPLSM1411 BLPLSM1411	96 95 95 96 96 96 96 96 96 96 96 92 22 22 22 22 22 22 22 22 22 22 22 22
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38716 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121316 BLPLSIM121316 BLPLSIM121316 BLPLSIM812114 BLPLSIMB12116 BLPLSIMB12118 BLPLSIMB12136 BLPLSIMB12136 BLPLSIM144 BLPLSM145 BLPLSM145 BLPLSM146 BLPLSM147 BLPLSM148 BLPLSM141 BLPLSM141 BLPLSM141 BLPLSM141 BLPLSM1411 BLPLSM1411 BLPLSM1412 BLPLSM1413 BLPLSM1414 BLPLSM1413 BLPLSM1414 BLPLSM1411 <	96 95 95 96 96 96 96 96 96 96 96 92 22 22 22 22 22 22 22 22 22 22 22 22
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38716 BLPLSIM38916 BLPLSIM38916 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121316 BLPLSIMB12114 BLPLSIMB12116 BLPLSIMB12118 BLPLSIMB121316 BLPLSM144 BLPLSM145 BLPLSM144 BLPLSM145 BLPLSM146 BLPLSM147 BLPLSM148 BLPLSM149 BLPLSM1410 BLPLSM1411 BLPLSM1412 BLPLSM1413 BLPLSM1414 BLPLSM1413 BLPLSMIM117 BLPLSMIM118 BLPLSMIM119 BLPLSMIM121	96 95 95 96 96 96 96 96 96 96 96 96 92 22 22 22 22 22 22 22 22 22 22 22 22
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38716 BLPLSIM38716 BLPLSIM38916 BLPLSIM38916 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121316 BLPLSIM812114 BLPLSIM812116 BLPLSIM812116 BLPLSIM812116 BLPLSIM8121316 BLPLSM144 BLPLSM144 BLPLSM144 BLPLSM145 BLPLSM146 BLPLSM147 BLPLSM148 BLPLSM149 BLPLSM1410 BLPLSM1411 BLPLSM1412 BLPLSM1413 BLPLSM1414 BLPLSM1414 BLPLSMIM117 BLPLSMIM118 BLPLSMIM119 BLPLSMIM120 BLPLSMIM121	96 95 95 96 96 96 96 96 96 96 96 92 22 22 22 22 22 22 22 22 22 22 22 22
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38716 BLPLSIM38916 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121316 BLPLSIM121316 BLPLSIM121316 BLPLSIM812114 BLPLSIM812116 BLPLSIM812116 BLPLSIM812116 BLPLSM141 BLPLSM144 BLPLSM144 BLPLSM145 BLPLSM145 BLPLSM146 BLPLSM147 BLPLSM148 BLPLSM149 BLPLSM1410 BLPLSM1411 BLPLSM1412 BLPLSM1413 BLPLSM1414 BLPLSM1414 BLPLSMIM117 BLPLSMIM118 BLPLSMIM119 BLPLSMIM112 BLPLSMIM121 BLPLSMIM123 BLPLSMIM124	96 95 95 96 96 96 96 96 96 96 96 92 22 22 22 22 22 22 22 22 22 22 22 22
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38716 BLPLSIM38716 BLPLSIM38916 BLPLSIM38916 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121516 BLPLSIM812114 BLPLSIM812116 BLPLSIM812116 BLPLSIM812116 BLPLSIM812116 BLPLSIM812116 BLPLSIM812116 BLPLSM144 BLPLSM144 BLPLSM144 BLPLSM145 BLPLSM145 BLPLSM145 BLPLSM146 BLPLSM147 BLPLSM148 BLPLSM149 BLPLSM1410 BLPLSM1411 BLPLSM1412 BLPLSM1413 BLPLSM1414 BLPLSMIM117 BLPLSMIM118 BLPLSMIM119 BLPLSMIM112 BLPLSMIM121 BLPLSMIM123 BLPLSMIM124	96 95 95 96 96 96 96 96 96 96 96 96 92 22 22 22 22 22 22 22 22 22 22 22 22
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38716 BLPLSIM38716 BLPLSIM38916 BLPLSIM38916 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121516 BLPLSIM812114 BLPLSIM812116 BLPLSIM812116 BLPLSIM812116 BLPLSIM812116 BLPLSIM812116 BLPLSIM812116 BLPLSM144 BLPLSM144 BLPLSM144 BLPLSM145 BLPLSM145 BLPLSM145 BLPLSM146 BLPLSM147 BLPLSM148 BLPLSM149 BLPLSM1410 BLPLSM1411 BLPLSM1412 BLPLSM1413 BLPLSM1414 BLPLSMIM117 BLPLSMIM118 BLPLSMIM119 BLPLSMIM112 BLPLSMIM121 BLPLSMIM123 BLPLSMIM124	96 95 95 96 96 96 96 96 96 96 96 92 22 22 22 22 22 22 22 22 22 22 22 22
BLPLSIM12916 BLPLSIM38516 BLPLSIM38716 BLPLSIM38716 BLPLSIM38716 BLPLSIM38916 BLPLSIM38916 BLPLSIM38916 BLPLSIM121116 BLPLSIM121316 BLPLSIM121516 BLPLSIM812114 BLPLSIM812116 BLPLSIM812116 BLPLSIM812116 BLPLSIM812116 BLPLSIM812116 BLPLSIM812116 BLPLSM144 BLPLSM144 BLPLSM144 BLPLSM145 BLPLSM145 BLPLSM145 BLPLSM146 BLPLSM147 BLPLSM148 BLPLSM149 BLPLSM1410 BLPLSM1411 BLPLSM1412 BLPLSM1413 BLPLSM1414 BLPLSMIM117 BLPLSMIM118 BLPLSMIM119 BLPLSMIM112 BLPLSMIM121 BLPLSMIM123 BLPLSMIM124	96 95 95 96 96 96 96 96 96 96 96 96 96 92 22 22 22 22 22 22 22 22 22 22 22 22





BLPLSMIM128 10	0
BLPLSMIM129 10	0
BLPLSMIM130 10	0
BLPLSMIM131 10	0
BLPLSMIM132 10	0
BLPLSMIM133 10	0
BLPLSMIM134 10	0
BLPLSMIM135 10	0
BLPLSMIM136 10	0
BLPLSMIM137 10	0
BLPLSMIM138 10	0
BLPLSMIM140 10	0
BLPLSMIM141 10	0
BLPLSMIM142 10	0
BLPLSMIM143 10	0
BLPLSMIM146 10	0
BLPLSMIM149 10	0
BLPLSMIM150 10	0
BLPLSMIM155 10	0
BLPLSMIM387 9	4
BLPLSMIM388	
BLPLSMIM389 9	4
BLPLSMIM1210	6
BLPLSMIM1211 9	6
BLPLSMIM1212 9	6
	6
	6
	6
	6
	6
	6
	6
	6
	6
	6
	6
	6
	6
	6
BLPLSMIM1232	
BLPLSMIM3417	
BLPLSMIM3418	-
BLPLSMIM3419	
	8
	8
BLPLSMIM3422	
BLPLSMIM3423	-
BLPLSMIM3424	
	8
	8
	8
	8
	8
	8
	8
	8
	8
	8
	8
	8
	8
	8
	8
	8
	8
	8
	8
	8
	8
	8
	8
	8
BLPLSMIM3450	

BLPLSMIM3455
BLPLSMIM3810 94
BLPLSMIM3811 94
BLPLSMIM3812 94
BLPLSMIM3813 94
BLPLSMIM3814 94
BLPLSMIM3815
BLPLSMIM3816
BLPLSMIM3817
BLPLSMIM3818
BLPLSWIWIS819
BLPMV4
BLPMV5
BLPMV6 128
BLPP140
BLPP141 26
BLPP142
BLPP143
BLPP144
BLPP381
BLPP383
BLPP384
BLPPB0
BLPPB1 53
BLPPB2 53
BLPPB3 53
BLPPB704
BLPPD141
BLPPD143
BLPPD381
BLPPD382 32
BLPPD383 32
BLPPD384 32
BLPPS141
BLPPTA3438 32
BLPPTA3438
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS58 31
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS58 31 BLPPTS716 31
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS58 31 BLPPTS716 31 BLPPTS916 31
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS58 31 BLPPTS716 31 BLPPTS916 31 BLPPTS11116 31
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS58 31 BLPPTS716 31 BLPPTS916 31 BLPPTS1116 31 BLPPTSM8 31
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS58 31 BLPPTS716 31 BLPPTS916 31 BLPPTS11116 31
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS58 31 BLPPTS916 31 BLPPTS1116 31 BLPPTSM8 31 BLPPTSM9 31 BLPPTSM10 31
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS58 31 BLPPTS916 31 BLPPTS1116 31 BLPPTSM8 31 BLPPTSM9 31 BLPPTSM10 31 BLPPTSM12 31
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS58 31 BLPPTS716 31 BLPPTS916 31 BLPPTS916 31 BLPPTSM8 31 BLPPTSM9 31 BLPPTSM10 31 BLPPTSM12 31 BLPPTSM13 31
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS58 31 BLPPTS716 31 BLPPTS916 31 BLPPTS916 31 BLPPTSM8 31 BLPPTSM9 31 BLPPTSM10 31 BLPPTSM12 31 BLPPTSM14 31
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS58 31 BLPPTS716 31 BLPPTS916 31 BLPPTSM8 31 BLPPTSM9 31 BLPPTSM9 31 BLPPTSM10 31 BLPPTSM12 31 BLPPTSM13 31 BLPPTSM13 31 BLPPTSM14 31 BLPPTSM15 31
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS58 31 BLPPTS716 31 BLPPTS916 31 BLPPTS916 31 BLPPTSM8 31 BLPPTSM9 31 BLPPTSM10 31 BLPPTSM12 31 BLPPTSM12 31 BLPPTSM13 31 BLPPTSM14 31 BLPPTSM15 31
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS58 31 BLPPTS716 31 BLPPTS916 31 BLPPTS916 31 BLPPTSM8 31 BLPPTSM9 31 BLPPTSM9 31 BLPPTSM10 31 BLPPTSM11 31 BLPPTSM12 31 BLPPTSM13 31 BLPPTSM14 31 BLPPTSM15 31 BLPPTSM16 31 BLPPTSM17 31
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS58 31 BLPPTS716 31 BLPPTS916 31 BLPPTS916 31 BLPPTSM8 31 BLPPTSM9 31 BLPPTSM10 31 BLPPTSM12 31 BLPPTSM12 31 BLPPTSM13 31 BLPPTSM14 31 BLPPTSM15 31
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS76 31 BLPPTS916 31 BLPPTSM8 31 BLPPTSM9 31 BLPPTSM116 31 BLPPTSM9 31 BLPPTSM12 31 BLPPTSM13 31 BLPPTSM14 31 BLPPTSM15 31 BLPPTSM16 31 BLPPTSM13 31 BLPPTSM14 31 BLPPTSM15 31 BLPPTSM16 31 BLPPTSM18 31 BLPPTSM18 31 BLPPTSM19 31 BLPPTSM19 31
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS58 31 BLPPTS716 31 BLPPTS916 31 BLPPTSM8 31 BLPPTSM9 31 BLPPTSM9 31 BLPPTSM9 31 BLPPTSM9 31 BLPPTSM9 31 BLPPTSM10 31 BLPPTSM12 31 BLPPTSM13 31 BLPPTSM14 31 BLPPTSM15 31 BLPPTSM16 31 BLPPTSM18 31 BLPPTSM18 31 BLPPTSM18 31 BLPPTSM19 31 BLPPTSM12 31
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS58 31 BLPPTS916 31 BLPPTSM8 31 BLPPTSM9 31 BLPPTSM116 31 BLPPTSM12 31 BLPPTSM13 31 BLPPTSM14 31 BLPPTSM15 31 BLPPTSM16 31 BLPPTSM18 31 BLPPTSM18 31 BLPPTSM16 31 BLPPTSM18 31 BLPPTSM18 31 BLPPTSM18 31 BLPPTSM18 31 BLPPTSM18 31 BLPPTSM19 31 BLPPTSM12 36 BLPTS12 36
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS58 31 BLPPTS716 31 BLPPTS916 31 BLPPTSM8 31 BLPPTSM9 31 BLPPTSM10 31 BLPPTSM11 31 BLPPTSM12 31 BLPPTSM13 31 BLPPTSM14 31 BLPPTSM15 31 BLPPTSM16 31 BLPPTSM18 31 BLPPTSM14 31 BLPPTSM15 31 BLPPTSM16 31 BLPPTSM18 31 BLPTSM19 31
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS58 31 BLPPTS716 31 BLPPTS916 31 BLPPTSM8 31 BLPPTSM9 31 BLPPTSM11 31 BLPPTSM12 31 BLPPTSM13 31 BLPPTSM14 31 BLPPTSM15 31 BLPPTSM16 31 BLPPTSM13 31 BLPPTSM14 31 BLPPTSM15 31 BLPPTSM18 31 BLPS12 36 BLPS12 36 BLPS12 36 BLPS121 33
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS58 31 BLPPTS716 31 BLPPTS916 31 BLPPTSM8 31 BLPPTSM9 31 BLPPTSM10 31 BLPPTSM11 31 BLPPTSM12 31 BLPPTSM13 31 BLPPTSM14 31 BLPPTSM15 31 BLPPTSM16 31 BLPPTSM18 31 BLPPTSM14 31 BLPPTSM15 31 BLPPTSM16 31 BLPPTSM18 31 BLPTSM19 31
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS38 31 BLPPTS38 31 BLPPTS38 31 BLPPTS38 31 BLPPTS4 31 BLPPTS58 31 BLPPTS66 31 BLPPTS916 31 BLPPTSM18 31 BLPPTSM10 31 BLPPTSM12 31 BLPPTSM13 31 BLPPTSM14 31 BLPPTSM15 31 BLPPTSM16 31 BLPPTSM18 31 BLPPTSM18 31 BLPPTSM18 31 BLPPTSM18 31 BLPTSM18 31 BLPS121 36 BLPS121 33 BLPS121 33 BLPS121 33 BLPS1238 33 BLPS124 33 <td< td=""></td<>
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS38 31 BLPPTS38 31 BLPPTS38 31 BLPPTS38 31 BLPPTS4 31 BLPPTS58 31 BLPPTS66 31 BLPPTS916 31 BLPPTSM18 31 BLPPTSM10 31 BLPPTSM12 31 BLPPTSM13 31 BLPPTSM14 31 BLPPTSM15 31 BLPPTSM16 31 BLPPTSM18 31 BLPPTSM18 31 BLPPTSM18 31 BLPPTSM18 31 BLPPTSM18 31 BLPS121 33 BLPS121 33 BLPS121 33 BLPS121 33 BLPS1238 33 BLPS124 33 <t< td=""></t<>
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS38 31 BLPPTS38 31 BLPPTS38 31 BLPPTS38 31 BLPPTS4 31 BLPPTS58 31 BLPPTS68 31 BLPPTS916 31 BLPPTSM18 31 BLPPTSM19 31 BLPPTSM11 31 BLPPTSM12 31 BLPPTSM13 31 BLPPTSM14 31 BLPPTSM15 31 BLPPTSM16 31 BLPPTSM18 31 BLPPTSM19 31 BLPPTSM18 31 BLPPTSM19 31 BLPS121 36 BLPS121 33 BLPS1234 33 BLPS1238 33 BLPS1278 33 BLPS1278 33
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS38 31 BLPPTS38 31 BLPPTS38 31 BLPPTS38 31 BLPPTS58 31 BLPPTS916 31 BLPPTS916 31 BLPPTSM18 31 BLPPTSM19 31 BLPPTSM12 31 BLPPTSM13 31 BLPPTSM14 31 BLPPTSM15 31 BLPPTSM16 31 BLPPTSM18 31 BLPPTSM19 31 BLPPTSM18 31 BLPPTSM19 31 BLPS121 36 BLPS121 36 BLPS1238 33 BLPS1238 33 BLPS1238 33 BLPS1278 33 BLPS1278 33 BLPS1278 33
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS38 31 BLPPTS38 31 BLPPTS38 31 BLPPTS4 31 BLPPTS4 31 BLPPTS58 31 BLPPTS916 31 BLPPTS916 31 BLPPTSM18 31 BLPPTSM12 31 BLPPTSM12 31 BLPPTSM12 31 BLPPTSM13 31 BLPPTSM14 31 BLPPTSM15 31 BLPPTSM16 31 BLPPTSM17 31 BLPPTSM18 31 BLPPTSM19 31 BLPS121 36 BLPS121 33 BLPS1238 33 BLPS1238 33 BLPS1258 33 BLPS1278 33 BLPS1278 33
BLPPTA3438 32 BLPPTEXT3 32 BLPPTS12 31 BLPPTS34 31 BLPPTS38 31 BLPPTS38 31 BLPPTS38 31 BLPPTS38 31 BLPPTS38 31 BLPPTS58 31 BLPPTS916 31 BLPPTS916 31 BLPPTSM18 31 BLPPTSM19 31 BLPPTSM12 31 BLPPTSM13 31 BLPPTSM14 31 BLPPTSM15 31 BLPPTSM16 31 BLPPTSM18 31 BLPPTSM19 31 BLPPTSM18 31 BLPPTSM19 31 BLPS121 36 BLPS121 36 BLPS1238 33 BLPS1238 33 BLPS1238 33 BLPS1278 33 BLPS1278 33 BLPS1278 33

BLPS3814	28
BLPS3834	28
BLPS3838	28
BLPS3858	28
BLPS3878	
BLPS12516	33
BLPS12716	33
BLPS12916	33
BLPS14316	22
BLPS14516	22
BLPS14532	22
	22
BLPS14716	
BLPS14732	
BLPS14916	22
BLPS14932	22
BLPS38516	28
BLPS38716	28
BLPS38916	28
BLPS81414	23
BLPS81438	23
BLPS121116	33
BLPS121316	
BLPS121516	
BLPS141132	
BLPS381116	
BLPS381316	
BLPS381516	
BLPS814516	
BLPSB12114	
BLPSB12118	
BLPSB121116	33
BLPSB121316	33
BLPSH1238	36
BLPSIM121	96
BLPSIM341	99
BLPSIM1212	96
BLPSIM1234	96
BLPSIM1238	96
BLPSIM1258	96
BLPSIM1278	
BLPSIM3434	
BLPSIM3478	
BLPSIM3812	
BLPSIM3814	
BLPSIM3834	
BLPSIM3838	
BLPSIM3858	
BLPSIM12716	
BLPSIM12710	96
BLPSIM38516	
BLPSIM38716	95
BLPSIM38916	95
BLPSIM121116	
BLPSIM121316	96
BLPSIM121516	
BLPSIM341116	99
BLPSIM341316	99
BLPSIM341516	99
BLPSIM381116	95
BLPSIMB342	99
BLPSIMB12114	96
BLPSIMB12118	96
BLPSIMB34112	99
BLPSIMB34112	99
BLPSIMB34114	99 99
BLPSIMB34134	99
BLPSIMB34138	99
BLPSIMB34158	99
BLPSIMB34178	99
BLPSIMB121116	
BLPSIMB121516	96
BLPSIMB121716	96
BLPSIMB341116	99



BLPSIMB341316	99
BLPSIMB341516	99
BLPSIMB341716	99
BLPSIMB341916	99
BLPSIMB3411116	99
BLPSIMB3411316	
BLPSIMB3411516	99
BLPSM128	33
BLPSM129	33
BLPSM143.5	
BLPSM144	
BLPSM144.5	
BLPSM145	
BLPSM145.5	
BLPSM146	
BLPSM147	
BLPSM148 BLPSM149	
BLPSM149	
BLPSM387	
BLPSM388	
BLPSM389	
BLPSM1210	
BLPSM1211	
BLPSM1212	
BLPSM1213	33
BLPSM1214	33
BLPSM1215	33
BLPSM1216	33
BLPSM1217	
BLPSM1218	33
BLPSM1219	33
BLPSM1220	
BLPSM1221	
BLPSM1222	
BLPSM1223	
BLPSM1224	33 33
BLPSM1227 BLPSM1230	
BLPSM1230	
BLPSM1232	
BLPSM1236	
BLPSM1410	
BLPSM1411	
BLPSM1412	
BLPSM1413	~~
BLPSM1414	22
BLPSM3810	27
BLPSM3811	27
BLPSM3812	27
BLPSM3813	
BLPSM3814	27
BLPSM3815	27
BLPSM3816	27
BLPSM3817 BLPSM3818	27
BLPSM3818 BLPSM3819	27 27
BLPSM3820	27
BLPSM3820	
BLPSM3822	
BLPSM3823	
BLPSM3824	
	100
	100
	100
	100
	100
BLPSMIM122	100
BLPSMIM123	100
	100
	100
	100
BLPSMIM127	100

BLPSMIM128	100
BLPSMIM129	100
BLPSMIM130	100
BLPSMIM131	100
BLPSMIM132	100
BLPSMIM133	100
BLPSMIM134	100
BLPSMIM135	100
BLPSMIM136 BLPSMIM137	100 100
BLPSMIM137	100
BLPSMIM139	100
BLPSMIM140	100
BLPSMIM141	100
BLPSMIM142	100
BLPSMIM143	100
BLPSMIM144	100
BLPSMIM145	100
BLPSMIM146	100
BLPSMIM147	100
BLPSMIM148	100
BLPSMIM149 BLPSMIM150	100 100
BLPSMIM150	100
BLPSMIM152	100
BLPSMIM153	100
BLPSMIM154	100
BLPSMIM155	100
BLPSMIM156	100
BLPSMIM157	100
BLPSMIM158	
BLPSMIM159 BLPSMIM160	100 100
BLPSMIM163	100
BLPSMIM165	100
BLPSMIM166	100
BLPSMIM167	100
BLPSMIM168	100
BLPSMIM169	
BLPSMIM387 BLPSMIM388	
BLPSMIM389	
BLPSMIM1210	
BLPSMIM1211	. 96
BLPSMIM1212	. 96
BLPSMIM1213	
BLPSMIM1214	
BLPSMIM1215 BLPSMIM1216	
BLPSMIM1217	
BLPSMIM1217	
BLPSMIM1219	
BLPSMIM1221	
BLPSMIM1222	
BLPSMIM1223	
BLPSMIM1224 BLPSMIM1227	
BLPSMIM1227	
BLPSMIM1229	
BLPSMIM1232	
BLPSMIM3417	. 98
BLPSMIM3418	
BLPSMIM3419	
BLPSMIM3420	
BLPSMIM3420 BLPSMIM3421	98
BLPSMIM3420 BLPSMIM3421 BLPSMIM3422	98 98
BLPSMIM3420 BLPSMIM3421	98 98 98
BLPSMIM3420 BLPSMIM3421 BLPSMIM3422 BLPSMIM3423	98 98 98 98
BLPSMIM3420 BLPSMIM3421 BLPSMIM3422 BLPSMIM3423 BLPSMIM3423 BLPSMIM3424 BLPSMIM3425 BLPSMIM3426	98 98 98 98 98 98
BLPSMIM3420 BLPSMIM3421 BLPSMIM3422 BLPSMIM3423 BLPSMIM3424 BLPSMIM3425 BLPSMIM3426 BLPSMIM3427	98 98 98 98 98 98 98 98
BLPSMIM3420 BLPSMIM3421 BLPSMIM3422 BLPSMIM3423 BLPSMIM3423 BLPSMIM3424 BLPSMIM3425 BLPSMIM3426	98 98 98 98 98 98 98 98 98

BLPSMIM3430	98
BLPSMIM3431	98
BLPSMIM3432	98
BLPSMIM3433	98
BLPSMIM3434	98
BLPSMIM3435	98
BLPSMIM3436	98
BLPSMIM3437	98
BLPSMIM3438	98
BLPSMIM3439	98
BLPSMIM3440	98
BLPSMIM3441	98
BLPSMIM3442	98
BLPSMIM3443	98
BLPSMIM3444	98
BLPSMIM3445	98
BLPSMIM3446	98
BLPSMIM3447	98
BLPSMIM3448	98
BLPSMIM3449	98
	98
BLPSMIM3450	
BLPSMIM3452	98
BLPSMIM3454	98
BLPSMIM3455	98
BLPSMIM3456	98
BLPSMIM3457	98
BLPSMIM3458	98
BLPSMIM3459	98
BLPSMIM3460	98
BLPSMIM3463	98
BLPSMIM3465	98
BLPSMIM3810	94
	94
BLPSMIM3811	
BLPSMIM3812	94
BLPSMIM3813	94
BLPSMIM3814	94
BLPSMIM3815	94
BLPSMIM3816	94
BLPSMIM3817	94
BLPSMIM3818	94
BLPSMIM3819	94
BLPSMS8	95
BLPSMS10	95
BLPSMS12	95
BLPSPS1216	35
BLPSPS1221	35
BLPSPS1258	
BLPSPS3816	
BLPSPS3821	29
	29
BLPSPS3858	
BLPSPS121316	35
BLPSPS121316 BLPSPS381316	35 29
BLPSPS121316 BLPSPS381316 BLPSQB1	35 29 53
BLPSPS121316 BLPSPS381316 BLPSQB1 BLPSQB2	35 29 53 53
BLPSPS121316 BLPSPS381316 BLPSQB1 BLPSQB2 BLPSTHD144	35 29 53 53 24
BLPSPS121316 BLPSPS381316 BLPSQB1 BLPSQB2 BLPSTHD144 BLPSTHD388	35 29 53 53 24 30
BLPSPS121316 BLPSPS381316 BLPSQB1 BLPSQB2 BLPSTHD144 BLPSTHD388	35 29 53 53 24 30
BLPSPS121316 BLPSPS381316 BLPSQB1 BLPSQB2 BLPSTHD144 BLPSTHD388 BLPSTHD1215	35 29 53 53 24 30 35
BLPSPS121316 BLPSPS381316 BLPSQB1 BLPSQB2 BLPSTHD144 BLPSTHD388 BLPSTHD1215 BLPSTHD3418	35 29 53 53 24 30 35 37
BLPSPS121316 BLPSPS381316 BLPSQB1 BLPSQB2 BLPSTHD144 BLPSTHD188 BLPSTHD1215 BLPSTHD3418 BLPSTWR4	35 29 53 53 24 30 35 37 47
BLPSPS121316 BLPSPS381316 BLPSQB1 BLPSQB2 BLPSTHD144 BLPSTHD1215 BLPSTHD1215 BLPSTHD3418 BLPSTWR4 BLPSTWR6	 35 29 53 53 24 30 35 37 47 47
BLPSPS121316 BLPSPS381316 BLPSQB1 BLPSQB2 BLPSTHD144 BLPSTHD1215 BLPSTHD1215 BLPSTHD3418 BLPSTWR4 BLPSTWR6 BLPT146TP	 35 29 53 53 24 30 35 37 47 47 26
BLPSPS121316 BLPSPS381316 BLPSQB1 BLPSQB2 BLPSTHD144 BLPSTHD1215 BLPSTHD1215 BLPSTHD3418 BLPSTWR4 BLPSTWR6 BLPT146TP BLPT147TP	35 29 53 24 30 35 37 47 47 26 26
BLPSPS121316 BLPSPS381316 BLPSQB1 BLPSQB2 BLPSTHD144 BLPSTHD1215 BLPSTHD1215 BLPSTHD3418 BLPSTWR4 BLPSTWR6 BLPT146TP	35 29 53 24 30 35 37 47 47 26 26
BLPSPS121316 BLPSPS381316 BLPSQB1 BLPSQB2 BLPSTHD144 BLPSTHD1215 BLPSTHD1215 BLPSTHD3418 BLPSTWR4 BLPSTWR6 BLPT146TP BLPT147TP	 35 29 53 53 24 30 35 37 47 26 26 26
BLPSPS121316 BLPSPS381316 BLPSQB1 BLPSQB2 BLPSTHD144 BLPSTHD1215 BLPSTHD1215 BLPSTHD3418 BLPSTWR4 BLPSTWR6 BLPT146TP BLPT147TP BLPT148TP BLPT149TP	 35 29 53 24 30 35 37 47 47 26 26 26 26 26
BLPSPS121316 BLPSPS381316 BLPSQB1 BLPSQB2 BLPSTHD144 BLPSTHD144 BLPSTHD144 BLPSTHD144 BLPSTHD144 BLPSTHD144 BLPSTHD1215 BLPSTHD3418 BLPSTWR4 BLPSTWR6 BLP1146TP BLPT148TP BLPT149TP BLPT1220	 35 29 53 53 24 30 35 37 47 26 26 26 36
BLPSPS121316 BLPSPS381316 BLPSQB1 BLPSQB2 BLPSTHD144 BLPSTHD144 BLPSTHD1215 BLPSTHD13418 BLPSTWR4 BLPSTWR6 BLP1146TP BLPT147TP BLPT149TP BLPT1220 BLPT1225	 35 29 53 53 24 30 35 37 47 26 26 26 26 36 36
BLPSPS121316 BLPSPS381316 BLPSQB1 BLPSQB2 BLPSTHD144 BLPSTHD144 BLPSTHD144 BLPSTHD144 BLPSTHD1215 BLPSTHD3418 BLPSTWR4 BLPSTWR6 BLP1146TP BLPT148TP BLPT149TP BLPT1220 BLPT1227	 35 29 53 53 24 30 35 37 47 47 26 26 26 36 36 36 36
BLPSPS121316 BLPSPS381316 BLPSQB1 BLPSQB2 BLPSTHD144 BLPSTHD1215 BLPSTHD388 BLPSTHD1215 BLPSTHD3418 BLPSTWR6 BLPT146TP BLPT147TP BLPT1420 BLPT1220 BLPT1223	 35 29 53 53 24 30 35 37 47 26 26 26 26 26 36 36 36 36 36
BLPSPS121316 BLPSPS381316 BLPSQB1 BLPSQB2 BLPSTHD144 BLPSTHD144 BLPSTHD144 BLPSTHD144 BLPSTHD1215 BLPSTHD3418 BLPSTWR4 BLPSTWR6 BLP1146TP BLPT148TP BLPT149TP BLPT1220 BLPT1227	 35 29 53 53 24 30 35 37 47 26 26 26 26 26 36 36 36 36 36
BLPSPS121316 BLPSPS381316 BLPSQB1 BLPSQB2 BLPSTHD144 BLPSTHD1215 BLPSTHD388 BLPSTHD1215 BLPSTHD3418 BLPSTWR6 BLPT146TP BLPT147TP BLPT1420 BLPT1220 BLPT1223	 35 29 53 53 24 30 35 37 47 26 26 26 26 26 36 36 36 36 36 36
BLPSPS121316 BLPSS381316 BLPSQB1 BLPSQB2 BLPSTHD144 BLPSTHD1215 BLPSTHD3418 BLPSTWR4 BLPSTWR6 BLPT146TP BLPT147TP BLPT1220 BLPT1225 BLPT1230 BLPT1240	 35 29 53 53 24 30 35 37 47 26 26 26 26 26 36 36 36 36 36 36 36 36 36
BLPSPS121316 BLPSS381316 BLPSQB1 BLPSQB2 BLPSTHD144 BLPSTHD1215 BLPSTHD1215 BLPSTHD3418 BLPSTWR4 BLPSTWR6 BLPT146TP BLPT147TP BLPT147TP BLPT14220 BLPT1220 BLPT1225 BLPT1226 BLPT1230 BLPT1245 BLPT1250	 35 29 53 53 24 30 35 37 47 26 26 26 26 26 36
BLPSPS121316 BLPSS381316 BLPSQB1 BLPSQB2 BLPSTHD144 BLPSTHD1215 BLPSTHD1215 BLPSTHD3418 BLPSTWR4 BLPSTWR6 BLPT146TP BLPT147TP BLPT1420 BLPT1220 BLPT1220 BLPT12245	 35 29 53 24 30 35 37 47 26 26 26 26 36





BLPT1260	36	
BLPT1260TP	34	
BLPT1410TP	26	
BLPT1415TP	26	
BLPT1420TP	26	
BLPT1425TP	26	
BLPT1427TP	26	
BLPT1430TP	26	
BLPT3810TP	31	
BLPT3815TP	31	
BLPT3820TP	31	
BLPT3825TP	31	
BLPT3827TP	31	
BLPT3830TP	31	
BLPT3840TP	31	
BLPT3845TP	31	
BLPT3850TP	31	
BLPT3855TP	31	
BLPTB10TP	53	
BLPTB15TP	53	
BLPTB20TP	53	
BLPTB25TP		
BLPTB30TP		
BLPTE144		
BLPTE145		
BLPTE146		
BLPTE147		
BLPTE148		
BLPTE384		
BLPTE385		
BLPTE386		
BLPTE387		
BLPTE388		
BLPTE1210		
BLPTE1212		
BLPTE1214		
BLPTE1216		
BLPTE1218		
BLPTE1220		
BLPTE1222		
BLPTE1222	34	
BLPTE3810		
BLPTE3811		
BLPTE3812		
BLPTE3814		
BLPTE3816		
BLPTE3818		
BLPTE3820		
BLPTHSM0142		
BLPTHSM0142 BLPTHSM0143		
BLPTHSM0143 BLPTHSM0144		
BLPTHSM0144 BLPTHSM0145		
BLPTHSM0145		
BLPTHSM0140 BLPTHSM0147		
BLPTHSM0147 BLPTHSM0148		
BLPTHSM0148 BLPTHSM0149		
BLPTHSM0149 BLPTHSM01410	25 25	
BLPTHSM01410 BLPTHSM01425		
BLPTL1220		
BLPTL1220 BLPTL1225		
BLPTL1225 BLPTL1227		
BLPTL1227 BLPTL1230		
BLPTL1230 BLPTL1240		
BLPTL1240 BLPTL1245		
BLPTL1245 BLPTL1250		
BLPTL1250 BLPTL1255		
BLPTL1255 BLPTL1260		
BLPTL1200 BLPTMBS1414		
BLPTMBS1414 BLPTMBS3814		
DLF 11VID33014		
BI DTS0148	25	
BLPTS0148	25	
BLPTS01410		
	25	

BLPTS01425	25
BLPTS01427	25
BLPTS01430	
BLPTS01440	
BLPTS01445	
BLPTS01447	
BLPTS01450	
BLPTS3810 BLPTS3815	31 31
BLPTS3813 BLPTS3820	31
BLPTS3825	31
BLPTS3827	31
BLPTS3830	31
BLPTS3840	31
BLPTS3845	31
BLPTS3850	31
BLPTS3855	31
BLPTS3860	31
BLPTSSC43	11 24
BLPTXK1.5 BLPTXK2	24 24
BLPTXK3	24 24
BLPTXK4	24
BLPTXK6	24
BLPUJ12	35
BLPUJ14	25
BLPUJ34	37
BLPUJ38	29
BLPXZN144	
BLPXZN145 BLPXZN146	
BLPXZN140 BLPXZN148	26
BLPXZN1410	26
BLPXZN1412	26
BLPXZNM125	36
BLPXZNM126	36
BLPXZNM128	36
BLPXZNM0384 BLPXZNM0385	
BLPXZNM0386	
BLPXZNM0388	
BLPXZNM1210	36
BLPXZNM1212	
BLPXZNM1214	
BLPXZNM1216 BLPXZNM03810	36 32
BLPXZNM03810 BLPXZNM03812	52
BLWM1.5	
BLWM2	
BLWM2.5	42
BLWM3	42
BLWM4	
BLWM5	
BLWM6 BLWM8	
BLWM10	
BLWM11	
BLWM12	47
BLWM13	47
BLWM14	
BLWM15	
BLWM16 BLWM17	
BLWM18	
BLWM19	
BLWSM9	
BLWTS9	
BMPEC5AP	
BMPL1000	
	19 19
	19
BMPM5 1	

	19
BOER8	
BOER12	40
BOER12	40
BOER16	40
BOER18	40
BOER20	40
BOER22	40
BOER24 BOER26	40 40
BOER28	40 40
BOER30	40
BOER32	40
BOER704	40
BOER708	40
BOERF10A	41
BOERF12A	41
BOERF14ABOERF16A	41 41
BOERF18A	41
BOERF20A	41
BOERF22A	41
BOERF24A	41
BOERF708A	41
BOERFLCG10	42
BOERFLCG12	42
BOERFLCG14	42 42
BOERFLCG16BOERFLCG18	42 42
BOERFLCG20	42
BOERFLCG22	42
BOERFLCG24	42
BOERFLCG708	42
BOERM6	
BOERM7	
BOERM8BOERM9	40
BOERM10	40
BOERM11	40
BOERM12	40
BOERM13	40
BOERM14	
BOERM15	
BOERM16 BOERM17	40 40
BOERM17BOERM18	40 40
BOERM19	40
BOERM21	40
BOERM22	40
BOERM24	40
BOERM25	40
BOERM704	40 40
BOERM712 BOERMF8A	40 41
BOERMF9A	41
BOERMF10A	41
BOERMF11A	41
BOERMF12A	41
BOERMF13A	41
BOERMF14A	41
BOERMF15ABOERMF16A	41 41
BOERMF17A	41
BOERMF18A	41
BOERMF19A	41
BOERMF712A	41
BOERMFLCG8	41
BOERMFLCG9	41
BOERMFLCG10 BOERMFLCG11	41 41
BOERMFLCG12	41
BOERMFLCG13	



BOERMFLCG14	41
BOERMFLCG15	41
BOERMFLCG16	41
BOERMFLCG17	41
BOERMFLCG18	41 41
BOERMFLCG19 BOERMFLCG712	41 41
BOERMS8	41
BOERMS9	41
BOERMS10	41
BOERMS11	41
BOERMS12	41
BOERMS13	41
BOERMS14	41
BOERMS15	41
BOERMS16	41
BOERMS17BOERMS18	41 41
BOERMS18	41
BOERMS712	41
BOERMSF8	46
BOERMSF9	46
BOERMSF10	46
BOERMSF11	46
BOERMSF12	46
BOERMSF13	46
BOERMSF14	46
BOERMSF15BOERMSF16	46 46
BOERMSF17	40 46
BOERMSF18	46
BOERMSF19	46
BOERS10	41
BOERS12	41
BOERS14	41
BOERS16	41
BOERS18	41
BOERS20	41
BOERS22	41 41
BOERS24 BOERS708	41 41
BOERSF10	41
BOERSF12	41
BOERSF14	41
BOERSF16	41
BOERSF18	41
BOERSF20	41
BOERSF22	41
BOERSF24	41
BOERSF708 BP5T-1R	41 72
BP5T-I	73
BP10002-I-DTT	75
BP10ST-I	73
BP10T-2R	72
BP10T-2RL	72
BP10T-I	73
BP50T-2R	72
BP50T-2RL	72
BP50T-I	73 72
BP100T-3R BP100T-3RL	72 72
BP100T-J	73
BP200T-3R	72
BP200T-3RL	72
BP200T-I	73
BP250T-3RL	72
BP300T- 4R	72
BP300T-1	73
BP501-I-DTT	75
BP501NMRMH BP600T- 4R	72 72
BP6001-4R	72

BP602NMRMH 72
BP1001-O-DTT 75
BP1002CF3 74
BP1002NMRMH 72
BP2003NMRMH 72
BP2401Cl3 74
BP2502-I-DTT 75
BP2502NMRMH 72
BP2503CF3
BP2503-F-DTT
BP3403NMRMH
BP6004-F-DTT
BP8004NMRMH
BP15005NMRMH
BPAP1
BPAPS1 129
BPB4 108
BPB8 108
BPB12
BPB16 108
BPB24 108
BPB32 108
BPB40 108
BPB48 108
BPBOX18 6
BPBOX20 6
BPC6
BPECT1 137
BPL501
BPN8B 108
BPN12B 108
BPN16B 108
BPN24B 108
BPN32B 108
BPRFPT10 32
BPRFR938
BPRFR938SG
BPRSR940
BPRSR940SG
BPRSR942
BPRTR936
BPRTR936SG 23
BPRTR936SG 23 BPS1 17
BPRTR936SG 23 BPS1 17 BPS2 17
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17 BPS5 17
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17 BPS5 17 BPS5 17 BPS5 17 BPS5 17
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17 BPS5 17 BPS5 17 BPS5 17 BPS5 17
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17 BPS5 17 BPS6 17 BPS6A 17
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17 BPS5 17 BPS6 17 BPS6A 17 BPS6A 17 BPS7 18
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17 BPS5 17 BPS6 17 BPS6A 17 BPS7 18 BPS8 18
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17 BPS5 17 BPS6 17 BPS6A 17 BPS7 18 BPS8 18 BPS9 18
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17 BPS5 17 BPS6 17 BPS6A 17 BPS7 18 BPS8 18 BPS9 18 BPS10 18
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17 BPS5 17 BPS6 17 BPS6A 17 BPS7 18 BPS8 18 BPS9 18 BPS10 18 BPS11 19
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17 BPS5 17 BPS6 17 BPS6A 17 BPS7 18 BPS8 18 BPS10 18 BPS11 19 BPS13 19 BPS14 19
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17 BPS5 17 BPS6 17 BPS6 17 BPS6A 17 BPS7 18 BPS9 18 BPS10 18 BPS11 19 BPS13 19 BPS14 19 BPTHM08 47
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17 BPS5 17 BPS6 17 BPS6A 17 BPS7 18 BPS9 18 BPS10 18 BPS11 19 BPS13 19 BPS14 19 BPTHM08 47 BPTHM09 47
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17 BPS5 17 BPS6 17 BPS6A 17 BPS7 18 BPS9 18 BPS10 18 BPS11 19 BPS13 19 BPS14 19 BPTHM08 47 BPTHM09 47
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17 BPS5 17 BPS6 17 BPS6 17 BPS7 18 BPS9 18 BPS10 18 BPS11 19 BPS12 19 BPS14 19 BPTHM08 47 BPTHM09 47 BPTHM11 47
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17 BPS5 17 BPS6 17 BPS6 17 BPS7 18 BPS8 18 BPS10 18 BPS11 19 BPS12 19 BPS14 19 BPTHM08 47 BPTHM10 47 BPTHM11 47 BPTHM12 47
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17 BPS5 17 BPS6 17 BPS6 17 BPS7 18 BPS8 18 BPS10 18 BPS11 19 BPS12 19 BPS14 19 BPTHM08 47 BPTHM10 47 BPTHM11 47 BPTHM12 47
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17 BPS5 17 BPS6 17 BPS6 17 BPS7 18 BPS8 18 BPS10 18 BPS11 19 BPS12 19 BPS14 19 BPTHM08 47 BPTHM10 47 BPTHM14 47 BPTHM14 47
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17 BPS5 17 BPS6 17 BPS6 17 BPS6 17 BPS6 17 BPS6 17 BPS6 17 BPS1 18 BPS1 18 BPS1 19 BPS11 19 BPS12 19 BPS13 19 BPTHM08 47 BPTHM10 47 BPTHM11 47 BPTHM12 47 BPTHM13 47 BPTHM14 47 BPTOTE 6
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17 BPS5 17 BPS6 17 BPS6 17 BPS6 17 BPS6 17 BPS6 17 BPS6 17 BPS1 18 BPS1 18 BPS1 19 BPS11 19 BPS12 19 BPS13 19 BPTHM08 47 BPTHM09 47 BPTHM11 47 BPTHM12 47 BPTHM13 47 BPTOTE 6 BPWORKBENCH 161
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17 BPS5 17 BPS6 17 BPS1 18 BPS1 18 BPS1 19 BPS12 19 BPS13 19 BPTHM08 47 BPTHM09 47 BPTHM10 47 BPTHM11 47 BPTHM12 47 BPTHM13 47 BPTOTE 6 BPWORKBENCH 161 BSGD75F48 50
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17 BPS5 17 BPS6 18 BPS1 18 BPS11 19 BPS12 19 BPS13 19 BPTHM08 47 BPTHM09 47 BPTHM10 47 BPTHM11 47 BPTHM12 47 BPTHM13 47 BPTOF 6 BPWORKBENCH 161 BSGD75F48 50
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17 BPS5 17 BPS6 17 BPS1 18 BPS1 18 BPS11 19 BPS12 19 BPS13 19 BPS14 19 BPTHM08 47 BPTHM09 47 BPTHM11 47 BPTHM12 47 BPTHM13 47 BPTHM14 47 BPGD75F48 50 BSGD75F47 50
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17 BPS5 17 BPS6 17 BPS6 17 BPS7 18 BPS8 18 BPS9 18 BPS10 18 BPS11 19 BPS12 19 BPS14 19 BPTHM08 47 BPTHM10 47 BPTHM12 47 BPTHM13 47 BPTHM14 47 BPTTM2 6 BPWORKBENCH 161 BSGD75F48 50 BSGD75F49 50 BSGD75PH08 50
BPRTR936SG 23 BPS1 17 BPS2 17 BPS3 17 BPS4P 17 BPS5 17 BPS6 17 BPS1 18 BPS1 18 BPS11 19 BPS12 19 BPS13 19 BPS14 19 BPTHM08 47 BPTHM09 47 BPTHM11 47 BPTHM12 47 BPTHM13 47 BPTHM14 47 BPGD75F48 50 BSGD75F47 50

BSGD75S3B	50
BSGD75S3R	50
BSGD75S3Y	50
BSGD100PH0B	50
BSGD100PH0R	
BSGD100PH0Y	50
BSGD100PH1B	
BSGD100PH1R	50
BSGD100PH1Y	50
BSGD100PH2B	50
BSGD100PH2R	50
BSGD100PH2Y	
BSGD10054B	50
BSGD100S4R	50
BSGD100S4Y	
BSGD125F5B	50
BSGD125F5R	50
BSGD125F5Y	50
BSGD125F6B	50
BSGD125F6R	50
BSGD125F6Y	50
BSGD12554B	
	50
BSGD125S4R	
BSGD125S4Y	50
BSGD125S5B	
BSGD125S5R	50
BSGD125S5Y	50
BSGD150F6B	50
BSGD150F6R	50
BSGD150F6Y	
BSGD150F8B	50
BSGD150F8R	
BSGD150F8Y	50
BSGD150PH0B	
BSGD150PHOR	50
BSGD150PH0Y	50
BSGD150PH1B	50
BSGD150PH1R	
BSGD150PH1Y	
BSGD150PH2B	
BSGD150PH2R	50
BSGD150PH2Y	
BSGD150PH3B	
BSGD150PH3R	50
BSGD150PH3Y	50
BSGD150S4B	50
BSGD150S4R	50
BSGD150S4Y	
BSGD15055B	
BSGD150S5R	
BSGD150S5Y	50
BSGD175F8B	
BSGD175F8R	
BSGD175F8Y	50
BSGD200PH1B	50
BSGD200PH1R	50
BSGD200PH1Y	50
BSGD200PH2B	50
BSGD200PH2R	50
BSGD200PH2Y	
BSGD200PH3B	50
BSGD200PH3R	
BSGD200PH3Y	
BSGD250F6B	
BSGD250F6R	50
BSGD250F6Y	50
BSGD250PH1B	50
BSGD250PH1R	
BSGD250PH1Y	
BSGD250PH2B	
BSGD250PH2R	
BSGD250PH2Y	
BSGD250S4B	50





BSGD250S4R	
BSGD250S4R	50
BSGD250S4Y	50
BSGD300PH1B	50
BSGD300PH1R	50
BSGD300PH1Y	50
BSGD300PH2B	50
BSGD300PH2R	50
BSGD300PH2Y	50
BSGDM38F6	52
BSGDM38PH2	52
BSGDM38PZ2	52
BSGDM65F2	52
BSGDM65PH00	52
BSGDM65PZ00	52
BSGDM75F3	52
BSGDM75F5	52
BSGDM75PH0	52
BSGDM75PH1	52
BSGDM75PZ0	52
BSGDM75PZ1	52
BSGDM75TX6	52
BSGDM75TX7	52
BSGDM75TX8	52
BSGDM75TX9	52
BSGDM100F3	52
BSGDM100F5	52
BSGDM100F6	52
BSGDM100PH0	
BSGDM100PH1	
BSGDM100PH2	
BSGDM100PZ0	52
BSGDM100PZ1	52
BSGDM100PZ2	52
BSGDM100TX10	52
BSGDM100TX15	52
BSGDM100TX20	52
BSGDM100TX25	52
	52
BSGDM100TX27	
BSGDM100TX30	52
BSGDM100TX40	52
BSGDM150F3	52
BSGDM150F5	52
BSGDM150F6	52
BSGDM150F8	52
BSGDM150PH0	
BSGDM150PH1	52
BSGDM150PH2	
BSGDM150PH3	
BSGDM150PZ0	52
BSGDM150PZ1	52
BSGDM150PZ2	52
BSGDM150PZ3	52
BSGDM200F5	
BSGDM200F6	
BSGDM200F8	
BSGDM200F9	52
BSGDM200PH2	52
BSGDM200PH3	52
BSGDM200PH4	52
BSGDM200PZ2	52
BSGDM200PZ3	52
BSGDM200PZ4	
BSGDM250F6	
BSGDM250PH2	
BSGDM250PZ2	52
BSGDV100PH0	51
BSGDV100S2	51
BSGDV100S3	
BSGDV10055	
BSGDV10034	
BSGDV150PH1	
BSGDV150S6	
BSGDV175PH2	51

BSGDV200PH3 51	
BSP6 60	
BT9 155	
BTC3A 142	
BTCP1 155	
BTG8 155	
BTQS500 148	
BTQS600 149	
BTQS1000 149	
BTWM1.5 47	
BTWM2.5 47	
BTWM3 47	
BTWM4 47	
BTWM5 47	
BTWM6 47	
BTWM7 47	
BTWM8 47	

C

CD7A 112	
CD10A 112	
CD12A 112	
CD16A 112	
CF19B 153	
CF700B 153	
CF811B 153	
CL404VIS 128	
CL406VIS 128	
CL408VIS	
CM6416 128	
CNT6521 120	
CW12A 47	
CW15A 47	
CW24A 47	

D

DBBP21	104
DBBPC21	104
DBBPT13	104
DEBUR300	128
DG530	136
DM6	121
DM61	121
DM62	121
DM63	121
DM64	121
DM65	121
DM66	121
DM67	121
DPFT528B	110

137 137 122 122 122 122 122
124
124
124
123
124
123
143
122
142
138
138
140

ETA125A	102
ETB14401A	94
ETB14410A	93
ETB14419A	94
ETB14420A	93
ETB14430A	94
ETB14438A	93
ETB14460A	93

FB300A 118
FB307D 119
FB308D 118
FB310B 118
FB316B 118
FB322 119
FB325A 118
FB326B 118
FB328A 119
FB335 118
FBL325A 118
FBM320 118
FBM322 118
FBS5 136
FSD1
FSD14 23
FSD38 23
FSDR
FSDR1
FUNN15 151
FW7630A 151
FW656714A 151
FW757715A 151
FWA62121A 151
FWK7A 151
FXLBP3
FXLBP6
FXLBP10

G

GA225	125
GA395	136
GA472	151
GA541	137
GA599A	148
GA3200	125
GAJ4A	42
GAJ4AP	42
GAJ6A	42
GAJ6AP	42
GAJ6SG	43
GAJ6SGAP	43
GAJ8A	42
GAJ8AP	42
GAJ8SG	43
GAJ8SGAP	43
GAJ10A	42
GAJ10AP	42
GAJ10SG	43
GAJ10SGAP	43
GAJ12A	42
GAJ12AP	42
GAJ12SG	43
GAJ12SGAP	43
GAJ15A	42
GAJ15AP	42
GAJ18A	42
GAJ18AP	42
GAJ24A	42
GAJ24AP	42
GAJS30A	42



GAJS30AP 42
GAM541 137
GDCT16 146
GLASS30BK 125
GLASS30R 125
GLASS31BK 125
GLASS31R 125
GLOVE103LA 124
GLOVE103LAB 124
GLOVE103MA 124
GLOVE103MAB 124
GLOVE103XLA 124
GLOVE103XLAB 124
GLOVE400L 124
GLOVE400M 124
GLOVE400S 124
GLOVE400XL 124
GLOVE400XXL 124

н

HBR15	110
HBR25	110
HCP3KT	142
HD4SG	110
HDSCISSORS	113
HP2	127
HP301C	155
HP650	157
HP650M	157
HRC1300380	129
HRC1401340	129
HRC1502170	129
HRC1502171	129
HRC1502172	129
HRC1502173	129
HRC1502174	129
HRC1600840	129
HRC1600850	129
HRC1600860	129
HRC1600870	129
HRC1600880	129
HRC1600890	129
HRC1800710	129
HRC4300557	129
HRC4301650	129
HRC4304482	129
HRC9000160	129
HRC9004484	129
HRC9004486	129
HRC9100614	129
111(2)100014	129

JCW8A	154
JT13B	104

1/0047	
KRB17	
KRB24	4
KRB2006KPQP	2
KRB2006KPQR	2
KRB2055KPQP	3
KRB2055KPQR	3
KRB13005KPRB	2
KRB13005KPRR	2
KRB13006KPRB	2
KRB13006KPRR	2
KRB13007KPRB	3
KRB13007KPRR	3
KRB13008KPRB	2
KRB13008KPRR	2

KRBC2TC	3
KRBC2TCPCM	3
KRBC3TD	3
KRBC3TDPCM	3
KRBC7TD	
KRBC7TDPCM	3
KRBC10TB	
KRBC10TBPCM	
KRBC15T	
KRBC15TPCM	
KRBC15TPCMTC	
KRBCSST	
KRBCSSTPCM	
KRU24B	
KRW48C	
KRW182B	
KRW184B	5

Μ

MAGWRENCH	135
MCAL6A	120
MCAL12A	120
MIC1B	121
MIC1MB	121
MIC2B	121
MIC2MB	121
MIC3B	121
MIC3DB	121
MIC4B	121
МІС4В	121
	121
MIC5B	
MIC5MB	121
MIC103B	121
MIC103MB	121
MICB1B	121
MICB2B	121
MICB3B	121
MICB4B	121
MICB5B	121
MICB103B	121
MICED1B	121
MICINSIDE12	121
MIGCARTA	161
ML6000COMBO	150
MRB5A	134
MRB10A	134
MRB12A	134
MRB15A	134
MSC1	150
MSC2	150
MT454C	139
MT501C	139
MT574C	139
MTPV1000	139
N	
NOZZLE360A	127
Р	
PBFG415	134
РЫГ 0415	126
ГПТЈ	120

PK23A 111
PK50A 111
PK52A 111
PK53A 111
PK500A 111
PKB50A 111
PKB52A 111
PKB53A 111
PKB500A 111
PKWSS53A 111
PMF147A 120
POLISHW8A 103
PR7 69
PR7-1 69
PR7-3 69
PR8 69
PR36 58
PR37 58
PR38
PR50A 58
PR51
PR52 58
PR53-1
PR53-3
PR54
PR54-1 69
PR54-3 69
PRC65A 58
PRH56A 58
PRH57A 58
PRH502A 58
PRH503 58
PSLR4 133
PSLR4-1 133
PSLR4-2 133
PSLR4-3 133
PSLR4-4 133
PSLR4-5 133
PSLR4-6
PSLR6 133
PT5C 126
PT5CBL
PWC6
PWC14
PWC19
PWC27
PWC28A
PWC34 134
PWC60 147
PWC80A

QJD8A-72	73
QJD12A	73
QJD16A	73
QJOM6A	73
QJOM7A	73
QJOM8A	73
QJOM9A	73
QJOM10A	73
QJOM11A	73
QJOM12A	73
QJOM13A	73
QJOM14A	73
QJOM15A	73
QJOM16A	73
QJOM17A	73
QJOM18A	73
QJOM19A	73



QJOM21A	73
QJOM22A	73
QJOM23A	73
QJOM24A	73
QJOM25A	73
QJOM26A	73
QJOM27A	73
QXD16A	73
QXD24A	73
QXD32A	73
QXOM18A	73
QXOM19A	73
QXOM20A	73
QXOM21A	73
QXOM22A	73
QXOM23A	73
QXOM24A	73
QXOM26A	73
QXOM29A	73
QXOM30A	73
QXOM32A	73
QXOM34A	73
QXOM36A	73
QYD12A	73
QYD16A	73
QYOM14A	73
QYOM15A	73
QYOM16A	73
QYOM17A	73
QYOM18A	73
QYOM19A	73
QYOM20A	73
QYOM21A	73
QYOM22A	73
QYOM23A	73
QYOM24A	73
QYOM25A	73
QYOM27A	73
QYOM29A	73
QYOM30A	73
QYOM32A	73
QYOM34A	73
QYOM36A	73
QZD24B	73
QZD32B	73
QZOM24A	73
QZOM25A	73
QZOM26A	73
QZOM27A	73
QZOM29A	73
QZOM30A	73
QZOM32A	73
QZOM34A	73
QZOM36A	73
-	

RBZ605 42	
RBZ810 42	
RBZ1214 42	
RBZ1618 42	
RBZ2022 47	
RBZ2428 47	
RBZM78 47	
RBZM605 42	
RBZM910 42	
RBZM1112 42	
RBZM1314 42	
RBZM1517 42	
RBZM1618 47	
RBZM1921	
RC40C	
RC50C	

	RC980	154
	RM130	154
	RTEMPB3A	141
	RULER12BSQ	120
	S	
	SBT26	153
	SDM11KT	135

SDM11KT 135
SDM32KT 135
SKRSST4107 7
SKRWT4008 7
SKRWT4800B 7
SNP2A 112
SQUAREB12 120
SQUAREB45 120
SQUAREB90 120
SQUAREB180 120
SQUARECOMB12 120
SVT275 147
SVTAB1400 146
SXLBP3 35
SXLBP6 35
SXLBP10

T10 42
T15 42
T20 42
T25 42
T27 42
T30 42
T40 42
T45 42
T50 42
TBS200A 136
TC28B1 115
TC28C 115
TC123C 115
TC123C1 115
TC123CR 115
TC123CRH 115
TEMP10 144
TF5A 114
TF275A 114
TF528D 115
TFM5A 114
TFM428 115
TIF160 147
TL100A 119
TLT5 140
TLT6 140
TLT7 140
TLT8000 140
TLT8003 140
TPGDL1000A 147
TPGIF1600 148
TPGP120 148
TPM100 119
TT12KT 141
TZK5 133
TZK7 133
U

UIM125	127
UIM225	127
UIM325	127
UKBU10	114
UKBU50PK	114
UPT2FL	127
UPT15	126

UPT35	127
UPT50A	127
UPT65	127
US710	111
US711	111
US712	111
USS103	111
V	

VAC201 150
VGP12406
VGP12412 68
VGP12418
VGP12424 68
VGP12509 68
VGP12808 69
VGP18110 68
VGP22406
VGP22412 68
VGP22418
VGP22424
VT1A 148
VT14 148

WE200A 129 WE200A1 129 WE200A2 129 WT1001-6 67 WT1003-6 67 WT1014-7 67 WT1014-8 67 WT1014-8 67 WT1014-7 67 WT1017C-6 67 WT5403-8 67 WT5414-9 67 WT8627-10 67

YA12AP 161
YA52PBSQC 134
YA109C 156
YA160A 125
YA261A 102
YA262A 102
YA263A 102
YA328A 119
YA427B 125
YA444B 112
YA444B1 112
YA481 6
YA482 6
YA483 6
YA484
YA486 6
YA512 160
YA580A 113
YA580A-1 113
YA581A 113
YA581A-1 113
YA714D 160
YA728A 151
YA734A 152
YA745A 152
YA750 152
YA751 152
YA752 152
YA772B 152
YA772B 152 YA801 152



YA824ASTR	138
YA824C	138
YA874BP	160
YA879A	110
YA900	110
YA1050B	104
YA1055B	135
YA1228	161
YA1544A	137
YA1707	160
YA1715	160
YA2440	136
YA2612B	142
YA3000C	149
YA3100	149
YA3202	138
YA3500	149
YA4000B	156
YA4274	150
YA4275	151
YA4280	125
YA4282	125
YA4603	128
YA5100B	122
YA6160	147
YA6910	141
YA7500	152
YA8005	138
YA8230	154
YA8610B	155
YA9329A	136
YA9350B	153
YA76462	141
YA76562	141
YA105020	135
YAS203A	102
YB2AP	161
YB3AP	161
YB5AP	161
YF2AP	160
YF3AP	160







Showing Millimeter Sizes, Fractional and Decimal Inch Sizes, and Drill Number Sizes

Note: To convert from inches to millimeters, multiply by 25.4; to convert from millimeters to inches, multiply by 0.03937

м	DE	F	DN	м	DE	F	DN	м	DE	F	DN	м	DE	F	DN	м	DE	F	м	DE	F
0.10	0.0039	-		1.85	0.0728	-	—	-	0.1660	—	19	7.25	0.2854	—	—	13.49	0.5313	17/32	35.00	1.3780	—
0.15	0.0059	—	—	—	0.0730	—	49	4.25	0.1673	—	—	7.30	0.2874	—	—	13.50	0.5315	—	36.00	1.4173	—
0.20	0.0079	-	-	1.90	0.0748	-	—	4.30	0.1693	-	_	_	0.2900	-	L	13.89	0.5469	35/64	36.51	1.4375	1 7/16
0.25	0.0098		—	-	0.0760	—	48	-	0.1695	-	18	7.40	0.2913	—	—	14.00	0.5512	-	37.00	1.4567	-
0.30	0.0118	_	-	1.95	0.0768	-	-	4.37	0.1719	11/64	-	-	0.2950	-	M	14.29	0.5625	9/16	38.00	1.4961	_
-	0.0135	—	80	1.98	0.0781	5/64	47	-	0.1730	—	17	7.50 7.54	0.2953	-	—	14.50	0.5709		38.10	1.5000	1 1/2
0.35	0.0138		79	2.00	0.0785	-	4/	4.40	0.1732	_	16	7.54	0.2969	19/64	_	14.68 15.00	0.5781	37/64	39.00 39.69	1.5354 1.5625	1 9/16
0.40	0.0145	1/64	-	2.00	0.0787	_	_	4.50	0.1770	_		7.00	0.3020	_		15.08	0.5938	19/32	40.00	1.5748	
0.40	0.0150	_	_		0.0810	_	46	-	0.1800	_	15	7.70	0.3031	_	_	15.48	0.6094	39/64	41.00	1.6142	
_	0.0160	_	78	_	0.0820	_	45	4.60	0.1811	_	_	7.75	0.3051	_		15.50	0.6102	_	41.28	1.6250	1 5/8
0.45	0.0177	_	_	2.10	0.0827	_	_	_	0.1820	_	14	7.80	0.3071	_	_	15.88	0.6250	5/8	42.00	1.6535	_
_	0.0180	_	77	2.15	0.0846	_		4.70	0.1850		13	7.90	0.3110	_		16.00	0.6299	_	42.86	1.6875	1 11/16
0.50	0.0197			_	0.0860		44	4.75	0.1870	—	—	7.94	0.3125	5/16	—	16.27	0.6406	41/64	43.00	1.6929	—
	0.0200		76	2.20	0.0866		_	4.76	0.1875	3/16	—	7.80	0.3150	—	_	16.50	0.6496	—	44.00	1.7323	—
-	0.0210	-	75	2.25	0.0886	-	_	4.80	0.1890	_	12	—	0.3160	—	0	16.67	0.6563	21/32	44.45	1.7500	1 3/4
0.55	0.0217	_	_	_	0.0890	_	43	—	0.1910	_	11	8.10	0.3189	—	_	17.00	0.6693	—	45.00	1.7717	_
—	0.0225	—	74	2.30	0.0906	—	_	4.90	0.1929	_	_	8.20	0.3228	—	_	17.07	0.6719	43/64	46.00	1.8110	—
0.60	0.0236	-	-	2.35	0.0925	-	-	-	0.1935	-	10	-	0.3230	-	Р	17.46	0.6875	11/16	46.04	1.8125	1 13/16
-	0.0240	-	73	-	0.0935	-	42	-	0.1960	-	9	8.25	0.3248	—	—	17.50	0.6890	-	47.00	1.8504	-
_	0.0250	-	72	2.38	0.0938	3/32	-	5.00	0.1969	-	_	8.30	0.3268	-	-	17.86	0.7031	45/64	47.63	1.8750	17/8
0.65	0.0256	—		2.40	0.0945	—	-	-	0.1990	—	8	8.33	0.3281	21/64	_	18.00	0.7087		48.00	1.8898	-
0.70	0.0260	-	71	2.45	0.0960	-	41	5.10	0.2008	_	7	8.40	0.3307	-	_	18.26	0.7188	23/32	49.00	1.9291	1 15/16
0.70	0.0276	_		2.45	0.0965	-	40		0.2010	13/64	/		0.3320	-	Q	18.50 18.65	0.7283		49.21 50.00	1.9375 1.9685	1 15/16
							40			13/04											
	0.0292	-	69	2.50	0.0984	-	39		0.2040	_	6	8.60	0.3386	-	— R	19.00 19.05	0.7480	— 3/4	50.80 51.00	2.0000 2.0079	2
0.75	0.0295		68	_	0.0995	-	38	5.20	0.2047	_	5	8.70	0.3390	_	n 	19.05	0.7656	49/64	52.00	2.0079	_
0.79	0.0313	1/32	8	2.60	0.1013	_		5.25	0.2055	_	_	8.73	0.3438	11/32	_	19.50	0.7677		52.39	2.0472	2 1/16
0.80	0.0315	1/32	_	2.00	0.1024	_	37	5.30	0.2007	_	_	8.75	0.3445		_	19.84	0.7813	25/32	53.00	2.0025	
-	0.0310	_	67	2.70	0.1040	_			0.2007	_	4	8.80	0.3465	_		20.00	0.7874		53.98	2.1250	21/8
_	0.0320	_	66		0.1065	_	36	5.40	0.2000	_	_		0.3480	_	S	20.00	0.7969	51/64	54.00	2.1250	
0.85	0.0335	-		2.75	0.1083				0.2130	_	3	8.90	0.3504	_	_	20.50	0.8071		55.00	2.1654	
_	0.0350	_	65	2.78	0.1094	7/64	_	5.50	0.2165	_	_	9.00	0.3543	_	_	20.64	0.8125	13/16	55.56	2.1875	2 3/16
0.90	0.0354	-	_	_	0.1100	_	35	5.56	0.2188	7/32	_	_	0.3580	_	т	21.00	0.8268	_	56.00	2.2047	_
_	0.0360	_	64	2.80	0.1102	_	_	5.60	0.2205	_	_	9.10	0.3583	_	_	21.03	0.8281	53/64	57.00	2.2441	_
_	0.0370	_	63	_	0.1110	_	34	_	0.2210		2	9.13	0.3594	23/64		21.43	0.8438	27/32	57.15	2.2500	2 1/4
0.95	0.0374	_	_		0.1130	_	33	5.70	0.2244	_		9.20	0.3622	_		21.50	0.8465	_	58.00	2.2835	_
	0.0380		62	2.90	0.1142	-	_	5.75	0.2264	_	_	9.25	0.3641	_	_	21.83	0.8594	55/64	58.74	2.3125	2 5/16
-	0.0390	-	61	—	0.1160	-	32	—	0.2280	_	1	9.30	0.3661	—	—	22.00	0.8661	_	59.00	2.3228	—
1.00	0.0394	_	_	3.00	0.1181	_	31	5.80	0.2283	_	_	_	0.3680	-	U	22.23	0.8750	7/8	60.00	2.3622	_
	0.0400		60	—	0.1200		—	5.90	0.2323	—	—	9.40	0.3701	—	—	22.50	0.8858	—	60.33	2.3750	2 3/8
—	0.0410	—	59	3.10	0.1220	—	—	—	0.2340	—	Α	9.50	0.3740	-	—	22.62	0.8906	57/64	61.00	2.4016	_
1.05	0.0413	—	_	3.18	0.1250	1/8	—	5.95	0.2344	15/64	—	9.53	0.3750	3/8	—	23.00	0.9055	—	61.91	2.4375	27/16
_	0.0420	_	58	3.20	0.1260	—	_	6.00	0.2362	—	—	—	0.3770	—	V	23.02	0.9063	29/32	62.00	2.4409	_
—	0.0430	—	57	3.25	0.1280	—	30	-	0.2380	—	В	9.60	0.3780	—	_	23.42	0.9219	59/64	63.00	2.4803	—
1.10	0.0433	-	-	_	0.1285	-	—	6.10	0.2402	-	—	9.70	0.3819	-	—	23.50	0.9252	-	63.50	2.5000	2 1/2
1.15	0.0453	-	-	3.30	0.1299	-	-	-	0.2420	-	C	9.75	0.3838	—	—	23.81	0.9375	15/16	64.00	2.5197	—
_	0.0465	2/51	56	3.40	0.1339	-	-	6.20	0.2441		-	9.80	0.3858	-		24.00	0.9449	_	65.00	2.5591	-
1.19	0.0469	3/64	-	- 2.50	0.1360	—	29	6.25	0.2460	_	D	-	0.3860	—	W	24.21	0.9531	61/64	65.09	2.5625	29/16
1.20 1.25	0.0472	-		3.50	0.1378	-		6.30 6.35	0.2480	1/4	E	9.90 9.92	0.3898	5/64	_	24.50	0.9646	31/32	66.00 66.68	2.5984 2.6250	2 5/8
											E				_	24.61		31/32			25/8
1.30	0.0512	-	55	3.57 3.60	0.1406	9/64	_	6.40 6.50	0.2520	_	_	10.00	0.3937	_		25.00 25.00	0.9843	63/64	67.00 68.00	2.6378 2.6772	_
1.35	0.0520	-		3.60	0.1417	-	27	0.50	0.2559	_	F	_	0.3970	_	Y	25.00	1.0000	03/04	68.26	2.6772	2 11/16
1.35	0.0550	_	54	3.70	0.1440	-		6.60	0.2598	_	г —	10.32	0.4040	3/32	- T	25.40	1.0000	-	69.00	2.0875	211/10
1.40	0.0550	_	-	3.70	0.1437	_	26	0.00	0.2558	_	G	10.32	0.4003			26.99	1.0230	1 1/16	69.85	2.7103	23/4
1.45	0.0551	_		3.75	0.1476	_		6.70	0.2638	_	_	10.50	0.4134	_	_	27.00	1.0630	_	70.00	2.7559	
1.50	0.0591	_	_		0.1470	_	25	6.75	0.2656	17/64	_	10.50	0.4219	27/64	_	28.00	1.1024	_	71.00	2.7953	_
-	0.0595	-	53	3.80	0.1496	-	_	6.75	0.2657	_	_	11.00	0.4331	-	_	28.58	1.1250	1 1/8	71.44	2.8125	2 13/16
1.55	0.0610	_			0.1520	_	24	_	0.2660	-	н	11.11	0.4375	7/16	_	29.00	1.1417		72.00	2.8346	
1.59	0.0625	1/16	-	3.90	0.1535	_	_	6.80	0.2677	_	_	11.50	0.4528	_	_	30.00	1.1811	_	73.00	2.8740	_
1.60	0.0630	_	_	_	0.1540	-	23	6.90	0.2717	-	-	11.51	0.4531	29/64	-	30.16	1.1875	1 3/16	73.03	2.8750	27/8
_	0.0635	_	52	3.97	0.1563	5/32	_	_	0.2720	_	I	11.91	0.4688	15/32	_	31.00	1.2205	_	74.00	2.9134	_
1.65	0.0650	_	-	_	0.1570	_	22	7.00	0.2756	-	_	12.00	0.4724	_	_	31.75	1.2500	1 1/4	74.61	2.9375	2 15/16
1.70	0.0669	_	-	4.00	0.1575	_	_	_	0.2770	_	J	12.30	0.4844	31/64	_	32.00	1.2598	_	75.00	2.9528	_
_	0.0670	_	51	_	0.1590	_	21	7.10	0.2795	_	_	12.50	0.4921	_	_	33.00	1.2992	—	76.00	2.9921	_
1.75	0.0689		_	—	0.1610		20	—	0.2810	_	К	12.70	0.5000	1/2	—	33.34	1.3125	1 5/16	76.20	3.0000	3
1.75			50	4.10	0.1614	_	_	7.14	0.2813	9/32	_	13.00	0.5118	_	_	34.00	1.3386	_			
_	0.0700	_	50	4.10	0.1014	_		7.17	0.2015	<i>J</i> / <i>J</i> Z		13.00	0.5110			51.00	1.5500				

M = Millimeters, DE = Decimal Equivalents, F = Fractional, DN = Drill Number/Letter

Blue-Point, No Compromise!





Blue-Point is a trademark of Snap-on Incorporated. © 2014 Snap-on Incorporated .